


## "FLUTEC" NON - RETURN VALVE


(Model code - NRV -8 to 40)



## Description:

- 8 Sizes flows up to 500 LPM.
- Max. Working pressure 1000 bar .
- Choice of cracking pressure 5/100PSI.
- Metal to Metal sealing (Steel poppet type construction).
- Prevents flow in reverse direction.
- Suitable for high pressure application for all types of flow media (Oil, Water, Air, Gas, etc.).





MODEL	THREADED SIZE IN. BSPP	RATED FLOW LPM	AMM	'B ' A / FMM	WTKGS
NRV <b>-</b> 8	1/4"	20	58	19	0.15
NRV <b>-</b> 10	3/8"	30	58	24	0.25
NRV <b>-</b> 12	1/2"	50	72	30	0.40
NRV <b>-</b> 16	3/4"	80	100	38	0.75
NRV - 20	1"	150	115	41	0.90
NRV - 25	1 - 1/4"	200	130	55	1.75
NRV - 30	1 - 1/2"	270	132	65	2.70
NRV <b>-</b> 40	2"	360	140	75	4.75

## FLUTEC VALVES

102, Alankar Indl. Estate, Near Virwani Indl. Estate, Vishweshwar Nagar, Aarey Cross Road. Goregaon (east)
Mumbai - 400 063.

Cell.: +91 9821043687, +91 9819743687 Telefax: +91 22 29271591

email: flutec1@hotmail.com,
sales@flutecvalves.com

Website: www.flutecvalves.in