

Real Race Cars Inc
 Concord, NC 28025
 (704) 784-4554

DYNomite Test Run: RRC New 1250 4-Sale #62 on 2010-09-30 @ 11-24-25

Date: 9/30/2010

Correction Method: SAE

Notes: 93 pump

RPM (RPM)	Hp (Hp)	Torque (ft-lb)	Avg-EGT (Degree F)	EGT #1 (Degree F)	EGT #2 (Degree F)	EGT #3 (Degree F)	EGT #4 (Degree F)	E-Temp (Degree F)
5900	96.80	85.67	972.1	980	968	971	969	211
6000	99.70	87.40	972.1	980	968	971	969	211
6100	103.2	88.89	972.1	980	968	971	969	211
6200	105.8	89.68	972.1	980	968	971	969	211
6300	108.3	90.26	972.0	980	968	971	969	212
6400	110.3	90.51	972.1	980	968	971	969	212
6500	111.9	90.39	972.0	980	968	971	969	212
6600	113.4	90.21	972.1	980	968	971	969	213
6700	115.7	90.73	972.1	980	968	971	969	213
6800	117.9	91.12	972.1	980	968	971	969	213
6900	119.7	91.08	972.1	980	968	971	969	214
7000	121.2	90.92	972.0	980	968	971	969	214
7100	123.2	91.15	972.1	980	968	971	969	214
7200	125.2	91.32	972.1	980	968	971	969	215
7300	126.2	90.75	972.1	980	968	971	969	215
7400	128.0	90.86	972.1	980	968	971	969	215
7500	129.2	90.49	972.1	980	968	971	969	216
7600	130.1	89.87	972.1	980	968	971	969	216
7700	130.4	88.95	972.1	980	968	971	969	216
7800	132.5	89.23	972.1	980	968	971	969	216
7900	133.1	88.49	972.1	980	968	971	969	217
8000	133.2	87.45	972.1	980	968	971	969	217
8100	132.8	86.11	972.1	980	968	971	969	217
8200	134.5	86.19	972.1	980	968	971	969	218
8300	135.0	85.40	972.1	980	968	971	969	218
8400	134.4	84.02	972.1	980	968	971	969	218
8500	135.2	83.54	972.0	980	968	971	969	218
8600	134.9	82.34	972.1	980	968	971	969	219
8700	135.8	82.01	972.0	980	968	971	969	219
8800	137.3	81.92	972.0	980	968	971	969	219
8900	137.0	80.84	972.0	980	968	971	969	220
9000	136.8	79.84	971.9	980	968	971	969	220
9100	136.8	78.91	971.9	980	968	971	969	220
9200	137.4	78.45	971.9	980	967	971	969	220
9300	137.8	77.82	971.9	980	967	971	969	220
9400	135.8	75.88	971.8	980	967	971	969	221
9500	134.7	74.62	971.8	980	967	971	969	221

Real Race Cars Inc
 Concord, NC 28025
 (704) 784-4554

DYNomite Test Run: RRC New 1250 4-Sale #70 on 2010-09-30 @ 11-40-45

Date: 9/30/2010

Correction Method: SAE

Notes: this run with 93 pump fuel & Oxytane to 5 gallons

RPM (RPM)	Hp (Hp)	Torque (ft-lb)	Avg-EGT (Degree F)	EGT #1 (Degree F)	EGT #2 (Degree F)	EGT #3 (Degree F)	EGT #4 (Degree F)	E-Temp (Degree F)
6000	99.29	86.85	978.6	988	973	978	975	214
6100	102.9	88.66	978.6	988	973	978	975	214
6200	105.8	89.65	978.5	988	973	978	975	214
6300	108.3	90.28	978.6	988	973	978	975	214
6400	110.8	90.94	978.6	988	973	978	975	215
6500	113.2	91.46	978.6	988	973	978	975	215
6600	115.4	91.78	978.6	988	973	978	975	215
6700	117.2	91.87	978.6	988	973	978	975	215
6800	119.3	92.13	978.6	988	973	978	975	215
6900	121.2	92.27	978.6	988	973	978	975	215
7000	122.8	92.15	978.6	988	973	978	975	215
7100	124.7	92.27	978.6	988	973	978	975	215
7200	126.6	92.34	978.6	988	973	978	975	215
7300	127.4	91.67	978.6	988	973	978	975	215
7400	129.1	91.67	978.6	988	973	978	975	216
7500	130.5	91.36	978.6	988	973	978	975	216
7600	131.5	90.85	978.6	988	973	978	975	216
7700	132.1	90.09	978.6	988	973	978	975	216
7800	133.3	89.80	978.6	988	973	978	975	216
7900	134.0	89.10	978.6	988	973	978	975	216
8000	134.1	88.02	978.6	988	973	978	975	216
8100	134.8	87.43	978.6	988	973	978	975	216
8200	135.9	87.08	978.6	988	973	978	975	216
8300	136.4	86.29	978.6	988	973	978	975	217
8400	135.9	84.96	978.6	988	973	978	975	217
8500	136.5	84.35	978.6	988	973	978	975	217
8600	137.8	84.16	978.6	988	973	978	975	217
8700	137.7	83.16	978.6	988	973	978	975	217
8800	138.2	82.47	978.5	988	973	978	975	217
8900	138.5	81.74	978.5	988	973	978	975	218
9000	139.3	81.29	978.5	988	973	978	975	218
9100	139.4	80.47	978.5	988	973	978	975	218
9200	140.2	80.04	978.4	988	973	978	975	218
9300	140.2	79.15	978.4	988	973	978	975	218
9400	138.6	77.42	978.3	988	972	978	975	218
9500	138.2	76.43	978.3	988	972	978	975	218
9600	137.4	75.17	978.3	988	972	978	975	218
9700	134.9	73.00	978.2	988	972	978	975	219
9800	133.0	71.40	978.1	988	972	978	975	219

Real Race Cars Inc
Concord, NC 28025
(704) 784-4554

DYNomite Test Run: RRC New 1250 4-Sale #67 on 2010-09-30 @ 11-33-25

Date: 9/30/2010

Correction Method: SAE

Notes: 100 octane

RPM (RPM)	Hp (Hp)	Torque (ft-lb)	Avg-EGT (Degree F)	EGT #1 (Degree F)	EGT #2 (Degree F)	EGT #3 (Degree F)	EGT #4 (Degree F)	E-Temp (Degree F)
6000	98.93	86.64	976.3	985	971	976	973	221
6100	102.9	88.61	976.4	985	971	976	973	221
6200	106.0	89.78	976.3	985	971	976	973	221
6300	108.4	90.34	976.4	985	971	976	973	221
6400	110.3	90.46	976.4	985	971	976	973	221
6500	112.5	90.89	976.4	985	971	976	973	221
6600	114.6	91.21	976.4	985	971	976	973	221
6700	116.8	91.56	976.3	985	971	976	973	221
6800	118.9	91.84	976.4	985	971	976	973	221
6900	120.1	91.36	976.4	985	971	976	973	221
7000	121.7	91.34	976.4	985	971	976	973	222
7100	123.9	91.65	976.3	985	971	976	973	222
7200	126.2	92.10	976.4	985	971	976	973	222
7300	127.3	91.57	976.4	985	971	976	973	222
7400	128.6	91.28	976.3	985	971	976	973	222
7500	129.9	90.95	976.4	985	971	976	973	222
7600	130.3	90.02	976.4	985	971	976	973	222
7700	130.8	89.23	976.3	985	971	976	973	222
7800	132.2	89.09	976.4	985	971	976	973	222
7900	133.5	88.73	976.3	985	971	976	973	222
8000	133.5	87.61	976.3	985	971	976	973	222
8100	133.4	86.50	976.3	985	971	976	973	223
8200	134.1	85.93	976.3	985	971	976	973	223
8300	134.6	85.19	976.3	985	971	976	973	223
8400	135.7	84.85	976.3	985	971	976	973	223
8500	136.9	84.58	976.3	985	971	976	973	223
8600	137.1	83.72	976.3	985	971	976	973	223
8700	136.4	82.35	976.3	985	971	976	973	224
8800	137.3	81.98	976.3	985	971	976	973	224
8900	139.3	82.20	976.2	985	971	975	973	224
9000	138.7	80.93	976.2	985	971	975	973	224
9100	137.4	79.27	976.2	985	971	975	973	224
9200	137.1	78.28	976.1	985	971	975	973	224
9300	136.4	77.04	976.1	985	971	975	973	224
9400	137.1	76.66	976.0	985	971	975	973	224
9500	139.3	77.04	976.0	985	970	975	973	224
9600	137.5	75.21	976.0	985	971	975	973	224
9700	133.9	72.49	975.9	985	970	975	973	224
9800	131.1	70.39	975.9	985	970	975	973	225