



Cushion-Mount™ Plus Tapes

with EH-Series Adhesive



Easy Mount Adhesive that holds the edge on cylinder diameters as small as 2"

3M EH-Series Tapes combine the air release of 3M E-Series Tapes with adhesive that resists edge lifting on small diameter cylinders. These ten tapes provide production enhancements for printers plus the print quality customers expect.

On easy with reduced air entrapment

- Unlike flat or pebbled liners, crosshatched microchannels in EH-Series liners allow air to bleed from between the tape and plate, and between the tape and cylinder
- Helps eliminate bubble problems for easier, virtually error-free mounting
- Setup is faster with smoother surfaces for cleaner print quality and higher productivity

Stays on with reduced edge-lifting

- Exclusive adhesive maintains tight contact between tape and plate to dramatically reduce edge lifting
- Saves prep, downtime, and labor of sealing plate edges

- Prevent blemishes in screen and process printing
- Help assure proper registration

Balancing solids and dots for customer satisfaction

- Choice of constructions for solids or halftones, or combination solids and dots

EH-Series and E-Series Selection Guide

Select EH-Series

E1820H, E1815H, E1720H, E1715H, E1020H, E1015H, E1920H, E1915H, E1120H, E1115H:

- Higher plate side adhesion
- Small diameter print cylinder
- 0.107" thick plate or greater
- Don't have time to clean back of plate

Select E-Series

E1820, E1815, E1720, E1715, E1020, E1015, E1920, E1915, E1120, E1115:

- Easier plate removal
- Larger diameter print cylinder
- 0.067" thick plate or less
- Clean back of plate

3M™ Combination Printing Tapes

3M™ Process Printing Tapes


Firm Combination Printing EH Tapes with Foam Carrier

Medium Firm Combination Printing EH Tapes with Foam Carrier

Standard Combination Printing EH Tapes with Foam Carrier

Soft Combination Printing EH Tapes with Foam Carrier

Process Printing EH Tapes with Foam Carrier



E1820H, E1815H, E1820, E1815:
Mostly solids in combination of solid and halftone

E1720H, E1715H, E1720, E1715:
Slightly more solids in combination of solid and halftone

E1020H, E1015H, E1020, E1015:
Solid and halftone are equally important

E1920H, E1915H, E1920, E1915:
Process and halftone predominate

E1120H, E1115H, E1120, E1115:
High quality process work and screen printing

NOTE ON SOLID AND DOTS REPRODUCTION: 40x magnification on dots; 20x on positive and reverse type; process magenta ink on 2 mil polyethylene film; 1 mil impression at 88 fpm, 800 line, 2.4 bcm.

PRODUCT USE: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

WARRANTY AND LIMITED REMEDY: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to repair or replace the product or refund the purchase price.

LIMITATION OF LIABILITY: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M

**Industrial and Transportation Business
Industrial Adhesives and Tapes Division**

Customer Response Center
900 Bush Avenue,
Building 21-1W-10
St. Paul, MN 55144-1000
1-800-362-3550
www.3M.com/flexo

Printed in U.S.A.
© 3M 2005 70-0709-5378-4

Quality **D**iscount **P**ress **P**arts & **E**quipment Inc.
Established since 1993

6088 Reega Ave
Egg Harbor Twp, NJ 08234
Phone: 1-800-646-2212 or 1-609-646-2212

Fax: 1-609-646-2212
Web: www.qualitydiscount.com
Email: sales@qualitydiscount.com