



PC SELECT INFIELD CONDITIONER

Typical Characteristics

Product Data

Product:

Pro's Choice Select Sports Field Conditioner

Manufacturer:

Oil-Dri Corporation of America
1-800-648-1166

Processing/Shipping Location:

1800 City Avenue North
Ripley, MS 38663

Description:

Natural mineral with a blend of Montmorillinite, illite, and amorphous silica. 40% minimum & 60% minimum amorphous silica. Material must be processed via rotary kiln operation at temperatures above 1200° Fahrenheit. Material must be screened and de-dusted.

Installation:

The following formula will be a guide for installing PC Select into your infield or root zone area. Infields should be conditioned at approximately 15% to 20% by volume. We recommend PC Select be rototilled 1-4 inches deep. Root zones should be approximately 20% by volume 4-6 inches deep depending on soils used.

Mineral Classification:

Fuller's Earth, Montmorillinite
(Calcium-Bentonite)

Color/Appearance:

Reddish Orange

Technical Data

| Product Specifications: | Typical Analysis | Test Procedure |
|-----------------------------------|-------------------------|----------------|
| Foreign material | None | SE307.01.01 |
| Bulk density, lbs/ft ³ | 33.4 lb/ft ³ | DN001.01.01 |
| pH | 5.3 | IN001.01.01 |
| Free moisture % | 0.4% | VL003.03.02 |
| Hardness % | 91.6% | HD001.02.01 |
| Wet Slaking % | 3.8% | HD005.01.01 |
| Dust index | 1.17 | PS005.02.02 |
| Grind Distribution | -10 / +16 | PS001.02.01 |
| Sieve analysis % | | |
| +6 mesh | 0% | |
| -6/+8 mesh | 2% | |
| -8/+16 mesh | 92% | |
| -16 mesh | 6% | |

Item Numbers:

A45202G40: 50 lb bags, 40 bags / pallet
A42202: Bulk Bag
A41202: Bulk Truck

