



PATRIOT
GEOSYNTHETICS

HI VIZ CONTRACTOR SILT FENCE

*WITH
STAKES*

Hi Viz Contractor Silt Fence with stakes is preassembled using 36" Hi Viz woven geotextile PATRIOT 100SF and hardwood stakes. The PATRIOT 100SF is made up of high tenacity polypropylene tapes. These tapes are woven to form stable and durable structure which allows the tapes to maintain their relative position. It is non-biodegradable and resistant to ultra violet degradation, rotting, and most soil chemicals. The Hi Viz Contractor Silt Fence with stakes is manufactured to meet or exceed the following minimum average roll values:



Assembled Unit Property	Test Method	Value
Post Size	Measured	1.25" x 1.25" x 48"
Post Spacing	Measured	10 ft
Post Composition	-	Hardwood with Pencil Point
Fabric Height	Measured	36 in
Unit Length	Measured	100 ft

PATRIOT 100SF Fabric

PROPERTY	TEST METHOD	MINIMUM AVERAGE ROLL VALUE ENGLISH
Tensile Strength (Grab)	ASTM D4632	100 x 100 lbs
Elongation	ASTM D4632	15%
CBR Puncture	ASTM D6241	300 lbs
Trapezoidal Tear	ASTM D4533	45 x 45 lbs
UV Resistance (500 hrs)	ASTM D4355	70%
Apparent Opening Size (AOS)	ASTM D4751	30 US Std. Sieve
Permittivity ASTM	ASTM D4491	0.05 sec ⁻¹
Water Flow Rate	ASTM D4491	6 gpm/ft ²

Disclaimer: Patriot Geosynthetics, as a whole, assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Nothing contained herein should be construed as creating an expressed or implied warranty, including warranties of merchantability and fitness, each of which is hereby disclaimed. There are no warranties that extend beyond the description on the face hereof. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.

AASHTO
**PRODUCT
EVALUATION
& AUDIT**
SOLUTIONS



INFO@PATRIOTGEOS.COM



PATRIOTGEOS.COM