

AETS DC GATE BARRIER, Brushless DC Motor, International German technology, Mechanical and electrical integrated design, Planetary gear drive, no noise, automatically unlocked when the power is off, speed can be adjusted based on Boom length.



#### Main Features

- The Running Speed can be adjusted from 1.5sec to 6sec
- Auto Reverse function
- High visibility red/green LED on the bottom side of the boom with safety rubber.
- Very intensive use, MCBF 5 million cycles.
- Anti-collision protection function

## Technical Data

Models	DC -6M	DC-ECO 4M	DC- DSP LED 4M
Power Supply	230AC	230AC	230AC
Rated Voltage of Motor	DC 24V	DC 24V	DC 24V
Running Speed	04s to 06s	1.5s to 3s	1.5s to 3s
Rated power	140W	140W	140W
Working temperature (motor)	-35°C~+85°C	-35°C~+85°C	-35°C~+85°C
IP Degree	IP44	IP44	IP44
Relative humidity	≤90%	≤90%	≤90%

### Arm Auto Reverse



Built in smart collision detection technology allows arm to auto reverse when hit with an obstacle during closing to prevent further scratches & dents on the vehicle. Optional photo beam allows arm to auto reverse earlier before hitting the vehicle..Optional rubber lining to protect the vehicle from further damages

## Green When Open



## Red When Closed

