

Operating the Display for SMLRO Model S9 S11 and G6 Bikes



To change display settings hold the Up and Down arrows simultaneously to enter the advanced settings menu. In this menu clicking the "M" (mode) button will toggle between each Parameter setting. To adjust the value of each setting click the up and down arrows accordingly.

Please visit Tryxpro.com often for more updated version of the display instruction under Product Support menu.

Setting	Function	Default	Description
P01	Display Brightness	1	Backlight display brightness. Level 1-3 (3 is brightest)
P02	Distance Units	1	Speed: KM or MPH
P04	Sleep	1	LCD Display sleep timer. With the default setting, the display will turn off after it has not been used
P08	Speed Limit	100	Speed limit in km/h. Range is 0-100. The input data here represents the maximum operating speed of the bike. The max value allowed is 100. Anything above this will not be recognized. Error: ± 1 km/h. 100 means no speed limit.
P09	Throttle Toggle	0	0: Throttle is active 1: Throttle is inactive
P11	PAS Sensitivity	3	Sensitivity of PAS sensor. When set to higher numbers, it will take more crank rotations for the motor to turn on. On lower numbers, it will take little crank rotation to turn on the motor.
P12	PAS Strength	1	Strength of PAS mode. When set to higher numbers, motor will come on stronger. On lower numbers, it will be more gentle.