Parts Mechanical and electrical EHJ



235 AVE LABROSSE, POINTE-CLAIRE, MONTRÉAL, (QUÉBEC) CANADA, H9R 1A3 **TÉL.: (514) 695-0772 - 800-667-0772** FAX: (514 695-0248 - 800-667-0248 **www.doorlec.com**



MODEL EHJ Drawing No. 1057 A Mechanical

nt pport- front pport - rear PP - 205 P- 3 set pre KW/SS
nt opport- front pport - rear PP - 205 P- 3 set
nt opport- front pport - rear PP - 205 P- 3 set
oport- front pport - rear PP - 205 P- 3 set
PP - 205 P- 3 set
PP - 205 P- 3 set
P- 3 set
P- 3 set
P- 3 set
P- 3 set
ore KW/SS
ore KW/SS
ore KW/SS
ore KW/SS
ore KW/SS
bore KW/SS
n)
(1"
)) h
em) bore
20 x 2.5 cm)
20 x 2.5 (11)
ert
cit
cm x 3.8 cm)
chi x 5.0 chi)
.59 cm) hole
.55 cm, noic
cm x 7 cm)
"
5 cm) dia.
e city diat
cm)
cm) .38 x 2.5 cm)
cm) .38 x 2.5 cm)

Part No.	DRAWING NO.	CODE NO.	DESCRIPTION
36	1057 A	26140	Cam shaft, threaded $\frac{5}{8}$ " x 10 $\frac{3}{4}$ " - 24
			(1.59 cm x 27 .3 cm - 24)
37	1057 A	11801	Oilite cam, grooved 5/8" - 24 x 3/8"
			(1.59 cm- 24 x 9.5 cm) wide
38	1057 A	11099	Truss head Bolt 10 - 32 x ³ /8"
39	1057 A	42402	Cover, control cabinet
39A	1057 A	42401	Base. Control cabinet
40	1057 A		Electric motor
			(see name plate for H.P. and voltage)
41	1057 A	11832	Spacers. Hex (when used)
42	1057 A	11280	Nut, 1/4" (.63 cm) - 20 nylon insert
43	1057 A	11198	Truss head bolt 1/4" - 20 x 3/4"
			(.63 cm - 20 x 1.9 cm)
44	1057 A	14212	Solenoid-brake lever, lower
45	1057 A	11280	Nut, 1/4" (.63 cm) - 20 nylon insert
46	1057 A	14211	Solenoid-brake lever, upper
47	1057 A	11198	Truss head bolt 1/4" - 20 x 3/4"
			(.63 cm- 20 x 1.9 cm)
48	1057 A	11290	Nut, hex 8 - 32
49	1057 A	30010	Cover, solenoid switch
50	1057 A	11231	Stove bolts 1/4" - 20 x 3 1/2"
			(.63 cm - 20 x 8.75 cm)
51	1057 A	14213	Brake plate
52	1057 A	26117	Cam retainer plate
53	1057 A	11261	Cap screw, hex 1/4" x 11/2" (.63 cm x 3.8 cm)
54	1057 A	20111	Cam retainer plate springs
55	1057 A	11280	Nut, 1/4" (.63 cm) - 20 nylon insert
56	1057 A	11282	Nut, nylon insert No. 6 (not shown)
57	1057 A	11283	Nut No. 6 (not shown)
58	1057 A	11361	Lock washer # 10 (not shown)
59	1057 A	11199	No. 6 Limit Switch Spacer (not shown)
60	1057 A	11201	Machine bolt No. 6 x 2" (5 cm) (not shown)
61	1057 A	20109	Hoist spring EHJ
62	1057 A	12122	Pocket wheel coupling
63	1057 A	11091	Nut, fine ⁵ / ⁸ - 24 for cam shaft (1.59 cm)
0.5	100771	11001	(not shown)
64	1057 A	26080	Shaft collar- 1" (2.5 cm) hole
65	1057 A	11251	Washer SAE 1" (2.5 cm) hole
66	1057 A	50685	Clutch Assembly including pillow
	100771	50005	xxxx speed bearings with metal housing
			with metal housing

.

. .



TROLLEY Drawing No. 1058 Mechanical

PART NO.	DRAWING NO.	CODE NO.	DESCRIPTION
1	1058		Operator Head (for reference only)
2	1058	23000	Trolley angles- length required: door height + 2' 6" (75 cm) Lin./Ft.
3	1058	24015	Connecting link# 65 (410)
3A	1058	24011	Connecting link # 41
4	1058	11697	Rod, threaded 3/8" -16 x 3 3/4" (.94 cm -16 x 9.38 cm)
5	1058	11289	Nut, hex 3/8" (9.5 mm) -16
6	1058	11253	Lock washer ³ / ₈ " (.94 cm)
7	1058	11536	Eye bolt ³ / ₈ " x 2 ¹ / ₂ " (.94 cm x 6.4 cm)
8	1058	50210	Spreader assembly, roller chain
9	1058	11696	Stud, threaded 3/8" - 16 x 7" (9.5 mm -16 x 178 mm)
10	1058	26180	Shaft collar 5/8" (1.59 cm) bore
11	1058	28412	Flange bearing 5/8" (1.59 cm) bore Oilite bushing
12A	1058	31115	Sprocket 410B9- 5/8" (1.59 cm) bore Oilite bushing
12B	1058	31127	Sprocket 41B12 - 5/8" (1.59 cm) bore Oilite
13	1058	26161	Tubing, mechanical 5 3/4" x 5/8" x 11 ga. (14.7 cm x 1.59 cm x 11 ga.)
14	1058	11363	Nut, hex ⁵ /16" - 18
15	1058	11378	Lock washer ⁵ /16 ["] (8 mm)
16	1058	11268	Cap screw, hex 5/16" x 1"
17	1058	12121	Carriage, cast iron
18	1058	11264	Cap screw, hex 3/8" x 2 3/4" (.94 cm x 7 cm)
26	1058	11003	Screw N.6- 32 x ³ /4" (No. 6- 32 x 19.50 mm)
27	1058	11282	Nut, nylon insert No. 6 (not shown)
28	1058	14021	Slide Release Channel
29	1058	11002	Screw No.6· 32 x 1/2" (No. 6- 32 x 13 mm)
30	1058	11003	Screw No. 6 - 32 x ³ / ₄ " (No. 6 - 32 x 19.50 mm)
31	1058	11264	Cap screw, hex $3/8'' \times 2^{3}/4''$ (.94 cm x 7 cm)
32	1058	11268	Cap screw, hex 5/16" x 1 "
37	1058		Carriage Bolt 1/4" 20 x 2 1/4" (6.3 mm - 20 x 57 mm) - Not supplied by us
39	1058	14133	Door arm, straight
40	1058	14130	Door arm, curved
41	1058	11811	Nut 1/4" (.63 cm) - 20
42	1058	12570	Door bracket, aluminum
43	1058	11264	Cap screw, hex 3/8" x 2 3/4" (.94 cm x 7 cm)
44	1058	24300	Sash chain (disconnect)
45	1058	14220	Trolley wall mount bracket
46A	1058	24065	Roller chain # 65 (410) Lin./Ft.
46B	1058	24041	Roller chain # 41 Lin./Ft.
47	1058	20101	Spring arm release
	_		
		OORLEG	D
1		CORPOR	ATION

TROLLEY Drawing No. 1058 A Mechanical

Part No.	DRAWING NO.	CODE NO.	DESCRIPTION						
1	1058 A	23000	Trolley angles - length required: door height + 2' 6" (75 cm) Lin./Ft.						
2			Trolley wall mount bracket						
3	1058 A	11289	Nut, hex 3/8" (9.5 mm) - 16						
4	1058 A	11253	Lock washer ³ / ₈ " (.94 cm)						
5	1058 A	11696	Stud, threaded 3/8"- 16 x 7" (9.5 mm- 16 x 178 mm)						
6	1058 A	26180	Shaft collar 5/8" (1.59 cm) bore						
7	1058 A	26161	Tubing, mechanical 5 3/4" x 5/8" x 11 ga. (14.7 cm x 1.59 cm x 11 ga.)						
8		31109	Sprocket 41B9 - 5/8" (1.59 cm) bore Oilite brushing						
8		31127	Sprocket idler with Oilite brushing 41B12						
9		50220	Lifting arm assembly						
10	1058 A	24041	Roller Chain RC41 - length = double door height, plus 5' 5" (1.5 m -12.5 m) Lin./Ft.						
11	1058 A	11536	Eye bolt ³ / ₈ " x 2 ¹ / ₂ " (.94 cm x 6.4 cm)						
12	1058 A	12121	Carriage, cast iron						
13	1058 A		Rod, threaded 3/8" - 16 x 3 3/4" (.94 cm - 16 x 9.38 cm)						
14	1058 A	50210	Spreader assembly, roller chain						
15	1058 A		Cap screw 1/4" - 20 x 1" (.63 cm- 20 x 2.5 cm) (not shown)						
16	1058 A		Nut 1/4" (.63 cm) - 20						
17	1058 A		Cap screw 5/16" - 20 x 1 1/4" (.78 cm- 20 x 3.2 cm) (not shown)						
18		11363	Nut, hex 5/16" - 18						
			CARRIAGE						
		12118	Sliding carriage aluminum						
		12119	Sliding carriage aluminum w/teflon insert						
		12120	Sliding carriage manual release to door arm						
_									
-									
-									
_		_							
-									