



# 915 / 916 / 955-SL

## HIGH PERFORMANCE SEALANTS

### ONE COMPONENT COLOR CHART\*



White



Medium Bronze



Stone



Bronze



Aluminum Stone



Light Gray



Limestone



Black



Tan



Terra Cotta

\*Actual product colors may vary slightly.

**BOSTIK HOTLINE**

**Smart help**  
**1-800-726-7845**

**Bostik, Inc.**  
11320 W Watertown Plank Road  
Wauwatosa, WI 53226  
[www.bostik.com/us](http://www.bostik.com/us)





# 915 / 916 / 955-SL

## HIGH PERFORMANCE SEALANTS

### COLORS AVAILABLE

ONE-COMPONENT PRODUCT	WHITE	STONE	ALUMINUM STONE	LIMESTONE	TAN	MEDIUM BRONZE	BRONZE	TERRA COTTA	LIGHT GRAY	BLACK
Bostik 915	●	●	●	●	●	●	●	●	●	●
Bostik 916	●	●		●	●	●	●			●
Bostik 955-SL				●						

### ONE-COMPONENT PRODUCTS

URETHANES	SPECIFICATIONS
Bostik 915	ASTM C-920, Type S, Grade NS, Class 35, Use NT, CAN/CGSB-19.13-M87, TT-S-00230C
Bostik 916	ASTM C-920, Type S, Grade NS, Class 25, Use NT, CAN/CGSB-19.13-M87, TT-S-00230C
Bostik 955-SL	ASTM C-920, Type S, Grade P, Class 35, Use T, TT-S-00230C

### COVERAGE CHART

Depth	Cartridge / Sausage	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	10.1 oz. Cartridge	97	49	32	24	19	16	13	12
	28 oz. Cartridge	267.8	134	88.3	66	54	44.6	37	33.5
	20 oz. Sausage	192	97	63	48	39	31	27	24
1/4"	10.1 oz. Cartridge		24	19	12	9	7	6	5
	28 oz. Cartridge		66	54	33.5	27	21	19	16
	20 oz. Sausage		48	39	24	19	15	14	12
3/8"	10.1 oz. Cartridge			10	7	6	5	4.5	4
	28 oz. Cartridge			29.7	21.3	17.6	14.8	12	8
	20 oz. Sausage			2.1	15	11	10	9	7
1/2"	10.1 oz. Cartridge				5.5	5	4	3.5	3
	28 oz. Cartridge				16.3	13.5	10.7	9.3	7.4
	20 oz. Sausage				11	10	8	7	5

**NOTE:** All values are approximations and can vary due to the joint dimension variations, porosity, and texture of the substrates.