




915FS™ & PRO-MS50™

HIGH PERFORMANCE SEALANTS


ONE COMPONENT COLOR CHART



White




Medium Bronze




Antique White




Bronze




Stone




Terra Cotta




Limestone




Aluminum Gray



Capital Tan



Light Gray



Desert Tan
PRO-MS 50 only



Black

BOSTIK HOTLINE

Smart help
1-800-726-7845


Bostik, Inc.

11320 W. Watertown Plank Road

Wauwatosa, WI 53226

A company of TOTAL

www.bostik-us.com



T1524 10.21.14

ONE-COMPONENT PRODUCTS

URETHANES	SPECIFICATIONS
Bostik 900™	ASTM C-920, Type S, Grade NS, Class 25, Use NT, CAN/CGSB-19.13-M87, TT-S-00230C
Bostik 915™	ASTM C-920, Type S, Grade NS, Class 35, Use NT, CAN/CGSB-19.13-M87, TT-S-00230C
Bostik 915FS™	ASTM C-920, Type S, Grade NS, Class 35, Use NT, CAN/CGSB-19.13-M87, TT-S-00230C
Bostik 916™	ASTM C-920, Type S, Grade NS, Class 25, Use NT, CAN/CGSB-19.13-M87, TT-S-00230C
Bostik 955-SL™	ASTM C-920, Type S, Grade P, Class 35, Use T, TT-S-00230C
SILICONE	SPECIFICATIONS
Bostik 1200™	+ /- 25% Joint Movement
Bostik 1250™	ASTM C-920, Type S, Grade NS, Class 25, Use NT, TT-S-00230C
HYBRID SEALANTS	SPECIFICATIONS
Bostik 2000™ Smooth & Textured	ASTM C-920, Type S, Grade NS, Class 25, Use NT, TT-S-00230C
Bostik 2020™	ASTM C-920, Type S, Grade NS, Class 50, Use NT, TT-S-00230C CAN/CGSB-19.13-M87
Bostik PRO-MS 50™	ASTM C-920, Type S Grade NS, Class 50, Use NT, AAMA 713-08, AAMA 808.3-10, TT-S-00230C

TWO-COMPONENT PRODUCTS

URETHANES Utilizes the Flex-Pak Colorant System	SPECIFICATIONS
Bostik 505™	ASTM C-920, Type M Grade NS, Class 25, Use T, G, A, M, TT-S-00227E
Bostik 555-SL™	ASTM C-920, Type M, Grade P, Class 25, Use T, G, A, M, TT-S-00227E

NOTE: For all two-component products refer to the Two-Component Color Chart T1541
For the remaining one-component products refer to the One-Component Color Chart T1540

COLORS AVAILABLE

ONE-COMPONENT PRODUCT	CLEAR (TRANSLUCENT)	WHITE	ANTIQUÉ WHITE	STONE	ALUMINIUM STONE	LIMESTONE	ALMOND	TAN	CAPITAL TAN	DESERT TAN	MEDIUM BRONZE	BRONZE	TERRA COTTA	ALUMINIUM GRAY	LIGHT GRAY	BLACK
Bostik 900™		•	•	•		•		•			•	•				•
Bostik 915™		•		•	•	•		•			•	•	•			•
Bostik 915FS™		•	•	•		•			•		•	•	•	•	•	•
Bostik 916™		•		•	•	•	•	•			•	•				•
Bostik 955-SL™						•										•
Bostik PRO-MS 50™		•	•	•		•			•	•	•	•	•	•	•	•
Bostik 1200™	•	•														•
Bostik 1250™	•															
Bostik 2000™ SMOOTH		•		•			•	•				•				
Bostik 2000™ TEXTURED		•														
Bostik 2020™		•		•				•				•				•

NOTE 1: Color may vary slightly from color chips, batch-to-batch and product-to-product because of the differences and variances in base polymers and raw materials.

NOTE 2: Please refer to the Technical Data Sheets for detailed installation guides prior to the use of our products.

NOTE 3: For colors other than those depicted in the chart above, please contact your Bostik Sales Representative.

COVERAGE CHART

Depth	Cartridge / Sausage	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	10.1 oz. cartridge	97	49	32	24	19	16	13	12
	28 oz. cartridge	267.8	134	88.3	66	54	44.6	37	33.5
	20 oz. sausage	192	97	63	48	39	31	27	24
1/4"	10.1 oz. cartridge		24	19	12	9	7	6	5
	28 oz. cartridge		66	54	33.5	27	21	19	16
	20 oz. sausage		48	39	24	19	15	14	12
3/8"	10.1 oz. cartridge			10	7	6	5	4.5	4
	28 oz. cartridge			29.7	21.3	17.6	14.8	12	8
	20 oz. sausage			2.1	15	11	10	9	7
1/2"	10.1 oz. cartridge				5.5	5	4	3.5	3
	28 oz. cartridge				16.3	13.5	10.7	9.3	7.4
	20 oz. sausage				11	10	8	7	5

NOTE: All values are approximations and can vary due to the joint dimension variations, porosity, and texture of the substrates.