Greenbox Liquid Tank Containers

GTO-20

Product Information

- Insulated, cylindrical stainless steel vessel.
- Transports via ship, rail, and road.
- ISO stackable up to 8 high.
- Bottom or top discharge.
- Walkable roof with access ladder.
- Designed to carry oils, chemicals, and food grade liquids
- CSC, ABS, AAR, TIR, / Customes, UIC certifiable.
- Can be customized to meet special requirements.



[GTO-20]

Capacity25000 liters5812 gallonsTare3500 KG7716 lbs.UsageOils, Chemicals, & Food grade liquidsMax. weight36000 KG79366 lbs.

Size 20ft

Compartments 1 / Vacuum tank

Heating system Steam Heating

Cladding type 2 mm GRP
Steel thickness 4.4 mm
Test pressure 6.0 Bar
Work pressure 4.0 Bar

Airline 1,5" BSP DN 40 Ball Valve

Insulation Rockwool on aluminum foil. Glasswool ends.

Discharge typeBottom / TopMaterialStainless steel 316

Certificate IMDG, US DOT CFR 49, RID/ADR, CSC, TC, TIR / Customs, UIC, ISO

1496/3

Disclaimer

- 1. All figures and calculations are based on the best information currently available.
- 2. Above information should be solely used as a reference as all Greenbox units are manufactured and designed to meet each customer's need.
- 3. Greenbox containers are material specific. Actual capacity and rating will vary greatly depending on the degree of customization with utilization of materials and the mechanicals adopted.









