

YnW Pure Stock Mini Cars 2026

1. Any front wheel drive automobile 110 in wheel base or smaller
2. Any rear wheel drive with a 107 in wheel base and smaller
3. 4 point cage and roll over bar is allowed, door bars no bigger then 2x4 and need to end 2 inches past the door post and be 8 inches off of the firewall, cross bars no bigger then 3x3. You can weld a gas tank holder but not a protector off rear bar behind the seat. 8 inches off rear package tray. All cage components need to have an 8 inch gap off any floor pan. No gussets off of any cage bar, just a simple 4 point cage.
4. Stock pedals, stock shifter, stock steering
5. You may single bead weld the struts for ride height or strut risers in the front or rear.
6. You may run a header but no protectors
7. no added coolers or water supply of any kind.
8. factory bumper for that car your running and bumper covers must be all the way removed, no tape, foam or anything on the bumper. Only welding on the bumpers are just to be welded directly to the frame with no metal added. You cannot shorten the frame in any way, crush points must stay on as well. Any signs that it has been manipulated with be automatic DQ.
9. Any wheel and tire
10. Wire or chain doors in 12 spots total, you may wrap the posts with duct tape. Drivers door can have a plate for safety over it. 12 inches tall 1/8 thick and can overlap the door seam by 2 inches.
11. Wire or chain the trunk and hood in 8 total spots. No allthread anywhere holding anything down.
12. You may have a battery box secured in the pass side of the car but cannot reinforce the car at all.
13. Front windshield bar is required or 9 wire in its place is fine as well. Has to mount within 2 inches of where the factory windshield sits. You can not have a rear windshield bar.

These rules are simple and they will be enforced to stay simple, if it's not covered that means you can not do it. This is an entry level class made to be very affordable.