



Technical Data Sheet

Product Description

BioFlo Eco 100 by BioFlo Technologies is the most effective non-toxic solvent on the market today for the elimination of difficult organic deposition (paraffin and asphaltene) in oil and gas wells, pipelines, and storage tanks. BioFlo Eco 100 works as effectively as toluene and xylene-based products but is biodegradable, non-carcinogenic, and non-toxic.

BioFlo Eco 100 can be used for onshore and offshore applications and has no harmful or long-lasting effects to aquatic ecosystems.

BioFlo Eco 100 is suitable for any difficult application that requires a cleaner and safer solution than what standard aromatics-based solvents can provide.

Physical Properties	Value
Flash Point (Tag CC)	149.20°F / 65.11°C
Boiling Point	380.40°F / 193.56°C
Pour Point	-92.90°F / -69.39°C
Specific Gravity 60°F/60°F	0.81
Density, lbs/gal @ 60°F	6.72
Average Molecular Weight	157.85
Relative Evaporative Weight	0.09
Vapor Pressure, torr @ 20°C	0.32
Viscosity cSt @ 20°C	1.92
Kauri-Butanol Value	33.75

BioFlo Technologies

BioFlo Technologies has been serving customers with comprehensive solutions since 2010. Our bilingual staff has extensive experience in every facet of the Oil and Gas industry. Please enquire for additional information in English or Spanish.

BioFlo Eco 100 Safety Data Sheet (SDS) available on request.

Contact Information

BioFlo Technologies, LLC

200 Crandon Blvd, Suite 203

Key Biscayne, FL 33149

+1 (305) 735-9991

info@bioflotech.com

