



Technical Data Sheet

Product Description

BioFlo Eco 200 by BioFlo Technologies is a high flash point, non-toxic solvent for eliminating difficult paraffin and asphaltene deposits in oil and gas wells, pipelines, and storage tanks. BioFlo Eco 200 has a flash point of over 200 F, is not considered flammable or combustible.

BioFlo Eco 200 is suited for applications that require a non-toxic solution and where a higher risk of spark exists or higher temperatures are present. BioFlo Eco 200 stays in solution through steam cycles and in wells with high downhole temperatures much better than low flash point aromatic solvents.

BioFlo Eco 200 is the safest, cleanest solvent on the market today.

Physical Properties	Value
Flash Point (Tag CC)	203.80°F / 95.44°C
Boiling Point	437.60°F / 225.33°C
Pour Point	-78.60°F / -61.44°C
Specific Gravity 60°F/60°F	0.82
Density, lbs/gal @ 60°F	6.83
Average Molecular Weight	181.90
Relative Evaporative Weight	0.03
Vapor Pressure, torr @ 20°C	0.12
Viscosity cSt @ 20°C	3.41
Kauri-Butanol Value	30.50

BioFlo Technologies

BioFlo Technologies has been serving customers with comprehensive solutions since 2010. Our bilingual staff has extensive experience in every facet of the Oil and Gas industry. Please enquire for additional information in English or Spanish.

BioFlo Eco 200 Safety Data Sheet (SDS) available on request.

Contact Information

BioFlo Technologies, LLC

200 Crandon Blvd, Suite 203

Key Biscayne, FL 33149

+1 (305) 735-9991

info@bioflotech.com

