

POWERFUL SOLUTIONS



3RD Floor SUSHEDEN Bldg.
LOTUS St. T..S. Cruz Subd.
Almanza Las Pinas City

Phone: 632 88428942
Fax: 632 88428941
E-mail: susheden@tri-isys.com

SUSHEDEN MARKETING INC.

▶ **HARNESING THE SUN'S ENERGY**



- **PUTTING THE BEST LIGHT FORWARD**
- **FRIENDLY**
- **ECONOMICAL**
- **COVERTING ENERGY FROM THE SUN TO A CAREFREE LIGHT**
- **ECOFRIENDLY**
- **COST EFFICIENT STREET LIGHT**



**SOLAR POLE POST
AND BASE**





SOLAR LAMP AND LAMP POST SPECIFICATION

ALL IN ONE INTERGRATED SOLAR STREET LIGHT		MODEL: SM40200-15
SOLAR PANEL	MAX POWER	40W/10V (POLY SILICON SOLAR PANEL)
	<u>LIFETIME</u>	<u>25 YEARS</u>
LED LAMP WITH PIR SENSOR	MAX POWER	200W
	LED BRAND	KINGBRIGHT
	LUMEN (LM)	4650 lm
	LIFE TIME	50000 HOURS
	COLOR	RENDERING INDEX (Ra) > 72
	VIEWING ANGLE	165
BATTERY	TYPE	12V / 36000 mA LITHIUM BATTERY
	LIFETIME	5 YEARS
CHARGE TIME	BY SUN	5- 6 hours (With Good Sunlight)
DISCHARGE TIME	FULL POWER	MORE 30- 40 hours
WORKING TEMPERATURE	RANGE °C	20°C-60°C
COLOR TEMPERATURE	RANGE (K)	2700-6500K
MOUNTING HEIGHT	RANGE (M)	15 ft. or 20 ft.
SPACE BETWEEN LIGHT	RANGE (M)	25-30M
MAIN MATERIAL OF LAMP	ALUMINUM ALOY	
CERTIFICATE	CE / ROHS/ IP65/ IES	
WARRANTY PERIOD	3 YEARS	
LAMP POST		4"X2" x 15 FT Round Steel tapered lamp post
		ELECTRO GALVANIZED, 10x10" base plate, 3/4 x20"
		anchor bolt, nuts and flat washer

High Quality
and affordable,
All-in-one
Decorative
Solar street
Light





SOLAR LAMP AND LAMP POST SPECIFICATION

ALL IN ONE INTERGRATED SOLAR STREET LIGHT		MODEL: SM40200-20
SOLAR PANEL	MAX POWER	40W/10V (POLY SILICON SOLAR PANEL)
	<u>LIFETIME</u>	<u>25 YEARS</u>
LED LAMP	MAX POWER	200W
WITH PIR SENSOR	LED BRAND	KINGBRIGHT
	LUMEN (LM)	4650 lm
	LIFE TIME	50000 HOURS
	COLOR	RENDERING INDEX (Ra) > 72
	VIEWING ANGLE	165
BATTERY	TYPE	12V / 36000 mA LITHIUM BATTERY
	LIFETIME	5 YEARS
CHARGE TIME	BY SUN	5- 6 hours (With Good Sunlight)
DISCHARGE TIME	FULL POWER	MORE 30- 40 hours
WORKING TEMPERATURE	RANGE °C	20°c-60°c
COLOR TEMPERATURE	RANGE (K)	2700-6500K
MOUNTING HEIGHT	RANGE (M)	15 ft. or 20 ft.
SPACE BETWEEN LIGHT	RANGE (M)	25-30M
MAIN MATERIAL OF LAMP	ALUMINUM ALOY	
CERTIFICATE	CE / ROHS/ IP65/ IES	
WARRANTY PERIOD	3 YEARS	
LAMP POST		4"X2" x 20 FT Round Steel tapered lamp post
		ELECTRO GALVANIZED, 10x10" base plate, 3/4 x20"
		anchor bolt, nuts and flat washer



SOLAR LAMP AND LAMP POST SPECIFICATION

ALL IN ONE INTERGRATED SOLAR STREET LIGHT		MODEL: SM49400-15
SOLAR PANEL	MAX POWER	40W/10V (POLY SILICON SOLAR PANEL)
	LIFETIME	25 YEARS
LED LAMP WITH PIR SENSOR	MAX POWER	300W
	LED BRAND	KINGBRIGHT
	LUMEN (LM)	4940 LM
	LIFE TIME	50000 HOURS
	COLOR	RENDERING INDEX (Ra) > 72
	VIEWING ANGLE	165
BATTERY	TYPE	12V / 36000 mA LITHIUM BATTERY
	LIFETIME	5 YEARS
CHARGE TIME	BY SUN	5- 6 hours (With Good Sunlight)
DISCHARGE TIME	FULL POWER	MORE 30- 40 hours
WORKING TEMPERATURE	RANGE °C	20°C-60°C
COLOR TEMPERATURE	RANGE (K)	2700-6500K
MOUNTING HEIGHT	RANGE (M)	15 ft. or 20 ft.
SPACE BETWEEN LIGHT	RANGE (M)	25-30M
MAIN MATERIAL OF LAMP	ALUMINUM ALOY	
CERTIFICATE	CE / ROHS/ IP65/ IES	
WARRANTY PERIOD	3 YEARS	
LAMP POST		4"X2" x 20 FT Round Steel tapered lamp post
		ELECTRO GALVANIZED, 10x10" base plate, 3/4 x20"
		anchor bolt, nuts and flat washer



SOLAR LAMP AND LAMP POST SPECIFICATION

ALL IN ONE INTERGRATED SOLAR STREET LIGHT		MODEL: SM49400-20
SOLAR PANEL	MAX POWER	40W/10V (POLY SILICON SOLAR PANEL)
	LIFETIME	25 YEARS
LED LAMP WITH PIR SENSOR	MAX POWER	300W
	LED BRAND	KINGBRIGHT
	LUMEN (LM)	4940 LM
	LIFE TIME	50000 HOURS
	COLOR	RENDERING INDEX (Ra) > 72
	VIEWING ANGLE	165
BATTERY	TYPE	12V / 36000 mA LITHIUM BATTERY
	LIFETIME	5 YEARS
CHARGE TIME	BY SUN	5- 6 hours (With Good Sunlight)
DISCHARGE TIME	FULL POWER	MORE 30- 40 hours
WORKING TEMPERATURE	RANGE °C	20°c-60°c
COLOR TEMPERATURE	RANGE (K)	2700-6500K
MOUNTING HEIGHT	RANGE (M)	15 ft. or 20 ft.
SPACE BETWEEN LIGHT	RANGE (M)	25-30M
MAIN MATERIAL OF LAMP	ALUMINUM ALOY	
CERTIFICATE	CE / ROHS/ IP65/ IES	
WARRANTY PERIOD	3 YEARS	
LAMP POST		4"X2" x 20 FT Round Steel tapered lamp post
		ELECTRO GALVANIZED, 10x10" base plate, 3/4 x20" anchor bolt, nuts and flat washer



SUSHE DEN MARKETING INC.
 3rd Floor SUSHE DEN Bldg. Lotus St. T.S Cruz Subd,
 Almanza Dos, Las Pinas City



SOLAR LAMP AND LAMP POST SPECIFICATION

ALL IN ONE INTERGRATED SOLAR STREET LIGHT		MODEL: SM49400-20-1
SOLAR PANEL	MAX POWER	40W/10V (POLY SILICON SOLAR PANEL)
	LIFETIME	25 YEARS
LED LAMP WITH PIR SENSOR	MAX POWER	300W
	LED BRAND	KINGBRIGHT
	LUMEN (LM)	4940 LM
	LIFE TIME	50000 HOURS
	COLOR	RENDERING INDEX (Ra) > 72
	VIEWING ANGLE	165
BATTERY	TYPE	12V / 36000 mA LITHIUM BATTERY
	LIFETIME	5 YEARS
CHARGE TIME	BY SUN	5- 6 hours (With Good Sunlight)
DISCHARGE TIME	FULL POWER	MORE 30- 40 hours
WORKING TEMPERATURE	RANGE °C	20°c-60°c
COLOR TEMPERATURE	RANGE (K)	2700-6500K
MOUNTING HEIGHT	RANGE (M)	15 ft. or 20 ft.
SPACE BETWEEN LIGHT	RANGE (M)	25-30M
MAIN MATERIAL OF LAMP	ALUMINUM ALOY	
CERTIFICATE	CE / ROHS/ IP65/ IES	
WARRANTY PERIOD	3 YEARS	
LAMP POST		4"X2" x 20 FT Round Steel tapered lamp post ELECTRO GALVANIZED, 10x10" base plate, 3/4 x20" anchor bolt, nuts and flat washer