Chapter 7 Quiz

Name:	Date:		
Directions:	Write the correct letter on the blank before each question.		
	 Life safety rope should be used to: (277) A. rescue victims. B. secure a ladder in place. C. hoist a saw to a second story window. D. cordon off an emergency incident scene. 		
	 Natural fiber ropes are: (278) A. resistant to mildew, mold, and shrinkage. B. permitted to be used for utility applications. C. less resistant to sunlight than synthetic ropes. D. permitted to be used for life safety applications. 		
	 Which type of rope construction is used for life safety ropes? (279) A. Laid B. Braided C. Kernmantle D. Braid-on-braid 		
	 4. What should be done if an inspection reveals that a rope has shards of glass or other foreign objects imbedded in it? (282) A. Remove the rope from service and have it destroyed. B. Remove the debris and document it in the rope log. C. Notify the supervisor and place the rope back in service. D. Continue using the rope until new rope can be purchased. 		
	 What should be done in order to ensure that ropes remain in good condition? (284) A. Keep all ropes away from rust. B. Paint the ends to prevent unraveling. C. Coil the rope in the same direction every time. D. Clean the rope with strong chemicals to remove grease. 		

	6.	Which type of webbing is commonly used for rescue applications? (286)
		A. Flat webbingB. Braided webbingC. Tubular webbingD. Kernmantle webbing
<u> </u>	7.	Which part of the rope is used to tie a knot? (287)
		A. Hitch endB. Working endC. Running partD. Standing part
	8.	A is a bend in the knot that is created by bending the rope back on itself while keeping the sides parallel. (288)
		A. loopB. hitchC. bightD. round turn
	9.	Which knot is used to provide an extra level of protection when tying other types of knots? (288)
		A. Water knotB. Clove hitchC. Figure-eight knotD. Overhand safety knot
	10.	A(an) knot is primarily used to attach a rope to an object such as a pike pole or hoseline. (288)
		A. clove hitchB. figure-eightC. overhand safetyD. figure-eight bend
	11.	The Occupational Safety and Health Administration (OSHA) prohibits using rope to hoist: (291)
		A. axes.B. saws.C. empty SCBA cylinders.D. pressurized SCBA cylinders.

-	12.	A is used to control equipment that is being hoisted by preventing it from spinning or snagging. (291)
		A. leverB. pulleyC. tag lineD. carabiner
	13.	How can utility rope be used during rescue operations? (295)
		A. RapellingB. Lifting rescuersC. Marking control zone perimetersD. Removing victims from swift water