

#### Interactive PDF

Version 2.0

|   | ••••••     |
|---|------------|
| PAGE NAVIGATION                         | <b>← →</b> |
| ••••••••••••••••••••••••••••••••••••••• |            |
| INTERNET LINK                           | k          |
|   | ••••••     |
| VIDEO/ANIMATION                         | ►          |
|   |            |

We make it visible.

ZEINS

# Experience creates trust. Today as in the past.

#### Corona extreme

The new spectrometer system for agribusiness from ZEISS

Introduction
 Applications
 Benefits
 Technology
 Software

> Tutorials

Technical Specifications



Successful agriculture production has always been a question of experience and commitment. Wrong decisions can have serious consequences. In today's ever changing environment, nature cannot be fully planned and accurate results cannot always be determined. However, through targeted examination of the process, it can be analyzed better.

With over twenty years of experience in process technology, ZEISS is one of the world leader in the measurement and analysis of continous process applications.

Through continuous collaboration with our customers, we have developed solutions which meet the highest performance demands, for which our customers can depend on in any process oriented situation. With acknowledged ZEISS competence in hardware, software and engineering, we are able to produce complete systems which can withstand extreme conditions with results that superior to lab measurements

Extremely resilient, extremely precise and extremely reliable – the new Corona extreme.



# High time for a solution. The new Corona extreme.

#### Corona extreme

The new spectrometer system for agribusiness from ZEISS

| > | Introd | luction |
|---|--------|---------|

| > | Applications |
|---|--------------|
| , | Applications |

```
Benefits
```

Technology

.....

Software

> Tutorials

|   | Tochnical | Spacifications |
|---|-----------|----------------|
| , | recinical | Specifications |

The quality of natural products is subject to natural fluctuations. Despite the inconsistency in the construction of the sample, consistent quality must be maintained in the final product. In addition, industry standard requirements for processing the materials and related documentation must be maintained. For this to be achieved accurate process control is essential. Process time and raw materials cost can be optimized so that production control can be maximized and waste can be minimized.





Continuously monitoring of samples can delivers much more information about the process. When the measurements are carried out in real-time with the precision of lab results, the process can be precisely optimized to maximize output. The seamless intergration of data into the information streams (traceability) also increases product safety.

With the introduction of the Corona extreme, we are offering our customers a complete solution comprising a spectrometer sensor and intuitive software – which can be tailored to each customers' specific needs.

Applications specific calibration and calibration support can be provided upon request.

# **Customers applications to date. Corona extreme.**

#### Corona extreme

The new spectrometer system for agribusiness from ZEISS

#### > Introduction

## > Applications

- > Benefits
- > Technology
- > Software
- > Tutorials
- ------

# > Technical Specifications

| Field testing/ seed cultivati | on |
|-------------------------------|----|
|-------------------------------|----|

| Application | analysis on plot harvester              |
|-------------|---|
| Products    | full maize plants, grass, unripe rye    |
|             | and wheat, grains such as wheat, rye,   |
|             | rapeseed, grain corn                    |
| Parameters  | determination of dry matter content     |
|             | and protein                             |
| Result      | determination of quality, yield mea-    |
|             | surement, evaluation of cultivation     |
|             | success during field harvests, cultiva- |
|             | tion of new varieties                   |

## Cereals trade

| Application | inspection at transshipment points   |
|-------------|--------------------------------------|
| Products    | grains such as wheat                 |
| Parameters  | measurement of moisture, protein,    |
|             | gluten, hardness, determination of   |
|             | quality                              |
| Result      | sorting, drying and storage, sale in |
|             | accordance with specification        |
|             |                                      |

## Grain processing

| Application | measurement on delivery             |
|-------------|-------------------------------------|
| Products    | grains such as wheat                |
| Parameters  | measurement of moisture, protein,   |
|             | gluten, hardness                    |
| Application | measurement during processing       |
| Parameters  | measurement of moisture, protein    |
|             | content, ash content and starch for |
|             | process control                     |
| Result      | guarantee of quality                |







## Corona extreme

The new spectrometer system for agribusiness from ZEISS

## > Introduction

> Applications

- > Benefits
- > Technology

Software

> Tutorials

>

. . . .

# > Technical Specifications

| Application | measurement on delivery                 |
|-------------|---|
| Products    | maize silage, grass silage, whole plant |
|             | silage (renewable resources), liquid    |
|             | manure, residual materials              |
| Parameters  | evaluation based on potential gas       |
|             | input – gas generation potential        |
| Application | measurement during process              |
| Parameters  | stability of fermentation based on      |
|             | individual acids                        |
| Result      | process control and optimization        |
|             | (room load, retention period)           |

# Feeding stuff / animal feed

| Application | measurement on delivery                 |
|-------------|---|
| Products    | feeding stuff / animal feed             |
| Parameters  | measurement of energy content           |
|             | (proteins, fiber fractions such as ADF, |
|             | NDF, lignin, cellulose, hemicellulose)  |
| Result      | process control and optimization        |
|             | (mixing processes) for the production   |
|             | of concentrated feed                    |
|             |   |

## Fertilization

| Application | measurement during or before spreading    |
|-------------|---|
| Products    | farmyard manure                           |
| Parameters  | measurement of nitrogen, ammoniacal       |
|             | nitrogen, phosphorous, potassium          |
| Result      | process optimization, compliance with     |
|             | legal stipulations, process optimization, |
|             | saving the cost of chemical fertilizers   |
|             | and targeted spreading in order to        |
|             | influence the quality of the harvest      |



# Precision decides. Every day, in real-time.

#### Corona extreme

The new spectrometer system for agribusiness from ZEISS

Introduction
 Application

> Benefits

Technology

.....

Software

> Tutorials

**Technical Specifications** )



# READY FOR EXTREMES

Few other spectrometer system from ZEISS incorporates as much application-related experience as the new Corona extreme.

This compact system is easy to install and may be used immediately after a short warm-up period.

The Corona extreme system can be operated independently using the embedded controller which enables a direct evaluation and output of the predicted data.

The spectrometer features fiber free, high energy illumination with outstanding optical properties and internal referencing.

Thus, reliable measurement results are provided for each sample. Within the Corona product family, the instrument calibration may be transferred from one measurement system to another. The instrument data communication are designed for a customer or user specific interface: ISO Bus, Ethernet, Digital IO.

# Reliability creates safety. Today, tomorrow and in the future.

#### Corona extreme

The new spectrometer system for agribusiness from ZEISS

| > Introduction |
|----------------|
|----------------|

| > / | Applicat | ions |
|-----|----------|------|
|-----|----------|------|

```
> Benefits
```

> Software

> Tutorials

> Technical Specifications

The idea for creating the Corona extreme was for the measuring sensor to become a core component of the process.

In order to accomplish this the extreme conditions under which processes run a were regarded as a the normal environment for the spectrometer system in practice – and not just for short term use, but for the entire product life cycle. For the Corona extreme, this concept was so successful that it gave the system its name. The integrated measuring head and the compact design incorporating a sapphire flange guarantees protection of the sensor at the interface with the material flow. The Corona extreme is designed to withstand shock values which exceed governental standards. With 50 g shock resistance, it exceeds all other systems by far and is ideally suited for daily use in the field.

The layout of the other environmental parameters has also been designed in accordance with the possible applications. This means that Corona extreme can precisely produce measurement data in temperatures ranging from -15 to +50°C in both moist and dusty conditions.

The spectrometer system is protected from supply voltage fluctuations and may be easily connected to a vehicle's on-board power supply. Due to its excellent optical design, the Corona extreme can also be used in labs.



Technology

# Corona extreme

The new spectrometer system for agribusiness from ZEISS

| •••••• |              |
|--------|--------------|
| >      | Introduction |

| > | Applications |  |
|---|--------------|--|

.....

- > Benefits
- > Technology

.....

> Software

.....

- Tutorials
- > Technical Specifications





## 1 Spectrometer

- plane grating spectrometer (PGS)
- internal b/w referencing
- two versions (with and without embedded PC)

## 2 Housing

■ IP 66 housing

# Interfaces

3

4

- innovative plug design
- Ethernet interface, optional ISO BUS (CAN BUS)

# Measuring head

- low voltage halogen lamps, longer service life 20.000 hours
- robust sapphire flange for connection to harvesting machinery and closed systems

# User-friendly and powerful. InProcess.

#### Corona extreme

The new spectrometer system for agribusiness from ZEISS

| ••••••   |              |
|----------|--------------|
| >        | Introduction |
| <b>.</b> |              |
| >        | Applications |

> Applications

Benefits

> Technology

.....

> Software

>

> Tutorials

.....

```
> Technical Specifications
```



# The InProcess software was developed specially for Corona extreme.

This software enables the user to control several spectrometers at the same time. In addition to performance, ease of use is the primary purpose of the software strategy. Thanks to its clear organization, it is intuitive to use for all levels of operators.

The graphic user interface is comprised of icon menus giving it a familiar feel of operation at first sight. In addition, users may configure sequences, calculations and display formats based on their individual requirements.

# Simple, intuitive, efficient.

#### Corona extreme

The new spectrometer system for agribusiness from ZEISS

> Introduction

#### > Applications

- > Benefits
- > Technology
- .....

## > Software

| > IULONAIS | > | Tutorials |
|------------|---|-----------|
|------------|---|-----------|

> Technical Specifications

#### Measurement menu

- access to "defined products"
- immediate start of measurement
- display of measurement as value, graph or spectrum
- display of limit values

#### Product set-up menu

- creation of "defined products"
- creation of measurement sequence
- calculation, evaluation and integration into higher-ranking process environment
- adjustment of views
- support of calibrations (chemometric models) which are produced using standard chemometric software e.g. by GRAMS, UNSCRAMBLER, UCAL
- control of events via Digital I/O

#### User management

setup of various user groups with different access levels

### **Measurement history**

- access to previous (completed) measurement runs
- file export

#### **Event history**





| 1 Administrator  | Infrocess Samilar  | 8                                  |
|--|--|------------------------------------|
| Event history  |  |                                    |
|  | (Ministration +) (Ministration +)  | Unaderswindged Drily               |
| <ul> <li>SESSELLEP.ScPA Measurement lystem</li> <li>Process controller Measurement lystem was also bed due to</li> </ul>   | Process solitative Measurent Types was admited fairt an Halfbelenselougien Open selences net acts an indexes of an dipot<br>La Halfbelense(Longlin: Open whereas wit acts an intervan if an illent.  | See                                |
| SECONTECTION     Index to initialize (Measurement and Andrecise) Service and     Advected galling (Measurement and         | (noli is ninka) Alexanentist Alexani (sona alexa (orgán el 15, forma alexa en anting leg<br>new longina el 15, forma antere anting leg   |                                    |
| <ul> <li>101/00111101 Par Measurement System</li> <li>Process controller Measurement System was also fed due to</li> </ul> | Process soft-file Measurement lyation was during during an insufficient dispersion software to when the<br>an insuffiguent information in pageneses and anomen   | les.                               |
| * 101001111119# Massementiples   | Garou where  |                                    |
| * 1010010.000P# Measuretlyten  | Pooes settile Measurent lyten vas dasted dar's ar baldericationplan Ecopior at '98' brans estena' (no settile) webe milipine   |                                    |
| * 121/2717/341P# Manusmettlyden  | Protect carbolin Mascument lystem was alored due to an StaderDosplice. In writing connection was buildly dowed by the write had  |                                    |
| * 10100173141 Par Manuscreet Spine   | Corrustere   |                                    |
| 0 1010014303PW   | Indek to initialize (SystelloperDarrol (or Systel (or) Source entered Systels 'W (or on external not initialized from specing connection to 'W) NELTITY 'W (or on external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W (or one external not initialized from specing connection to 'W) NELTITY 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing connection to 'W) (or one external not initialized from specing conection to 'W) | alout Temperint.                   |
| 0 101001430.00PM   | India to initialia (Diploty ad Darred Der Diplot II) Consultatione Diplatin VI Consultationer not initialized Error specing consistence for 1982 1982 1977. H Consultationer and initialized   | el Time periodica.                 |
| C REALIZING AND  | Inside to initially (Massementian). Reflective) (none externer: W) (none externer: not initialized. Error specing connection to 19); NJ 1117. No connection could be made because the two  | pri machine active.                |
| C STATISTICS N   | Unable to initialize/DigitalDedput/Darmel Der Digital Del Dorosa enterner Digitals. W Dorosa enterner not initialized Dror spening connection to TRE 1882-1177. W Dorosa enterner not initia   | and Trapetal.                      |
| 50.000 x 200 PM  | India to static (by larged and in-bytets) (now where by the Vincewatere of statical free garage structure is 'N NE 117. Hintewatere at static  | el Trespetelon.                    |
|  |  | <ul> <li>A share proved</li> </ul> |

# Take the time. Allow us to present the Corona extreme.

#### Corona extreme

The new spectrometer system for agribusiness from ZEISS

> Introduction

| > | Applications | 5 |
|---|--------------|---|

```
> Benefits
```

> Technology

Software

> Tutorials

> Technical Specifications

In terms of their functioning, the Corona extreme system's components have to meet very demanding requirements. The compact spectrometer system is extremely low maintenance and easy to service. The system's functionality is described in detail below.

#### First steps

- installation of the system
- measurement with an available product
- Watch it at youtube.com



- creation of a measurement sequence
- calculation (import calibration)
- display of the results
- display of limit values

Watch it at youtube.com





# **Technical Specifications**

### Corona extreme

The new spectrometer system for agribusiness from ZEISS

| > | Introduction |
|---|--------------|
| > | Applications |
| > | Benefits     |

```
> Technology
```

-----

Software

Tutorials

> Technical Specifications

|  | Corona extreme           |
|--|--------------------------|
| Spectrometer                                 | diode array spectrometer |
| Polychromator                                | PGS                      |
| Measurement range                            | 950 – 1650 nm            |
| Mean spectral pixel pitch                    | 3 nm                     |
| Spectral resolution (half width at 1/10 max) | ≤ 10 nm                  |
| Wavelength accuracy                          | ≤ 1 nm                   |
| Wavelength reproducibility                   | ≤ 0.1 nm                 |
| Light source                                 | halogen                  |
| Protection standard                          | IP 66                    |
| Dimensions W x H x D in mm                   | 256 x 190.5 x 253        |
| Weight                                       | 10 kg                    |
| Range of operating temperatures              | –15 °C to +50 °C         |
| Power supply voltage                         | 9-36 V SELV              |

## Corona extreme

The new spectrometer system for agribusiness from ZEISS

-----

> Introduction

Applications

> Benefits

> Technology

......

> Software

-----

Tutorials

> Technical Specifications

Carl Zeiss Spectroscopy GmbH Carl-Zeiss-Promenade 10 07745 Jena

CHILE Thera Ltda Phone: + 56 22417 7700 E-Mail: info@theraltda.com www.theraltda.com



