



















Co-Star 7.7m

STRONG BODY STRUCTURE



ANATOMY OF A GOOD BUS



POWER STEERING



PERSONALIZED INTEGRATED




REVERSE CAMERA

3-POINT PASSENGER SEAT BELT



HIGH PERFORMANCE JAPANESE TECHNOLOGY ENGINE



GETRAG 6 SPEED TRANSMISSION



JAPAN PROFICIENT TECHNOLOGY OF CHASSIS



STAINLESS STEEL WHEEL CASING



ELECTRIC FOLDING DOOR



REVERSE SENSOR



KEY FEATURES



Adjustable Driver Seat




















PERFORMANCE & SAFETY



HIGH PERFORMANCE JAPANESE TECHNOLOGY ENGINE




- Low Fuel Consumption
- Low Noise Design
- Reliable & Easy Maintenance

AIR BRAKE





Anti Lock Braking System



STRONG BODY STRUCTURE



- Close Ring Framework Body
- Full Length Welding Roof & Brazing.
- Anti Corrosion, Safe & Durable
- Euro Standard




Vehicle Cathodic Electrophoresis





- Bosch's high pressure common rail fuel injection
- Reasonable light-weight design
- Efficient low-emission design

OUTPUT (kW[HP]/rpm): 112[150]/2800 TORQUE (Nm/rpm): 382/1600~2800



GETRAG 6 SPEED TRANSMISSION

- German Technology
- Smooth Gear Shifting
- Low Noise Design



GEARBOX - GETRAG 6MTI420DA							
Speed Ratio	1st	2nd	3rd	4th	5th	6th	Rev
	5.979	3.434	1.862	1.297	1	0.759	5.701
Main Paduation Patio - 5 125							

Main Reduction Ratio: 5.125

CAM CO-STAR (JMV6770CFR) **ENGINE** Engine Model JX4D30A4H In line 4 Cylinder DOHC, 16 Valve Common Rail, Turbocharged **Engine Type** Intercooler Engine, Electronically Controlled. Displacement (L) 2.892 **Emission Standard EURO IV** 112[150]/2800 Rated Output (kW(PS)/rpm) Torque (N.m/rpm) 382/1600-2800 Fuel Diesel Fuel Tank Capacity (L) 90 **TECHNICAL DIMENSION** Overall LxWxH (mm) 7725 x 2050 x 2710 4435 Wheelbase (mm) 190 Min. Ground Clearance (mm) Wheel Thread (Front/Rear) mm 1665 / 1525 Front / Rear Overhang (mm) 1150 / 2140 **SEATING** 27+1 Seating Capacity MASS Curb Weight (kg) 4435 Gross Vehicle Weight (kg) 7500 **CHASIS & SUSPENSION** Steering Hydraulic Power Steering 8.4 Min. Turning Radius (m) Brake System ABS, Front Disc & Rear Drum Air Brake with Exhaust Brake & Load Sensing Proportional Valve Suspension System Non-independent, Leaf Spring (Front 3 / Rear 4) Wheel Size 7.50R16T, Rim:16:6J Tire 7.50R16T 14PR **ELECTRICAL** Battery 12V 14V / 150A Alternator **FEATURES & ACCESSORIES** Electric Folding Door Inner Luggage Rack & Top Handrail Reverse Sensor & Reverse Camera + Radar Luxury Synthetic Leather Seats + 3 Point Seat Belt **Emergency Exit With Roof Ventilator** Interior Cabin Lamp + Sliding Window

YEARS OR 100,000KM WARRANTY Whichever comes first

Stainless Steel Wheel Casing






Certified By

MP3 Player with 4 Speakers



SEAT LAYOUT



27+1 Seater (32 Passengers Capacity Including Standing)

DIMENSIONS



Side View



Side View (With Sliding Door)



Front View

NOTABLE APPLICATIONS



WORKER **TRANSPORT**



SCHOOL TRANSPORT



CITY COMMUTER BUS



MOBILE CLINIC



ENFORCEMENT BUS

CO-STAR CITY BUS & MODIFICATIONS ATTACHMENT



Barn Door Modification



Wheelchair Lift Add On

R&A MARKETING SDN BHD

CONSISTENT | ACTIVE | MOBILE Sole Distributor of CAM

Sendok Group Building, Lot 1564, Batu 4, 42100 Klang, Selangor Darul Ehsan, Malaysia. Email: info@sendokgroup.com Tel: +603-3345 5600 Fax:+03-3291 9658



M Sendok Group

Branch & Dealer Chop

Disclaimer: All features & specification shown in this brochure is subject to change without prior notice and may vary according to locality. The color(s) of the vehicle(s) and interior shown here in may slightly differ from actual vehicle.