




BE MORE PRODUCTIVE & PROFITABLE

Be it the need of printing short-runs or long-runs, labels requiring quick job change over versioning, variable data, security printing, Kolorsmart+ UV Inkjet Label Production Press is equipped with all the features required to perform most label printing application with accurate and quick spot color matching as well as consistent color reproduction.

Pre-Inkjet Flexo Station can be used for priming, coating or single-color printing along with up to 6-colors (W+CMYK+O) UV Inkjet unit, the combination of 4-step gray level printing, with specially formulated inks provide smooth natural gradations from highlights to shadows high-quality sharp texts and photo-quality images with fine details.



Higher Flexibility



High Quality



Great Value Addition



Profitability



Fast Turnaround Time



Increased Productivity

Kolorsmart+ brings the fastest return on investment and maximum profits to the label printers producing label in the most cost-effective ways with high-productivity of up to 50 m/min which enables label printers across the globe to grow faster.

TECHNICAL SPECIFICATION

Print Head	Piezo DoD, Gray scale
Web Width	Up to 350 mm
Speed	Up to 50 m/min
Drop Volume	3-14 pL (4 Gray level)
Substrate	40-200 um (Label paper supported, other materials - perform test)
Air Supply Requirement	Compressed Air, 6-8 Bar, Moisture & Oil Free
Ink Systems	Closed loop with Degas
Ink Tanks	5 Litres
Color	CMYK + White + Special color
Electrical Requirements	Standard 3 phase, 410-440 V, 50-60 Hz, 32 A
Ink Type	UV LED Curable, Hi-opacity White
Dimensions	4550 x 2175 x 2050 mm
Weight	1800 Kg

PRINT

What you need
When you need
How much you need

DIGITAL PRINT ENGINE

Print Width	Up to 324 mm (12.75")
Resolution	600 x 600 dpi native, @ 4 level gray scale, 600x1200 dpi Configurable
File Format	PDF, PDF/VT, TIFF, JPEG, BMP & other database files
Workflow	Advanced Colour Management & RIP Solution
Ink Curing	Inter Colour UV LED Pinning, Full Curing by UV LED / Arc Lamp with Chilled Drum Rollers

WEB CONTROL SYSTEM (Fully Servo Driven)

Unwinder Diameter	700 mm, core 76 mm
Rewinder Diameter	700 mm, core 76 mm
Other Accessories	Pre-Inkjet Flexo Station, Web Cleaner with Antistatic Bar, Corona Treater
Flexo Unit	Coating, Printing, Primer with UV Curing

ENVIRONMENTAL DATA

Optimal Temperature Range:	20-24°C (68-72-degree F)
Ink Storage	18-22°C (68-77-degree F)
Optimum Humidity Range	Humidity 40-60%, Non Condensing

INDUSTRY WIDE APPLICATIONS



Scan to know more



ThinAir Consulting
Cloud City Designs

40 West Littleton Blvd • Suite 210262 • 80120 USA

970.329.1001

303.594.8183



MONOTECH SYSTEMS LIMITED

Head Office : 8B, "Chaitanya Exotica", 24 Venkatnarayana Road, T. Nagar, Chennai - 600 017, Tamilnadu, India
Phone: +91 44 2815 7928/7894/7933, 4350 2232

R&D Center : B-15, InfoCity Phase 1, Sector 34, Gurugram-122 001, Haryana, India
Phone: +91 124 2371 771, +91 999 958 5324 Toll free (India): 1-800-102-4567
Email : jetsciglobal@monotech.in | www.jetsciglobal.com | www.monotech.in



monotechsyste.ms



monotechsyste.ms



monotechsyste.ms

