

LED BATTEN 3CCT SELECT

BTN320 / BTN340 / BTN360

The Lumax batten is an economical replacement for traditional fluorescent battens.

Able to be directly mounted to the ceiling and offering centre cable entry or through wiring to suit most applications.

Fitted with a shatterproof opal polycarbonate diffuser for wide and even lighting distribution.

The BTN series provides a flicker free lighting environment, with 3 colour selector switch and is suitable for most indoor applications.

Very simple installation and fitted with an efficient and reliable Tridonic driver.



Lumax	BTN320	BTN340	BTN360
Input	240V		
Body	Steel White paint		
Diffuser	Polycarbonate UV resistant		
Driver	Tridonic		
LED Diodes	Epistar		
Beam angle	120 deg		
Wattage	20W	40W	60W
Amps	0.1A	0.2A	0.3A
Lumen output	2000lm	4000lm	6000lm
Power Factor (PFC)	>.90		
CRI (Colour Rendering Index)	>80+		
CCT (Correlated Colour Temp)	3000K/4000K / 6500K		
IP Rating	IP20		
Dimensions	600x72x72	1200x72x72	1500x72x72
Cable entry	Centre entry/through wiring		
Gear tray	White steel		
Operating Temp range	-20+40 deg		
Electrical Class	Class I		
Warranty	5 years		

FITTING COLOURS:

White

INPUT VOLTAGE
240V



OUTPUT POWER
BTN320 **20W**
BTN340 **40W**
BTN360 **60W**



LUMENS
BTN320 **2,000**
BTN340 **4,000**
BTN360 **6,000**



COL TEMP
3,000K
4,000K
6,500K



WARRANTY
5 YEARS

