

LED 3CCT WIDE FLANGE DOWNLIGHT

BUTSON

The Lumax BUTSON downlight is suitable for all residential and commercial applications where high quality and reliable lighting is required, with a larger flange needed to cover existing installation marks

Utilizing 2835 SMD LEDs matched perfectly to our flicker free high frequency driver to ensure perfect light distribution and smooth dimming if required.

Able to be covered by thermal insulation meeting IC-F and IC-4 standards and easy to install.

The remote driver consists of large screw terminal connectors for ease of installation as well as looping possibilities if need.









SWITCH ON BACK OF LIGHT FITTING









Lumax	BUTSON
Input	240V
Body & Trim	Aluminium Die cast
Diffuser	PMMA Opal
Driver	Remote high frequency flicker free
LED Diodes	SMD2835
Beam angle	90 deg
Wattage	11 Watt
Dimmable	Phase cut-off
Lumen output	1000lm
Power Factor (PFC)	>.95
CRI (Colour Rendering Index)	>85+
CCT (Correlated Colour Temp)	3000K / 4000K / 5000K
IP Rating	IP65
Cut out	90mm
Height	33mm
Overall diam	120mm
Operating Temp range	-20+50 deg
Electrical Class	Class II
Warranty	5 years



WIDER

Flange

FITTING COLOURS:

White



INPUT VOLTAGE 240V

OUTPUT POWER



LUMENS

11W

1000



COL TEMP

3,000K 4,000K 5,000K



DIMMABLE **YES**



CUT HOLE **90MM**



WARRANTY **5 YEARS**

