

LED DOWNLIGHT

3CCT HIGH OUTPUT

DL313



Suitable for all residential and commercial applications where high quality, excellent colour rendering and high light output is required.

Very shallow recessing depth of only 35mm. Able to be covered by thermal insulation meeting IC-F and IC-4 standards and easy to install.

The remote driver is fitted, with a flex and plug for ease of installation. Very high lumen output suitable for high ceiling installations. The ThermoPlastic used in the housing and flange is suitable for under eaves and is resistant to salt air degradation.



LED COLOUR TEMPERATURE CHANGING

SWITCH ON BACK OF LIGHT FITTING



FITTING COLOURS:


White

| Lumax | DL313 |
|------------------------------|-----------------------|
| Body | ThermoPlastic |
| Diffuser | PMMA Opal |
| Driver | Remote |
| - Soft Start | ✓ |
| - Overload Protection | ✓ |
| - Short Circuit Protection | ✓ |
| LED Diodes | SMD 2835 |
| Beam angle | 120 deg |
| Wattage | 10 Watt |
| Dimmable | Phase cut-off |
| Lumen output | 1100lm |
| Power Factor (PFC) | >.90 |
| CRI (Colour Rendering Index) | >85+ |
| CCT (Correlated Colour Temp) | 3000K / 4000K / 6500K |
| IP Rating (Below Ceiling) | IP65 |
| Cut out | 90mm |
| Height | 35mm |
| Overall diam | 106mm |
| Operating Temp range | -20+50 deg |
| Electrical Class | Class II |
| Flex & Plug | Included |
| Warranty | 5 years |

INPUT VOLTAGE 
240V

OUTPUT POWER 
10W

LUMENS 
1100

ADJ COL TEMP 
3,000K
4,000K
6,500K

DIMMABLE 
YES

CUT HOLE 
90MM

WARRANTY 
5 YEARS