


# LED LOW GLARE ADJUSTABLE DOWNLIGHT

## DL6A

Smart, stylish, powerful and compact, this range incorporates the latest in IC technology to provide important alternatives for projects requiring reduced glare from a small aperture. Suited to highlight works of art and other features utilizing either 38° or 60° lens options which are included in the kit.

Able to be covered in approved thermal insulation and provided with quick connect terminals suitable for looping. Available in White and Black powder coated finish.



FITTING COLOURS:

Black



White



### LED COLOUR TEMPERATURE CHANGING SWITCH ON DRIVER


INPUT VOLTAGE  
**240V**

OUTPUT POWER  
**6.5W**

LUMENS  
**650**

COL TEMP  
**3000K**  
**4000K**  
**6000K**

DIMMABLE  
**YES**

CUT HOLE  
**68-78MM**

WARRANTY  
**3 YEARS**


Lumax	DL6A
Input	240V
Body	Die cast
Lens	Optical PC
Driver	Ingergral IC
LED Diodes	Samsung
Beam angle	38 or 60 deg Selectable Lens
Wattage	6.5Watt
Dimmable	Phase cut off/Triac
Lumen output	650 lumens
Power Factor Correction (PFC)	0.95
Colour temperature (3 CCT Switch)	3000K / 4000K / 6000k
IP Rating	IP44
Cut out	68-78
Height	45mm
Overall Diam	90mm
Connection	Quick fit supplied 2 x 2.5mm
Tilt	25 Deg
Electrical Class	Class II
Warranty	3 Years