

M-40 SPEEDWAY

Compact 2018 Rules

Body:

- 1. Must be subcompact, 4 cylinder front or rear wheel drive. Station wagons and pickups are allowed. No convertibles of 4 wheel drives. RWD cars must weigh 2400 lbs. FWD cars must weigh 2200 lbs.
- 2. Adjustable trailing arms ok. Racing shocks ok. Screw jacks allowed. Racing clutch ok.
- 3. Body must be sheet metal or aluminum and stock appearing. Pickups must enclose bed. Stock appearing aftermarket noses are allowed. Rear end must be enclosed. NO outlaw type bodies.
- 4. Doors must be welded or bolted shut. Fiberglass hood ok, no holes.
- 5. Must run full windshield. May be glass or lexan.
- 6. Maximum 6" spoiler no wider than rear deck.
- 7. Safely constructed 4 post cage with minimum 3 bars on driver's side and one bar on passenger side. Window net required.
- 8. Must have firewall between driver and engine AND driver and fuel tank.
- 9. Fenders may be trimmed for tire clearance only.
- 10. Hood and truck must be pinned. No bolting down.
- 11. Stock type A-arms, struts and ball joints only.
- 12. Cars must remain original track width as manufactured.
- 13. Aftermarket brake pedal assemblies allowed.
- 14. No coil-over type adjusters.
- 15. No quick change type or trick automatic transmissions or rear ends. 9 inch Ford rear end ok with 4 link.

Engine:

- 1. Engine must 4 cylinder, carb fed in stock location.
- 2. Single carburetors only, not to exceed 2 barrels. Maximum 1" spacer including gaskets. Holley 4412 Carburetor will be allowed. No reworking, grinding or altering carburetor in any way. Fuel injection allowed on FWD cars only.
- 3. Head must not be after market. After market intake ok.
- 4. Exhaust must be single and completely sealed and must exit behind driver. Headers will be allowed. 100 DB muffler mandatory.
- After market ignition system allowed. After market cap and wires allowed. 1 gal radiator overflow can
 M-40 SPEEDWAY Compact 2018 Rules
 required.

M-40 SPEEDWAY

Compact 2018 Rules

- 6. Fuel cells are strongly recommended. Fuel tank must be safely secure with 4 steel straps. If moving fuel tank into hatchback are or pickup bed, must have firewall between driver. Fuel cells must be enclosed in steel can.
- 7. Steel lines or braded hose must be used as fuel line from fuel tank to carburetor. No fuel line in cockpit area.

Tires and Wheels:

- 1. Maximum 8 inch steel wheels only.
- 2. Hoosier 790/850 or any 60-65-70-75-80 series radial (175-235). No recaps, McCreary or other aftermarket made for racing tires. NO tire soaking or compound enhancers allowed.

If you are legal at another track, you are legal at M-40. You must bring your rules and be registered at your home track to qualify. This is a one time pass only. If you decide to run for points at M40, you must meet M40 rules.

M40 Speedway reserves the right to alter these rules with reasonable notice.