









2 Leg Bridle

Capacity Rated in TONS

Diameter (Inches)	IPS		EIPS		IPS		EIPS		IPS		EIPS	
	Vertical		60°		45°		30°					
												
1/4	1.1	1.3	0.97	1.1	0.79	0.91	0.56	0.65				
5/16	1.7	2.0	1.5	1.7	1.2	1.4	0.87	1.0				
3/8	2.5	2.9	2.2	2.5	1.8	2.0	1.2	1.4				
7/16	3.4	3.9	2.9	3.4	2.4	2.7	1.7	1.9				
1/2	4.4	5.1	3.8	4.4	3.1	3.6	2.2	2.5				
9/16	5.5	6.4	4.8	5.5	3.9	4.5	2.8	3.2				
5/8	6.8	7.8	5.9	6.8	4.8	5.5	3.4	3.9				
3/4	9.7	11	8.4	9.7	6.9	7.9	4.9	5.6				
7/8	13	15	11	13	9.3	11	6.6	7.6				
1	17	20	15	17	12	14	8.5	9.8				
1-1/8	21	24	18	21	15	17	10	12				
1-1/4	26	30	22	26	18	21	13	15				
1-3/8	31	36	27	31	22	25	15	18				
1-1/2	37	42	32	37	26	30	18	21				
1-3/4	49	57	43	49	35	40	25	28				
2	64	73	55	63	45	52	32	37				
2-1/4	77	89	67	77	55	63	39	44				
2-1/2	94	109	82	94	67	77	47	54				
2-3/4	113	130	98	113	80	92	57	65				
3	133	153	115	133	94	108	67	77				

3 Leg Bridle

Capacity Rated in TONS

Diameter (Inches)	IPS		EIPS		IPS		EIPS		IPS		EIPS	
	Vertical		60°		45°		30°					
												
1/4	1.7	1.9	1.5	1.7	1.2	1.4	0.84	0.97				
5/16	2.6	3.0	2.3	2.6	1.8	2.1	1.3	1.5				
3/8	3.7	4.3	3.2	3.7	2.6	3.0	1.9	2.2				
7/16	5.1	5.8	4.4	5.0	3.6	4.1	2.5	2.9				
1/2	6.6	7.6	5.7	6.6	4.6	5.4	3.3	3.8				
9/16	8.3	9.6	7.2	8.3	5.8	6.8	4.1	4.8				
5/8	10	12	8.8	10	7.2	8.3	5.1	5.9				
3/4	15	17	13	15	10	12	7.3	8.4				
7/8	20	23	17	20	14	16	9.9	11				
1	26	29	22	26	18	21	13	15				
1-1/8	31	36	27	31	22	26	16	18				
1-1/4	39	44	33	38	27	31	19	22				
1-3/8	46	53	40	46	33	38	23	27				
1-1/2	55	63	48	55	39	45	27	32				
1-3/4	74	85	64	74	52	60	37	42				
2	95	110	83	95	68	78	48	55				
2-1/4	116	133	101	116	82	94	58	67				
2-1/2	141	163	123	141	100	115	71	82				
2-3/4	170	195	147	169	120	138	85	97				
3	200	230	173	199	141	162	100	115				





4 Leg Bridle

Product failure can result in INJURY OR DEATH. Product failure results from misuse, damage, and excessive wear. Responsibility lies with the user of these products. Adhere to industry standards and regulations.

WIRE ROPE SLINGS - MULTI LEG



Capacity Rated in TONS

Diameter (Inches)	IPS		EIPS		IPS		EIPS		IPS		EIPS					
	Vertical				60°				45°				30°			
																
1/4	2.2		2.6		1.9		2.2		1.6		1.8		1.1		1.3	
5/16	3.5		4.0		3.0		3.5		2.5		2.8		1.7		2.0	
3/8	5.0		5.7		4.3		5.0		3.5		4.1		2.5		2.9	
7/16	6.8		7.8		5.9		6.7		4.8		5.5		3.4		3.9	
1/2	8.7		10		7.6		8.8		6.2		7.1		4.4		5.1	
9/16	11		13		9.5		11		7.8		9.0		5.5		6.4	
5/8	14		16		12		14		9.6		11		6.8		7.8	
3/4	19		22		17		19		14		16		9.7		11	
7/8	26		30		23		26		19		21		13		15	
1	34		39		30		34		24		28		17		20	
1 1/8	42		48		36		42		30		34		21		24	
1 1/4	51		59		44		51		36		42		26		30	
1 3/8	62		71		54		62		44		50		31		36	
1 1/2	73		84		63		73		52		60		37		42	
1 3/4	98		113		85		98		70		80		49		57	
2	127		147		110		127		90		104		64		73	
2 1/4	155		178		134		154		109		126		77		89	
2 1/2	189		217		163		188		133		154		94		109	
2 3/4	226		260		196		225		160		184		113		130	
3	266		306		231		265		188		216		133		153	

Product failure can result in INJURY OR DEATH. Product failure results from misuse, damage, and excessive wear. Responsibility lies with the user of these products. Adhere to industry standards and regulations.