

Deck Toggle System

Responsibility lies with the user of these products. Always refer to your local building code prior to installing. Structural integrity of mounting surfaces are the responsibility of the installer. Cable railings are intended for architectural use only.

The strength of the cable assembly is limited to the screw strength and attaching base material.

Deck Toggle Turnbuckle – Stainless Tubular Bodies



Machine Swage

Thread (b)	Wire Size (c)	Body L (d)	Open L (e)	Closed L (e)	Screw Size (I)	Hole Spacing (k)
1/4-28 UNF	1/8"	4-1/4"	9-1/8"	6-3/8"	1/4"	1-1/2"
1/4-28 UNF	5/32"	4-1/4"	9-1/4"	6-1/2"	1/4"	1-1/2"
1/4-28 UNF	3/16"	4-1/4"	9-1/4"	6-1/2"	1/4"	1-1/2"
5/16-24 UNF	3/16"	4-3/4"	10-1/8"	7-1/8"	5/16"	1-3/4"
5/16-24 UNF	1/4"	4-3/4"	10-1/4"	7-1/8"	5/16"	1-3/4"
3/8-24 UNF	1/4"	5-1/4"	11-1/8"	7-3/4"	3/8"	2.0"

Handy Crimp

Thread (b)	Wire Size (c)	Body L (d)	Open L (e)	Closed L (e)	Screw Size (I)	Hole Spacing (k)
1/4-28 UNF	1/8"	4-1/4"	9-3/8"	6-5/8"	1/4"	1-1/2"
1/4-28 UNF	3/16"	4-1/4"	9-1/4"	6-1/2"	1/4"	1-1/2"
5/16-24 UNF	3/16"	4-3/4"	10-1/8"	7-1/8"	5/16"	1-3/4"

Hayn Grip Swageless Fittings

Thread (b)	Wire Size (c)	Body L (d)	Open L (e)	Closed L (e)	Screw Size (I)	Hole Spacing (k)
1/4-28 UNF	1/8"	4-1/4"	9-3/8"	6-5/8"	1/4"	1-1/2"
1/4-28 UNF	3/16"	4-1/4"	9-1/4"	6-1/2"	1/4"	1-1/2"

Deck Toggle Jaw



Machine Swage

Wire Size (c)	Length (e)	Screw Size (I)	Hole Spacing (k)		
1/8"	2-1/8"	1/4"	1-1/2"		
5/32"	1-7/8"	1/4"	1-1/2"		
3/16"	1-5/8"	1/4"	1-1/2"		
3/16"	2-1/8"	5/16"	1-3/4"		
1/4"	2.0"	5/16"	1-3/4"		
1/4"	2-1/8"	3/8"	2.0"		



Deck Toggle System

Responsibility lies with the user of these products. Always refer to your local building code prior to installing. Structural integrity of mounting surfaces are the responsibility of the installer. Cable railings are intended for architectural use only.

	~ :
Handy	(, ki ko k
IIaliav	OHILLO

Wire Size (c)	Length (e)	Screw Size (I)	Hole Spacing (k)
1/8"	2-1/8"	1/4"	1-1/2"
3/16"	1-13/16"	1/4"	1-1/2"

Hayn Grip Swageless Fitting

Wire Size (c)	Length (e)	Screw Size (I)	Hole Spacing (k)
1/8"	1-3/4"	1/4"	1-1/2"
3/16"	1-3/4"	1/4"	1-1/2"