


A -1338 Cradle Grab Hook

- · Forged Alloy Steel Quenched and Tempered.
- Innovative cradle design allows for 100% efficiency of Grade 100 chain.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby & U.S.A. in raised letters.
- · Suitable for use with Grade 100 and Grade 80 chain.
- The use of A-1338 Cradle Grab Hook will allow 100 percent of the chain sling capacity.
 When used to hook back to chain leg to form a choker, the angle of the choke must be 120 degrees or greater. When used as a chain shortener, minimize twist of chain and ensure chain is fully engaged in hook.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color Crosby Grade 100 Alloy Products."



L-1338 Cradle Grab Hook














A/L-1338 Cradle Grab Hook

Chain Size		Working Load	A-1338	L-1338	Weight	Dimensions (in.)						S-4338 Replacement
(in.)	(mm)	Limit (lbs.)*	Stock No.	Stock No.	Each (lbs.)	Α	В	С	D	Е	F	Latch Kit Stock No.
1/4	7	4300	1049417	1049480	.45	1.72	2.54	2.20	3.88	1.50	.88	1048426
5/16	8	5700	1049426	1049489	.99	1.72	2.54	2.18	3.88	1.50	.88	1048426
3/8	10	8800	1049435	1049498	1.80	1.85	3.09	2.58	4.69	1.83	1.09	1048435
1/2	13	15000	1049444	1049507	3.92	2.39	3.83	3.28	5.88	2.25	1.42	1048444
5/8	16	22600	1049453	1049516	7.00	2.67	4.52	3.85	7.03	2.94	1.75	1048453

 $[\]ensuremath{^*}$ Ultimate Load is 4 times the Working Load Limit.





A -1358 Grab Hook


- Forged Alloy Steel Quenched and Tempered.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby & U.S.A. in raised letters.
- · Suitable for use with Grade 100 and Grade 80 chain.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color Crosby Grade 100 Alloy Products."



L -1358 Grab Hook

В

D












A/L-1358 Grab Hook -

Chain Size		Working Load	A-1358	L-1358	Weight	Dimensions (in.)					S-4338 Replacement
(in.)	(mm)	Limit (lbs.)*	Stock No.	Stock No.	Each (lbs.)	Α	В	C	D	F	Latch Kit Stock No.
1/4	7	4300	1049610	1049605	1.00	1.72	2.54	2.20	3.88	.88	1048426
5/16	8	5700	1049629	1049614	.99	1.72	2.54	2.18	3.88	.88	1048426
3/8	10	8800	1049638	1049623	1.80	1.85	3.09	2.58	4.69	1.09	1048435
1/2	13	15000	1049647	1049634	3.92	2.39	3.83	3.28	5.88	1.42	1048444
5/8	16	22600	1049656	1049643	7.00	2.67	4.52	3.85	7.03	1.75	1048453
* Ultimate Load is 4 times the Working Load Limit.											



C