

OMTPA TECH FORM

OWNER: _____

DRIVER: _____

ADDITIONAL DRIVER: _____

TRACTOR: _____

- HELMENT
- FIRE SUIT/SHOES
- WHEELIE BARS NO HIGHER THAN 10" FROM GROUND FARTHEST POINT BEHIND REAR TIRES
- WHEELIE BARS ARE ABLE TO SUPPORT WEIGHT OF VEHICLE
- HITCH MUST PULL BELOW CENTER, NO MORE THAN 15 DEGREES FROM LEVEL. MUST HAVE SAFETY HITCH
- WHEELS AND LUG NUTS MUST ALL BE INTACT
- SKIDS OR SKIS MUST BE ABLE TO SUPPORT WEIGHT OF VEHICLE AND MUST BE LOWEST POINT BELOW THE FRONT AXEL
- SIDE SHIELDS ARE IN PLACE AND CORRECT THICKNESS
- DRIVE SHAFT SHIELDS AND RESTRAINTS ARE IN PLACE AND CORRECT THICKNESS
- KILL SWITCH/AIR SHUT OFF WORK AND ARE IN ACCESSIBLE LOCATION
- FIRE EXTINGUESTER SHOWS GREEN AND IS IN DRIVERS REACH
- DRIVERS RESTRAINTS OR SEATBELT ARE NOT TORN AND ARE WORKING CORRECTLY
- MUST HAVE DEADMAN THROTTLE
- TURBO COVERS AND SHIELDS/CROSSHATCH BOLTS OR SPACERS
- BELL HOUSING, TRANSMISSION COVER OR BLANKETS

OWNER PRINT: _____

OWNER SIGNATURE: _____

TECH SIGNATURE: _____ DATE: _____