



XERGUN 2800

PRODUCT DATA SHEET

XERGUN 2800 is a conventional, general purpose gun mix with less than 1% iron and is designed for applications up to 2800°F. Xergun 2800 is an economical alternative for applications including incinerators, reheat furnaces, power plants and mineral processing.

Maximum Service Temperature	2800°F
Water Required for Mixing (as a % of weight)	N/A %
Material Required Per Cubic Foot	128 - 137 lbs.
Packaging	64 - 55lb bags / pallet 1,000+lb Super Sacks

TYPICAL CHEMICAL ANALYSIS

Al₂O₃	SiO₂	CaO	TiO₂	Fe₂O₃	Alkalis
44.3	48.5	4.5	1.4	0.9	0.4

TYPICAL PHYSICAL PROPERTIES

Test Temperature (°F)	Bulk Density (pcf)	C.C.S. (psi)	CMOR (psi)	Apparent Porosity (%)	Permanent Linear Change (%)
220	127 - 133	4000	1200	----	-0.1 to 0.0
1500	121 - 126	5000	700	----	-0.3 to 0.0

Xertech Specialties
1422 Hoelzer Ct.
Dailey Industrial Park
Pacific, MO 63069
Ph: (636) 271-0586; Fax: (636) 271-0587

www.xertechllc.com
mail@xertechllc.com

Rel 06-19