

**Coleman 95.5% Efficient Gas Furnace**  
**Single Stage Gas Valve**  
**PSC Four Speed Blower Motor**  
**Model # TG9S**



Special Benefits -Compact 33" height and standard cabinet widths. Multi-position design with minimal conversion requirements. Airflow leakage rate of less than 2% of total airflow @ 1" ESP. PSC four-speed direct-drive motor with large, quiet blower. Fully supported, slide-out blower assembly for easy service access. Tubular aluminized steel primary heat exchanger. High-level self-diagnostic controls with fault codes. Fully gasketed, independent access doors with view ports. All models are propane convertible.

PSC: Permanent Split Capacitor Motor. Four Set Speeds. 100% On and 100% Off

2 to 5 Tons

40k to 120k BTU

Monthly Investment Payment as low as \$40 to \$50

Easy Access Installed \$ 3200-\$3500 Plus Tax

Attic or Crawl Space \$ 3350-\$3900 Plus Tax

**Coleman 96% Efficient Gas Furnace**  
**Two Stage Gas Valve**  
**ECM Blower Motor**  
**Model # TM9Y**



Special Benefits -Compact 33" height and standard cabinet widths. Multi-position design with minimal conversion requirements. Airflow leakage rate of less than 2% of total airflow @ 1" ESP. TM8Y uses advanced standard ECM motor for efficiency and comfort. Fully supported, slide-out blower assembly for easy service access. Tubular aluminized steel primary heat exchanger. High-level self-diagnostic controls with fault codes. Fully gasketed, independent access doors with view ports. All models are propane convertible.

ECM: Electronically Controlled Motor. Starts Slow and Increases Speed. Up to 50% Energy Savings From PSC Motors.

1st Stage Gas is Half the BTU's, 2nd Stage is full BTU's

Up to 15% Gas Savings

3 to 5 Tons

60k to 120k BTU

Monthly Investment Payment as low as \$45 to \$55

Easy Access Installed \$ 3400-\$3700 Plus Tax

Attic or Crawl Space \$ 3550-\$4050 Plus Tax

**Coleman 97.7% Efficient Gas Furnace**  
**Two Stage Gas Valve**  
**Modulating Variable Blower Motor**  
**Model # CP9C**



Special Benefits -Compact 33" height and standard cabinet widths. Multi-position design with minimal conversion requirements. Airflow leakage rate of less than 2% of total airflow @ 1" ESP. CP9C uses advanced modulating variable-speed ECM motor for efficiency and comfort. Fully supported, slide-out blower assembly for easy service access. Tubular aluminized steel primary heat exchanger. High-level self-diagnostic controls with fault codes. Fully gasketed, independent access doors with view ports. All models are propane convertible.

Modulating Variable Speed ECM: Electronically Controlled Motor. Starts Slow and Increases Speed to match desired air flow. Up to 65% Energy Savings From PSC Motors.

1st Stage Gas is Half the BTU's, 2nd Stage is full BTU's

Up to 35% Gas Savings Over Standard 80% Efficient Unit

3 to 5 Tons

60k to 120k BTU

Monthly Investment Payment as low as \$50 to \$60

Easy Access Installed \$ 3750-\$4000 Plus Tax

Attic or Crawl Space \$ 3950-\$4250 Plus Tax