

Fuel

Noise

Emissions

Maintenance







Enhanced Design Features

Power —

The Falcon Solar Light 201 harnesses the suns power through 3 extendable high grade solar panels that ensure maximum lighting performance and brightness.

Design Quality -

The Falcon Solar Light 201 has been manufactured with high grade steel and is powder coat painted to the highest standards and c/w certified high quality electrical components.

Security

The Falcon Solar lighting tower comes complete with galvanized retractable stabilizers for added security when in operation.

Easy Set Up -

The Falcon Solar lighting tower comes complete with automatic telescopic mast operated by a push button device conveniently located on the unit.

Our Mission

We design products that harvest clean energy, minimising the impact on the environment.

In line with the UK and European governments commitments of realizing zero net carbon by 2050, we are focused on reducing carbon emissions throughout our business and supply chains by bringing the most innovative and advance products to market in line with progress to a circular economy.



Features

Falcon Solar Light 201 is a compact and powerful portable solar lighting tower. The FSL-201 features 4 LED lamps which provides a brighter and more environmentally-friendly lighting system.

The innovative solar panel and trailer design make the FSL-201 easy to transport and set up without taking up valuable space.





Superior Features



Manually extendable & adjustable Solar PV panels designed to maximise the suns rays during day light hours



4 x 100W tiltable LED lighting system with 7m electrically extendable mast and 360° rotation head providing 2400 sq.m of lighting coverage



Intelligently designed electrical control panel display providing multiple user optimisation options

SECTORS



CONSTRUCTION



SPECIAL EVENTS



OIL, GAS & MINING



HARD TO REACH
AREAS



MILITARY

Advanced Security Features

WiFi Dual Light Source Smart Trackball Camera

- The Falcon Solar Light 201 also comes with WiFi operated CCTV security camera which comes with 3D humanoid detection to realize intelligent tracking .
- Support dual light function, move frame measurement trigger to turn on white light.
- Support motion detection alarm and push of abnormal pictures found.
- Built-in microphone and speaker function, which can realize two-way voice intercom.
- Support 18 times optical zoom, support full synchronization focus.
- Support IP66 waterproof function, applicable to a wider range of scenarios.
- Support 256 preset position functions, easily cope with various scenarios.
- TF card supports up to 128G, and supports cloud storage function.
- Support AP hotspot function, which can realize direct device connection and disconnection monitoring.
- Intelligent voice prompt, one-key connection, simple operation.
- External 5db, WiFi dual antenna, stable information, coordinated and beautiful appearance.
- Metal front face, suitable for a variety of application scenarios

Applicable Scenarios

Warehouses, Underground Parking Lots, Bars, Hotel, Office Area, Bank, Supermarket, Concerts, Etc.



360° ROTATABLE CAMERA



→ SUPPORTS 18x OPTICAL ZOOM





IP66 WATERPROOF FUNCTION




→ 3D HUMANOID DETECTION
















Dimensions

Length (L) (mm)	2300	Weight (Kg)	774
Width (W) (mm)	1250	Loading capacity in 40 HQ (units)	09
Height (H) (mm)	2550		



Harvesting Clean Energy / Protecting Our Environment



Model (FSL-201)



Model	UP 2000 - HM6022
Max. Battery Charging Current	60 A
Rated Voltage	24 V
Max. PV Input Power	2500 W
Max. Output Efficiency	99.5%
Utility Input Voltage	176VAC~264VAC (Default); 90VAC~280VAC (Programmable)
Utility Input Frequency	40~65Hz
Max. Utility Charge Current	GOA (con
Continuous Output Power (Inverter)	2000W
Output Voltage Range	220VAC (-6%~+3%); 230VAC (-10%~+3%)
Output Frequency Range	50/60Hz±0.2%
Max. Output Efficiency	93% Falcon
Protection Class	IP30
Quantity	lpcs



Maximum Power (Pmax)	550 W
Maximum Power Voltage (Vmp)	41.96 V
Maximum Power Current (Imp)	13.11 A
Power Tolerance	0/+5W
Lifting Angle	45°
Extending Type	Sliding
Extending area	6.85m²
Battery Bank	
Туре	Lithium-lon battery
Model	2 x 100AH 25.6V
Voltage	25.6 (One battery)
Maximum Charging Current	100A
Quantity	1 pcs
Trailer	
Model	AL-KO B750 (On Road)
Loading Capacity	750 Kg
Drawing Bar	Ball Type Fak
Pulling Speed	≤ 80km/h
Mast	
Model	LHSL - 1000A1
Maximum Lifting Height	7.5m
Mast type	Electric



	DC 24V	
.ED Power	100W (One Lamp)	
ight Bean Angle	60°	
ED Luminous Efficiency	160lm/w	
Correlated Color Temperature	3000 - 5700K	
Protection Class	IP67	
tandby Gasoline Genero	itor	
Maximum Power	1.5 kW	
Rate Voltage	AC 230V	
thers		
Battery Charger	AC 220V-240V 20A	
nverter	500W (DC 24V-AC 230V, 50/60Hz)	
Web Camera	HD-IP Wi-Fi Operated	
4G Router	Provide 4G wireless network	

Notes	

DyMac United Kingdom -





Harvesting Clean Energy / Protecting Our Environment

Long Lane Farm, Ascot Road, Holyport, Maidenhead,
Berkshire, United Kingdom, SL6 3LG

T: +44 300 303 3353 E: sales@dymacuk.com www.dymacuk.com