	cx210	**cx220**	
Axes			
Panel length (max.)	mm	3050	
Panel width (max.)	mm	1300	
Panel thickness (max.)	mm	95	
Panel weight (max.)	kg	70	
X-Y-Z axes speed (max.)	m/min	70 - 40 - 30	
F31LTC drilling head			
Vertical spindles	no.	21	
Horizonal spindles in X - Y directions	no.	6 - 4	
Spindles rotation speed	rpm	up to 8000 with optional inverter	
Integrated blade in X axis	Ø mm rpm	125 up to 9700 with optional inverter	
Motor power	kW (Hp)	2,2 (3)	
F21L drilling head			
Vertical spindles	no.	-	13
Horizonal spindles in X - Y directions	no.	-	6 - 2
Spindles rotation speed	rpm	-	up to 8000 with opt. inverter
Integrated blade in X axis	Ø mm rpm	-	125 up to 8000 with opt. inverter
Motor power	kW (Hp)	-	2,2 (3)
0-90° saw-blade/clamex unit			
Diameter	mm	125	
Rotation speed	rpm	5500	
Electrospindle			
Motor power (max.)	kW	7,5	
Rotation speed	rpm	up to 24000	
Dowel insertion unit			
Supply system		water/vinyl glue	
Available tools on tool changer	no.	6	