APPLICATION FOR BUILDING PERMIT - COMMERCIAL Uniform Construction Code (UCC)

APPLICATION TYPE Check one that applies:	 () Accessibility Review () Alteration/Renovation () New Structure/Facility () Plan Revision/Part Occ 	() Addition () New Building () Phased Approval () Unapproved Building
Use/Occupancy	A-1 A-2 A-3 A-4	A-5 B E
Classification	F-1 F-2 H-1 H-2	EX DE VIDEO DE LA COMPANIO MESTA DE LA COMPANIO DEL COMPANIO DEL COMPANIO DE LA COMPANIO DEL COMPANIO DE LA COMPANIO DEL COMPANIO DE LA COMPANIO DEL COMPANIO DEL COMPANIO DE LA COMPANIO DE LA COMPANIO DE LA COMPANIO DEL COMPANIO DE LA COMPANIO DEL COMPANION DEL COMPANION DEL COMPANIO DEL COMPANIO DEL COMPANIO DEL COMPANIO DEL COMPANIO DEL COMPANION DEL COMPANIO DELICA DEL COMPANIO DEL COMPANIO DEL COMPANIO DEL COMPANION DEL COMPANION DEL COMPAN
Circle one that applies:	I-1 I-2 I-3 I-4	M R-1 R-2
	R-3 R-4 S-I S-2	
•		TO TOOL
	Township Name:	County:
SITE AND NAME:	Owner's Name:	Phone:()
	Street Name & #	City:
	Contractor's Name:	Phone:() -
	Workers Comp attached ()	yes () no Exemption () yes () no
INFORMATION:	Street Name & #	
	Project Address and #	City:
	Project Zoning District:	Tax Map Lot and Block #:
	Project Size (Long ft.) (\	Vide fl.) (Height fl.) (Square Fl.)
	Construction Cost (Labor & M	
PROJECT DATA NEEDED FOR PLAN REVIEW	Number of stories above grad Fire Suppression () Full (New construction area (Section view drawing provided Accessible routes and parking Architect/Engineer Name: Architect/Engineer Phone No:) Partial () None) Sq. Ft. Floor area addition () d () yes (0 no g shown on plan (yes) () no
Type of construction from	n Chapter 6 of the Internationa	I Building Code (circle one)
IA IB	11A 11B 111A 11	11B 1V VA VB
Electricity Supplier:	9	Electric DR#
Nat. Gas Supplier:		Mark Ordon #
Truss drawings supplied Design Occupancy Load	(required) () Yes () No -# of Persons ()	Supplier name:
Building Code Department Use Twp. Administation Fee State Training Fee Building Inspection Fee Electric Inspection Fee	\$ Only: \$ \$	
Plumbing Inspection Fee HVAC Inspection Feë	\$ \$ \$	Occupancy Permit Fee \$
Fire Inspection Fee Accessible review TOTAL DUE	\$ \$ \$	Note: Permit shall be granted or denied within 30 business days of filing date. Section 403.43 of Act 45 as amended
		Excel/Robin/Forms/Application for Building Permit (UCC)-Commercial

SITE PL	ANS:		
☐ Yes	□ N/A	a.	the state of the s
☐ Yes	□ N/A	b.	and separate vicinity (site location) map. Show the correct street address, parcel number and required municipal zoning (if
☐ Yes	□ N/A	C.	there is local zoning ordinance) on the site plans. Show and identify all property lines and rights-of-way, with distance from property lines and adjacent buildings on site plans.
Yes	□ N/A	d.	
☐·Yes	□ N/A	e.	Show accessible curb cuts, ramps and access ways to the building.
☐ Yes ☐ Yes	□ N/A □ N/A	f. g.	
Yes	□ N/A	h.	
Yes	□ N/A	i.	Show existing and proposed utilities (with backflow preventers) to serve the site.
Yes Yes	□ N/A □ N/A	j. k.	
Yes	N/A	1.	
Yes	N/A	m.	
ARCHITECTURAL PLANS:			
☐ Yes	□ N/A	a.	
			size (but not more than $36" \times 42"$), drawn to a scale of not less than $1/8" = 1'$. Indicate (or reproduce) the approved, tested hourly rating, number and location of all rated
			members and assemblies (walls, columns, beams, floor and ceiling, and ceiling and
			roof fire-rated design assemblies).
			Show all fire-rated walls (both existing and new) with their ratings, if not shown elsewhere.
Yes	□ N/A	b.	Drawings submitted without required fire-rated walls shown will be rejected. Show the square footage of each floor on the corresponding floor plans.
Yes	□ N/A	C.	Identify the names and uses of each room.
Yes	□ N/A	d.	Furnish door schedule(s), including size, type, rating (if any) and hardware.
Yes Yes	□ N/A □ N/A	e. f.	Provide all glazing schedules. Show elevations with dimensions defining overall building height, floor-to-floor heights,
<u>_</u> , 100	1111		or heights to ridge and eave as applicable to the type of building construction listed on the UCC application. (Note: Where an existing building is involved, photographs of all
			sides of the building may be submitted to show elevations. These will be acceptable only if they show all elements necessary to determine compliance with the UCC.)
Yes	□ N/A	g.	Provide basement percentage-below-grade calculations.
☐ Yes	I N/A	h.	Indicate roof slopes, drainage system and sized through wall scuppers, if applicable to
☐ Yes	□ N/A	i.	the project. Show fixed seating for assembly occupancy to allow determination of occupancy posting required by <i>International Building Code</i> .
Yes	□ N/A	j.	Show wall sections with proposed material sizes, construction and fire-rated assemblies.
Yes	□ N/A	k.	Show proposed plumbing fixtures and privacy screens on the plans.
Yes	□ N/A	1.	If masonry construction is proposed, include the following information:
			Type of brick ties and spacing of weep holes Control joints
	VICE-2017		Placement of wall flashing and reinforcement.
Yes	□ N/A	m.	If appropriate for the proposed occupancy, plans should identify all hazardous material
			control areas, fire barriers and the required fire-resistance ratings for these barriers. All identified control areas shall list the name, class, quantity and method of storage of all
			hazardous materials processed, manufactured or used in a manufacturing process and
			contained within its fire barriers. Provide a Material Safety Data Sheet for each listed
Yes	FI N/A	л.	hazardous material. See sections 414 and 415 of the <i>International Building Code</i> . Show the floor slab vapor barrier.
UCC-2 REV 1			and the state of t

Yes Yes	□ N/A □ N/A		details shall meet or exceed the rating of construction being penetrated. The
			penetration details shall be exactly as tested by an approved testing laboratory or agency and shall include their system numbers. New penetrations of existing fire-rated
☐ Yes	□ N/A		
Yes	□ N/A	r.	Provide on the drawings the calculations for the means of egress widths for the entire floor occupancy load and the existing capacity of all exits including all stairs, doors, corridors and ramped exits.
☐-Yes	□ N/A	s.	
STRUCT	URAL PI	LANS	:
Yes	□ N/A	a.	Show foundation plans indicating the proposed slab elevations and type of foundation (i.e., mat foundation, caissons, spread footings, etc.).
Yes Yes	□ N/A □ N/A	b.	Provide preliminary soil analysis data done by a licensed engineer, if required.
Yes	N/A		
Yes	□ N/A	e.	Indicate grade beam sizes.
☐ Yes ☐ Yes	□ N/A □ N/A	f. g.	Indicate a footing schedule defining footing sizes and the required reinforcing. Show the established footing depth below grade and method of frost protection
Yes	☐ WA	h,	allowed in section 1805.2.1 of the International Building Code. Indicate the thickness of the floor slab, size of reinforcing, slab elevations, and type
☐ Yes ☐ Yes	□ N/A □ N/A	i. j.	and details of foundations. Indicate location, size and amount of reinforcing steel. Show foundation corner reinforcing bars and minimum overlapping (as applicable to
☐ Yes ☐ Yes	□ N/A □ N/A	K. 1.	project structure). Provide strength of concrete according to designed soil reports. Show beams, joists, girders, rafters, and/or truss layouts and details of connections.
☐ Yes ☐ Yes	□ N/A □ N/A	т. п.	structural steel stud gage, gage size, and connections. Indicate the sizes and species of all wood members and their respective design strength. Show all columns, girders, joists, purlins, beams and base plates; for wood
Yes	□N/A	Ο.	construction show all headers. Provide a complete lintel schedule.
Yes	□ N/A	p.	Indicate the type of anchoring for steel bearing directly on masonry.
Yes	□ N/A	q.	Indicate design dead and live, wind, snow, seismic loads for floor areas, roofs, balconies, porches, breezeways, corridors, stairs, mezzanines and platforms. Show concentrated loads, i.e. file rooms, machinery and forklift areas, if greater than those shown on the Code Summary Sheet. Identify shear walls, bracing, strapping
☐ Yes	□ N/A	r.	fastening, reinforcement and any special anchoring required. Where applicable, indicate on roof framing plan where concentrated loads
Yes	□ N/A	S.	(mechanical equipment, cranes, etc.) will be placed. Indicate on foundation and framing plans the location and lateral load resisting system. (Show walls, braced frames, moment connections, etc.)
FIRE PRO	OTECTIO	N PL	ANS:
☐Yes	□ N/A	a.	Complete a sprinkler design data sheet and include it on the first plan of the sprinkler
	□ N/A"		drawings.
☐ 162	E WA	IJ.	Show floor plans for each floor with sprinkler piping layout, pipe sizes, pipe hanger details, piping materials, doors, walls and room identities.
			Often, these shop drawings are not available at the time of initial plan submission. If this is the case, write in "NA," but note the following: These shop drawings must be submitted for Department review and approval

			at least two weeks before the projected installation date.
			• Failure to obtain approval of these drawings before installation could result not only
			in delay of the final inspection and issuance of an occupancy permit, but also in
Yes	□ N/A		removal and reconstruction of installations which fail to meet UCC requirements. Show ceiling plans with sprinkler head(s) layout, walls, soffits, openings, doors,
∐ res	[] IN/A	C.	dimensions and room identities.
Yes	□ N/A	d.	Verify system design by providing hydraulic calculations along with the following:
time!	Account		Recent water flow test
			10 percent safety margin
			Type of backflow-preventer or reduced pressure zone showing equivalent
			foot loss
Yes	E N/A	6	Fire pump summary Note the type of sprinkler system used (e.g., 13, 13D, or 13R)
Yes	N/A	f.	For residential occupancies such as apartments and condominiums, show sprinkler
			head locations at breezeways if applicable.
☐ Yes	□ N/A	g.	Indicate the certified testing laboratory agency (e.g., U.L.), their test number and
			hourly ratings of all new and/or affected rated members and assemblies (i.e.
			columns, beams, floor/ceiling and ceiling/roof fire-rated design assemblies). Show all new and/or affected fire-rated walls with their ratings, if not shown elsewhere.
Yes	□ N/A	h.	All penetrations of fire-rated construction must be per manufacturer's details. Details
			shall meet or exceed ratings of construction being penetrated. Penetration details
			shall be exactly as tested by a certified testing laboratory or agency and shall
			include their system numbers. All new penetrations of existing fire-rated walls and assemblies shall be shown with appropriate designs.
Yes	□ N/A	i.	Provide a fire alarm riser showing connection to a UL-approved central station.
	LJ 1 1		Show tamper switches on both OS and Y valves of backflow prevention device,
	F		unless shown elsewhere.
Yes	☐ N/A	j.	Indicate commodity class (per section 2303 of the International Fire Code) and
Yes	□ N/A	k	height of any storage. Provide Material Safety Data Sheets for any hazardous materials (also specified
			under "Architectural Plans").
☐ Yes	☐ N/A	1.	Where special temperature-rated or high-temperature sprinklers are required, show
			sprinkler type(s) per area, office size, cut sheets with K-factor, water requirements,
			spray pattern, coverage and other pertinent data.
SYSTEM	CALCULA	TIOI	NS (FIRE PROTECTION):
all new bu	ally calcula	ted a	and pipe schedule fire systems should be designed with a 10 percent safety margin for litions to existing buildings. Calculations for hydraulic systems should include:
	munys and		
Yes	☐ N/A		Flow and pressure at each flowing sprinkler head
Yes	□ N/A	b.	Flow diagram for a grid system.
	IG PLANS		
	-	•	
Yes	N/A	a.	
			 Show the domestic water, fire, and irrigation services. Show the location of water meters, backflow protection type and location.
			3. Show the sanitary sewer service from building to public sewer or approved
			private sewage disposal system.
Yes	□ N/A	b.	and the second of the second o
-			lint, acid, sand).
Yes	N/A	C.	Provide plumbing plan layouts for each floor. These should show the water
			distribution and drain-waste-vent piping, and all details, notes, legends, and schedules necessary to define the system being installed.

☐ Yes ☐ Yes	□ N/A □ N/A	d. e.	Provide fixture and equipment schedule showing fixture number, detailed description, hot water, cold water, waste and vent connection sizes and other
☐ Yes	□ N/A	f.	pertinent data. Identify all fixtures on floor plans and in riser diagrams with the plumbing fixture
Yes	□ N/A	.g.	schedule number. Supply and Waste/Vent piping shall be shown on the floor plans. All pipe sizes shall be clearly shown. In congested areas (e.g., restaurants, grocery stores, etc.), isometrics are required.
Yes	□ N/A		On buildings two stories and above, provide isometric diagrams and/or schematic riser diagrams for Supply and Waste/Vent piping and identify the risers by number (e.g., R1, R2, etc.). Show where all riser base terminations connect to the building drain, along with all interconnected piping on each floor plan. All pipe sizes shall be elegable defined.
Yes	□ N/A	i.	Show the water, sanitary drain-waste-vent piping and storm leader sturants.
☐Yes	□ N/A	j,	Indicate sizes and materials for above/below grade. Show slope of horizontal sanitary and storm drains that equal or exceed 3" diameter, if less than 1/8" per foot.
Yes	□ N/A	k.	Indicate roof drains and emergency roof drains/scuppers with the areas they impact. Note that "emergency" = "secondary" = "overflow," see following roof
			drainage examples: Roof Drain - 6" RD (16880 SF) Emergency Roof Drain - 6" ERD (8180 SF) Parapet Wall Scupper - 8" x 5" WS (4000 SF) Emergency Scupper - 8" x 7" ES (4200 SF)
Yes	□ N/A □ N/A	I. M.	
Yes	□ N/A	n.	All penetrations of fire-rated construction must be per manufacturer's details. The details shall meet or exceed rating of construction being penetrated. The penetration details shall be exactly as tested by an approved testing laboratory or agency and shall include their system numbers.
Yes Yes Yes	N/A N/A N/A	o. p. q.	Room names and numbers for each floor should be on a floor plan for each level. Provide minimum facilities calculations. Column line notations, if provided on the architectural/structural plans, shall be indicated on the plumbing plans.
MECHAN	IICAL PLA	NS:	
Yes Yes Yes	□ N/A □ N/A □ N/A	b. c.	Show all required wall louvers, penetrations and fans. Indicate roof-mounted equipment locations. Show all mechanical equipment, piping, ductwork (above/below slab) on the
Yes	□ N/A	d.	mechanical floor and/or roof plan. Provide mechanical plans for each floor and the roof. These shall show the ductwork layouts, schedules, notes, legends, piping schematics, and details necessary to
Yes Yes Yes Yes	N/A N/A N/A N/A	e. f. g. h.	define the system being installed. Indicate air distribution devices and show cfm for all supply, return and exhaust devices. Indicate the location of all equipment components required for a complete system. Show the smoke ventilation of atriums and pressurization of high-rise stairwells. Show condensation drains, primary and secondary, from the unit to the point of discharge.
Yes Yes	□ N/A □ N/A	i. j.	Indicate toilet exhaust requirements. Show mechanical room layouts at sufficient scale for dimensions and details to be
☐ Yes ☐ Yes	IN/A N/A	к. I.	ascertained. Show the size of duct runs. Indicate controls for fan shutdown: emergency manual and automatic smoke detection.

Yes	□ N/A	m.	Show the location of all UL 555-certified fire dampers, ceiling radiation dampers,
∏Yes	□ N/A	n.	smoke dampers, and fire doors. Show all fire-rated walls (both existing and new) with their ratings on the mechanical plans.
Yes	☐ N/A	0.	All penetrations of fire-rated construction must be per manufacturer's details.
Yes	□ N/A	p.	Room names and numbers for each floor should be on a floor platt tot each level.
Yes Yes	□ N/A □ N/A	q. r.	Provide outside air ventilation rate per the International Mechanical Code. Column line notations, if provided on the architectural/structural plans, shall be
L 103	E		identified on the mechanical plans
☐ Yes	□ N/A	5.	Provide gas piping layout on the floor plan for each floor. If it is a multi-story building, all gas piping shall be shown per floor. Include pipe sizes, water column, and type of material. Provide a schedule of connected equipment, total BTUH demand, total equivalent length, and most remote gas appliance.
ELECTRI	ICAL PLA		
☐Yes	□ N/A		Provide panel schedules with circuit and feeder loading, overcurrent protection, and NEC load summaries for all new and/or affected panels and services (loading has to be evaluated by highest phase); include fault current data, short circuit ratings and fault current protection co-ordination.
Yes	□ N/A		Provide a single line riser diagram showing all new and/or affected services, feeders wire sizes and insulation types and conduit sizes and types.
Yes	□ N/A		Indicate number of services and their physical locations; clearly indicate mains and characteristics
Yes	☐ N/A	d.	Indicate the grounding electrode conductor size with new and/or affected services and transformers; where necessary provide details or notes on methods.
Yes	□ N/A	e.	Show physical locations of all new and/or affected panels and switchgear (indicate front).
Yes Yes	N/A N/A	f. g.	Indicate receptacle plans with circuitry. Indicate lighting plans with circuitry.
Yes	E N/A	h.	Show electrical plans for each affected floor, including the roof.
Yes	□ N/A	i.	Show wiring method(s), conduit sizes and types, termination temperature (60, 75,
Yes	□ N/A	i.	90) requirements, conductor sizes and insulation types. Indicate the design and/or operation for any of the following applicable life safety
		٠,٠	systems: emergency generators, smoke evacuation, shaft pressurization and relief,
	F N1/0	T.	smoke detection, egress and emergency lighting, and fire alarms.
Yes	□ N/A	k.	Indicate how special needs such as classified (hazardous), corrosive and patient care are treated. Provide detailed plan of classified areas, the classifications and
			how complied with (i.e. hangers, waste treatment and collection, flammable dusts,
	F=1 NI/A		gases or liquids, spray booths, vehicle servicing and parking, etc.).
Yes	☐ N/A	١.	Provide all HVAC nameplate data, including MCA and MOCP. List all other appliance and/or equipment (other than those which will be connected to a general
			use receptacle) with nameplate data (i.e., voltage, phasing, HP, KVA, FLA, RLA, etc.).
Yes	□ N/A	m.	Indicate all motor horse power ratings, if not supplied elsewhere.
Yes	□ N/A	n.	Indicate the certified testing laboratory or agency (e.g., UL), their test # and hourly ratings of all new and/or affected rated members and assemblies (i.e. columns,
			beams, floor/ceiling, and ceiling/roof fire-rated design assemblies). Show all new
			and/or affected fire-rated walls with their ratings, if not shown elsewhere.
Yes	☐ N/A	Ο,	All penetrations of fire-rated construction must be per manufacturer's details. The
			details shall meet or exceed ratings of construction being penetrated. Penetration details shall be exactly as tested by an approved testing laboratory or agency and
			shall include their system numbers. New penetrations of existing fire-rated walls and
there are	11-011		assemblies shall be shown with appropriate designs.
Yes	NA	p.	Provide all applicable International Energy Conservation Code compliance data on the Building Code Summary sheet or on the electrical plans.
Yes	☐ N/A	q.	All submittals should include a listing and labeling statement. (All electrical
	2000 - 100 -	13	materials, devices, appliances and equipment shall be labeled and listed by a
			certified testing laboratory or agency.)