



## ES-35

- 35-lb capacity
- Tumbler diameter: 30"
- Tumbler depth: 30"
- Tumbler volume: 12.27 cu. ft.
- Door opening: 19 ½"
- Wheel-supported basket
- Dual-paned door glass
- 6" (H) x 31 ½" (W) x 40 ¾" (D)
- Fits through standard 36" door
- Net weight: 462 lbs
- Drive motor: ¼ HP
- Blower motor: ½ HP
- Available in gas, electric & steam
- Heat input (gas): 55,000 Btu/hr (50Hz) / 64,000 Btu/hr (60Hz)
- Airflow CFM (gas): 266 (50Hz) / 319 (60Hz)
- 100% axial airflow
- Exhaust connection: 6"
- Microprocessor
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Eco-dry system with R.M.C.
- Stainless steel front, cabinet & basket
- Single-phase reversing basket



## ES-50

- 50-lb capacity
- Tumbler diameter: 37"
- Tumbler depth: 25 ¾"
- Tumbler volume: 16.02 cu. ft.
- Door opening: 27 ½"
- Wheel-supported basket
- Dual-paned door glass
- 70-½" (H) x 38 ¼" (W) x 40 ½" (D)
- Fits through standard 42" door
- Net weight: 610 lbs
- Drive motor: ½ HP
- Blower motor: ½ HP
- Single-phase reversing basket
- Available in gas, electric & steam
- Heat input (gas): 110,000 Btu/hr
- Airflow CFM (gas): 500 (50Hz) / 600 (60Hz)
- 100% axial airflow
- Exhaust connection: 8"
- Microprocessor
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Eco-dry system with R.M.C.
- Stainless steel front, cabinet & basket
- Prison package



## ES-76

- 75-lb capacity
- Tumbler diameter: 37"
- Tumbler depth: 35 ½"
- Tumbler volume: 22.09 cu. ft.
- Door opening: 27 ½"
- Wheel-supported basket
- Dual-paned door glass
- 70 ½" (H) x 38 ¼" (W) x 49 13/16" (D)
- Fits through standard 42" door
- Net weight: 745 lbs
- Drive motor: ½ HP
- Blower motor: ½ HP
- Single-phase reversing basket
- Available in gas, electric & steam
- Heat input (gas): 110,000 Btu/hr (50Hz) / 130,000 Btu/hr (60Hz)
- Airflow CFM (gas): 500 (50Hz) / 600 (60Hz)
- 100% axial airflow
- Exhaust connection: 8"
- Microprocessor
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Eco-dry system with R.M.C.
- Stainless steel front, cabinet & basket



## ES-3535

- 35-lb capacity x 2
- Tumbler diameter: 30"
- Tumbler depth: 30"
- Tumbler volume: 12.27 cu. ft.
- Door opening: 19 ½"
- Dual-paned door glass
- 80 ½" (H) x 31 ½" (W) x 70 7/16" (D)
- Net weight: 600 lbs
- Drive motor: ¼ HP
- Blower motor: ½ HP
- Available in electric & steam
- Heat input (gas): 64,000 Btu/hr
- Airflow CFM (gas): 380 (50Hz)
- 100% Axial Airflow
- Exhaust connection: 6"
- Microprocessor
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Eco-dry system with R.M.C.
- Single-phase reversing basket



## AD-24

- 20-lb capacity
- Tumbler diameter: 27 1/4"
- Tumbler depth: 24"
- Tumbler volume: 8.1 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 65" (H) x 28 1/2" (W) x 36 1/2" (D)
- Net weight: 426 lbs
- Drive motor: 1/2 HP
- Available in gas & electric
- Heat input (gas): 60,000 Btu/hr
- Airflow CFM: 333 (50Hz) / 400 (60Hz)
- Radial airflow
- Exhaust connection: 6"
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Electric Heat



## AD-25V

- 25-lb capacity
- Tumbler diameter: 32 3/4"
- Tumbler depth: 19"
- Tumbler volume: 9.26 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 72" (H) x 34 3/4" (W) x 29 3/4" (D)
- Net weight: 407 lbs
- Drive motor: 1/2 HP
- Available in gas, electric & steam
- Heat input (gas): 78,000 Btu/hr
- Airflow CFM: 383 (50Hz) / 460 (60Hz)
- Radial airflow
- Exhaust connection: 8"
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Reversing basket
- Stainless steel front, cabinet & basket



## AD-30V

- 30-lb capacity
- Tumbler diameter: 32 3/4"
- Tumbler depth: 25 5/8"
- Tumbler volume: 12.5 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 72" (H) x 34 1/4" (W) x 38" (D)
- Fits through standard 36" door
- Net weight: 534 lbs (gas & electric) / 593 lbs (steam)
- Drive motor: 1/2 HP
- Available in gas, electric & steam
- Heat input (gas): 100,000 Btu/hr
- Airflow CFM: 383 (50Hz) / 460 (60Hz)
- Radial airflow
- Exhaust connection: 8"
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- 3-phase reversing basket incl. 1/2 HP blower motor
- Stainless steel front, cabinet & basket



## AD-285

- 30-lb capacity
- Tumbler diameter: 17 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.18 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 69 1/2" (H) x 28 1/2" (W) x 45 1/2" (D)
- Fits through standard 36" door
- Net weight: 455 lbs
- Drive motor: 1/2 HP
- Available in gas
- Heat input (gas): 72,000 Btu/hr
- Airflow CFM: 313 (50Hz) / 375 (60Hz)
- Radial airflow
- Exhaust connection: 6"
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Stainless steel front, cabinet & basket



## AD-50V

- 50-lb capacity
- Tumbler diameter: 32 3/4"
- Tumbler depth: 37 1/2"
- Tumbler volume: 18.3 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 72" (H) x 34 1/4" (W) x 49 3/4" (D)
- Fits through standard 36" door
- Net weight: 651 lbs (gas & electric) / 683 lbs (steam)
- Drive motor: 3/4 HP
- Available in gas, electric & steam
- Heat input (gas): 150,000 Btu/hr
- Airflow CFM: 625 (50Hz) / 750 (60Hz)
- Radial airflow
- Exhaust connection: 8"
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- 3-phase reversing basket incl. 1/2 HP blower motor
- Stainless steel front, cabinet & basket
- Prison package



## AD-78

- 75-lb capacity
- Tumbler diameter: 44 1/2"
- Tumbler depth: 24 7/8"
- Tumbler volume: 22.4 cu. ft.
- Door opening: 31 3/4"
- Steel door with gasketless glass
- 84 5/16" (H) x 46 13/16" (W) x 35" (D)
- Fits through standard 36" door
- Net weight: 888 lbs (gas & electric)
- Drive motor: 1 HP (non-reversing)
- Available in gas & electric
- Heat input (gas): 204,000 Btu/hr
- Airflow CFM: 1,000 (50Hz) / 1,200 (60Hz)
- Radial airflow
- Exhaust connection: 10"
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- 3-phase reversing basket incl. 1/2 HP blower motor
- Stainless steel front, cabinet & basket
- Prison package



## AD-758V

- 75-lb capacity
- Tumbler diameter: 36 1/4"
- Tumbler depth: 36"
- Tumbler volume: 21.5 cu. ft.
- Door opening: 31 3/8"
- Steel door with gasketless glass
- 75 1/8" (H) x 38 1/4" (W) x 48" (D)
- Fits through standard 48" door
- Net weight: 721 lbs (gas & electric) & 816 lbs (steam)
- Drive motor: 1/2 HP
- Available in gas, electric & steam
- Heat input (gas): 175,000 Btu/hr
- Gas & electric airflow CFM: 833 (50Hz) / 1,000 (60Hz)
- Steam airflow CFM: 1,000 (50Hz) / 1,200 (60Hz)
- Radial airflow
- Exhaust connection: 8"
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Stainless steel front, cabinet & basket
- Reversing basket



## AD-115

- 115-lb capacity
- Tumbler diameter: 42"
- Tumbler depth: 41 1/4"
- Tumbler volume: 33.1 cu. ft.
- Door opening: 31 5/8"
- Steel door with gasketless glass
- 84" (H) x 46 1/8" (W) x 63 9/16" (D)
- Fits through standard 48" door
- Net weight: 1,260 lbs
- 3-phase reversing basket
- Drive motor: 3/4 HP
- Blower motor: 3 HP
- Available in gas, electric & steam
- Heat input (gas): 343,000 Btu/hr
- Airflow CFM: 1,750 (50Hz) / 2,100 (60Hz)
- Exhaust connection: 14"
- Removable front panel
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Stainless steel front, cabinet & basket



## AD-320

- 20-lb capacity x 2
- Tumbler diameter: 27 1/4"
- Tumbler depth: 25"
- Tumbler volume: 8.4 cu. ft.
- Door opening: 21 1/2"
- Coin / Card Ready
- Heat input (gas): 60,000 Btu/hr per Pocket
- Airflow CFM: 333 (50Hz) / 400 (60Hz)
- Microprocessor
- Axial airflow
- Steel door with gasketless glass
- 78 1/4" (H) x 29 3/4" (W) x 38 7/8" (D)
- Exhaust connection: 6"
- Available in gas, electric & steam
- Fits through standard 36" door
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System)



## AD-236

- 30-lb capacity x 2
- Tumbler diameter: 27 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.1 cu. ft.
- Door opening: 21 1/2"
- Coin / Card Ready
- Heat input (gas): 160,000 Btu/hr per Pocket
- Airflow CFM: 333 (50Hz) / 400 (60Hz)
- Microprocessor
- Radial airflow
- Steel door with gasketless glass
- 76 1/4" (H) x 28 1/2" (W) x 53 1/2" (D)
- Exhaust connection: 8"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Available in 3-phase electric



## AD-30x2R

- 30-lb capacity x 2
- Tumbler diameter: 30"
- Tumbler depth: 27"
- Tumbler volume: 11 cu. ft.
- Door opening: 21 1/2"
- Heat input (gas): 72,000 Btu/hr per Pocket
- Airflow CFM: 450 (60Hz) / 450 (60Hz)
- Dual micro-controls
- Trans-axial airflow
- Steel door with gasketless glass
- 78 5/16" (H) x 31 1/2" (W) x 40 3/16" (D)
- Exhaust connection: 6"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- Multi-colored door trim
- Single-phase reversing basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System)



## AD-330

- 30-lb capacity x 2
- Tumbler diameter: 27 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.1 cu. ft.
- Door opening: 21 1/2"
- Coin / Card Ready
- Heat input (gas): 68,000 Btu/hr per Pocket
- CFMs - 333 (50Hz) / 400 (60Hz)
- Microprocessor
- Axial airflow
- Steel door with gasketless glass
- 78 1/4" (H) x 29 3/4" (W) x 43 7/8" (D - electric) / 48 15/16" (D - steam)
- Exhaust connection: 6"
- Available in gas, electric & steam
- Fits through standard 36" door
- 3-year limited warranty

#### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System)



## AD-333

- 30-lb capacity x 2
- Tumbler diameter: 27 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.1 cu. ft.
- Door opening: 21 1/2"
- Coin / Card Ready
- Heat input (gas): 72,000 Btu/hr per Pocket
- Airflow CFM: 340 (50Hz) / 400 (60Hz)
- Microprocessor
- Trans-axial airflow
- Steel door with gasketless glass
- 78 1/4" (H) x 29 3/4" (W) x 53" (D)
- Exhaust connection: 8"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

#### CUSTOMIZABLE OPTIONS

- Grey or white front & cabinet



## AD-444

- 45-lb capacity x 2
- Tumbler diameter: 32 3/4"
- Tumbler depth: 30"
- Tumbler volume: 14.6 cu. ft.
- Door opening: 27"
- Coin / Card Ready
- Heat input (gas): 106,000 Btu/hr per pocket
- Airflow CFM: 442 (50Hz) / 530 (60Hz)
- Microprocessor
- Trans-axial airflow
- Steel door with gasketless glass
- 80 15/16" (H) x 34 5/16" (W) x 53 3/16" (D)
- Exhaust connection: 8"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

#### CUSTOMIZABLE OPTIONS

- Grey or white front & cabinet
- Single 10" exhaust connection



## AD-4545

- 45-lb capacity x 2
- Tumbler diameter: 32 3/4"
- Tumbler depth: 30"
- Tumbler volume: 14.6 cu. ft.
- Door opening: 27"
- Coin / Card Ready
- Heat input (gas): 112,000 Btu/hr per pocket
- Airflow CFM: 500 (50Hz) / 600 (60Hz)
- Microprocessor
- Radial airflow
- Steel door with gasketless glass
- 81 1/16" (H) x 34 5/16" (W) x 53 1/4" (D)
- Exhaust connection: 8"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

#### CUSTOMIZABLE OPTIONS

- Grey or white front & cabinet
- Single 10" exhaust connection
- Stainless steel front, cabinet & basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System) on Phase-7 machines



## AD-45x2R

- 45-lb capacity x 2
- Tumbler diameter: 32 3/4"
- Tumbler depth: 30"
- Tumbler volume: 14.6 cu. ft.
- Door opening: 27"
- Coin / Card Ready
- Heat input (gas): 94,000 Btu/hr per pocket
- Airflow CFM: 525 (50Hz) / 525 (60Hz)
- Two individual micro-controls
- Trans-axial airflow
- Steel door with gasketless glass
- 81" (H) x 34 1/4" (W) x 47 7/8" (D)
- Exhaust connection: 10"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

#### CUSTOMIZABLE OPTIONS

- Stainless Steel or grey front or cabinet
- Stainless steel basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System) on Phase-7 machines



## AD-35i

- 35-lb capacity
- Intuitive micro controls
- Wheel-supported basket
- Stainless basket & fronts
- Fits through standard 36" door
- Pre-heat system
- Trans-axial airflow
- Direct spark ignition
- Simplified inverter drive system
- Variable drum speed
- Fully insulated cabinet
- Single-phase reversing basket
- Drive motor: 1 HP
- Blower motor: ½ HP
- Exhaust connection: 8" (not available in steam)
- Available in gas & electric
- Heat input (gas): 70,000 Btu/hr
- Airflow CFM: 340 (50Hz) / 440 (60Hz)
- S.A.F.E. (Sensor Activated Fire Extinguishing System)

### CUSTOMIZABLE OPTIONS

- Automatic airflow compensator
- Double-pane door glass (vended, standard OPL)



## AD-50i

- 50-lb capacity
- Intuitive micro controls
- Wheel-supported basket
- Stainless basket & fronts
- Fits through standard 36" door
- Pre-heat system
- Trans-axial airflow
- Direct spark ignition
- Simplified inverter drive system
- Variable drum speed
- Fully insulated cabinet
- Single-phase reversing basket
- Drive motor: 1 HP
- Blower motor: ¾ HP
- Exhaust connection: 8"
- Available in gas, electric & steam (only for OPL)
- Heat input (gas): 125,000 Btu/hr
- Airflow CFM: 810 (50Hz) / 850 (60Hz)
- S.A.F.E. (Sensor Activated Fire Extinguishing System)

### CUSTOMIZABLE OPTIONS

- Automatic airflow compensator
- Double-pane door glass (vended, standard OPL)



## AD-80i

- 80-lb capacity
- Intuitive micro controls
- Wheel-supported basket
- Stainless basket & fronts
- Fits through standard 42" door
- Pre-heat system
- Trans-axial airflow
- Direct spark ignition
- Simplified inverter drive system
- Variable drum speed
- Fully insulated cabinet
- Single-phase reversing basket
- Drive motor: 1 HP
- Blower motor: ¾ HP
- Exhaust connection: 8"
- Available in gas, electric & steam (only for OPL)
- Heat input (gas): 135,000 Btu/hr
- Airflow CFM: 880 (50Hz) / 920 (60Hz)
- S.A.F.E. (Sensor Activated Fire Extinguishing System)

### CUSTOMIZABLE OPTIONS

- Automatic airflow compensator
- Double-pane door glass (vended, standard OPL)



## AD-120i

- 120-lb capacity
- Intuitive micro controls
- Wheel-supported basket
- Stainless basket & fronts
- Fits through standard 48" door
- Pre-heat system
- Trans-axial airflow
- Direct spark ignition
- Simplified inverter drive system
- Variable drum speed
- Fully insulated cabinet
- Single-phase reversing basket
- Drive motor: 2 HP
- Blower motor: 1 HP
- Exhaust connection: 10"
- Available in gas, electric (only for OPL) & steam (only for OPL)
- Heat input (gas): 250,000 Btu/hr
- Airflow CFM: 1,350 (50Hz / 60Hz)
- S.A.F.E. (Sensor Activated Fire Extinguishing System)

### CUSTOMIZABLE OPTIONS

- Automatic airflow compensator
- Double-pane door glass (vended, standard OPL)




## AD-30X2Ri

- 30-lb capacity, double pocket
- Intuitive micro controls
- Wheel-supported basket
- Stainless basket & fronts
- Fits through standard 36" door
- Pre-heat system
- Trans-axial airflow
- Direct spark ignition
- Simplified inverter drive system
- Variable drum speed
- Fully insulated cabinet
- Single-phase reversing baskets
- Drive motor: 1/4 HP
- Blower motor: 1/2 HP
- Exhaust connections: 8"
- Available in gas only
- Heat input (gas): 72,000 Btu/hr
- Airflow CFM: 375 (50Hz) / 450 (60Hz)
- S.A.F.E. (Sensor Activated Fire Extinguishing System)

### CUSTOMIZABLE OPTIONS

- Double-pane door glass (vended, standard OPL)



## AD-45X2Ri

- 45-lb capacity, double pocket
- Intuitive micro controls
- Wheel-supported basket
- Stainless basket & fronts
- Fits through standard 36" door
- Pre-heat system
- Trans-axial airflow
- Direct spark ignition
- Simplified inverter drive system
- Variable drum speed
- Fully insulated cabinet
- Single-phase reversing baskets
- Drive motors: 1/4 HP
- Blower motors: 1/2 HP
- Exhaust connections: 10"
- Available in gas only
- Heat input (gas): 94,000 Btu/hr
- Airflow CFM: 440 (50Hz) / 525 (60Hz)
- S.A.F.E. (Sensor Activated Fire Extinguishing System)

### CUSTOMIZABLE OPTIONS

- Double-pane door glass (vended, standard OPL)



## AD-24

- 20-lb capacity
- Tumbler diameter: 27 1/4"
- Tumbler depth: 24"
- Tumbler volume: 8.1 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 65" (H) x 28 1/2" (W) x 36 5/8" (D)
- Net weight: 426 lbs
- Drive motor: 1/2 HP
- Exhaust connection: 6"
- Available in gas & electric
- Heat input (gas): 60,000 Btu/hr
- Airflow CFM: 333 (50Hz) / 400 (60Hz)

### CUSTOMIZABLE OPTIONS

- Electric Heat



## AD-285

- 30-lb capacity
- Tumbler diameter: 17 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.18 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 69 1/2" (H) x 28 1/2" (W) x 45 5/8" (D)
- Fits through standard 36" door
- Net weight: 455 lbs (gas)
- Drive motor: 1/2 HP
- Exhaust connection: 6"
- Available in gas
- Heat input (gas): 72,000 Btu/hr
- Airflow CFM: 313 (50Hz) / 375(60Hz)
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Stainless steel front, cabinet & basket



## AD-30V

- 30-lb capacity
- Tumbler diameter: 32 3/4"
- Tumbler depth: 25 5/8"
- Tumbler volume: 12.5 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 72" (H) x 34 1/4" (W) x 38" (D)
- Fits through standard 36" door
- Net weight: 534 lbs (gas & electric) / 593 lbs (steam)
- Drive motor: 1/2 HP
- Exhaust connection: 8"
- Available in gas, electric & steam
- Heat input (gas): 100,000 Btu/hr
- Airflow CFM: 383 (50Hz) / 460 (60Hz)
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- F.S.S. (Fire Suppression System)
- 3-phase reversing basket incl. 1/2 HP blower motor
- Stainless steel front, cabinet & basket



## AD-50V

- 50-lb capacity
- Tumbler diameter: 32 3/4"
- Tumbler depth: 37 1/2"
- Tumbler volume: 18.3 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 72" (H) x 34 1/4" (W) x 49 3/4" (D)
- Fits through standard 36" door
- Net weight: 651 lbs (gas & electric) / 683 lbs (steam)
- Drive motor: 3/4 HP
- Exhaust connection: 8"
- Available in gas, electric & steam
- Heat input (gas): 150,000 Btu/hr
- Airflow CFM: 625 (50Hz) / 750 (60Hz)
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- F.S.S. (Fire Suppression System)
- 3-phase reversing basket incl. 1/2 HP blower motor
- Stainless steel front, cabinet & basket
- Prison package



## AD-758V

- 75-lb capacity
- Tumbler diameter: 36 1/4"
- Tumbler depth: 36"
- Tumbler volume: 21.5 cu. ft.
- Door opening: 31 1/8"
- Steel door with gasketless glass
- 75 1/8" (H) x 38 1/4" (W) x 48" (D)
- Net weight: 721 lbs (gas & electric) / 816 lbs (steam)
- Drive motor: 1 HP (non-reversing)
- Exhaust connection: 8"
- Available in gas, electric & steam
- Heat input (gas): 175,000 Btu/hr
- Airflow CFM: 833 (50Hz) / 1,000 (60Hz)
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- F.S.S. (Fire Suppression System)
- 3-phase reversing basket incl. 1/2 HP drive motor & 1 HP blower motor
- Stainless steel front, cabinet & basket
- Prison package



## AD-78

- 75-lb capacity
- Tumbler diameter: 44 1/2"
- Tumbler depth: 24 7/8"
- Tumbler volume: 22.4 cu. ft.
- Door opening: 31 7/8"
- Steel door with gasketless glass
- 84 5/16" (H) x 46 13/16" (W) x 35" (D)
- Fits through standard 36" door
- Net weight: 888 lbs (gas & electric)
- Drive motor: 1 HP (non-reversing)
- Exhaust connection: 8"
- Available in gas & electric
- Heat input (gas): 204,000 Btu/hr
- Airflow CFM: 1,000 (50Hz) / 1,200 (60Hz)
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- F.S.S. (Fire Suppression System)
- 3-phase reversing basket incl. 1/2 HP blower motor
- Stainless steel front, cabinet & basket
- Prison package



## AD-115

- 115-lb capacity
- Tumbler diameter: 42"
- Tumbler depth: 41 1/4"
- Tumbler volume: 33.1 cu. ft.
- Door opening: 31 7/8"
- Steel door with gasketless glass
- 84" (H) x 46 1/8" (W) x 63 9/16" (D)
- Fits through standard 48" door
- Net weight: 1,260 lbs (gas)
- F.S.S. (Fire Suppression System)
- 3-phase reversing basket
- Drive motor: 3/4 HP
- Blower motor: 3 HP
- Exhaust connection: 14"
- Removable front panel
- Available in gas, electric & steam
- Heat input (gas): 343,000 Btu/hr
- Airflow CFM: 1,170 (50Hz) / 2,100 (60Hz)
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- Steel steam coil
- Prison package
- DR version



## AD-120

- 120-lb capacity
- Tumbler diameter: 44 5/8"
- Tumbler depth: 42 1/8"
- Tumbler volume: 38.10 cu. ft.
- Door opening: 31 7/8"
- Steel door with gasketless glass
- 84" (H) x 46 1/8" (W) x 63 9/16" (D)
- Fits through standard 48" door
- Net weight: 1,260 lbs (gas)
- F.S.S. (Fire Suppression System)
- 3-phase reversing basket
- Drive motor: 3/4 HP
- Blower motor: 3 HP
- Exhaust connection: 14"
- Removable front panel
- Available in gas, electric & steam
- Heat input (gas): 343,000 Btu/hr
- Airflow CFM: 1,170 (50Hz) / 2,100 (60Hz)
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- Steel steam coil
- Prison package
- DR version



## AD-285

- 30-lb capacity
- Tumbler diameter: 17 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.18 cu. ft.
- Door opening: 21 1/2"
- Steel door with gasketless glass
- 69 1/2" (H) x 28 1/2" (W) x 45 1/2" (D)
- Fits through standard 36" door
- Net weight: 455 lbs (gas)
- Drive motor: ½ HP
- Exhaust connection: 6"
- Available in gas
- Heat input (gas): 72,000 Btu/hr
- Airflow CFM: 313 (50Hz) / 375(60Hz)
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Stainless steel front, cabinet & basket



## AD-202

- 200-lb capacity
- Tumbler diameter: 55 5/8"
- Tumbler depth: 43 1/2"
- Tumbler volume: 61.2 cu. ft.
- Door opening: 40 3/4"
- Robust wheel drive
- Easy to load vertical steel doors
- Stainless steel basket with removable panels
- 106" (H) x 60 3/4" (W) x 58" (D)
- Gas model weight: 2,100 lbs (gas)  
/ 2,349 lbs (steam)
- 3-phase reversing basket
- Drive motor: 3 HP
- Blower motor: 7 1/2 HP
- Exhaust connection: 20" (gas & steam)
- Removable front panel
- Available in gas & steam
- Heat input (gas): 590,000 Btu/hr
- Airflow CFM (gas): 4,200 (50/60Hz)
- Airflow CFM (steam): 4,400 (50/60Hz)

### CUSTOMIZABLE OPTIONS

- F.S.S. (Fire Suppression System)
- Stainless steel sides
- Steel steam coil
- Prison package
- DR version



## AD-320

- 20-lb capacity x 2
- Tumbler diameter: 27 1/4"
- Tumbler depth: 25"
- Tumbler volume: 8.4 cu. ft.
- Door opening: 21 1/2"
- Heat input (gas): 60,000 Btu/hr per Pocket
- Airflow CFM: 333 (50Hz) / 400 (60Hz)
- Microprocessor
- Axial airflow
- Steel door with gasketless glass
- 78 1/4" (H) x 29 3/4" (W) x 38 7/8" (D)
- Exhaust connection: 6"
- Available in gas, electric & steam
- Fits through standard 36" door
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System)



## AD-236

- 30-lb capacity x 2
- Tumbler diameter: 27 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.1 cu. ft.
- Door opening: 21 1/2"
- Heat input (gas): 80,000 Btu/hr per Pocket
- Airflow CFM: 333 (50Hz) / 400 (60Hz)
- Microprocessor
- Radial airflow
- Steel door with gasketless glass
- 78 1/4" (H) x 28 1/2" (W) x 53 1/2" (D)
- Exhaust connection: 8"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System)
- Available in 3-phase electric



## AD-330

- 30-lb capacity x 2
- Tumbler diameter: 27 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.1 cu. ft.
- Door opening: 21 1/2"
- Heat input (gas): 68,000 Btu/hr per Pocket
- Airflow CFM: 333 (50Hz) / 400 (60Hz)
- Microprocessor
- Axial airflow
- Steel door with gasketless glass
- 78 1/4" (H) x 29 3/4" (W) x 43 1/8" (D - electric) / 48 15/16" (D - steam)
- Exhaust connection: 6"
- Available in gas, electric & steam
- Fits through standard 36" door
- 3-year limited warranty

### CUSTOMIZABLE OPTIONS

- Stainless steel front, cabinet & basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System)



## AD-333

- 30-lb capacity x 2
- Tumbler diameter: 27 1/4"
- Tumbler depth: 30"
- Tumbler volume: 10.1 cu. ft.
- Door opening: 21 1/2"
- Heat input (gas): 72,000 Btu/hr per Pocket
- Airflow CFM: 340 (50Hz) / 400 (60Hz)
- Microprocessor
- Trans-axial airflow
- Steel door with gasketless glass
- 78 1/4" (H) x 29 3/4" (W) x 53" (D)
- Exhaust connection: 8"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

#### CUSTOMIZABLE OPTIONS

- Grey or white front & cabinet



## AD-444

- 45-lb capacity x 2
- Tumbler diameter: 32 3/4"
- Tumbler depth: 30"
- Tumbler volume: 14.6 cu. ft.
- Door opening: 27"
- Heat input (gas): 106,000 Btu/hr per Pocket
- Airflow CFM: 442 (50Hz) / 530 (60Hz)
- Microprocessor
- Trans-axial airflow
- Steel door with gasketless glass
- 80 15/16" (H) x 34 5/16" (W) x 53 3/16" (D)
- Exhaust connection: 8"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

#### CUSTOMIZABLE OPTIONS

- Grey or white front & cabinet
- Single 10" exhaust connection



## AD-4545

- 45-lb capacity x 2
- Tumbler diameter: 32 3/4"
- Tumbler depth: 30"
- Tumbler volume: 14.6 cu. ft.
- Door opening: 27"
- Heat input (gas): 112,000 Btu/hr per Pocket
- Airflow CFM: 500 (50Hz) / 600 (60Hz)
- Microprocessor
- Radial airflow
- Steel door with gasketless glass
- 81 1/16" (H) x 34 5/16" (W) x 53 1/4" (D)
- Exhaust connection: 8"
- Available in gas
- Fits through standard 36" door
- 3-year limited warranty

#### CUSTOMIZABLE OPTIONS

- Grey or white front & cabinet
- Single 10" exhaust connection
- Stainless steel front, cabinet & basket
- S.A.F.E. (Sensor Activated Fire Extinguishing System)



## AD-210

- 200-lb capacity
- OPL
- Available in gas & steam
- 208-575V / 50Hz / 60Hz / 3 ph
- Heat input (gas): 650,000 Btu/hr
- Steam consumption: 890 lb/hr
- Airflow CFM: 5,300 (gas) / 5,417 (50Hz steam) / 6,500 (60Hz steam)
- Microprocessor
- Self-cleaning blower
- Stainless steel basket
- 3-year limited warranty
- Front panel access
- 11" wheel drive
- Tilt option(s)



## AD-310

- 300-lb capacity
- OPL
- Available in gas & steam
- 208-575V / 50Hz / 60Hz / 3 ph
- Heat input (gas): 1,125,000 Btu/hr
- Steam consumption: 1,153 lb/hr
- Airflow CFM: 6,500 (gas) / 8,500 (steam)
- Microprocessor
- Self-cleaning blower
- Stainless steel basket
- 3-year limited warranty
- Front panel access
- 11" wheel drive
- Tilt option(s)



## AD-410

- 400-lb capacity
- OPL
- Available in gas & steam
- 208-575V / 50Hz / 60Hz / 3 ph
- Heat input (gas): 1,400,000 Btu/hr
- Steam consumption: 1,257 lb/hr
- Airflow CFM: 9,200 (gas) / 10,300 (steam)
- Microprocessor
- Self-cleaning blower
- Stainless steel basket
- 3-year limited warranty
- Front panel access
- 11" wheel drive
- Tilt option(s)



## AD-464

- 460-lb capacity
- OPL
- Available in gas & steam
- 208-480V / 50Hz / 60Hz / 3 ph
- Gas BTUs - 2,800,000
- Steam Consumption: 2,071 lb/hr
- CFMs - 13,000 (gas & steam)
- Microprocessor
- Self-cleaning blower
- Stainless steel basket
- 3-year limited warranty
- Front panel access
- 11" wheel drive
- Tilt option(s)



## ADFG-5

- Dries five sets of turnout gear
- 81 ¾" (H) x 54 24/25" (W) x 31 1/10" (D)
- Net weight: 513 lbs
- Exhaust connection: 6"
- Heat input: 12 kW
- Airflow CFM: 300
- Self diagnostic microprocessor control
- Two independent heating and fan systems
- Directed airflow
- Drainage basin

### CUSTOMIZABLE OPTIONS

- Red, white, or stainless steel cabinet
- Glove hanger
- Boot hanger
- Adjustable single shelf



## ADFG-6

- Dries six sets of turnout gear
- 81 ¾" (H) x 64 24/25" (W) x 31 1/10" (D)
- Net weight: 606 lbs
- Exhaust connection: 6"
- Heat input: 12 kW
- Airflow CFM: 300
- Self diagnostic microprocessor control
- Two independent heating and fan systems
- Directed airflow
- Drainage basin

### CUSTOMIZABLE OPTIONS

- Red, white, or stainless steel cabinet
- Glove hanger
- Boot hanger
- Adjustable single shelf



## ADH-120

- 120-lb capacity
- Tumbler diameter: 44 1/2"
- Tumbler depth: 42 1/2"
- Tumbler volume: 38 1/2 cu. ft.
- Steam dimensions: 118" (H) x 48 1/2" (W) x 62 1/2" (D)
- Electric dimensions: 129 3/4" (H) x 48 1/2" (W) x 62 1/2" (D)
- Net weight: 1,915 lbs
- Intuitive micro controls
- Stainless steel basket support assembly
- Stainless steel front, base, outer drum, & filter housing
- High temp & high pressure monitors
- 3-phase motor with reversing basket
- Drive motor: 3/4 HP
- Blower motor: 3 HP
- Exhaust connection: 16"
- Available in electric & steam
- Steam consumption: 450 lb/hr
- Airflow CFM: 1,950 (steam) / 2,150 (electric)



## ADH-170

- 170-lb capacity
- Tumbler diameter: 51 1/2"
- Tumbler depth: 42 1/2"
- Tumbler volume: 42 1/2 cu. ft.
- Steam dimensions: 131 1/8" (H) x 55 1/4" (W) x 62 1/4" (D)
- Electric dimensions: 131 1/8" (H) x 55 1/4" (W) x 62 1/4" (D)
- Net weight: 2,220 lbs
- Intuitive micro controls
- Stainless steel basket support assembly
- Stainless steel front, base, outer drum, & filter housing
- High temp & high pressure monitors
- 3-phase motor with reversing basket
- Drive motor: 1 HP
- Blower motor: 7 1/2 HP
- Exhaust connection: 18"
- Available in electric & steam
- Steam consumption: 725 lb/hr
- Airflow CFM: 4,400 (steam) / 3,700 (electric)