

CUSTOMIZED UL FIRE RATED DOORS

DOORMAXTM
A U T O M A T I C
Protect Safety & Security

2025

CARGEM MANAGEMENT CORPORATION

P & E Bldg. Suite 1201, No. 12 United corner First Sts.
Barangay Kapitolyo, Pasig City 1603
Metro Manila, Philippines
Contact Nos.: 8631-9520; 8634-4746
Email Address: cmcnivra@gmail.com
Website: www.doormax.com.ph



Company introduction

Our Principal is a leading professional manufacturer of fire door & window and other special doors, located in the international metropolis -Shanghai, established in 2003.

The Enterprise has more than 15 years experience with two production bases located in Shanghai and Jiangsu. Main products cover UL&CE fire door & fire window, explosion proof door, sound proof door, hospital door, clean room door and other special door.

Benefit from advanced technique and efficient international marketing exploration. Our product have gained good reputation as reliable partner in over 50 countries and regions such as North America, Europe, Australia, South America, Middle East, South Asia , Southeast Asia, etc.

Our Products constantly strive to provide professional doors solution by providing premium products at competitive prices. Complete range of production line can meet different requirement from various customers. We sincerely hope to establish lasting business relationships with customers worldwide.

UL&EN Fire Door



DOORMAX Automatic fire door meets UL/NFPA/EN/BS standard, complying these criteria as UL 10B, UL10C, NFPA-252,EN-1634-1,BS-476-22. Doors are with UL/EN certificate. UL/NFPA/EN/BS 20 minutes up to 3 hours fire rating. Available with fire proof glazing and top light widely applied to Industrial, Commercial, Chemical, Nuclear and Medical Industries.

Frame

Various kinds design of frame profiles are available, suitable for different installation environment.

Hardware Available

UL/Non-UL panic bar, external level trim, door closer, hinge, flush bolt, vision glass, magnetic door holder, coordinator, smoke seal, handle lock, automatic door bottom seal etc.

Option

Door and frame surface finish could be customized according to RAL color chart.



Certified with
UL/NFPA/EN/BS 20 minutes
up to 3 hours fire rating



Certified with UL/NFPA/EN/BS
20 minutes up to 3 hours fire
rating




Certified with
UL/NFPA/EN/BS 20 minutes
up to 3 hours fire rating


UL STEEL FIRE DOOR




UL STEEL FIRE DOOR



STEEL FIRE DOOR



STEEL FIRE DOOR



STEEL FIRE DOOR



FIRE DOOR CROSS SECTION VIEW

STEEL DOOR SKIN:

16GA(1.5mm),18GA(1.1mm),20GA(0.9mm)
A40 Galvanized Or Cold-rolled Steel Skins
Construction is 1-3/4 " (45mm)Thickness

Hinge,closer,lock and strike plate reinforcements
shall be provided.

Hinge reinforcement:10GA(3.5mm)

Closer reinforcement:12GA(2.5mm)

Lock reinforcement:16GA(1.5mm)

Strike plate reinforcement:16GA(1.5mm)


The top,bottom and side closures are fabricated
from 16GA(1.5mm) thick channel shaped steel sections
welded to the front and back door skins.
Flush top channel:16GA(1.5mm)

Laser-welded side-seamed edge.

Widths up to and including 4 ' 0 "


Heights up to and including 8 ' 0 "

Available with polystyrene core or honeycomb core.



FIRE DOOR FRAME CONSTRUCTION VIEW


MASONRY/STUD CONSTRUCTION FRAME



Wire Anchor T Anchor Universal Anchor Tube Anchor

Jamb Depth	4-3/4 "	5-3/4 "	6-1/4 "	6-3/4 "	7-1/4 "	7-3/4 "	8-1/4 "	8-3/4 "	9-1/4 "	10-1/4 "
Throat Opening	3-3/4 "	4-7/8 "	5-1/4 "	5-3/4 "	6-1/4 "	6-3/4 "	7-1/4 "	7-3/4 "	8-1/4 "	9-1/4 "


DRYWALL FRAME



Compression Anchor Snap in sill Anchor

Jamb Depth	4-3/4 "	5-7/8 "	6-1/4 "	6-5/8 "	7-1/4 "	7-3/4 "	8-1/4 "
Throat Opening	3-3/4 "	4-7/8 "	5-1/4 "	5-5/8 "	6-1/4 "	6-3/4 "	7-1/4 "

Frame Profiles



xunzhong steel fire doors conform or exceed SDI/HMMA industrial standards,fire tested and certified with UL,Intertek/WH from 20Min up to 3hrs fire rating,complying criteria as NFPA252,UBC7-2,UL10(b),UL10(c)

WOODEN FIRE DOOR

”

Certified withUL/NFPA/EN/BS
20 minutes up to 90
minutes fire rating
Single Door customized
Max Size: 4*8 feet





UL WOODEN FIRE DOOR

”

Certified with UL/NFPA/EN/BS
20 minutes up to 90 minutes
fire rating
Double Door customized Max
Size: 8*8 feet
Available with panic bar

UL WOODEN FIRE DOOR



UL FIRE DOOR



UL FIRE DOOR



HOSPITAL DOOR



HOSPITAL DOOR



HOSPITAL DOOR



MEDICAL DOOR



SOUND PROOF DOOR



EXPLOSION PROOF DOOR





WOODEN DOOR



STEEL SHUTTER PROOF DOOR



MATERIAL: STEEL/ALUMINUM ALLOY

AVAILABLE SIZE: CUSTOMIZED

BASIC SETTING: MOTOR, REMOTE CONTROL, SWITCH

STEEL SHUTTER DOOR




MATERIAL: STEEL/ALUMINUM ALLOY

AVAILABLE SIZE: CUSTOMIZED

BASIC SETTING: MOTOR, REMOTE CONTROL, SWITCH

STEEL SHUTTER DOOR



INDUSTRIAL FOLDING DOOR





FACTORY





FACTORY






FACTORY





FACTORY





FACTORY




SUCCESSFUL CASE





APPLICATION





2025

THANK YOU