Model	BA140
Weight Capacity	400 lb (181 kg)
Maximum Speed <sup>2</sup>	Up to 8 mph (12.8 km/h)
Ground Clearance <sup>3</sup>	1.57" at motor skid plate 2.68" at front bumper 4.45" at mid-deck
Turning Radius <sup>3</sup>	53″
Dimensions <sup>3</sup>	Length: 49.6" Width: 27.83"
Seat-to-Deck Height <sup>3</sup>	18.11″
Front & Rear Tires <sup>3</sup>	9" pneumatic
Suspension	Full suspension
Range Per Charge <sup>2,5</sup>	20Ah Battery Pack: Up to 14.5 mi (23.3 km) at 220 lb (100 kg) Up to 11.25 mi (18.1 km) at 400 lb (181 kg) 40Ah Battery Pack: Up to 29 mi (46.7 km) at 220 lb (100 kg) Up to 22.5 mi (36.2 km) at 400 lb (181 kg)
Total Weight <sup>6</sup>	183.4 lb (83.2 kg) with 20 Ah battery 197.8 lb (89.7 kg) with 40 Ah battery
Standard Seating <sup>3</sup>	Type: Stadium seat with slider Material: Black Vinyl Width: 18.31" Depth: 17.32" Weight: 34.8 lb (15.8 kg)
Drive System	Rear-wheel drive, sealed transaxle, 36-volt DC motor
Dual Braking System	Regenerative and electromechanical
Battery Require- ments <sup>4</sup>	<b>Type:</b> Lithium-ion battery pack <b>Size:</b> 20Ah or 40Ah
Battery Pack Weight <sup>7</sup>	<b>20 Ah:</b> 20.8 lb (9.4 kg) <b>40 Ah:</b> 35.2 lb (16 kg)
Battery Charger	4 amp, off-board charger

1 Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.

- 2 Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of +10%, -5%.
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 Lithium-ion, AGM, Gel-Cell, or Hybrid Gel (Hybrid Gel is defined as Nano Silica Gel Electrolyte with High Quality Glass Mat Separators) type required.
- 5 Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 6 Includes standard seat.
- 7 Battery weight may vary based on manufacturer.





# UNLEASH ZOOM!

**8 MPH** 





CAPACITY

TOP SPEED SUS

**SUSPENSION** 



#### FDA Class II Medical Device<sup>1</sup>



Enjoy maximum visibility with LED lighting.

Accessorize your Bandit.

Intuitive controls provide a carefree driving experience.

### BUILT FOR THE BOLD.

It's time to discover what's really out there. With impressive ground clearance, a top speed of 8 mph (12.8 km/h), and a lithium-ion battery pack which powers up to a 29-mi (46.7 km) range, the Baja<sup>®</sup> Bandit is built for exploring the unknown and confidently tackling rugged terrain away from the beaten path.

## FEATURES

- 4.5" ground clearance
- 400 lb (181 kg) weight capacity
- Competitive 53" turning radius
- Infinite tiller adjustment lever
- USB port for charging your devices
- Full LED lighting package for maximum visibility
- Full bumper package (standard)
- Supplemental hand brake for additional stopping power
- Feather-touch disassembly
- Seat post with full suspension
- The upgradable dual lithium-ion battery configuration will deliver up to a 29-mi (46.7 km) range on a single charge (14.5 mi (23.3 km) with the standard single lithium-ion battery)
- 3-year warranty on lithium-ion battery



#### ACCESSORIES

- 50/60/70" lap belt
- Cup holder
- Cell phone holder
- Rearview mirror
- Saddlebag
- Safety flag
- Weather cover

Only one rear accessory can be used at a time.

- Walker holder
- 3" single or double cane or crutch holder
- Forearm crutch holder
- Wishbone crutch holderOxygen holder
- Quad cane holder
- Rear basket

Cup holder, rear basket and saddlebag can be ordered as a bundle.