

Hose bibbs

Hose bibbs are part of our everyday life. They allow us to hook up a garden hose to water the plants, wash the car, clean out the gutters, fill the swimming pool, etc. However, every time you connect a garden hose to a hose bibb, you are extending the end of the water line. To make sure that no harmful materials are drawn back into the garden hose, a vacuum breaker should be installed on each hose bibb. When the hose bibb is exposed to freezing conditions, make sure to use a self-draining, frost-proof vacuum breaker.






NOTE

Make sure to use only listed or approved products. Should you have any questions regarding the selection or installation of proper backflow protection, check with your local city building and safety department.

Boilers

Due to the pressure that may build up inside of a boiler, the pressure of the boiler water may exceed that of the water feeding the boiler. The boiler water (which may be chemically treated with poisonous anti-corrosion compounds, etc.) may be pushed, or backpressured, into the make-up water line. This chemically contaminated water may be forced back into your home's potable water system, unless there is an appropriate backflow preventer that is designed for backpressure.



LOCAL CONTACTS

Iowa-American Water Company Mr. Brock Earnhardt (563) 324-3264

City of Davenport - Mr. Bill Miller (563) 326-7745

City of Bettendorf - Mr. Joe Creek (563) 344-4074

2002 © University of Southern California



Foundation for Cross-Connection Control and Hydraulic Research

Prevalence of Cross-Connections in Household Plumbing

We would like to thank you for participating in this water-use survey. The purpose of the study is to conduct a water-use survey to determine if there are any unprotected cross-connections present in the household plumbing system. A cross-connection is a connection between the drinking water plumbing system and any other source, which may contribute to the degradation of the quality of the drinking water.



Your local water company, health, and building and safety departments work hard to provide the safest water possible to your home. However, once this water enters your property, there are common problems that may arise due to improper changes in, or misuse of, your plumbing system.

During the review of the various uses of water within your household, some of the following may have been found. This brochure is intended to provide some additional information to answer your questions.


Our Homes...

Have you ever considered all of the places that you use water in your home? You may be surprised how many different ways that water can be used, and possibly misused.

This brochure discusses a few of the uses of water that you might want to pay more attention to in order to protect the purity of the water you drink, cook with, or bath in. Let's look at a few examples.

Sinks, Tubs, Tanks

The faucets in your bathroom or kitchen must be located so that the end of the faucet is above the overflow level of the sink or tub. Fill lines to water troughs or tanks must also be physically separated or "air-gapped." If there is no air-gap, then the contents of the sink, tub, or tank may be sucked or "backsiphoned" into the water line during a loss of water pressure.



Toilets

MUST BE PHYSICALLY Toilets need water to flush the waste mate-SEPARATED OR BALLCOCK WITH AIRGAPPED. (A ANTI-SIPHON VALVE. rial into the sewer system. The water that PLASTIC OR METAL MUST BE ABOVE THE CLP IS TYPICALLY WATER LEVEL AT LEAST flushes the toilet enters into the toilet tank USED TO HOLD THE MAKE UPTUBE TO TUIE IN PLACE) REFILL THE "BOWL" from the small hose or pipe connected to the bottom of the toilet tank. It is essential that the float-valve (or anti-siphon ballcock) VVATER LEVEL inside of the toilet tank is the correct type PLOAT MAY ALSO so that the contents of the toilet tank BE A BALL ON A LONG ROD don't get back into the drinking FLOAT MOVES! water system in your house. TO (DINTROL WATER LEVEL As shown in the illustration, the anti-siphon ballcock and refill tube must be TOILET WATER TO TANK FLUSH BOWL above the water level WATER in the tank. TOILET LINE

Irrigation

Irrigation systems make watering of your lawn or garden much easier, but if not properly constructed, contaminants may backflow into your drinking water. Backflow protection may be provided with vacuum breakers (atmospheric (AVB) or pressure (PVB or SVB)) or reduced pressure principle assemblies (RP).

Water pooling around sprinkler heads may be contaminated by chemicals, fertilizers, or animal waste.

