



# SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 Product identifier

Product name: Bio-Flex, Part A Product code: Bio-Flex, Part A

Synonym(s): Bio-renewable epoxy resin system

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Coating resin

Uses advised against: None specified

## 1.3 Details of the supplier and of the safety data sheet

BIO-DEK™, LLC 2827 Andrew Ave

Pascagoula, MS 39567 USA

+1-228-205-3255

#### 1.4 Emergency telephone number

CHEMTREC: +1-800-424-9300 - 24 HR EMERGENCY

#### **SECTION 2 - HAZARDS IDENTIFICATION**

#### 2.1 Classification of substance or mixture

Product definition: Mixture

#### Classification in accordance with 29 CFR 1910.1200 (OSHA HCS) and Regulation EC No. 1272/2008

Skin Irritation - Category 2 [H315] Sensitization, Skin - Category 1 [H317] Eye Irritation - Category 2A [H319]

Aquatic Toxicity, Chronic - Category 2 [H411]

#### 2.2 Label elements

Hazard symbol(s):







Signal word: Warning

Hazard statement(s): H315 + H319 - Causes skin irritation and serious eye irritation

H317 - May cause an allergic skin reaction H411 - Toxic to aquatic life with long lasting effects

### **Precautionary statements**

[Prevention] P261 - Avoid breathing mist or vapor.

P264 - Wash hands and other exposed skin areas thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment

P280 - Wear protective gloves, protective clothing and eye protection.

[Response] H302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 - Specific treatment: Get medical help if you feel unwell. Refer to the product label or to Section 4 of this SDS.

P333 + P337 + P317 - If skin irritation or rash occurs or if eye irritation persists: Get medical help.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

H391 - Collect spillage.

[Disposal] P501 - Dispose of contents and containers in accordance with national and local regulations.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

None as defined under 29 CFR 1910.1200.

#### 2.4 Unknown acute toxicity (US)

No data available

# **SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Not applicable

Effective Date: 24 September 2025 Page 1 of 8

BIO-DEK™ Bio-Flex, Part A

#### 3.2 Mixtures.

% by Weight	Ingredient	CAS Number	EC Number	Index Number	GHS Classification
< 70	Bisphenol A/epichlorohydrin epoxy resin	Proprietary			H315, H317, H319, H411
< 35	Reactive diluent	Proprietary			H315, H317
< 0.5	Titanium dioxide	13463-67-7	236-675-5		H351*

<sup>\*</sup>The classification of titanium dioxide as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10µm.

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with the applicable provisions of paragraph (i).

There are no additional ingredients present in this product which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

# **SECTION 4 - FIRST AID MEASURES**

# 4.1 Description of first aid measures

**Inhalation:** If product vapor causes respiratory irritation or distress, move the exposed person to fresh air immediately. If breathing is difficult or irregular, administer oxygen; if respiratory arrest occurs, start artificial respiration by trained personnel. If unconscious, maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If symptoms persist or if you feel unwell, seek medical attention.

**Eyes:** Immediately flush eyes with large amounts of water or saline solution for at least 15 minutes, occasionally lifting the upper and lower lids. Remove contact lenses, if present and easy to do, after first 2 minutes and continue rinsing. If irritation persists seek medical attention, preferably from an ophthalmologist.

**Skin:** Flush skin with large amounts of water while removing contaminated clothing. Wash the affected area with soap and water followed by thorough rinsing. Wash contaminated clothing and shoes before reuse. Discard items that cannot be decontaminated, including leather articles such as shoes, belts and watchbands. If irritation persists, rash develops or if you feel, seek medical attention.

**Ingestion:** Rinse mouth with water if the person is conscious. Remove dentures if present. Give 1 - 2 glasses of water to drink if the person is conscious, alert, able to swallow and not experiencing respiratory difficulty. Vomiting may occur spontaneously. To prevent aspiration of material into the lungs, lay the person on one side with the head lower than the waist. Never give anything by mouth to an unconscious or convulsing person. Do not leave the person unattended. Seek immediate medical attention.

# 4.2 Most important symptoms and effects, both acute and delayed

### Potential health symptoms and effects

Eyes: Causes serious eye irritation with redness, swelling, pain and tearing. Vapor can cause eye irritation.

**Skin:** Causes skin irritation. Prolonged contact with unprotected skin can cause localized redness, itching, blisters, chemical burns and pain/discomfort. May cause an allergic skin reaction with subsequent sensitization upon re-exposure to this material. Individuals previously sensitized can experience allergic skin reactions with symptoms of redness, itching, swelling and rash upon re-exposure to material.

**Inhalation:** Not expected to be an inhalation hazard due to the low volatility of this material. May cause respiratory irritation when heated with runny nose, cough, sore throat, sneezing, wheezing and shortness of breath.

**Ingestion:** Causes irritation of the gastrointestinal tract with nausea, vomiting, abdominal pain and diarrhea. Aspiration of material into the lungs during swallowing or vomiting causing lung inflammation and chemical pneumonitis, which may be fatal. Symptoms of aspiration into the lungs include coughing, gasping, choking, shortness of breath, bluish colored skin, rapid breathing and rapid heart rate

Chronic: May cause skin sensitization with subsequent contact dermatitis upon re-exposure to this material in susceptible individuals.

# 4.3 Indication of any immediate medical attention and special treatment needed

### Advice to doctor and hospital personnel

Treat symptomatically and supportively.

# **SECTION 5 - FIRE FIGHTING MEASURES**

### 5.1 Extinguishing media

**Suitable methods of extinction:** Use extinguishing media such as water fog or spray, carbon dioxide, alcohol resistant foam or dry chemical. **Unsuitable methods of extinction:** Water jets or streams may spread the fire.

#### 5.2 Special hazards arising from the substance or mixture

Closed containers may explode due to the buildup of pressure when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent or may be delayed. Obtain medical attention.

**Explosion hazards**: This product is not an explosion hazard.

#### 5.3 Advice to firefighters

Full protective equipment including self-contained breathing apparatus should be used. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat. If possible, water contaminated by this material should be contained from being discharged to any waterway, sewer or drain to prevent environmental contamination.

Effective Date: 24 September 2025 Page 2 of 8

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Evacuate non-essential personnel. Wear appropriate protective clothing and equipment designated in Section 8.2, including respiratory protection. Ventilate the area. Remove all sources of ignition. NO SMOKING. Clean up spills immediately. Spill creates a slip hazard.

### 6.2 Environmental precautions

Avoid dispersal of spilled material or runoff and prevent contact with soil and entry into drains, sewers or waterways. Use water sparingly to minimize environmental contamination and reduce disposal requirements.

### 6.3 Methods and materials for containment and cleaning up

Approach spill from upwind direction. DO NOT FLUSH SPILL DOWN THE DRAIN. Cover drains and contain spill. Cover spill with a large quantity of inert absorbent. Do not use combustible material such as sawdust. Collect material and place into an approved container for proper disposal. Observe possible material restrictions (Sections 7.2 and 10.5). Do not allow material or runoff from rinsing contaminated areas to enter floor drains or storm drains and ditches that lead to waterways. Dispose of contents, containers and waste material via a licensed waste disposal contractor.

### 6.4 Reference to other sections

See Section 13 for additional waste treatment information.

# **SECTION 7 - HANDLING AND STORAGE**

#### 7.1 Precautions for safe handling

Wear all appropriate personal protective equipment specified in Section 8.2. Do not get in eyes or on skin or clothing. Do not inhale mist or vapor. NO SMOKING. If normal use of material presents a respiratory hazard, use only adequate ventilation or wear an appropriate respirator. Wash contaminated clothing and shoes thoroughly before reuse. Discard items that cannot be decontaminated, including leather articles such as shoes, belts and watchbands

#### Advice on protection against fire and explosion

Keep away from heat, hot surfaces and incompatible materials.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in dry, cool, well-ventilated areas away from incompatible materials (see Section 10.5), food and drink. Store between 10 - 35 °C (50 - 95 °F). Keep from freezing. Prolonged storage of material or cold temperatures may result in reversible crystallization. Crystallized material can be liquified by heating slowly to 50 °C (122 °F) for 6 - 24 hours.

Transfer only to approved containers having correct labeling. Keep container tightly closed when not in use. Protect containers from physical damage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Containers are hazardous when empty as they contain product residue. Use appropriate containment to avoid environmental contamination. Ventilate closed areas. Keep out of reach of children.

### 7.3 Specific end uses

Apart from the uses mentioned in Section 1.2, no other specific uses are stipulated.

# SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## 8.1 Control parameters

# Occupational exposure limit values

Obdepational exposure limit values					
CAS Number	Ingredient	OSHA PEL	ACGIH TLV	NIOSH	
13463-67-7	Titanium dioxide	5 mg/m³ TWA, resp. fraction	10 mg/m <sup>3</sup> TWA		
		10 mg/m³ TWA, total dust			

# 8.2 Exposure controls

**Engineering measures:** Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. Use adequate ventilation. Local exhaust is preferable. Refer to Section 7.1.

**Individual protection measures:** Wear protective clothing to prevent repeated or prolonged contact with product. Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the representative supplier.

**Hygiene measures:** Facilities storing or using this material should be equipped with an eyewash station and safety shower. Change contaminated clothing. Preventive skin protection is recommended. Wash hands thoroughly after use, before eating, drinking, smoking or using the lavatory.

Eye/face protection: Wear chemical splash goggles or safety glasses with unperforated side shields during use.

**Hand protection:** Wear gloves recommended by glove supplier for protection against materials in Section 3. Gloves should be impermeable to chemicals and oil. Breakthrough time of selected gloves must be greater than the intended use period.

Skin protection: Wear protective clothing. Wear protective boots if the situation requires.

Respiratory protection: Always use an approved respirator when vapor/aerosols exceed permissible exposure limits. Where risk assessment

Effective Date: 24 September 2025 Page 3 of 8

shows air-purifying respirators are appropriate use a half-mask respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

## Environmental exposure controls: Do not empty into drains.

PPE must not be considered a long-term solution to exposure control. PPE usage must be accompanied by employer programs to properly select, maintain, clean, fit and use. Consult a competent industrial hygiene resource to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.







# **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1 Information on basic physical and chemical properties

Appearance Opaque, colored, viscous liquid or semi-paste

Odor Mild, characteristic **Odor Threshold** No data available Molecular Weight Not applicable **Chemical Formula** Not applicable На No data available **Melting Point** Not applicable **Boiling Point Range** No data available **Evaporation Rate** No data available Flammability (solid, gas) Not applicable

Flash Point > 140 °C (> 284 °F) [estimated]

No data available **Autoignition Temperature Decomposition Temperature** No data available Lower Explosive Limit (LEL) No data available **Upper Explosive Limit (UEL)** No data available No data available Vapor Pressure **Vapor Density** No data available **Specific Gravity** No data available **Bulk Density** No data available Viscosity No data available Solubility in Water Negligible Partition Coefficient (n-octanol/water) No data available Not applicable **Oxidizing Properties** Not applicable **Explosive Properties** No data available Volatiles by Weight @ 21 °C

9.2 Other Data

Particle Characteristics No data available

# **SECTION 10 - STABILITY AND REACTIVITY**

# 10.1 Reactivity

No special reactivity has been reported during normal conditions of handling and use.

#### 10.2 Chemical Stability

This material is stable under recommended conditions of storage and handling.

# 10.3 Possibility of hazardous reactions

Reacts exothermically with amines, generating considerable heat buildup.

#### 10.4 Conditions to avoid

Avoid high temperatures, hot surfaces and contact with incompatible materials.

### 10.5 Incompatible materials

Strong oxidizing agents, strong alkalis, strong acids, amines

## 10.6 Hazardous decomposition products

Thermal decomposition products may include oxides of carbon, smoke, toxic fumes and gases.

Effective Date: 24 September 2025 Page 4 of 8

BIO-DEK™ Bio-Flex, Part A

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

## 11.1 Information on toxicological effects

#### Acute oral toxicity

No data available

#### Acute inhalation toxicity

No data available

#### Acute dermal toxicity

No data available

#### Skin irritation

Causes skin irritation.

#### Eye irritation

Causes severe eye irritation.

#### Sensitization

May cause an allergic skin reaction.

### Carcinogenicity

No data available

#### Germ cell mutagenicity

No data available

#### Reproductive toxicity

No data available

## Specific organ toxicity - single exposure

May cause respiratory irritation.

#### Specific organ toxicity - repeated exposure

No data available

#### **Aspiration hazard**

No data available

#### 11.2 Further information

**Carbon Black** is considered a hazard by inhalation. IARC Group 2B Carcinogen - *Possibly carcinogenic to humans*; ACIGH A4 Carcinogen - *Not classifiable as a human carcinogen*. Carbon Black was once considered carcinogenic because of impurities; however, new manufacturing techniques have eliminated contamination. NIOSH considers carbon black in the presence of polycyclic aromatic hydrocarbons (PAHs) to be a potential occupational carcinogen as defined by the OSHA carcinogen policy [29 CFR 1990]. Not listed as a carcinogen by OSHA.

**Titanium Dioxide**: IARC Group 2B Carcinogen - *Possibly carcinogenic to humans*. Not listed as a carcinogen by ACGIH, OSHA or NTP. The IARC summary concluded, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials such as paint".

No data is available regarding the mutagenicity or teratogenicity of this product, nor is there any available data that indicates it causes adverse developmental or fertility effects.

Handle in accordance with good industrial hygiene and safety practice.

# **SECTION 12 - ECOLOGICAL INFORMATION**

### 12.1 Toxicity

This material is toxic to aquatic life with long lasting effects.

# 12.2 Persistence and degradability

This material cannot be considered readily biodegradable.

## 12.3 Bioaccumulation potential

The bioaccumulation potential for this material is moderate.

# 12.4 Mobility in soil

The potential for mobility in soil is low.

#### 12.5 Results of PBT and vPvB assessment

This mixture contains no substances considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher

#### 12.6 Endocrine disrupting properties

This material does not contain substances considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Effective Date: 24 September 2025 Page 5 of 8

BIO-DEK™ Bio-Flex, Part A

# 12.7 Other effects

#### Additional ecological information

Do not allow material to enter surface waters, wastewater or soil.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods

**Methods of disposal:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. The generation of waste should be avoided or minimized whenever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products in accordance with national, state and local regulations. Disposal of this product should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA U-Series: No listings above the reportable threshold (de minimis)

# **SECTION 14 - TRANSPORT INFORMATION**

**Note:** Transportation information provided is for reference only. Customer is urged to consult 49 CFR 100 - 177, IMDG, IATA, EC, United Nations TDG and WHMIS (Canada) information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

Limited quantity for miscellaneous materials in Packing Group III when inner packagings are not over 5.0 liters (1.3 gallons) net capacity each, packed in a strong outer packaging.

USA DOT (Ground Transportation) NOT REGULATED FOR TRANSORT

**TDG (Transportation of Dangerous Goods)** 

Proper Shipping Name Environmentally hazardous substance, liquids, n.o.s. (Epoxy resins)

Hazard Class 9 UN UN3082

Packing Group III
Marine Pollutant Yes

IMO/IMDG (Water Transportation)

Proper Shipping Name Environmentally hazardous substance, liquids, n.o.s. (Epoxy resins)

Hazard Class 9

UN UN3082
Packing Group III
Marine Pollutant Yes
EMS Number F-A, S-F

ICAO/IATA (Air Transportation)

Proper Shipping Name Environmentally hazardous substance, liquids, n.o.s. (Epoxy resins)

Hazard Class 9

UN UN3082

Packing Group III

**Quantity Limitations** 49 CFR 175.27 and 175.75 - Cargo Aircraft Only: No limit; Passenger Aircraft: No limit

RID/ADR (Rail Transportation)

Proper Shipping Name Environmentally hazardous substance, liquids, n.o.s. (Epoxy resins)

 Hazard Class
 9

 UN
 UN3082

 Packing Group
 III

# **SECTION 15 - REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for substance or mixture

**U. S. Federal Regulations** 

OSHA Hazard Communication Standard: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

OSHA Process Safety Management Standard: This product is not regulated under OSHA PSM Standard 29 CFR 1910.119.

EPA Risk Management Planning Standard: This product is not regulated under EPA RMP Standard (RMP) 40 CFR Part 68.

EPA Federal Insecticide, Fungicide and Rodenticide Act: This product is not a registered Pesticide under the FIFRA, 40 CFR Part 150.

**EPA Safe Drinking Water Act (SDWA):** None of the components of this product exceed the threshold (de minimis) reporting levels established by SWDA.

Toxic Substance Control Act (TSCA) Inventory: All substances in this product are listed on the TSCA Inventory. This product is not subject to

Effective Date: 24 September 2025 BIO-DEK™ Bio-Flex, Part A

Page 6 of 8

Placard(s)

Marine Pollutant

TSCA 12(b) Export Notification.

Drug Enforcement Administration (DEA) List 2, Essential Chemicals (21 CFR 1310.02(b)) and 1310.4(f)(2)) and Chemical Code Number No listings

Drug Enforcement Administration (DEA) Lists 1 & 2, Exempt Chemical Mixtures (21 CFR 1310.12(c)) and Code Number: No listings

Department of Homeland Security (DHS) Chemical Facility Anti-Terrorism Standards (CFATS) Chemicals: No listings

Superfund Amendments and Reauthorization Act (SARA)

SARA Section 311/312 Hazard Categories: Causes skin irritation and serious eye irritation

May cause an allergic skin reaction

**SARA 313 Information:** None of the chemicals in this product exceed the threshold (de minimis) reporting levels established by Section 313 of the Emergency Planning and Community Right-to Know Act of 1986.

**SARA 302/304 Extremely Hazardous Substances:** None of the chemicals in this product exceed the threshold (de minimis) reporting levels established by these sections of Title III of SARA.

**SARA 302/304 Emergency Planning & Notification:** None of the chemicals in this product exceed the threshold (de minimis) reporting levels established by these sections of Title III of SARA.

Comprehensive Response Compensation and Liability Act (CERCLA): None of the components of this product exceed the threshold (de minimis) reporting levels for hazardous wastes established by CERCLA.

#### Clean Air Act (CAA)

This product does not contain hazardous air pollutants (HAPs) designated in CAA Section 112 (b).

This product does not contain Class 1 or Class 2 ozone depletors.

#### Clean Water Act (CWA)

This product does not contain hazardous substances.

This product does not contain priority pollutants.

This product does not contain toxic pollutants.

#### **U.S. State Regulations**

#### California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

**WARNING:** This product can expose you to *Epichlorohydrin* (trace), which is known to the state of California to cause cancer, birth defects or other reproductive harm. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.

#### Other U.S. State Inventories

None of the components in this product exceed of the reporting threshold (de minimis) of any State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants lists.

#### Canada

WHMIS Hazard Classification: May cause an allergic skin reaction

Canadian National Pollutant Release Inventory (NPRI): This product contains no chemicals above the reporting threshold (de minimis) listed on the NPRI.

### **European Economic Community**

WGK, Germany (Water danger/protection): 2 (obviously hazardous to water)

# **Global Chemical Inventory Lists**

Country	Inventory Name	Listed
Canada	Domestic Substance List (DSL)	Yes
Canada	Non-Domestic Substance List (NDSL)	No
Europe	Inventory of New and Existing Chemicals (EINECS)	Yes
United States	Toxic Substance Control Act (TSCA)	Yes
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
New Zealand	New Zealand Inventory of Chemicals (NZIoC)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (KECI)	Yes
Philippines Philippines Inventory of Chemicals and Chemical Substances (PICCS)		Yes

<sup>\*</sup>Yes - All components of this product comply with the inventory requirements administered by the governing country.

# 15.2 Chemical safety assessment

A chemical safety assessment was not carried out for this product.

Effective Date: 24 September 2028 BIO-DEK™ Bio-Flex, Part A

No - One or more components of this product are not on the inventory or are exempt from listing or will require registration.

# **SECTION 16 - OTHER INFORMATION**

# **Hazardous Material Information System (HMIS)**

# HEALTH FLAMMABILITY PHYSICAL HAZARD C PERSONAL PROTECTION

C = safety goggles, gloves & apron

#### **HMIS Hazard Rating Legend**

0 = Minimal, 1 = Slight, 2 = Moderate,

3 = Serious, 4 = Severe,

\* = Chronic Health Hazard

#### NFPA Hazard Rating Legend

0 = Insignificant, 1 = Slight, 2 = Moderate,

3 = High, 4 = Extreme

# National Fire Protection Association (NFPA)



Instability

**Special** 

#### **Abbreviation Key**

ACGIH	American Conference of Governmental Industrial Hygienists	$LD_Lo$	Lowest Lethal Dose
ADR	Accord Dangereux Routier (European regulations concerning the international transport of dangerous goods by road)	mppcf	Millions of Particles Per Cubic Foot
CAS	Chemical Abstract Services	NA	North America
CFR	Code of Federal Regulations	NAERG	North American Emergency Response Guide Book
COC	Cleveland Open Cup	NIOSH	National Institute for Occupational Safety & Health
DOT	Department of Transportation	NTP	National Toxicology Program
EC <sub>50</sub>	Half maximal effective concentration	OSHA	Occupational Safety and Health Administration
EMS	Emergency Response Procedures for Ships Carrying Dangerous	PBT	Persistent, Bioaccumulating and Toxic
EPA	Environmental Protection Agency	PEL	Permissible exposure limit
ErC <sub>50</sub>	Reduction of Growth Rate	PMCC	Pensky-Martens Closed Cup
ERG	Emergency Response Guide Book	ppm	Parts Per Million
FDA	Food and Drug Administration	RCRA	Resource Conservation and Recovery Act
GHS	Globally Harmonized System of Classification and Labelling of Chemicals (GHS)	RID	Dangerous Goods by Rail
HCS	Hazard Communication Standard	RQ	Reportable Quantity
IARC	International Agency for Research on Cancer	TCC/Tag	Tagliabue Closed Cup
IATA	International Air Transport Association	TLV	Threshold Limit Value
IC <sub>50</sub>	Half Maximal Inhibitory Concentration	TSCA	Toxic Substance Control Act
ICAO	International Civil Aviation Organization	TWA	Time-weighted Average
IDLH	Immediately Dangerous to Life and Health	UN	United Nations
IMDG	International Maritime Dangerous Goods	VOC	Volatile Organic Compounds
IMO	International Maritime Organization	vPvB	Very Persistent and Very Bioaccumulating
LC <sub>50</sub>	50% Lethal Concentration	WHMIS	Workplace Hazardous Materials Information System
LD <sub>50</sub>	50% Lethal Dose		

## **DISCLAIMER OF RESPONSIBILITY**

The information herein is given in good faith and is believed to be accurate and correct; however, no warranty, expressed or implied, is made. BIO-DEK™, LLC assumes no responsibility for personal injury or property damage that may arise from the use of this material since the conditions of handling and use are beyond our control. It is the responsibility of the user to determine the suitability of this information for the adoption of the safety precautions as may be necessary. It is the responsibility of the user to comply with all Federal, State and local laws and regulations regarding use of this product. Vendees or users assume all risks associated with the use of this material. We reserve the right to revise Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the company to make sure that the Safety Data Sheet is the latest issue.

Revision date: 24 September 2025, Version 2 Supersedes SDS: 14 February 2023, Version 1

<end of document>

Effective Date: 24 September 2025 BIO-DEK™ Bio-Flex, Part A