

**Prepared for:**  
Byron Shumaker  
HEIMAN FIRE EQUIPMENT BB  
25814 RUDOLPH AVE  
  
SIOUX FALLS, SD 57107  
Phone: 6055435098

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com

## S P E C I F I C A T I O N   P R O P O S A L

	Description	Weight Front	Weight Rear
<b>Price Level</b>	M2 PRL-28M (EFF:MY25 ORDERS)		
<b>Data Version</b>	SPEC PRO 21 DATA RELEASE VER 041		
<b>Vehicle Configuration</b>	M2 106 PLUS CONVENTIONAL CHASSIS 2025 MODEL YEAR SPECIFIED SET BACK AXLE - TRUCK STRAIGHT TRUCK PROVISION, NON-TOWING LH PRIMARY STEERING LOCATION	5,709	3,450
<b>General Service</b>	TRUCK CONFIGURATION DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES) EPA EMISSIONS CERTIFICATION FOR 50 STATE REGISTRATION - CARB EXEMPT, FIRE AND EMERGENCY VEHICLES ONLY (INCLUDES 6X4 INCH LABEL SHIPPED LOOSE) NONE FIRE SERVICE EMERGENCY VEHICLES BUSINESS SEGMENT LIQUID BULK COMMODITY TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS MAXIMUM 8% EXPECTED GRADE SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE MEDIUM TRUCK WARRANTY		

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
EXPECTED FRONT AXLE(S) LOAD : 14600.0 lbs		
EXPECTED REAR DRIVE AXLE(S) LOAD : 26000.0 lbs		
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 40600.0 lbs		

### Truck Service

FIRE TANK - NO MAIN DRIVELINE DRIVEN SPLIT-  
 SHAFT PTO/PUMP  
 ROSENBAUER  
 EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE  
 FRAME "XX" INCHES : 32.0 in

### Engine

CUM L9 360EV HP @ 2200 RPM, 2200 GOV RPM, 1150 LB-FT @ 1200 RPM, R/F/E	640	30
---	-----	----

### Electronic Parameters

68 MPH ROAD SPEED LIMIT  
 CRUISE CONTROL SPEED LIMIT 5 MPH HIGHER  
 THAN ROAD SPEED LIMIT  
 PTO MODE ENGINE RPM LIMIT - 1200 RPM  
 PTO MODE BRAKE OVERRIDE - SERVICE  
 BRAKE APPLIED  
 PTO RPM WITH CRUISE SET SWITCH - 1200  
 RPM  
 PTO RPM WITH CRUISE RESUME SWITCH - 1200  
 RPM  
 PTO MODE CANCEL VEHICLE SPEED - 15 MPH  
 PTO GOVERNOR RAMP RATE - 500 RPM PER  
 SECOND  
 FUEL DOSING OF AFTERTREATMENT ENABLED  
 IN PTO MODE-CLEANS HYDROCARBONS AT  
 HIGH TEMPERATURES ONLY  
 ONE TEM PTO SPEED  
 PTO SPEED 1 SETTING - 1200 RPM  
 PTO MINIMUM RPM - 700  
 REGEN INHIBIT SPEED THRESHOLD - 5 MPH  
 PTO 1, NO SWITCH, TEM SUPPLIED REQUEST  
 AND INTERLOCKS, WITH PTO CONNECTIONS,  
 ENGAGE BEFORE DRIVING INTERLOCK  
 PTO 2, NO SWITCH, TEM SUPPLIED REQUEST  
 AND INTERLOCKS, WITH PTO CONNECTIONS,  
 ENGAGE BEFORE DRIVING INTERLOCKS

### Engine Equipment

**Prepared for:**

Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**

Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
EPA 2010/GHG 2024 CONFIGURATION		
STANDARD OIL PAN		
ENGINE MOUNTED OIL CHECK AND FILL		
SIDE OF HOOD AIR INTAKE WITH NFPA COMPLIANT EMBER SCREEN AND FIRE RETARDANT DONALDSON AIR CLEANER		
DR 12V 275 AMP 40-SI BRUSHLESS PAD ALTERNATOR WITH REMOTE BATTERY VOLTAGE SENSE	10	
(2) DTNA GENUINE, FLOODED STARTING, MIN 2000CCA, 370RC, THREADED STUD BATTERIES	10	
BATTERY BOX FRAME MOUNTED		
STANDARD BATTERY JUMPERS		
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
NON-POLISHED BATTERY BOX COVER		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	2	
PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS		
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
GVG, FIRE AND EMERGENCY SERVICE VEHICLES ENGINE WARNING		
CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF WITH BRAKE LAMPS	20	
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE EXITING FORWARD OF REAR TIRES	10	5
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH		
STANDARD EXHAUST SYSTEM LENGTH		
RH HORIZONTAL TAILPIPE, EXIT FORWARD OF REAR TIRES	20	20
6 GALLON DIESEL EXHAUST FLUID TANK		

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
100 PERCENT DIESEL EXHAUST FLUID FILL		
LH UNDER CAB DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
AIR POWERED ON/OFF ENGINE FAN CLUTCH		
AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED		
CUMMINS SPIN ON FUEL FILTER		
COMBINATION FULL FLOW/BYPASS OIL FILTER		
1100 SQUARE INCH ALUMINUM RADIATOR	70	
ANTIFREEZE TO -60F, ETHYLENE GLYCOL PRE- CHARGED SCA HEAVY DUTY COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
AUXILIARY ENGINE COOLING USING WATER FROM FIRE PUMP		
LOWER RADIATOR GUARD		
ALUMINUM FLYWHEEL HOUSING		
ELECTRIC GRID AIR INTAKE WARMER		
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH		
<b>Transmission</b>		
ALLISON 3000 EVS AUTOMATIC TRANSMISSION WITH PTO PROVISION	200	60
<b>Transmission Equipment</b>		
ALLISON VOCATIONAL PACKAGE 198 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODEL EVS		
ALLISON VOCATIONAL RATING FOR FIRE TRUCK/EMERGENCY VEHICLE APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES		
PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		

**Prepared for:**

Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**

Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE ALTERNATE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED		
DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH BLUNTCUTS		
ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR		
(2) CUSTOMER INSTALLED MUNCIE CS10 SERIES PTO'S		
PTO MOUNTING, LH SIDE AND TOP RH SIDE OF MAIN TRANSMISSION ALLISON		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED		
TRANSMISSION PROGNOSTICS - ENABLED 2013		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

**Front Axle and Equipment**

DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74  
 DROP SINGLE FRONT AXLE

10

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
FIRE AND EMERGENCY SEVERE SERVICE, NON-ASBESTOS FRONT LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW TAS-85 POWER STEERING	40	
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE		
<b>Front Suspension</b>		
14,600# TAPERLEAF FRONT SUSPENSION	170	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
<b>Rear Axle and Equipment</b>		
CUMMINS-MERITOR RS-26-185 26,000# T-SERIES SINGLE REAR AXLE	255	
5.63 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	20	20
DRIVER CONTROLLED TRACTION DIFFERENTIAL - SINGLE REAR AXLE		20
(1) DRIVER CONTROLLED DIFFERENTIAL LOCK REAR VALVE FOR SINGLE DRIVE AXLE		
INDICATOR LIGHT FOR EACH DIFFERENTIAL LOCKOUT SWITCH, ENGAGE AT SPEEDS 5MPH OR LESS, DISENGAGE W/IGN OFF		
MERITOR 16.5X7 P CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, CAST SHOES	40	

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
FIRE AND EMERGENCY SEVERE SERVICE NON-ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)		
GUNITE HEAVY WEIGHT CAST IRON REAR BRAKE DRUMS	30	
REAR BRAKE DUST SHIELDS		5
REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		
HALDEX AUTOMATIC REAR SLACK ADJUSTERS		
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE		
<b>Rear Suspension</b>		
26,000# FLAT LEAF SPRING REAR SUSPENSION WITH HELPER AND RADIUS ROD		170
SPRING SUSPENSION - NO AXLE SPACERS		
STANDARD AXLE SEATS IN AXLE CLAMP GROUP		
FORE/AFT CONTROL RODS		
<b>Pusher / Tag Equipment</b>		
NO PUSHER/TAG BRAKE DUST SHIELDS		
<b>Brake System</b>		
AIR BRAKE PACKAGE		
WABCO 4S/4M ABS WITH TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
STD U.S. FRONT BRAKE VALVE		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
AIR DRYER MOUNTED INBOARD ON LH RAIL		
STEEL AIR TANKS MOUNTED AFT INSIDE AND/OR BELOW FRAME JUST FORWARD OF REAR SUSPENSION, NO TRIPLE OR TORPEDO TANKS		
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER ON ALL TANK(S)		

**Prepared for:**

Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**

Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
<b>Trailer Connections</b>		
NO TRAILER AIR HOSE		
NO AIR HOSE HANGER		
NO TRAILER ELECTRICAL CABLE		
<b>Wheelbase &amp; Frame</b>		
5925MM (233 INCH) WHEELBASE		
11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	310	120
1900MM (75 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-20	90
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 120.47 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 117.47 in		
CALC'D FRAME LENGTH - OVERALL : 337.46 in		
CALCULATED FRAME SPACE LH SIDE : 133.0 in		
CALCULATED FRAME SPACE RH SIDE : 87.85 in		
SQUARE END OF FRAME		
FRONT CLOSING CROSSMEMBER		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD CROSSMEMBER BACK OF TRANSMISSION		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REARMOST CROSSMEMBER		
STANDARD SUSPENSION CROSSMEMBER		
<b>Chassis Equipment</b>		
THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30	
FRONT TOW HOOKS - FRAME MOUNTED BUMPER MOUNTING FOR SINGLE LICENSE PLATE	15	
NO MUDFLAP BRACKETS		
NO REAR MUDFLAPS		
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS		
GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE		
3D STEP VEHICLE MODEL		

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
TANK BODY 0 TO 1500 GALLONS CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD		
<b>Fifth Wheel</b>		
NO FIFTH WHEEL		
<b>Fuel Tanks</b>		
50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH  RECTANGULAR FUEL TANK(S)  PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS  FUEL TANK(S) FORWARD  PLAIN STEP FINISH  FUEL TANK CAP(S)  DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR  EQUIFLO INBOARD FUEL SYSTEM  HIGH TEMPERATURE REINFORCED NYLON FUEL LINE  FUEL COOLER MOUNTED LEFT HAND IN RAIL	20  -5  10	
<b>Tires</b>		
MICHELIN XZE 12R22.5 16 PLY RADIAL FRONT TIRES  MICHELIN XDN2 12R22.5 16 PLY RADIAL REAR TIRES	50  140	
<b>Hubs</b>		
CONMET PRESET PLUS PREMIUM IRON FRONT HUBS  CONMET PRESET PLUS PREMIUM IRON REAR HUBS		
<b>Wheels</b>		
ALCOA ULA18X 22.5X8.25 10-HUB PILOT 5.81 INSET ALUMINUM DISC FRONT WHEELS	-62	
ALCOA ULA18X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS		-124
POLISHED FRONT WHEELS; OUTSIDE ONLY POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY		
FRONT WHEEL MOUNTING NUTS		

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
REAR WHEEL MOUNTING NUTS		
<b>Cab Exterior</b>		
154 INCH BBC HIGH-ROOF ALUMINUM CONVENTIONAL CREW CAB	430	250
AIR CAB MOUNTING		
CAB ROOF REINFORCEMENTS FOR ROOF MOUNTED COMPONENTS	2	
LH AND RH EXTERIOR GRAB HANDLES WITH SINGLE RUBBER INSERT		
HOOD MOUNTED CHROMED PLASTIC GRILLE		
CHROME HOOD MOUNTED AIR INTAKE GRILLE		
FIBERGLASS HOOD		
FREIGHTLINER NAMEPLATES		
HOOD LINER, ADDED FIREWALL AND FLOOR HEAT INSULATION	5	
SINGLE ELECTRIC HORN		
REAR LICENSE PLATE MOUNT END OF FRAME		
INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL		
LED AERODYNAMIC MARKER LIGHTS		
DAYTIME RUNNING LIGHTS		
OMIT STOP/TAIL/BACKUP LIGHTS AND PROVIDE WIRING WITH SEPARATE STOP/TURN WIRES TO 4 FEET BEYOND END OF FRAME		-5
STANDARD FRONT TURN SIGNAL LAMPS		
AUTOMATIC ON/OFF, ENGINE COMPARTMENT, HOOD ACTIVATED WORK LIGHT WITH MANUAL OVERRIDE	1	
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
STANDARD SIDE/REAR REFLECTORS		
63X14 INCH TINTED REAR WINDOW		
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
RH AND LH ELECTRIC POWERED WINDOWS		
1-PIECE SOLAR GREEN GLASS WINDSHIELD		

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED		
<b>Cab Interior</b>		
RUGGED TRIM PACKAGE GRAY & CARBON VINYL INTERIOR "RUGGED" CARBON WITH PREMIUM GUNMETAL ACCENT (RUGGED) MOLDED PLASTIC DOOR PANEL MOLDED PLASTIC DOOR PANEL BLACK MATS WITH SINGLE INSULATION (1)DASH MOUNTED 12V POWER OUTLET, (1)DASH MOUNTED DUAL USB-C OUTLET FORWARD ROOF MOUNTED CONSOLE LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS DIGITAL ALARM CLOCK IN DRIVER DISPLAY (2) CUP HOLDERS LH AND RH DASH M2/SD DASH 5 LB. FIRE EXTINGUISHER HEATER, DEFROSTER AND AIR CONDITIONER STANDARD HVAC DUCTING MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH PREP KIT FOR CUSTOMER INSTALLED AUXILIARY HEATER, PLUMBING FROM ENGINE TO RAIL UNDER CAB WITH SHUTOFF VALVES STANDARD HEATER PLUMBING AUXILIARY HEATER PLUMBING VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR BINARY CONTROL, R-134A PREMIUM INSULATION SOLID-STATE CIRCUIT PROTECTION AND FUSES 12V NEGATIVE GROUND ELECTRICAL SYSTEM PREMIUM LED CAB LIGHTING REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS ALL UNIT(S) KEYED ALIKE WITH CUSTOMER SPECIFIED KEY NUMBER FT1031 KEY QUANTITY OF 2	10	

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION		
TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB	10	
SEATS INC 911 UNIVERSAL SERIES HIGH BACK AIR SUSPENSION DRIVER SEAT WITH NFPA 1901-2009/2016 COMPLIANT SEAT SENSOR	50	
SEATS INC 911 UNIVERSAL SERIES SCBA NON SUSPENSION PASSENGER SEAT WITH UNDERSEAT STORAGE AND NFPA 1901-2009/2016 COMPLIANT SEAT SENSOR	40	15
SEATS INC 911 UNIVERSAL SERIES SCBA NON SUSPENSION LH, RH AND CENTER REAR PASSENGER SEATS WITH UNDER SEAT STORAGE AND NFPA 1901-2009/2016 COMPLIANT SEAT SENSOR	60	25
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
BLACK CORDURA PLUS CLOTH DRIVER SEAT COVER		
BLACK CORDURA PLUS CLOTH PASSENGER SEAT COVER		
BLACK CORDURA PLUS CLOTH REAR PASSENGER SEAT COVER		
NFPA 1901-2009 HIGH VISIBILITY ORANGE SEAT BELTS		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES		
DRIVER AND PASSENGER INTERIOR SUN VISORS		
INTERFACE CONNECTORS AND WIRING FOR CUSTOMER PROVIDED LED STEP LIGHTING		

### Instruments & Controls

CONFIGURABLE LOWER PANEL WITH INTEGRATED UPPER STORAGE  
 ENGINE REMOTE INTERFACE WITH PARK BRAKE AND NEUTRAL INTERLOCKS  
 BRIGHT ARGENT FINISH GAUGE BEZELS  
 LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM WITH (1) ADDITIONAL PARK SWITCH FOR CUSTOMER USE  
 DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
ELECTRONIC AIR RESTRICTION INDICATOR DISPLAYED IN DRIVER DISPLAY		
ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY		
DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS		
QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS		
NO ADDITIONAL EXTRA SWITCH ACCUATORS		
QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS		
ENGINE REMOTE INTERFACE CONNECTOR AT POWERTRAIN INTERFACE CONNECTOR		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
DIGITAL TRANSMISSION OIL TEMPERATURE IN DRIVER DISPLAY		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
WIRING PROVISION FOR CUSTOMER FURNISHED ROOF MOUNTED LIGHTBAR WITH 2 WIRES HANDLE UP TO 30 AMPS OF CURRENT		
PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE		
NO OBSTACLE DETECTION SYSTEM		
NO REVERSE PROXIMITY SENSOR		
NO DR ASSIST SYSTEM		
NO VEHICLE STABILITY ADVISOR OR CONTROL		
NO LANE DEPARTURE WARNING SYSTEM		
ELECTRIC ENGINE OIL PRESSURE GAUGE		

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
CENTER OVERHEAD INSTRUMENT PANEL BLANK		
1 QUIKFIT PROGRAMABLE MODULE (QPM/XMC) W/ (4) 20AMP FUSED RELAYS	10	
NFPA VEHICLE DATA RECORDER AND SEATBELT DISPLAY		
NO RADIO		
NO AM/FM RADIO ANTENNA		
STANDARD RADIO WIRING WITH STEERING WHEEL CONTROLS		
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
DETROIT CONNECT PLATFORM HARDWARE		
3 YEARS DAIMLER CONNECTIVITY BASE PACKAGE ON (FEATURES VARY BY MODEL) POWERED BY DETROIT CONNECT ON CUMMINS ENGINES		
TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL		
IGNITION SWITCH CONTROLLED ENGINE STOP		
NO HARDWIRE SWITCH #1		
NO HARDWIRE SWITCH #2		
NO HARDWIRE SWITCH #3		
NO HARDWIRE SWITCH #4		
STEERING WHEEL MOUNTED ELECTRIC HORN CONTROL		
NO TRAILER HAND CONTROL BRAKE VALVE		
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
ALTERNATING FLASHING HEADLAMP SYSTEM WITH BODY BUILDER CONTROLLED ENGAGEMENT		
ONE VALVE PARKING BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR		

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

	Description	Weight Front	Weight Rear			
	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY					
<b>Design</b>	PAINT: ONE SOLID COLOR					
<b>Color</b>	CAB COLOR A: L0762EY MED RED ELITE EY BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT NO CAB/BODY EXTERIOR DECALS STANDARD E COAT/UNDERCOATING					
<b>Certification / Compliance</b>	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS					
<b>T O T A L   V E H I C L E   S U M M A R Y</b>						
<b>Weight Summary</b>						
	Weight	Weight	Total			
	Front	Rear	Weight			
Factory Weight <sup>+</sup>	7922 lbs	4616 lbs	12538 lbs			
Total Weight <sup>+</sup>		4616 lbs	12538 lbs			

(+) Weights shown are estimates only.


If weight is critical, contact Customer Application Engineering.

(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

## DIMENSIONS



### VEHICLE SPECIFICATIONS SUMMARY - DIMENSIONS

Model .....	M2106
Wheelbase (545) .....	5925MM (233 INCH) WHEELBASE
Rear Frame Overhang (552).....	1900MM (75 INCH) REAR FRAME OVERHANG
Fifth Wheel (578).....	NO FIFTH WHEEL
Mounting Location (577) .....	NO FIFTH WHEEL LOCATION
Maximum Forward Position (in).....	0
Maximum Rearward Position (in) .....	0
Amount of Slide Travel (in).....	0
Slide Increment (in).....	0
Desired Slide Position (in).....	0.0
Cab Size (829).....	154 INCH BBC HIGH-ROOF ALUMINUM CONVENTIONAL CREW CAB
Sleeper (682).....	NO SLEEPER BOX/SLEEPERCAB
Exhaust System (016) .....	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE EXITING FORWARD OF REAR TIRES

### TABLE SUMMARY - DIMENSIONS

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com


Dimensions	Inches
Bumper to Back of Cab (BBC)	153.5
Bumper to Centerline of Front Axle (BA)	40.7
Front Axle to Back of Cab (AC)	112.8
Min. Cab to Body Clearance (CB)	3.0
Back of Cab to Centerline of Rear Axle(s) (CA)	120.5
Effective Back of Cab to Centerline of Rear Axle(s) (Effective CA)	117.5
Back of Cab Protrusions (Exhaust/intake) (CP)	2.0
Back of Cab Protrusions (Side Extenders/Trim Tab) (CP)	0.0
Back of Cab Protrusions (CNG Tank)	0.0
Back of Cab Clearance (CL)	3.0
Back of Cab to End of Frame	195.3
Cab Height (CH)	74.1
Wheelbase (WB)	233.3
Frame Overhang (OH)	74.8
Overall Frame Length	337.5
Overall Length (OAL)	348.8
Rear Axle Spacing	0.0
Unladen Frame Height at Centerline of Rear Axle	41.9

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.

**Prepared for:**  
 Bryon Shumaker  
 HEIMAN FIRE EQUIPMENT BB  
 25814 RUDOLPH AVE  
 SIOUX FALLS, SD 57107  
 Phone: 6055435098

**Prepared by:**  
 Carolyn LeBeau  
 I-STATE TRUCK CENTER  
 2901 WEST 60TH STREET N  
 SIOUX FALLS, SD 57107  
 Phone: 605-336-2995  
 E-Mail:  
 carolyn.lebeau@istatetruck.com

## T U R N I N G   R A D I U S



Turning radius graphic and data provided strictly for comparisons between model configurations. Weather, road surfaces, and tire treads affect the results. It is strongly suggested that actual vehicles be measured before constructing any roads/driveways using this information. For specific figures regarding your configuration, please contact your C&E representative.

	Dimensions	Tolerance
Wall to Wall Diameter (ft)	64.6	+/- 3.0
Curb to Curb Diameter (ft)	63.0	+/- 3.0
Turning Radius (ft)	31.0	+/- 1.5

### VEHICLE SPECIFICATIONS SUMMARY - TURNING RADIUS

Model .....	M2106
Cab Size (829).....	154 INCH BBC HIGH-ROOF ALUMINUM CONVENTIONAL CREW CAB
Wheelbase (545) .....	5925MM (233 INCH) WHEELBASE
Front Tires (093).....	MICHELIN XZE 12R22.5 16 PLY RADIAL FRONT TIRES
Width (in) .....	11.4
Front Axle (400).....	DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE
Kingpin Intersection (in) .....	71.5
Bumper (556) .....	THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS
Width (in) .....	93.5
Bumper Miter to Front Axle (in) .....	21.458
Primary Steering Location (003) .....	LH PRIMARY STEERING LOCATION
Steering Gear (536) .....	TRW TAS-85 POWER STEERING
Dual Steering Gear .....	NONE
Ram.....	NONE
Rear Axle (420) .....	CUMMINS-MERITOR RS-26-185 26,000# T-SERIES SINGLE REAR AXLE
Axle Spacing (624) .....	NO AXLE SPACING

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.

**Prepared for:**  
Bryon Shumaker  
HEIMAN FIRE EQUIPMENT BB  
25814 RUDOLPH AVE  
  
SIOUX FALLS, SD 57107  
Phone: 6055435098

**Prepared by:**  
Carolyn LeBeau  
I-STATE TRUCK CENTER  
2901 WEST 60TH STREET N  
SIOUX FALLS, SD 57107  
Phone: 605-336-2995  
E-Mail:  
carolyn.lebeau@istatetruck.com