

Heiman Stock WK254

BID SPECIFICATIONS

FOR

**ROSENBAUER CUSTOM FIRE
APPARATUS**

One (1)
00-00-1499

OVERALL HEIGHT

An overall height restriction has not been specified for this apparatus.

One (1)
00-00-1509

OVERALL LENGTH

An overall length restriction has not been specified for this apparatus.

One (1)
00-00-1519

OVERALL WIDTH

An overall width restriction has not been specified for this apparatus.

One (1)
00-00-1529

WHEELBASE

A wheelbase restriction has not been specified for this apparatus.

One (1)
00-00-1539

ANGLE OF APPROACH

The angle of approach for the apparatus shall not be less than eight (8) degrees as specified by the current edition of the NFPA 1901 Guideline.

One (1)
00-00-1549

ANGLE OF DEPARTURE

The angle of departure for the apparatus shall not be less than eight (8) degrees as specified by the current edition of the NFPA 1901 Guideline.

One (1)
00-00-1640

NFPA MOBILE WATER EQUIPMENT ALLOWANCE

In compliance with the current NFPA guidelines, the apparatus shall be engineered to provide an allowance of 1000 pounds of fire department provided loose equipment.

One (1)
00-00-1799

One (1)
00-00-3220

CONTRACT CHANGE NOTICE

The quoted delivery time is based upon our receipt of the specified materials required to produce the apparatus in a timely manner. "Delivery" means the date company is prepared to make physical possession of vehicle available to the customer.

The Company shall not be responsible nor deemed to be in default on account of delays in performance due to causes which are beyond the Company's control which make the Company's performance impracticable, including but not limited to civil wars, insurrections, strikes, riots, fires, storms, floods, other acts of nature, explosions, earthquakes, accidents, any act of government, delays in transportation, inability to obtain necessary labor supplies or manufacturing facilities, allocation regulations or orders affecting materials, equipment, facilities or completed products, failure to obtain any required license or certificates, acts of God or the public enemy or terrorism, failure of transportation, pandemics, epidemics, quarantine restrictions, failure of vendors (due to causes similar to those within the scope of this clause) to perform their contracts or labor troubles causing cessation, slowdown, or interruption of work.

After execution and acceptance of this Purchase Process, the Buyer may request that the Company incorporate a change to the Products or the Specifications for the Products by delivering a Change Order to the Company; provided, however, that any such Change Order must be in writing and include a description of the proposed change sufficient to permit the Company to evaluate the feasibility of such Change Order. Within seven (7) working days of receipt of a Change Order, the Company will inform the Buyer in writing of the feasibility of the Change Order, the earliest possible implementation date for the Change Order, of any increase or decrease in the Purchase Price resulting from such Change Order, and of any effect on production scheduling or delivery resulting from such Change Order. The Company shall not be liable to the Buyer for any delay in performance or delivery arising from any such Change Order. Purchase Price may be modified only by mutual written agreement of the Parties because of changes to the Apparatus required or requested by the Buyer during the construction process pursuant to Appendix C, Change Order Policy. Any changes in the Purchase Price resulting from changes to the Apparatus required or requested by the Buyer during the construction process shall be stated in the Change Order signed by both parties. Additional Changes: If various state or federal regulatory agencies (e.g., NFPA, DOT, EPA) require changes to the specification and/or the product that result in a cost increase to comply therewith this cost will be added to the Purchase Price to be paid by the customer.

One (1)
01-06-0500

CENTER OF GRAVITY

The apparatus, prior to acceptance, will be required to meet the vehicle stability of the applicable NFPA Automotive Fire Apparatus Standard.

A calculated center of gravity shall be provided. The calculated or measured center of gravity (CG) shall be no higher than 80-percent of the rear axle track width. If so, a tilt table test at the apparatus body builder's facility or Electronic Stability Control (ESC) must be provided on the chassis meeting the requirement of the NFPA 1901 Guideline.

One (1)
01-07-0060

ENGINEERING BLUEPRINTS

ROSENBAUER has submitted "proposal" blueprints which are "representative" of the vehicle being proposed and these have been generated on computer-aided-design (CAD) equipment.

The blueprints are provided as follows:

Sheet No. 1:

- Left side exterior view
- Right side exterior view
- Rear exterior view

ROSENBAUER shall provide construction drawings for approval prior to actual construction of the vehicle.

The design of the equipment is in accordance with the best engineering practices. The equipment design and accessory installation shall permit accessibility for use, maintenance and service. All components and assemblies shall be free of hazardous protrusions, sharp edges, cracks or other elements, which might cause injury to personnel or equipment.

All oil, hydraulic, and air tubing lines and electrical wiring shall be located in protective positions properly attached to the frame or body structure and shall have protective loom or grommets at each point where they pass through structural members, except where a through-frame connector is necessary.

Parts and components will be located or positioned for rapid and simple inspection and recognition of excessive wear or potential failure. Whenever functional layout of operating components determines that physical or visual interference between items cannot be avoided, the item predicted to require the most maintenance shall be located for best accessibility.

One (1)
01-07-1100

CHANGE ORDERS

To ensure the proper engineering and construction of the purchaser's custom fire apparatus in a timely manner, the contractor shall consider the order final and complete after any changes made during the pre-construction conference are mutually approved. Change orders requested after the pre-construction conference are discouraged. It shall be understood and agreed that any changes, if approved, after the order has been released to Engineering, shall constitute a valid cause for production delay and without penalty to the contractor.

One (1)

== Pumper/Tanker Warranties - 1242.024 12/04/24 ==

One (1)
01-16-0100

BODY WARRANTY

The manufacturer shall provide a one (1) year body warranty. The manufacturer shall supply details of their warranty information with their bid submission.

One (1)
01-19-0250

ALUMINUM BODY WARRANTY - FIVE YEAR

Rosenbauer America, LLC warrants to the original purchaser only, that the all-aluminum body, fabricated by Rosenbauer America, LLC, under normal use and with reasonable maintenance, be structurally sound and will remain free from corrosion perforation for a period of FIVE (5) years.

This warranty does not apply to the following items that are covered by a separate warranty: paint finish, hardware, moldings, and other accessories attached to this body. In addition, this warranty does not apply to any part or accessory manufactured by others and attached to this body.

ROSENBAUER AMERICA, LLC MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THE ALUMINUM BODY AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND HEREBY DISCLAIMED.

Rosenbauer America, LLC will replace without charge, repair or make a fair allowance for any defect in material or workmanship demonstrated to its satisfaction to have existed at the time of delivery or not due to misuse, negligence, or accident. If Rosenbauer America, LLC elects to repair this body, the extent of such repair shall be determined solely by Rosenbauer America, LLC, and shall be performed solely at the Rosenbauer America, LLC factory, or at an approved facility. The expense of any transportation to or from such repair facility shall be borne by the purchaser and is not an item covered under this warranty.

Rosenbauer America, LLC will not be liable for damages and under no circumstances will its liability exceed the price for a defective body. The remedies set forth herein are exclusive and in substitution for all other remedies to which the purchaser would otherwise be entitled.

Rosenbauer America, LLC will be given a reasonable opportunity to investigate all claims. The purchaser must commence any action arising out of, based upon or relating to agreement or the breach hereof, within twelve months from the date the cause of the action occurred.

Note: Surety bond, if required, will cover standard one year warranty period only and will not cover any extended warranties allowed by seller or other component manufacturers.

One (1)
01-19-2800

GALVANIZED SUBFRAME WARRANTY

Subject to the provisions, limitations and conditions set forth in this warranty, Rosenbauer America, LLC (hereby referred to as "seller"), hereby warrants to each original purchaser only that each new hot dip galvanized body subframe (exclusive of paint finish and hardware) is structurally sound and free of all structural defects of both material and workmanship and further warrants that it will maintain such structural integrity for the duration of ownership by the original purchaser. This warranty terminates upon transfer of possession or ownership by the original purchaser.

This warranty is conditioned upon normal use and reasonable maintenance of such subframe; prompt written notice of all defects to seller or one of the seller's then authorized dealers in the area; no repair or additions there to except by seller or authorized by it; said defect not resulting

from misuse, negligence, accident, remount, overloading beyond applicable weight rating by customer or third parties. If any such conditions are not complied with, this warranty shall become void and unenforceable.

Should repairs become necessary under the terms or the warranty, the extent of that repair shall be determined solely by the seller and shall be performed solely at Rosenbauer America, LLC or a repair facility designated by the seller. The expense of any transportation to or from such repair facility shall be that of the purchaser and is not an item covered by this warranty.

Seller reserves the unrestricted right at any time from time to time to make changes in the design of and/or improvements on its products without thereby imposing any obligation on itself to make corresponding changes or improvements in or on its products theretofore manufactured.

EXCLUSIONS AND LIMITATIONS: THIS MANUFACTURER'S WARRANTY IS PROVIDED IN PLACE OF ANY AND ALL OTHER REPRESENTATIONS OR IMPLIED WARRANTIES. NO PERSON IS AUTHORIZED TO MAKE ANY REPRESENTATIONS OR WARRANTY ON BEHALF OF ROSENBAUER AMERICA, LLC OR ANY OF ITS DISTRIBUTORS OTHER THAN SET FORTH IN THIS MANUFACTURER'S WARRANTY. YOUR RIGHT TO SERVICE AND REPLACEMENT OF PARTS ON THE TERMS EXPRESSLY SET FORTH HERIN ARE YOUR EXCLUSIVE REMEDIES AND NEITHER THE MANUFACTURER NOR ANY OF ITS DISTRIBUTORS SHALL BE LIABLE FOR DAMAGES, WHETHER ORDINARY, INCIDENTAL OR CONSEQUENTIAL.

Note: Surety bond, if required, will cover standard one year warranty period only and will not cover any extended warranties allowed by seller or other component manufacturers.

One (1)
01-20-0250

PAINT WARRANTY FIVE YEAR

The PPG paint performance guarantee will cover the areas of the vehicle finished with the specified product for a period of FIVE (5) years beginning the day the vehicle is delivered to the purchaser.

The full apparatus body, manufactured and painted by Rosenbauer America, LLC, shall be covered for the following paint failures as outlined on the guarantee certificate:

- Peeling or delaminating of the topcoat and/or other layers of paint.
- Cracking or checking.
- Loss of gloss caused by cracking, checking, or hazing.
- Any paint failure caused by defective PPG Fleet Finishes, which are covered by this guarantee.

All guarantee exclusions, limitations, and methods of claims are covered in the full certificate provided to the original purchaser.

Note: Surety bond, if required, will cover standard one year warranty period only and will not cover any extended warranties allowed by seller or other component manufacturers.

One (1)

LETTERING WARRANTY

Rosenbauer America, LLC warrants to the original purchaser only, that the lettering and striping, installed by Rosenbauer America, LLC, will remain free from defects for a period of one (1) year under normal use.

Rosenbauer America, LLC will replace without charge, repair or make a fair allowance for any defect in material or workmanship demonstrated to its satisfaction to have existed at the time of delivery or not due to misuse, negligence, or accident. If Rosenbauer America, LLC elects to repair this item, the extent of such repair shall be determined solely by Rosenbauer America, LLC, and shall be performed solely at the Rosenbauer America, LLC factory, or at an approved facility. The expense of any transportation to or from such repair facility shall be borne by the purchaser and is not an item covered under this warranty.

One (1)
01-18-0900

WATER TANK WARRANTY

The manufacturer shall provide a warranty for the G3 water tank. The manufacturer shall supply details of their warranty information with their bid submission.

One (1)
01-33-3100

BODY MANUAL - PRINTED

Rosenbauer shall provide with the vehicle upon delivery, one (1) complete delivery manual. This manual shall be in a notebook type binder, with reference tabs for each section of the vehicle.

Within each section shall be:

- Individual component manufacturer instruction and parts manuals
- Warranty forms for the body
- Warranty forms for all major components
- Warranty instructions and format to be used in compliance with warranty obligations
- Wiring diagrams
- Installation instruction and drawings for major parts
- Visual graphics and electronic photos for the installation of major parts
- Necessary normal routine service forms, publications and components of the body portion of the apparatus
- Technical publications for training and instruction on major body components
- Warning and safety related notices for personnel protection
- Cab and chassis manuals on parts, service and maintenance shall be provided

Dealer will assemble.

--ship manual materials loose. Dealer to assemble manual.

One (1)
02-90-1100

FREIGHTLINER CHASSIS

A Freightliner 2-door chassis per the attached specifications shall be furnished:

One (1)

== Use Drop Down to Add RBM Chassis - 1242.024 12/04/24 ==

One (1)

== Pumper/Tanker-DC Electrical System - 1242.024 12/04/24 ==

One (1)
50-03-1000

LOW VOLTAGE ELECTRICAL SYSTEM SPECIFICATIONS

The electrical system shall include all panels, electrical components, switches and relays, wiring harnesses and other electrical components. The electrical equipment installed by the apparatus manufacturer shall conform to current automotive electrical system standards, the latest Federal DOT standards, and the requirements of the applicable NFPA standards.

All wiring shall be stranded copper or copper alloy conductors of a gauge rated to carry 125 percent of the maximum current for the protected circuit. Voltage drops in all wiring from the power source to the using device shall not exceed 10 percent. The wiring and wiring harness and insulation shall be in conformance to applicable SAE and NFPA standards. The wiring harness shall conform to SAE J-1128 with GXL temperature properties. All exposed wiring shall be protected in a loom with a minimum 289 degree Fahrenheit rating. All wiring looms shall be properly supported and attached to body members. The electrical conductors shall be constructed in accordance with applicable SAE standards, except when good engineering practice requires special construction.

The wiring connections and terminations shall use a method that provides a positive mechanical and electrical connection and shall be installed in accordance with the device manufacturer's instructions. Electrical connections shall be with mechanical type fasteners and large rubber grommets where wiring passes through metal panels.

The wiring between the cab and body shall be joined using Deutsche type connectors or an enclosed in a terminal junction panel area. This system will permit body removal with minimal impact on the apparatus electrical system. All connections shall be crimp-type with insulated shanks to resist moisture and foreign debris such as grease and road grime. Weather-resistant connectors shall be provided throughout to ensure the integrity of the electrical system.

Any electrical junction or terminal boxes shall be weather resistant and located away from water spray conditions. In addition, the main body junction panel shall house the automatic reset breakers and relays where required.

There shall be no exposed electrical cabling, harnesses, or terminal connections located in compartments, unless they are enclosed in a junction box or covered with a removable electrical panel. The wiring shall be secured in place and protected against heat, liquid contaminants and damage. Wiring shall be uniquely identified every three-inches (3") by color coding or

permanent marking with a circuit function code and identified on a reference chart or electrical wiring schematic per requirements of applicable NFPA #1901 standards.

The electrical circuits shall be provided with low voltage overcurrent protective devices. Such devices shall be accessible and located in required terminal connection locations or weather resistant enclosures. The overcurrent protection shall be suitable for electrical equipment and shall be automatic reset type and meet SAE standards. All electrical equipment, switches, relays, terminals, and connectors shall have a direct current rating of 125 percent of maximum current for which the circuit is protected. The system shall have electro-magnetic interference suppression provided as required in applicable SAE standards.

The electrical system shall include the following:

- Electrical terminals in weather exposed areas shall have a non-conductive grease or spray applied. A corrosion preventative compound shall be applicable to all terminal plugs located outside of the cab or body.
- The electrical wiring shall be harnessed or be placed in a protective loom.
- Holes made in the roof shall be caulked with silicone. Large fender washers shall be used when fastening equipment to the underside of the cab roof.
- Any electrical component that is installed in an exposed area shall be mounted in a manner that will not allow moisture to accumulate in it.
- A coil of wire must be provided behind an electrical appliance to allow them to be pulled away from mounting area for inspection and service work.
- All lights that have their sockets in a weather exposed area shall have corrosion preventative compound added to the socket terminal area.

The warning lights shall be switched in the chassis cab with labeled switches in an accessible location. Individual rocker switches shall be provided only for warning lights provided over the minimum level of warning lights in either the stationary or moving modes. All electrical equipment switches shall be mounted on a switch panel mounted in the cab convenient to the operator. The warning light switches shall be of the rocker type. For easy nighttime operation, an integral indicator light shall be provided to indicate when the circuit is energized. All switches shall be appropriately identified as to their function.

A single warning light switch shall activate all required warning lights. This switch will allow the vehicle to respond to an emergency and "call for the right of way". When the parking brake is applied, a "blocking right of way" system shall automatically activate per requirements of the applicable NFPA standards. All "clear" warning lights shall be automatically turned off upon application of the parking brake.

NFPA REQUIRED TESTING OF ELECTRICAL SYSTEM

The apparatus shall be electrically tested upon completion of the vehicle and prior to delivery. The electrical testing, certifications, and test results shall be submitted with delivery

documentation per requirements of the applicable NFPA standards. The following minimum testing shall be completed by the apparatus manufacturer:

1. Reserve capacity test:

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged. The engine shall be shut off and the minimum continuous electrical load shall be activated for ten (10) minutes. All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a failed test.

2. Alternator performance test at idle:

The minimum continuous electrical load shall be activated with the engine running at idle speed. The engine temperature shall be stabilized at normal operating temperature. The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

3. Alternator performance test at full load:

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed. The test duration shall be a minimum of two (2) hours. Activation of the load management system is permitted during this test. However, if an alarm sounds due to excessive battery discharge, as detected by the system requirements in the NFPA standards, or a system voltage of less than 11.7 volts dc for more than 120 seconds is present, the test has failed.

4. Low voltage alarm test:

Following the completion of the above tests, the engine shall be shut off. The total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates. The battery voltage shall be measured at the battery terminals. With the load still applied, a reading of less than 11.7 volts dc for a 12 volt system shall be considered a test failure. The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.

NFPA REQUIRED DOCUMENTATION

The following documentation shall be provided on delivery of the apparatus:

- a. Documentation of the electrical system performance tests required above.
- b. A written load analysis, including:

1. The nameplate rating of the alternator.

2. The alternator rating under the conditions.
3. Each specified component load.
4. Individual intermittent loads.

One (1)
50-05-1510

WEATHER RESISTANT ELECTRICAL JUNCTION BOX

The electrical junction or terminal boxes shall be weather resistant and located away from water spray conditions. In addition, the main body junction panel shall house the automatic reset breakers and relays where required. The main body junction panel shall be located in the pump compartment.

One (1)
50-12-1100

ELECTRICAL CONSOLE WITH EMERGENCY LIGHT SWITCH PANEL

An electrical console shall be constructed of .125" smooth aluminum material and mounted in the cab of the truck chassis. Console shall be designed and installed between the driver and passenger seats. The top face of the console shall be designed as the switch panel for all emergency light switches. The switch panel shall be hinged for easy access to the switch connections.

All emergency light switches shall be lighted, rocker style. Switches shall be internally lit when the switch circuit is in the on position. A plug-in identification label is to be provided and installed adjacent to each rocker switch with backlighting provided behind the label.

SWITCHES

A rocker style internally lighted switch shall be provided and wired through a heavy-duty relay to activate power to the emergency lights. The emergency lights shall be activated by a single "MASTER SWITCH" on the electrical console.

-G3 console

One (1)
50-15-1100

BATTERY SYSTEM

The battery system shall be supplied with the chassis.

One (1)
50-15-3100

MASTER ELECTRIC SWITCH

A battery disconnect switch shall be located conveniently to the driver of the apparatus. The switch shall disconnect the 12 volt power supply from the battery system.

One (1)
50-20-1210

SHORE POWER RECEPTACLE - 120 VOLT

A 120-volt manual shore power inlet with weatherproof cover shall be provided on the apparatus.

-terminate wiring in center console receptacle

One (1)
50-20-1124

SHORE POWER PLUG

The shore power plug shall be located in the step area below the left front cab door of the commercial chassis.

Two (2)
51-00-1700

12 VOLT POWER SOURCE

Two (2) 12 volt power and ground connection rated at 30 amps shall be provided, on the apparatus, **one (1) in the right body electrical box and one (1) in the left body electrical box.**

Two (2)
51-00-4000

The power source shall be run through the chassis master battery switch and shall be deactivated when the master switch is in the "OFF" position.

One (1)
52-01-1200

BACK-UP ALARM

An automatic electric back-up alarm shall be wired to the back-up light circuit, and mounted under the rear of the apparatus body.

One (1)
52-02-1100

BACKUP CAMERA

A chassis supplied rear camera system shall be mounted on the rear of the vehicle. All system components shall be installed by the apparatus body manufacturer.

One (1)
52-08-1009

HAND LIGHTS

All NFPA required portable hand lights supplied by the Customer must be installed before the apparatus is placed into service.

One (1)
53-01-1200

MARKER LIGHTS

LED marker lights shall be installed on the vehicle in conformance to the Department of Transportation requirements.

One (1)
53-02-1300

LICENSE PLATE BRACKET

A stainless steel license plate bracket shall be provided at the rear of the apparatus.

One (1)

TAIL LIGHTS

One (1) pair of Whelen 604BTT LED tail/brake lights shall be provided on the rear of the apparatus. The rectangular lights shall be 4" x 6" LED with a red lens.

One (1)
53-04-2600

TURN SIGNALS

One (1) pair of Whelen, 604T turn signals with populated arrow shape shall be provided. The rectangular LED lights shall be 4" x 6" in dimension and shall have an amber lens.

One (1)
53-06-3500

BACKUP LIGHTS

One (1) pair of Whelen 604BU LED backup lights shall be installed on the rear of the apparatus body. The dimensions shall be 4" x 6" and the lens color shall be clear.

One (1)
53-07-1200

FOUR LIGHT BEZEL

One (1) pair of tail light cluster bezels shall be supplied. Each bezel shall be designed to hold the specified rear lights located at the lower rear corners of the body.

One (1)
53-05-1800

MID BODY LED TURN SIGNALS

One (1) pair of mid body LED turn signals shall be provided. The location of the turn lights shall be at mid-body near the rear wheel axle.

One (1)
54-02-1400

CAB GROUND LIGHTS

Two (2) LED ground lights shall be installed on the chassis cab, one under each cab door.

One (1)
54-02-2320

CAB STEP LIGHTS

There shall be LED cab step lights supplied below the chassis cab doors. The lights shall be mounted below the cab doors and illuminate the chassis cab steps. There shall be two (2) LED lights located on each side of the chassis cab.

One (1)
54-03-1600

REAR STEP GROUND LIGHTS

Two (2) LED ground lights shall be installed under rear step of the apparatus.

One (1)
54-04-1999

The ground lights shall automatically activate when the parking brake is applied.

Two (2)
54-10-1450

REAR TAILBOARD LIGHTS

Two (2) LED step lights with clear lens shall be installed to illuminate the step surfaces at the rear of the apparatus body.

One (1)
54-11-2100

The step/walkway light switch shall be installed and wired to the parking brake.

One (1)
54-15-5924

LEFT SIDE BODY SCENE LIGHTING

The following scene lighting shall be located on the left side of the body:

One (1)
54-15-1290

SCENE LIGHT

One (1) Whelen M9 Series Model # M9LZC scene light(s) shall be provided. The steady burn scene light shall incorporate Linear Super-LED® and Smart LED® technology.

The M9LZC shall be furnished with a chrome trim ring, a rubber gasket, screws, and screw grommets for installation. The M9LZC shall have the ability to be installed as a surface mount scene light.

Voltage: +12v

Size: H=6.51", W=10.34", D=1.892"

Amp Draw: 6.0 Amps

Lens Color: Clear

One (1)
54-15-1460

The scene light shall be installed on a treadplate mounting plate.

One (1)
54-15-6400

SCENE LIGHT SWITCHING

One (1) scene light switch with indicator shall be installed on the cab main switch panel to control the left side scene light(s). The switch shall be labeled "LEFT SCENE".

One (1)
54-15-5928

RIGHT SIDE BODY SCENE LIGHTING

The following scene lighting shall be located on the right side of the body:

One (1)
54-15-1290

SCENE LIGHT

One (1) Whelen M9 Series Model # M9LZC scene light(s) shall be provided. The steady burn scene light shall incorporate Linear Super-LED® and Smart LED® technology.

The M9LZC shall be furnished with a chrome trim ring, a rubber gasket, screws, and screw grommets for installation. The M9LZC shall have the ability to be installed as a surface mount scene light.

Voltage: +12v

Size: H=6.51", W=10.34", D=1.892"

Amp Draw: 6.0 Amps

Lens Color: Clear

One (1)
54-15-1460

The scene light shall be installed on a treadplate mounting plate.

One (1)
54-15-6500

SCENE LIGHT SWITCHING

One (1) scene light switch with indicator shall be installed on the cab main switch panel to control the right side scene light(s). The switch shall be labeled "RIGHT SCENE".

One (1)
54-15-5932

REAR BODY SCENE LIGHTING

The following scene lighting shall be located on the rear of the body:

One (1)
54-15-1290

SCENE LIGHT

One (1) Whelen M9 Series Model # M9LZC scene light(s) shall be provided. The steady burn scene light shall incorporate Linear Super-LED® and Smart LED® technology.

The M9LZC shall be furnished with a chrome trim ring, a rubber gasket, screws, and screw grommets for installation. The M9LZC shall have the ability to be installed as a surface mount scene light.

Voltage: +12v

Size: H=6.51", W=10.34", D=1.892"

Amp Draw: 6.0 Amps

Lens Color: Clear

One (1)
54-15-6600

SCENE LIGHT SWITCHING

One (1) scene light switch with indicator shall be installed on the cab main switch panel to control the rear scene light(s). The switch shall be labeled "REAR SCENE".

One (1)
54-15-6700

SCENE LIGHT SWITCHING

The rear scene lights shall activate automatically upon placing the transmission into reverse.

One (1)
55-11-2100

DOOR OPEN LIGHT

A red flashing, warning light shall be provided and installed in the driver's compartment to indicate an open passenger or apparatus compartment door. The warning light shall also be attached to folding equipment racks and light towers as specified. The light shall be a flashing Whelen OS red LED (OSROOFCR) light and shall be properly marked and identified.

One (1)
56-01-1380

ELECTRONIC SIREN

A Federal Signal PA300 siren, model PA300-100, full function and programmable 100 watt electronic siren shall be mounted in the cab. The siren shall have the following features: seven position rotary selector switch, digital Grover air horn, wail, yelp, priority, and Hi-Lo tones, radio rebroadcast, P.A. with a hard wired microphone and P.A. volume control. The system includes two (2) programmable Convergence Network serial ports for network devices and two programmable auxiliary backlit buttons (by default set to air horn and manual siren). The siren is fully programmable through the Convergence Network software. Hands free operation shall allow the operator to turn the siren on and off from the horn ring through a horn/siren selector switch. The siren shall be capable of driving (1) 100-watt speaker. The new PA300-100 comes with a five (5) year warranty.

One (1)
56-02-1750

SPEAKER

One (1) Whelen model #SA315P, nylon composite speaker shall be installed. The speaker shall be wired to the electric siren located in the cab.

One (1)
56-03-1800

SPEAKER LOCATION

The siren speaker shall be installed on the apparatus bumper extension, as determined by the body manufacturer.

One (1)
57-02-1900

LIGHTBAR

One (1) Whelen Justice series light bar shall be included with the apparatus cab. The light bar shall be a model JE2NFPA and shall be mounted on the roof of the cab, towards the front, above the windshield.

The light bar shall feature:

- A 56" light bar designed for high performance
- Four (4) red Linear Super LED corner modules
- Four (4) red CON3 LED hinged modules
- Two (2) white CON3 LED hinged modules with exterior clear optic lenses
- Clear hard coated lenses to provide extended life/luster protection against UV & chemical stresses
- Designed in accordance with NFPA Zone A requirements

One (1)

WARNING LIGHT ACTIVATION

The warning lights shall be activated through the master warning switch.

One (1)
58-71-1820

UPPER REAR WARNING LIGHTS

One (1) pair of Whelen Super LED, rotating beacons, P/N L31H*F, shall be installed, one each side on the upper rear of the apparatus body. The unit shall have dimensions of 4" high x 7-9/16" deep.

One (1)
57-20-8100

The driver side warning light shall be a Whelen LED rotator, model L31HRF with a red lens.

One (1)
57-20-8101

The officer side warning light shall be a Whelen LED rotator, model L31HRF with a red lens.

One (1)
58-74-5100

REAR WARNING LIGHT MOUNTING

The upper rear lights shall be mounted on cast aluminum stanchions attached to the apparatus body, one on each side.

One (1)
58-03-2100

LOWER FRONT WARNING LIGHTS

One (1) pair of Whelen model LINZ6 LED warning lights shall be installed, one each side on the front of the chassis cab. The warning light shall incorporate six Super-LEDs, a clear non-optic hard coated polycarbonate lens, clear optic collimator and utilize a metalized reflector for maximum output. The dimensions of the lights shall be 2" x 4".

One (1)
57-20-2000

The driver side warning light shall be a Whelen Model LINZ6R red LED with clear lens.

One (1)
57-20-2001

The officer side warning light shall be a Whelen Model LINZ6R red LED with clear lens.

One (1)
58-09-2100

INTERSECTION WARNING LIGHTS

One (1) pair of Whelen model LINZ6 LED warning lights shall be installed, one each side of the chassis. The warning light shall incorporate six Super-LEDs, a clear non-optic hard coated polycarbonate lens, clear optic collimator and utilize a metalized reflector for maximum output. The dimensions of the lights shall be 2" x 4".

One (1)
57-20-2000

The driver side warning light shall be a Whelen Model LINZ6R red LED with clear lens.

One (1)

57-20-2001

The officer side warning light shall be a Whelen Model LINZ6R red LED with clear lens.

One (1)
58-26-2100

LOWER MID-BODY WARNING LIGHTS

One (1) pair of Whelen model LINZ6 LED warning lights shall be installed, one each side one of the apparatus, mid body. The warning light shall incorporate six Super-LEDs, a clear non-optic hard coated polycarbonate lens, clear optic collimator and utilize a metalized reflector for maximum output. The dimensions of the lights shall be 2" x 4".

One (1)
57-20-2000

The driver side warning light shall be a Whelen Model LINZ6R red LED with clear lens.

One (1)
57-20-2001

The officer side warning light shall be a Whelen Model LINZ6R red LED with clear lens.

One (1)
58-36-2100

LOWER REAR SIDE WARNING LIGHTS

One (1) pair of Whelen model LINZ6 LED warning lights shall be installed, one each side of the apparatus body, towards the rear of the body. The warning light shall incorporate six Super-LEDs, a clear non-optic hard coated polycarbonate lens, clear optic collimator and utilize a metalized reflector for maximum output. The dimensions of the lights shall be 2" x 4".

One (1)
57-20-2000

The driver side warning light shall be a Whelen Model LINZ6R red LED with clear lens.

One (1)
57-20-2001

The officer side warning light shall be a Whelen Model LINZ6R red LED with clear lens.

One (1)
58-81-1520

LOWER REAR WARNING LIGHTS

One (1) pair of Whelen model #600 Super LED warning lights shall be installed, one each side on the lower rear of the apparatus body. The dimensions of the lights shall be 4" x 6".

One (1)
57-20-4010

The driver side warning light shall be a Whelen Model 60R02FRR red-LED with a red lens.

One (1)
57-20-4011

The officer side warning light shall be a Whelen Model 60R02FRR red-LED with a red lens.

One (1)

== Pumper/Tanker-Chassis Modifications - 1242.024 12/04/24 ==

One (1)
09-90-9901

S.O.R./ Dealer supplied chassis

One (1)
10-02-1100

FLUID DATA PLAQUE

A fluid data plaque containing required information shall be provided based on the applicable components for this apparatus, compliant with NFPA Standards:

- Engine oil
- Engine coolant
- Chassis transmission fluid
- Drive axle lubricant
- Power steering fluid
- Pump transmission lubrication fluid
- Other NFPA applicable fluid levels or data as required

Location shall be in the driver's compartment or on driver's door.

One (1)
10-02-1300

NO RIDE LABEL

A "NO RIDERS" label shall be applied on the vehicle at the rear step area or other applicable areas. The label shall warn personnel that riding in or on these areas, while the vehicle is in motion is prohibited.

One (1)
10-02-1500

HEIGHT LENGTH & WEIGHT WARNING LABEL

A highly visible label indicating the overall height, length, and weight of the vehicle shall be installed in the cab dash area.

CAB SEATING POSITION LIMITS

A label shall be installed in the cab to indicate seating positions for firefighters. A weight allowance of 250 pounds for each shall be factored into the gross vehicle weight rating of the chassis.

One (1)
10-02-2500

HELMET WARNING TAG

A label shall be installed in the cab, visible from each seating position. The label shall read "CAUTION: DO NOT WEAR HELMET WHILE SEATED." Helmets must be properly stowed while the vehicle is in motion according to the current edition of NFPA 1901.

One (1)
10-03-6000

REAR TOWING PROVISIONS

There shall be two tow eyes furnished under the rear of the body and attached directly to the chassis frame rails. There shall be a reinforcement spreader bar connecting the two tow eyes. Tow eyes are to be constructed of 3/8" plate steel with a 4" I.D. hole, large enough for passing through a tow chain end hook.

One (1)
80-43-2400

The tow plates shall be painted black.

One (1)
10-04-0002

Bumper, Existing Commercial Bumper

One (1)
10-06-1110

HUB AND LUG NUT COVERS

The apparatus shall have chrome or stainless steel hub and lug nut covers on the front and single rear axles.

One (1)
10-08-2100

REAR MUD FLAPS

A pair of black mud flaps shall be installed behind the rear wheels.

One (1)
10-19-4000

AIR SHORELINE CONNECTION

One (1) compressed air inlet fitting shall be provided for connection to an external air source to maintain the air brake pressure. The air inlet shall have a check valve installed to prevent air from escaping from the air storage tanks on the chassis.

The air inlet fitting shall be located in the driver's side step or door area.

One (1)

== Midship Pumper/Tanker Pump & Plumbing - 1242.024 12/04/24 ==

One (1)
20-01-1700

DEALER SUPPLIED/INSTALLED ENGINE DRIVEN PUMP

WATER TANK TO PUMP LINE

Provide one (1) 2-1/2" NPTF port in the side of the tank with a 'J' tube to draw water from the tank sump. Provide an access hole in the rear wall of L1.

One (1)
22-50-0100

The tank to pump valve shall be controlled at the pump operator's panel.

One (1)
24-61-1250

Provide one (1) 2" NPTF port in the side of the tank for a future tank fill. Provide an access hole in the rear wall of L1.

One (1)
20-31-1400

DEALER PROVIDED PUMP TEST

One (1)

One (1)
26-01-9999

One (1)
26-55-1100

One (1)
27-35-4300

LABELS TO BE DEALER SUPPLIED AND INSTALLED

WATER TANK LEVEL GAUGE - PUMP PANEL

The apparatus shall be equipped with an Innovative Controls, part number 3050684, Soft-Glo Tank Level Monitor System shall be installed. The system shall include an electronic display module, a pressure transducer-based sender unit, and a 15' connection cable. The display module shall show the volume of water in four (4) distinct sections, using multi-color and programmable super bright LED's. The electronic display module shall be waterproof and shock resistant being encapsulated in a urethane-based potting compound. The potted display module shall be mounted to a chrome plated panel-mount bezel with a durable easy-to-read polycarbonate insert featuring blue graphics and a water icon.

All programming functions shall be accessed and performed from the front of the display module. The programming includes self-diagnostics, manual or self-calibration, and networking capabilities to connect remote slave displays. Low tank level warnings shall include flashing red LEDs starting below the 1/4 level and an output for an audible alarm.

The display module shall receive an input signal from a pressure transducer. This stainless steel sender unit shall be installed on the outside of the water tank near the bottom. All wiring, cables and connectors shall be waterproof without the need for sealing grease.

Location of water tank level monitor shall be at the pump panel.

Locate coiled up, not mounted in compartment L1

One (1)
27-36-5353

GAUGE BEZEL - BLUE

The gauge shall have a blue bezel.

One (1)

One (1)
47-01-0500

BOOSTER TANK

Booster Tank shall be constructed to meet and or exceed the requirements set forth in the NFPA pamphlet 1901, 2009 edition. Booster tanks shall be constructed of 1/2" thick UV stabilized Copolymer Polypropylene virgin grade sheet stock. All material used, seen and unseen, shall be a minimum of 1/2" non-corrosive UV stabilized stress relieved Copolymer Polypropylene

thermoplastic, black in color and UV stabilized for maximum protection. The booster and/or foam tank shall be a specific configuration and so designed to be completely independent of the body compartments. All baffles and structural components shall have rabbet and dado joint construction to gain mechanical advantage. All components must be extrusion welded on all sides, walls, gussets, baffles, top and bottom to add structural support. After all components are extrusion welded, they must be visually, electronically and hydraulically tested to insure maximum strength and integrity. The top of the booster tank must be fitted with removable lifting eyes to facilitate easy removal. All swash partitions (Transverse and Longitudinal) must be manufactured from $\frac{1}{2}$ " UV Stabilized Copolymer Polypropylene. All partitions must be designed and equipped with proper venting and passageways to allow movement of air and water through the compartments. All partitions must be designed to provide maximum water flow. All longitudinal and transverse partitions must be interlocked, and extrusion welded to each other as well as the walls of the tank.

Tank to have a **Lifetime Warranty**.

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of $\frac{1}{2}$ " Copolymer Polypropylene with a minimum dimension of 12"x 8". The tower shall be located in the front corner, unless otherwise specified. The tank shall have a $\frac{1}{2}$ " thick removable Copolymer Polypropylene screen and hinged cover. Located inside the cover shall be a combination vent and overflow pipe. The minimum I.D of 4" schedule 40 Copolymer polypropylene pipe shall run inside the tank to behind the rear wheels, to maximize the traction.

The tank lid shall be constructed of UV Stabilized $\frac{1}{2}$ " Copolymer Polypropylene. The tank must have a removable lid to allow for complete inside inspection and cleaning, per NFPA 1901 A.18.2.2. All mechanical fasteners used to hold the lid shall be stainless steel, utilizing bolts and locking nuts. The tank must be designed in such a way to keep the fasteners from contact with the contents of the tank. A minimum of two lifting dowels must be incorporated into the tank to facilitate installation and removal of the tank.

There shall be one sump standard per tank. The sump shall be located in the front quarter of the tank, unless otherwise specified. On all tanks that require a front suction, a 3" schedule 40 Copolymer pipe shall be installed that will incorporate a dip tube from the front of the tank to pump location. The sump shall be a minimum of 10"x10"x5". The sump shall have a minimum of a 3" npt machined outlet. The sump shall be used as a combination clean out and drain. All tanks shall have anti-swirl plate located above the sump.

One (1)
47-01-1055

WATER TANK - 2000-GALLON

The apparatus shall be equipped with a two-thousand (2000) gallon polypropylene water tank.

One (1)
47-01-1900

WATER TANK

The booster tank shall be a TEE shape and design to allow for maximum compartmentation, and a lower center of gravity.

One (1)
25-50-2500

DIRECT TANK FILL

A 2-1/2" diameter direct tank fill inlet shall be provided, including a 2-1/2" female NH swivel, plug and screen.

One (1)
24-62-1250

The valve shall be located and controlled on the right side rear of body.

One (1)
22-55-4050

The valve shall be an Akron 8000 Series two and one half-inch (2-1/2") valve with a stainless ball.

One (1)
25-50-2670

The valve shall be equipped with a manually operated, swing-type manual control located adjacent the intake. The valve shall be equipped with a color-coded name plate.

One (1)
25-62-1200

The direct tank fill inlet shall include a 2-1/2" female NH swivel, plug and screen.

QUICK DUMP - REAR

A Newton 10" quick dump valve shall be provided and externally mounted. The location shall be at the center rear of the apparatus.

--provide cut out in rear body to accommodate change to electric dump valve

-trim around quick dump assembly to be dealer supplied

One (1)
25-62-2100

A manual operated lever control shall be used to open and close the rear dump valve.

One (1)
25-62-2600

The Newton dump valve installed on the water tank shall be constructed of stainless steel.

One (1)
29-10-1000

HOSEBED SINGLE AXLE

The hose bed compartment deck shall be constructed entirely from maintenance-free, extruded aluminum slats. The slats shall have an anodized, radiused ribbed top surface. The slats shall be of widths approximately 3/4" high x 6" wide and shall be welded into a one-piece grid system to prevent the accumulation of water and allow ventilation to assist in drying hose.

The apparatus hose body shall be properly reinforced without the use of angles or structural shapes and free from all projections that might injure the fire hose.

The main apparatus hose body shall run the full length of the apparatus body from behind the pump panel area to the rear face of the body.

One (1)
29-10-5100

The upper rear interior of the hose body on the right and left sides shall be overlaid with brushed stainless steel to protect the painted surface from damage by hose couplings.

One (1)
30-01-1800

HOSE BED STORAGE CAPACITY

The hose bed shall be designed to have a storage capacity for a minimum of 55 cubic feet of fire department supplied fire hose.

1/8" ALUMINUM BODY

The body shall be fabricated of aluminum extrusions, smooth aluminum sheet and aluminum treadplate.

The aluminum extrusion alloy shall be 6061 with a temper rating of T6 and have a tensile strength of 45,000 PSI and yield strength of 40,000 pounds. The aluminum extrusions shall 3" x 3" aluminum tubing, 1-3/4" x 3" aluminum tubing and 3" x 3" aluminum angle and specially designed extrusions, up to .250" wall thickness where applicable.

The smooth aluminum sheet material alloy shall be 5052 with a temper rating of H32 and have a tensile strength of 33,000 PSI and yield strength of 28,000 pounds.

The aluminum treadplate alloy shall be 3003 with a temper rating of H22 and have a tensile strength of 30,000 PSI and yield strength of 28,000 pounds.

The extrusions shall be designed as structural-framing members with the smooth aluminum and treadplate fabricated to form compartments, hosebeds, and floors. All aluminum material shall be welded together using the latest mig spray pulse arc welding system.

Compartment floors shall be of the sweep out design with the floor higher than the compartment door lip and to be water and dust proof. All compartments shall be made to the maximum practical dimensions to provide maximum storage capacity. To ensure maximum storage space, the apparatus shall be constructed without any void spaces between the body and the compartment walls. Double wall construction does not meet this requirement.

All exterior compartments shall have polished aluminum drip moldings installed above the doors where necessary to prevent water from entering the compartments.

Wheel well panels shall be formed aluminum that is welded in place. There shall be no visible bolt heads, retention nuts or fasteners on the exterior surface of the panel. To fully protect the wheel well area from road debris and to aid in cleaning, a full depth radius wheel well liner shall be provided. The frame side of the wheel well area on each side of the opening shall be attached to the frame side of the front and rear compartments. All seams on the frame side of the body shall be welded and caulked to prevent moisture from entering the compartments.

The rear wheel wells shall be radius cut for a streamlined appearance. A fenderette shall be furnished at each rear wheel well opening, held in place with stainless steel fasteners.

FASTENERS

All aluminum and stainless-steel components shall be attached using stainless steel fasteners.

Compartment door hinges, handrails and running boards shall be attached using minimum 1/4" diameter machine bolt fasteners.

3/16" diameter fasteners shall only be used in nonstructural areas such as door handles, trim moldings, gauge mounting, etc.

One (1)
30-01-2250

ELECTROLYSIS CORROSION CONTROL

The apparatus shall be assembled using ECK or electrolysis corrosion control, on all high corrosion potential areas, such as door latches, door hinges, trim plates, fenderettes, etc. This coating is a high zinc compound that shall act as a sacrificial barrier to prevent electrolysis and corrosion between dissimilar metals. This shall be in addition to any other barrier material that may be used.

All 1/4" diameter and smaller screws and bolts shall be stainless steel.

Due to the expected life of the vehicle, proposals will only be acceptable from manufacturers that include these corrosion features.

One (1)
30-02-2200

COMPARTMENT FLOORS

The compartment floors shall be constructed of smooth aluminum material, to match the compartment interior walls.

One (1)
30-10-1100

GALVANIZED SUB-FRAME

The apparatus body subframe shall be constructed entirely of heavy steel structural channel material.

Two full frame lengths, three-inch (3") 3.4 pound per foot longitudinal steel channels shall form the sides of the body subframe and sides of the water tank cradle. Subframe crossmembers shall be fabricated with three inch (3") 3.4 pound per foot heavy steel channel cross members welded to the longitudinal body subframe sides and the full length frame pads.

Two full frame length 1/2" x 3" flat steel frame pads shall be attached to the body subframe and rest on top of the chassis frame rails for proper frame weight distribution.

The steel frame pads, longitudinal steel channels and subframe crossmembers shall be attached to the chassis frame rails using heavy "U" bolt fasteners to allow removal of the subframe and body assembly from the chassis. There shall be a barrier provided between the subframe and body to prevent electrolysis.

The rear subframe and lower body platform support members shall be of the "two piece" design, fabricated of 3.4 lb. per foot heavy channel and welded to the full length subframe channel liners at the rear.

A minimum of two rear platform support channels shall be provided and constructed of 3.4 lb. Per foot heavy steel material. Each support channel shall have welded in gusset where the support meets the rear subframe rails.

After fabrication the entire subframe assembly shall be hot dip galvanized to prevent corrosion. The hot dip galvanized subframe shall have a lifetime warranty against failure due to corrosion.

This steel subframe shall carry the weight of the apparatus body, tank, water and equipment. This method of apparatus construction gives an excellent strength/weight ratio.

One (1)
31-01-1300

BODY CONFIGURATION

The aluminum apparatus body shall be up to 220" long, reference the drawing for actual body length.

One (1)
44-06-2200

SINGLE AXLE WHEEL AREA

For ease of accessibility and maintenance, wheel well panels shall be double break formed painted smooth plate that is welded in place.

To fully protect the wheel well area from road debris and to aid in cleaning, a full depth (minimum of 25") radius wheel well liner shall be provided. Wheel well liner shall be smooth aluminum to prevent corrosion.

One (1)
44-06-4100

FENDERETTES

The rear wheel wells shall be radius cut for a streamlined appearance. A polished aluminum fenderette shall be furnished at each rear wheel well opening, held in place with concealed stainless-steel fasteners.

One (1)
31-01-2105

BODY WIDTH

The overall width of the pumper body shall not exceed 102".

COMPARTMENT DEPTH

One (1)
29-00-1300

The lower portion of the side compartments on the pumper body shall be 26" deep.

One (1)
32-03-0033

HOSEBED WIDTH

The width of the pumper body hosebed shall be 74".

One (1)
32-03-1033

COMPARTMENT HEIGHT

The left side body compartments shall be 33" high.

Two (2)
30-02-1150

COMPARTMENT HEIGHT

The right side body compartments shall be 33" high.

ROLL UP DOOR CONSTRUCTION

The roll up door(s) shall be fabricated from aluminum extrusions and be manufactured and assembled in the United States.

The door slats shall be double-wall extrusions with dimensions of 1.366" high x .315" thick. The exterior surface shall be flat and the interior surface concave to deflect loose equipment to prevent the door from jamming. Each slat shall have interlocking end shoes to prevent the slat from moving side to side resulting in binding of the door. Each slat shall be separated by a co-extruded PVC and rubber inner seal to prevent metal to metal contact and minimize dirt and moisture from entering the compartment. The inner seal shall not be visible from the exterior to maintain a clean appearance of door. The slats shall have interlocking joints with a folding locking flange to provide security and prevent penetration by sharp objects.

The track shall be a one (1) piece aluminum assembly that has an attaching flange and finishing flange incorporated into the design that facilitates installation and provides a finished look to the door without additional trim or caulking. A low-profile side seal shall be utilized to maximize usable compartment space.

A drip rail designed to prevent water from dripping into the compartment shall be provided. The drip rail shall have a built in replaceable non-contacting seal to eliminate scratching of the surface of the door.

Bottom rail extrusion must have smooth back to prevent loose equipment from jamming the door and have "V" shaped double seal to prevent water and debris from entering the compartment. The door latch system shall be a full width one (1) piece lift bar that enables the user to operate with one hand.

The roll mechanism shall have a clip system that connects the curtain slats to the operator drum to allow for easy tension adjustment without tools. A four (4) inch diameter counterbalanced operator drum shall be incorporated to assist in lifting the door.

One (1)
32-05-1030

LEFT FRONT COMPARTMENT

There shall be one (1) low compartment located ahead of the rear wheels. The compartment shall be equipped with a low roll up door.

The compartment shall be equipped with the following:

One (1)
44-40-1100

One (1) louver with filter shall be installed in the compartment.

One (1)
55-01-1252

COMPARTMENT LIGHTS

Two (2) ROM vertically mounted roll-up compartment LED V5 door lights shall be installed one each side of the door opening. The compartment lights shall be integrated into the roll-up door tracks with the light actuation with the door opening.

The lights shall have a polycarbonate lens to eliminate breakage from impact and eliminate heat buildup.

One (1)
55-06-1100

The compartment light will be controlled by an automatic "On-Off" switch located on each compartment door.

One (1)
32-06-1030

RIGHT FRONT COMPARTMENT

There shall be one (1) low compartment located ahead of the rear wheels. The compartment shall be equipped with a low roll up door.

The compartment shall be equipped with the following:

One (1)
44-40-1100

One (1) louver with filter shall be installed in the compartment.

One (1)
55-01-1252

COMPARTMENT LIGHTS

Two (2) ROM vertically mounted roll-up compartment LED V5 door lights shall be installed one each side of the door opening. The compartment lights shall be integrated into the roll-up door tracks with the light actuation with the door opening.

The lights shall have a polycarbonate lens to eliminate breakage from impact and eliminate heat buildup.

One (1)
55-06-1100

The compartment light will be controlled by an automatic "On-Off" switch located on each compartment door.

One (1)
33-60-1100

REAR BODY CONFIGURATION

One (1)
32-08-0600

The rear of the apparatus body shall be of the flat back design.

One (1)
33-61-1400

REAR COMPARTMENT

There shall be no compartment located on the rear of the body.

REAR STEP - 14" BOLT-ON

A 14" deep step surface shall be provided at the rear of the apparatus body, bolted in place and easily removable for replacement or repair. The tailboard shall be constructed of .188" aluminum diamond plate or equal non-slip surface in compliance with NFPA #1901 standards. The ends of the tailboard shall be designed with approximately a 30-degree angle on each side.

A label shall be provided warning personnel that riding on the rear step while the apparatus is in motion is prohibited.

--NO drop tailboard

One (1)

== Pumper/Tanker-Common Body Parts - 1242.024 12/04/24 ==

One (1)
44-01-1450

FRONT BODY PROTECTION PANELS

Aluminum tread plate overlays and panels shall be installed on the front of the body compartment from the lower edge to the top of the compartment doors.

One (1)
44-01-6000

CATWALKS - DOOR HEADER

One (1)
44-01-4000

The door header and the top of the compartments shall be aluminum treadplate.

REAR BODY PROTECTION PANELS

The rear body panels of the body shall be a smooth material, to allow for the proper application and installation of a "Chevron" stripe on the rear.

One (1)
44-02-1100

EXTRUDED ALUMINUM RUB RAILS

Full body length polished aluminum rub rails shall be bolted in place on the lower right and left body sides. The side rub rails shall be a heavy extruded aluminum "C" channel.

One (1)
44-02-2000

NYLON SPACERS FOR RUB RAILS

There shall be nylon spacers provided between the rub rail and the body. This shall allow wash out and replacement in the event of damage.

One (1)

== Pumper/Tanker-AC Electrical System - 1242.024 12/04/24 ==

One (1)
60-17-0001

One (1)

== Pumper/Tanker-Equipment Systems - 1242.024 12/04/24 ==

One (1)

== Pumper/Tanker - Single Axle - Pnt/Ltr/St - 1242.024 12/04/24 ==

One (1)
80-22-1504

BODY PAINT PROCESS

While constructing the truck body, all aluminum parts that are to be finish painted shall be properly fitted on the body and then removed to be painted as individually. The back side of all aluminum parts shall be sanded smooth of any burrs and sharp edges.

During reassembly of the apparatus, care shall be exercised in fitting and fastening the parts back in their respective position on the vehicle.

All aluminum parts shall be bolted to the body using stainless steel fasteners. Zinc or Cadmium plated fasteners are not acceptable. All bright metal fittings, if unavailable in stainless steel shall be heavily chrome plated. Iron fittings shall be copper plated prior to chrome plating.

All seams shall be caulked both inside and along the exterior edges with a urethane automotive sealant to prevent moisture from entering between any body panels.

The body and all parts shall be thoroughly washed with a grease cutting solvent (PPG DX330) prior to any sanding. After the body has been sanded and the weld marks and minor imperfections are filled and sanded, the body shall be washed again with (PPG DX330) to remove any contaminants on the surface.

The next two to four coats (depending on need) shall be a PPG DelFleet F4936 High Solids Epoxy Gray Primer. The film build shall be 4-6 mils when dry. The primer surfacer coat, after appropriate dry time, shall be sanded with 320-600 grit sandpaper to ensure maximum gloss of the paint. The last step is the application of at least three coats of PPG Delfleet polyurethane

two-component color (single stage). The film build being 2-3 mils dry. The single stage polyurethane, when mixed with corresponding catalyst shall provide a UV barrier to prevent fading and chalking.

All products and technicians are certified by PPG every two (2) years.

One (1)
80-06-1100

APPARATUS COLOR

--body to match chassis red

One (1)
80-30-1100

INTERIOR COMPARTMENT FINISH

Two (2) apparatus side compartment interiors are to be painted with a spatter finish material. The compartments shall be cleaned with a grease remover, and then the surface sanded and prepared for painting. The compartment shall be provided with two (2) coats of white epoxy. The compartments are then coated with a splatter paint top coat.

One (1)
80-42-1500

TOUCH-UP PAINT

One (1) two (2) ounce bottle of touch-up paint shall be furnished with the completed truck at final delivery.

One (1)
80-50-1100

LETTERING

The dealer shall supply the apparatus lettering.

One (1)
80-70-1100

REFLECTIVE STRIPING

The dealer shall supply reflective striping for the apparatus in compliance to applicable NFPA standards.

One (1)
80-72-1200

CHEVRON STRIPING

The inner rear portion of the body shall have 3M reflective striping installed. The chevron style striping shall be applied at a 45-degree upward angle pointing towards the center upper portion of the rear panel.

One (1)
80-75-1500

COLOR OF STRIPING MATERIAL

The color of the striping material shall be red.

One (1)
80-75-1800

COLOR OF STRIPIING MATERIAL

The color of the striping material shall be yellow.
One (1)

== Pumper/Tanker - Loose Equipment - 1242.024 12/04/24 ==
One (1)
90-58-1000

DEALER SUPPLIED EQUIPMENT

The following items shall be supplied by the Dealer:

DEALER SUPPLIED EQUIPMENT

The following items shall be supplied by the Dealer:

Onboard battery charger

Lettering 4" up to 50 letters

Body refelective stripe.

FIREFIGHTING SYSTEM, DEALER INSTALLED

The fire pump and associated equipment will be installed by the dealership and consist of the following items:

AUXILIARY FIRE PUMP SPECIFICATIONS

WATERAX gas fire pump will be installed.

FUEL SYSTEM

The gasengne will be supplied by an auxiliary fuel tank.

WARRANTY

The pump shall carry a two (2) year parts replacement warranty.

HAND PUMP PRIMER ASSEMBLY

There shall be a hand primer assembly plumbed into the pump volute. The hand pump primer assembly shall be located to allow the primer to be operated with the pump mounted in the specified compartment.

ELECTRIC START SYSTEM FOR AUXILIARY FIRE PUMP

The electric start system for the auxiliary fire pump shall be connected to the chassis electrical system. There shall be an on/off switch and push to start switch located near the pump operator's position.

2-1/2" GATED INTAKE

{Quantity} 2-1/2" gated suction intake shall be installed on the plumbing system to supply the auxiliary fire pump from an external water supply. The valve shall be a quarter turn ball valve and shall have 2-1/2" NST male threads of brass, chrome plated brass, or stainless-steel material.

The control handle shall be installed directly on the valve, with a labeled handle. The intake shall be provided with a removable screen and a 2-1/2" NST rocker cap with a retaining cable or chain installed.

An Innovative Controls 3/4" cast bronze quarter-turn drain/bleeder valve shall be installed. The valve shall be complete with a chrome plated bronze ball, reinforced Teflon seals, and blow-out proof stem rated to 600 PSI. A chrome plated zinc handle shall be provided on each drain valve complete with a recessed ID label provision. The handle shall lift, open and push down to close.

WATER TANK TO PUMP LINE

A 2-1/2" water tank to fire pump line shall be provided with a full flow quarter turn ball valve, 3" piping, and with flex hose and stainless-steel hose clamps. The tank to pump line shall be equipped with a check valve to prevent pressurization of the water tank.

The line shall be flow tested during the fire pump testing and shall meet applicable requirements of NFPA standards.

The tank to pump valve shall be controlled at the pump operator's panel.

The specified valve shall be an Akron 8000 Series two- and one-half inch (2-1/2") valve with a stainless ball.

For valve actuation, the specified discharge shall be equipped with a side mount valve control. The ergonomically designed 1/4 turn push-pull T-handle shall be chrome plated zinc with recessed labels for color coding and signage. The gear-control rod, double laminated locking clips, and rod housing shall be stainless steel and provide true positive lock that will eliminate valve drift. Bronze and Teflon impregnated stainless steel bushings in both ends of rod housing shall eliminate rod deflection, never need lubrication and ensure consistent long-term operation.

The control assembly shall include a decorative chrome-plated zinc panel mounted bezel with recessed color-coded label.

{Quantity} 2-1/2" IC discharge pressure gauges (0-400 PSI) shall be provided. The face of the gauge shall be a WHITE dial with black letters. The gauges will be located on the pump instrument panel.

FIRE PUMP TO WATER TANK FILL LINE

A 2" fire pump to water tank refill and pump bypass cooler line shall be provided. The valve shall be a full flow quarter turn ball valve with 2" piping and flex hose to tank. The valve control handle shall have a nameplate located near the valve control.

2-1/2" DISCHARGE

A 2-1/2" discharge shall be installed on the left side of the apparatus. The discharge shall be controlled by a quarter turn ball valve located at the pump. The manually operated swing type control shall be located adjacent to the valve. A nameplate label shall be provided adjacent to the control handle.

An Innovative Controls 3/4" cast bronze quarter-turn drain/bleeder valve shall be installed. The valve shall be complete with a chrome plated bronze ball, reinforced Teflon seals, and blow-out proof stem rated to 600 PSI. A chrome plated zinc handle shall be provided on each drain valve complete with a recessed ID label provision. The handle shall lift, open and push down to close.

{Quantity} 2-1/2" NST rocker lug chrome plated vented cap and cable or chain securement shall be provided.

FIRE PUMP TEST

The fire pump shall undergo pump tests per applicable sections of NFPA standards, prior to delivery of the completed apparatus.

The pump testing certificate shall be furnished with the apparatus on delivery.