

Prepared for:
Heather Fox
ROSENBAUER AMERICA BB
100 3RD ST
LYONS, SD 57041
Phone: 605-543-5591

Prepared by:
Carolyn LeBeau
I-STATE TRUCK CENTER
2901 WEST 60TH STREET N
SIOUX FALLS, SD 57107
Phone: 605-336-2995
E-Mail:
carolyn.lebeau@istatetruck.com

S P E C I F I C A T I O N P R O P O S A L

	Description	Weight Front	Weight Rear
Price Level	M2 PRL-28M (EFF:MY25 ORDERS)		
Data Version	SPEC PRO 21 DATA RELEASE VER 002		
Vehicle Configuration	M2 106 PLUS CONVENTIONAL CHASSIS 2025 MODEL YEAR SPECIFIED SET BACK AXLE - TRUCK STRAIGHT TRUCK PROVISION, NON-TOWING LH PRIMARY STEERING LOCATION	5,709	3,450
General Service	TRUCK CONFIGURATION DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES) EPA EMISSIONS CERTIFICATION FOR 50 STATE REGISTRATION - CARB EXEMPT, FIRE, EMERGENCY AND MILITARY VEHICLES ONLY (INCLUDES 6X4 INCH LABEL SHIPPED LOOSE) NONE FIRE SERVICE EMERGENCY VEHICLES BUSINESS SEGMENT LIQUID BULK COMMODITY TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS MAXIMUM 8% EXPECTED GRADE SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE MEDIUM TRUCK WARRANTY		

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
EXPECTED FRONT AXLE(S) LOAD : 16000.0 lbs		
EXPECTED REAR DRIVE AXLE(S) LOAD : 27000.0 lbs		
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 43000.0 lbs		
Truck Service		
FIRE TANK - NO MAIN DRIVELINE DRIVEN SPLIT- SHAFT PTO/PUMP		
ROSENBAUER		
EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0 in		
Engine		
CUM L9 360EV HP @ 2200 RPM, 2200 GOV RPM, 1150 LB-FT @ 1200 RPM, R/F/E	640	30
Electronic Parameters		
60 MPH ROAD SPEED LIMIT		
CRUISE CONTROL SPEED LIMIT 5 MPH HIGHER THAN ROAD SPEED LIMIT		
PTO MODE ENGINE RPM LIMIT - 1250 RPM		
PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED		
PTO RPM WITH CRUISE SET SWITCH - 1200 RPM		
PTO RPM WITH CRUISE RESUME SWITCH - 1200 RPM		
PTO MODE CANCEL VEHICLE SPEED - 15 MPH		
PTO GOVERNOR RAMP RATE - 500 RPM PER SECOND		
FUEL DOSING OF AFTERTREATMENT ENABLED IN PTO MODE-CLEANS HYDROCARBONS AT HIGH TEMPERATURES ONLY		
ONE TEM PTO SPEED		
PTO SPEED 1 SETTING - 1200 RPM		
PTO MINIMUM RPM - 700		
REGEN INHIBIT SPEED THRESHOLD - 5 MPH		
PTO 1, NO SWITCH, TEM SUPPLIED REQUEST AND INTERLOCKS, WITH PTO CONNECTIONS, ENGAGE BEFORE DRIVING INTERLOCK		
Engine Equipment		
EPA 2010/GHG 2024 CONFIGURATION		
STANDARD OIL PAN		
ENGINE MOUNTED OIL CHECK AND FILL		

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
SIDE OF HOOD AIR INTAKE WITH NFPA COMPLIANT EMBER SCREEN AND FIRE RETARDANT DONALDSON AIR CLEANER		
DR 12V 275 AMP 40-SI BRUSHLESS PAD ALTERNATOR WITH REMOTE BATTERY VOLTAGE SENSE	10	
(2) DTNA GENUINE, FLOODED STARTING, MIN 2000CCA, 370RC, THREADED STUD BATTERIES	10	
BATTERY BOX FRAME MOUNTED STANDARD BATTERY JUMPERS		
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
NON-POLISHED BATTERY BOX COVER		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	2	
PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS	2	
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
GVG, FIRE AND EMERGENCY SERVICE VEHICLES ENGINE WARNING		
CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF WITH BRAKE LAMPS	20	
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE EXITING FORWARD OF REAR TIRES	10	5
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH		
STANDARD EXHAUST SYSTEM LENGTH		
RH HORIZONTAL TAILPIPE, EXIT FORWARD OF REAR TIRES	20	20
6 GALLON DIESEL EXHAUST FLUID TANK		
100 PERCENT DIESEL EXHAUST FLUID FILL		
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
NO MUFFLER/TAIPIPE SHIELD	-10	
AIR POWERED ON/OFF ENGINE FAN CLUTCH		
AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED		
CUMMINS SPIN ON FUEL FILTER		
COMBINATION FULL FLOW/BYPASS OIL FILTER		
NO COOLANT FILTER	-10	
1100 SQUARE INCH ALUMINUM RADIATOR	70	
ANTIFREEZE TO -60F, ETHYLENE GLYCOL PRE-CHARGED SCA HEAVY DUTY COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
AUXILIARY ENGINE COOLING USING WATER FROM FIRE PUMP		
LOWER RADIATOR GUARD		
ALUMINUM FLYWHEEL HOUSING		
ELECTRIC GRID AIR INTAKE WARMER		
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH		
Transmission		
ALLISON 3000 EVS AUTOMATIC TRANSMISSION WITH PTO PROVISION	200	60
Transmission Equipment		
ALLISON VOCATIONAL PACKAGE 198 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODEL EVS		
ALLISON VOCATIONAL RATING FOR FIRE TRUCK/EMERGENCY VEHICLE APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES		
PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE ALTERNATE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED		
DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH BLUNTCUTS		
ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR		
CUSTOMER INSTALLED MUNCIE CS10 SERIES PTO		
PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION ALLISON		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED		
TRANSMISSION PROGNOSTICS - ENABLED 2013		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK	15	
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

Front Axle and Equipment

DETROIT DA-F-16.0-5 16,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE	190
MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	10

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
FIRE AND EMERGENCY SEVERE SERVICE, NON-ASBESTOS FRONT LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW TAS-85 POWER STEERING	40	
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE		
Front Suspension		
16,000# TAPERLEAF FRONT SUSPENSION	200	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
Rear Axle and Equipment		
CUMMINS-MERITOR RS-25-160 27,000# R- SERIES FIRE/EMERGENCY SERVICE SINGLE REAR AXLE		230
6.14 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	20	20
MERITOR 16.5X7 P CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, CAST SHOES		20
FIRE AND EMERGENCY SEVERE SERVICE NON- ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)		
GUNITE HEAVY WEIGHT CAST IRON REAR BRAKE DRUMS	30	
REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		
HALDEX AUTOMATIC REAR SLACK ADJUSTERS		
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE		

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
Rear Suspension		
27,000# FLAT LEAF SPRING REAR SUSPENSION WITH HELPER AND RADIUS ROD FOR FIRE/EMERGENCY SERVICE SPRING SUSPENSION - NO AXLE SPACERS STANDARD AXLE SEATS IN AXLE CLAMP GROUP FORE/AFT CONTROL RODS	170	
Pusher / Tag Equipment		
NO PUSHER/TAG BRAKE DUST SHIELDS		
Brake System		
AIR BRAKE PACKAGE WABCO 4S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES FIBER BRAID PARKING BRAKE HOSE STANDARD BRAKE SYSTEM VALVES STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM STD U.S. FRONT BRAKE VALVE RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE BW AD-9 BRAKE LINE AIR DRYER WITH HEATER AIR DRYER MOUNTED INBOARD ON LH RAIL STEEL AIR TANKS MOUNTED AFT INSIDE AND/OR BELOW FRAME JUST FORWARD OF REAR SUSPENSION, NO TRIPLE OR TORPEDO TANKS BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER ON ALL TANK(S)	20	
Trailer Connections		
NO TRAILER AIR HOSE NO AIR HOSE HANGER NO TRAILER ELECTRICAL CABLE		
Wheelbase & Frame		
5175MM (204 INCH) WHEELBASE 11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT	170	110
	150	370

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
1900MM (75 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 71 INCH TO 80 INCH	-30	120
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 138.19 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 135.19 in		
CALC'D FRAME LENGTH - OVERALL : 307.93 in		
CALCULATED FRAME SPACE LH SIDE : 103.47 in		
CALCULATED FRAME SPACE RH SIDE : 105.57 in		
CALC'D SPACE AVAILABLE FOR DECKPLATE : 0.0 in		
SQUARE END OF FRAME		
FRONT CLOSING CROSSMEMBER		
LIGHTWEIGHT HEAVY DUTY ALUMINUM ENGINE CROSSMEMBER	-12	
STANDARD CROSSMEMBER BACK OF TRANSMISSION		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REARMOST CROSSMEMBER		
STANDARD SUSPENSION CROSSMEMBER		

Chassis Equipment

THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30
FRONT TOW HOOKS - FRAME MOUNTED	15
BUMPER MOUNTING FOR SINGLE LICENSE PLATE	
NO MUDFLAP BRACKETS	
NO REAR MUDFLAPS	
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS	
GRADE 8 THREADED HEX HEADED FRAME FASTENERS	
EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE	
3D STEP VEHICLE MODEL	
TANK BODY 1501 TO 3000 GALLONS	
CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD	

Fifth Wheel

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
NO FIFTH WHEEL		
Fuel Tanks		
50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH	20	
RECTANGULAR FUEL TANK(S)		
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
FUEL TANK(S) FORWARD		
PLAIN STEP FINISH		
FUEL TANK CAP(S)		
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR	-5	
EQUIFLO INBOARD FUEL SYSTEM		
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
FUEL COOLER MOUNTED LEFT HAND IN RAIL	10	
Tires		
MICHELIN X WORKS Z 315/80R22.5 20 PLY RADIAL FRONT TIRES	100	
MICHELIN XDN2 12R22.5 16 PLY RADIAL REAR TIRES	140	
Hubs		
CONMET PRESET PLUS PREMIUM IRON FRONT HUBS		
CONMET PRESET PLUS PREMIUM IRON REAR HUBS		
Wheels		
ALCOA ULTRA ONE 89U64X 22.5X9.00 10-HUB PILOT 5.99 INSET ALUMINUM FRONT WHEELS	-28	
ALCOA ULA18X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS	-124	
POLISHED FRONT WHEELS; OUTSIDE ONLY		
POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY		
FRONT WHEEL MOUNTING NUTS		
REAR WHEEL MOUNTING NUTS		
Cab Exterior		
106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB AIR CAB MOUNTING		

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
CAB ROOF REINFORCEMENTS FOR ROOF MOUNTED COMPONENTS		
LH AND RH EXTERIOR GRAB HANDLES WITH SINGLE RUBBER INSERT		
HOOD MOUNTED CHROMED PLASTIC GRILLE		
CHROME HOOD MOUNTED AIR INTAKE GRILLE		
FIBERGLASS HOOD		
FREIGHTLINER NAME PLATES		
HOOD LINER, ADDED FIREWALL AND FLOOR HEAT INSULATION	5	
SINGLE ELECTRIC HORN		
REAR LICENSE PLATE MOUNT END OF FRAME		
INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL		
LED AERODYNAMIC MARKER LIGHTS		
DAYTIME RUNNING LIGHTS		
OMIT STOP/TAIL/BACKUP LIGHTS AND PROVIDE WIRING WITH SEPARATE STOP/TURN WIRES TO 4 FEET BEYOND END OF FRAME		-5
STANDARD FRONT TURN SIGNAL LAMPS		
AUTOMATIC ON/OFF, ENGINE COMPARTMENT, HOOD ACTIVATED WORK LIGHT WITH MANUAL OVERRIDE	1	
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
STANDARD SIDE/REAR REFLECTORS		
63X14 INCH TINTED REAR WINDOW		
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
RH AND LH ELECTRIC POWERED WINDOWS		
1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD		
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED		

Cab Interior

RUGGED TRIM PACKAGE
 GRAY & CARBON VINYL INTERIOR "RUGGED"

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
CARBON WITH PREMIUM GUNMETAL ACCENT (RUGGED)		
MOLDED PLASTIC DOOR PANEL		
MOLDED PLASTIC DOOR PANEL		
BLACK MATS WITH SINGLE INSULATION		
(1)DASH MOUNTED 12V POWER OUTLET, (1)DASH MOUNTED DUAL USB-C OUTLET		
FORWARD ROOF MOUNTED CONSOLE		
LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS		
DIGITAL ALARM CLOCK IN DRIVER DISPLAY		
(2) CUP HOLDERS LH AND RH DASH		
M2/SD DASH		
5 LB. FIRE EXTINGUISHER	10	
HEATER, DEFROSTER AND AIR CONDITIONER		
STANDARD HVAC DUCTING		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
PREP KIT FOR CUSTOMER INSTALLED AUXILIARY HEATER, PLUMBING FROM ENGINE TO BACK OF CAB WITH SHUTOFF VALVES		
STANDARD HEATER PLUMBING		
AUXILIARY HEATER PLUMBING		
VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR		
BINARY CONTROL, R-134A		
PREMIUM INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
PREMIUM LED CAB LIGHTING		
REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS	2	
ALL UNIT(S) KEYED ALIKE WITH CUSTOMER SPECIFIED KEY NUMBER FT1031		
KEY QUANTITY OF 2		
LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION		
NO MATTRESS	-20	-15
TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB	10	

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
SEATS INC 911 UNIVERSAL SERIES HIGH BACK AIR SUSPENSION DRIVER SEAT WITH NFPA 1901-2009/2016 COMPLIANT SEAT SENSOR	50	
SEATS INC 911 UNIVERSAL SERIES HIGH BACK NON SUSPENSION PASSENGER SEAT WITH UNDERSEAT STORAGE AND NFPA 1901-2009/2016 COMPLIANT SEAT SENSOR	25	10
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
BLACK CORDURA PLUS CLOTH DRIVER SEAT COVER		
BLACK CORDURA PLUS CLOTH PASSENGER SEAT COVER		
NFPA 1901-2009 HIGH VISIBILITY ORANGE SEAT BELTS		
FIXED STEERING COLUMN		
4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES		
DRIVER AND PASSENGER INTERIOR SUN VISORS		

Instruments & Controls

NO INSTRUMENT PANEL-DRIVER
 CONFIGURABLE LOWER PANEL WITH INTEGRATED UPPER STORAGE
 ENGINE REMOTE INTERFACE WITH PARK BRAKE AND NEUTRAL INTERLOCKS
 BLACK GAUGE BEZELS
 LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM WITH (1) ADDITIONAL PARK SWITCH FOR CUSTOMER USE
 DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE
 ELECTRONIC AIR RESTRICTION INDICATOR DISPLAYED IN DRIVER DISPLAY
 ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES
 KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY
 PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY
 DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY
 HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
2 INCH ELECTRIC FUEL GAUGE		
ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS		
QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS		
QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS		
ENGINE REMOTE INTERFACE CONNECTOR AT POWERTRAIN INTERFACE CONNECTOR		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
DIGITAL TRANSMISSION OIL TEMPERATURE IN DRIVER DISPLAY		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE		
NO OBSTACLE DETECTION SYSTEM		
NO DR ASSIST SYSTEM		
NO VEHICLE STABILITY ADVISOR OR CONTROL		
NO LANE DEPARTURE WARNING SYSTEM		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
CENTER OVERHEAD INSTRUMENT PANEL		
BLANK		
1 QUIKFIT PROGRAMMABLE MODULE (QPM/XMC) W/ (4) 20AMP FUSED RELAYS	10	
NFPA VEHICLE DATA RECORDER AND SEATBELT DISPLAY		
AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939		
DASH MOUNTED RADIO		
(2) RADIO SPEAKERS IN CAB		
AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF	2	
NO CB RADIO MOUNTING PROVISION		
NO DIGITAL SATELLITE AUDIO RECEIVER ANTENNA		
STANDARD RADIO WIRING WITH STEERING WHEEL CONTROLS		

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
DETROIT CONNECT PLATFORM HARDWARE		
3 YEARS DAIMLER CONNECTIVITY BASE PACKAGE ON (FEATURES VARY BY MODEL) POWERED BY DETROIT CONNECT ON CUMMINS ENGINES		
TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL		
IGNITION SWITCH CONTROLLED ENGINE STOP		
STEERING WHEEL MOUNTED ELECTRIC HORN CONTROL		
NO TRAILER HAND CONTROL BRAKE VALVE		
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
ALTERNATING FLASHING HEADLAMP SYSTEM WITH BODY BUILDER CONTROLLED ENGAGEMENT		
ONE VALVE PARKING BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR		
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT		
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY		

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0762EY MED RED ELITE EY
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
 PAINT
 STANDARD E COAT/UNDERCOATING

Certification / Compliance

Prepared for:
Heather Fox
ROSENBAUER AMERICA BB
100 3RD ST
LYONS, SD 57041
Phone: 605-543-5591

Prepared by:
Carolyn LeBeau
I-STATE TRUCK CENTER
2901 WEST 60TH STREET N
SIOUX FALLS, SD 57107
Phone: 605-336-2995
E-Mail:
carolyn.lebeau@istatetruck.com

Description	Weight Front	Weight Rear
U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS		

T O T A L V E H I C L E S U M M A R Y

Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	7683 lbs	4641 lbs	12324 lbs
Total Weight ⁺	7683 lbs	4641 lbs	12324 lbs

(+) Weights shown are estimates only.


If weight is critical, contact Customer Application Engineering.

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

DIMENSIONS



VEHICLE SPECIFICATIONS SUMMARY - DIMENSIONS

Model	M2106
Wheelbase (545)	5175MM (204 INCH) WHEELBASE
Rear Frame Overhang (552).....	1900MM (75 INCH) REAR FRAME OVERHANG
Fifth Wheel (578).....	NO FIFTH WHEEL
Mounting Location (577)	NO FIFTH WHEEL LOCATION
Maximum Forward Position (in).....	0
Maximum Rearward Position (in)	0
Amount of Slide Travel (in).....	0
Slide Increment (in).....	0
Desired Slide Position (in).....	0.0
Cab Size (829).....	106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB
Sleeper (682).....	NO SLEEPER BOX/SLEEPERCAB
Exhaust System (016)	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE EXITING FORWARD OF REAR TIRES

TABLE SUMMARY - DIMENSIONS

Prepared for:
 Heather Fox
 ROSENBAUER AMERICA BB
 100 3RD ST
 LYONS, SD 57041
 Phone: 605-543-5591

Prepared by:
 Carolyn LeBeau
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N
 SIOUX FALLS, SD 57107
 Phone: 605-336-2995
 E-Mail:
 carolyn.lebeau@istatetruck.com

Dimensions	Inches
Bumper to Back of Cab (BBC)	106.3
Bumper to Centerline of Front Axle (BA)	40.7
Front Axle to Back of Cab (AC)	65.6
Min. Cab to Body Clearance (CB)	3.0
Back of Cab to Centerline of Rear Axle(s) (CA)	138.2
Effective Back of Cab to Centerline of Rear Axle(s) (Effective CA)	135.2
Back of Cab Protrusions (Exhaust/intake) (CP)	2.0
Back of Cab Protrusions (Side Extenders/Trim Tab) (CP)	0.0
Back of Cab Protrusions (CNG Tank)	0.0
Back of Cab Clearance (CL)	3.0
Back of Cab to End of Frame	213.0
Cab Height (CH)	67.5
Wheelbase (WB)	203.7
Frame Overhang (OH)	74.8
Overall Frame Length	307.9
Overall Length (OAL)	319.3
Rear Axle Spacing	0.0
Unladen Frame Height at Centerline of Rear Axle	41.9

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.

Prepared for:
Heather Fox
ROSENBAUER AMERICA BB
100 3RD ST
LYONS, SD 57041
Phone: 605-543-5591

Prepared by:
Carolyn LeBeau
I-STATE TRUCK CENTER
2901 WEST 60TH STREET N
SIOUX FALLS, SD 57107
Phone: 605-336-2995
E-Mail:
carolyn.lebeau@istatetruck.com

T U R N I N G R A D I U S



Turning radius graphic and data provided strictly for comparisons between model configurations. Weather, road surfaces, and tire treads affect the results. It is strongly suggested that actual vehicles be measured before constructing any roads/driveways using this information. For specific figures regarding your configuration, please contact your CAE representative.

	Dimensions	Tolerance
Wall to Wall Diameter (ft)	61.6	+/- 3.0
Curb to Curb Diameter (ft)	60.1	+/- 3.0
Turning Radius (ft)	29.5	+/- 1.5

VEHICLE SPECIFICATIONS SUMMARY - TURNING RADIUS

Model	M2106
Cab Size (829).....	106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB
Wheelbase (545).....	5175MM (204 INCH) WHEELBASE
Front Tires (093).....	MICHELIN X WORKS Z 315/80R22.5 20 PLY RADIAL FRONT TIRES
Width (in).....	12.5
Front Axle (400).....	DETROIT DA-F-16.0-5 16,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE
Kingpin Intersection (in).....	71
Bumper (556)	THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS
Width (in).....	93.5
Bumper Miter to Front Axle (in).....	21.458
Primary Steering Location (003)	LH PRIMARY STEERING LOCATION
Steering Gear (536).....	TRW TAS-85 POWER STEERING
Dual Steering Gear	NONE
Ram.....	NONE
Rear Axle (420)	CUMMINS-MERITOR RS-25-160 27,000# R-SERIES FIRE/EMERGENCY SERVICE SINGLE REAR AXLE
Axle Spacing (624)	NO AXLE SPACING

Performance calculations are estimates only. If performance calculations are critical, please contact Customer Application Engineering.

Prepared for:
Heather Fox
ROSENBAUER AMERICA BB
100 3RD ST
LYONS, SD 57041
Phone: 605-543-5591

Prepared by:
Carolyn LeBeau
I-STATE TRUCK CENTER
2901 WEST 60TH STREET N
SIOUX FALLS, SD 57107
Phone: 605-336-2995
E-Mail:
carolyn.lebeau@istatetruck.com