

LIMITED WARRANTY AND REMEDY POLYESTER COIL COATED FINISHES

ARCONIC ARCHITECTURAL PRODUCTS LLC

A wholly owned subsidiary of Arconic

REYNOBOND® ALUMINUM COMPOSITE MATERIAL. REYNOLUX® PROFILE PRODUCTS. AND FLAT SHEET PRODUCTS

Coated with Duragloss® 1000, Duragloss® 3000, Duragloss® 5000, Duragloss® DL, Duragloss® PFX (PrismFX™)

This warranty is issued by Arconic Architectural Products LLC ("Arconic") to the property owner (the "owner") identified below and applies to the finish on Arconic REYNOBOND aluminum composite material, profiled products, flat sheet products and coil products coated with either Duragloss® 1000, Duragloss® 3000, Duragloss® 5000, Duragloss® DL, or Duragloss® PFX (PrismFX™), (the "products") and installed at the property (the "property") identified below.

PROPERTY OW	NER						
PROPERTY ADI	DRESS						
		STATE (OR COUNTY)					
DATE INSTALLE	ED						
CUSTOMER'S NAME							
CUSTOMER'S ADDRESS							
CITY		STATE (OR COUNTY)		ZIP			
CUSTOMER'S S	SIGNATURE						
PRODUCTS:	☐ Reynobond ACM	Reynolux Profile Prod	ducts				
SUBSTRATE:	Aluminum						
PRODUCTS:	☐ Colorweld 300	☐ Colorweld 500	☐ Colorweld 500 Mica	☐ Colorweld 500 XL			
COATINGS:	☐ Duragloss 1000	☐ Duragloss 3000	☐ Duragloss 5000				
☐ Duragloss DL (Designline)		ignline)	☐ Duragloss PFX (PrismFX)				

Warranty coverage is subject to the terms, conditions, limitations, remedies and legal rights set forth below:

- 1. The duration of this warranty (the "warranty period") shall be in accordance with the warranty table shown below in this document and shall apply worldwide.
- 2. The warranty period shall commence six (6) months from Arconic's initial shipment of the product, or upon substantial completion of the job, whichever occurs first.
- 3. Arconic warrants that during the warranty period the products will not peel, check, or crack (except for such slight crazing or cracking as may occur on normal roll-formed edges or break bends at the time of roll forming or other fabrication of pre-painted panels, sheet or coil and which is accepted in the industry as standard or peeling due to corrosion of the metal substrate) as a direct result of manufacturing defects.
- 4. Arconic warrants that, in the absence of ponding or standing water, the products will not chalk in excess of a numerical rating of 8 for vertical exposure or 6 when applied on non-vertical exposure during the warranty periods explained in charts 1 and 2 when measured in accordance with the standard procedures specified in ASTM D-4214, Method A. Notwithstanding the foregoing, Arconic makes no warranty against chalking for any embossed Products that are installed 46° or more from the vertical.
- 5. Arconic warrants that, in the absence of ponding or standing water, the products will not fade or change during the warranty periods explained in charts 1 and 2 in excess of 5∆ E units, when measured according to ASTM D-2244-02, paragraph 6.2.2 CIEL*a*b*10°. Measurements are taken on exposed paint surfaces which have been sufficiently cleaned of external deposits and chalk. Notwithstanding the foregoing, Arconic makes no warranty against fading or color change for any embossed products that are installed 46° or more from the vertical.
- 6. For Duragloss 3000 finishes, Arconic warrants that the percent gloss (60°) loss will not exceed 20% when measured on vertical exposed painted surfaces which have been cleaned of external deposits and the corresponding values measured on unexposed original painted surfaces. The gloss shall be measured using standard procedures as defined by ASTM D523.
- 7. This warranty covers only the particular defects described in this certificate and only if they arise during normal use and service. It does not cover defects attributable to causes or occurrences beyond Arconic's control and unrelated to the manufacturing process, including but not limited to, faulty or improper installation, normal weathering, exposure to, mildew, unreasonable use, misuse, physical abuse, accidental



damage, vandalism, use of incompatible accessories, fire, flood, earthquake, lighting, ice or windstorms, or other acts of God, windborne objects, building settlement or structural failures (including walls and foundations) or the use of harmful cleaning compounds, intermittent or continual submersion in water or any other liquid or solid material, deliberate damage, improper handling by erectors, improper fabrication of flat sheet or coil, mechanical damage or any other physical damage. Arconic recommends that there be a systematic fresh water rinse maintenance program in effect in areas of high salt concentration (such as adjacent to the seashore and/or an industrial atmospheres) so as to prevent the accumulation of concentrated salt deposits.

- 8. This warranty shall apply only under normal atmospheric conditions (which excludes corrosive or aggressive atmospheres, such as those contaminated with chemical fumes or salt spray or high continuous humidity. Locations between 0 to 1000 m/ 3280ft from salt water or within a mile of mile of an industrial facility (steel mills, power generating stations, oil fields, oil refineries, ore mines, chemical plants, paper mills, or where adverse environmental fallout or exposure is anticipated) are excluded from this warranty.
- 9. This warranty does not cover damage to the coating that occurs prior to installation of the product, including, without limitation, contamination occurring during shipment of the product to the jobsite or during storage at the jobsite. Forming REYNOBOND® panels at temperatures below an ambient temperature of 60°F (16°C) may adversely affect the appearance and performance of the Duragloss finish.
- 10. This warranty applies only to products with Arconic's standard substrate metals (i.e., galvanized steel conforming to the latest issue of ASTM A924 and ASTM A653, G90 Class, or aluminum of either 3105, 3003, 3004, 5005, Alclad 3003 or Alclad 3004 alloy). Unless this warranty is extended to the owner through a separate document signed by an officer of Arconic, it shall not apply if the owner or Arconic's customer requested the use of a substrate metal that is non-standard.
- 11. Non-uniform color changes that result from unequal exposure to sunlight and/or the elements are not covered by this Limited Warranty unless such color change meets the definition of Color Change above.
- 12. All claims hereunder must be submitted in writing to: Arconic Architectural Products, P.O. Box 4129 Eastman, GA 31023-4129. This claim must be accompanied by this certificate, fully completed and signed by the customer that furnished the product to the owner or a copy therefore. IN ORDER TO QUALIFY FOR WARRANTY COVERAGE, ALL CLAIMS MUST BE SUBMITTED WITHIN THIRTY (30) DAYS FROM THE DATE THE DAMAGE OR DEFECT IS FIRST DISCOVERED OR COULD HAVE BEEN DISCOVERED, BUT IN NO EVENT MAY CLAIMS BE SUBMITTED MORE THAN THIRTY (30) DAYS FOLLOWING THE EXPIRATION OF THE WARRANTY PERIOD.
- 13. Arconic shall be given a reasonable opportunity to inspect the product claimed to be defective. If after inspection of the product, Arconic determines that the claimed defect is covered by this warranty, Arconic, as its sole option, shall refinish, repair, or replace, the defective product without charge to the owner.
- 14. In no event does Arconic's warranty cover the cost of labor or sundry materials required to remove and/ or replace any defective product.
- 15. All warranty work will be performed by Arconic or by a company, customer, contractor, applicator, or distributor selected by Arconic. At no time does this warranty confer upon the claiming party or any other party the right to proceed with repair, replacement or restoration without written notice and agreement by a duly authorized officer of Arconic. Any such work undertaken by the claiming party or any other party shall be for the claiming party's own account and shall result in this warranty becoming null and void. Since there may be a color variance between the replacement or refinished product and the originally installed product due to the normal weathering (i.e. exposure to sunlight and extremes of temperature and weather and aging) of the originally installed product, this condition shall not be indicative of a defect in either the replacement or refinished product of the originally installed product.
- 16. Arconic reserves the right to discontinue or modify its product lines and coating colors. If the original product or coating color is no longer available, Arconic, will, at its option, either substitute a product or coating color of comparable quality or refund the purchase price of the defective product only.
- 17. The warranty period applicable to any refinished, repaired or replaced products shall be for the remaining un-expired portion of the original warranty period.
- 18. IT IS UNDERSTOOD AND AGREED THAT THE REMEDIES PROVIDED FOR HEREIN ARE EXCLUSIVE WHETHER FOR BREACH OF EXPRESS WARRANTIES OR OTHERWISE AND SHALL CONSTITUTE THE OWNER'S EXCLUSIVE REMEDY AND ARCONIC'S EXCLUSIVE LIABILITY. IN NO EVENT SHALL ARCONIC BE LIABLE FOR DIRECT, INDIRECT, INCIDENTAL, PUNITIVE, SPECIAL OR CONSEQUENTIAL DAMAGES FOR ANY BREACH OF ANY EXPRESS OR IMPLIED WARRANTIES IN CONNECTION WITH THE PRODUCT. THIS WARRANTY IS THE ONLY EXPRESS WARRANTY EXTENDED BY ARCONIC IN CONNECTION WITH THE PRODUCT, AND IT EXCLUDES ALL OTHER WARRANTIES, REPRESENTATIONS OR GUARANTEES, EXPRESS OR IMPLIED, WRITTEN OR ORAL, BY OPERATION OF LAW OR OTHERWISE, INCLUDING WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. ARCONIC'S AGGREGATE TOTAL CUMULATIVE LIABLITY UNDER THIS WARRANTY IS LIMITED TO THE DOLLAR AMOUNT OF THE PURCHASE PRICE.
- 19. Owner is solely responsible for proper selection of Arconic's products. Owner agrees that it will use Arconic products ony for their intended uses and according to the specifications and limitations established by Arconic from time to time. Owner acknowledges and agrees that Arconic products are to be used for commercial applications and are not intended for residential individual single family dwellings. Owner shall indemnify, defend and hold Arconic harmless from and against any and all damages arising out of or relating to use in residential individual single family dwellings, improper product selection, application, use, misuse, neglect, abuse of products or incorporation of products.
- 20. This warranty is extended only to the owner and is not assignable or transferable. Any such assignment or transfer shall render the warranty null and void.

Page 2 WTY1003 EC 97914-019



- 21. Laws and building and safety codes governing the design and use of glazed or coated materials vary widely. Seller does not control the selection of glazing or coating materials and assumes no responsibility therefore.
- 22. This warranty sets forth the entire agreement between the owner and Arconic relating to the products This warranty may not be modified or changed except by a written document signed by an officer of Arconic Architectural Products LLC.
- 23. The sale of Arconic's products hereunder with shipping addresses located in the United States shall be governed by the laws of the Commonwealth of Pennsylvania, excluding its laws related to choice or conflicts of law. The sale of Arconic products hereunder with shipping addresses located in Canada shall be governed by the laws of Ontario and the federal laws of Canada applicable therein. The United Nations Convention on Contracts for the International Sale of Goods is expressly disclaimed and does not apply to the sale of Seller products. Any and all disputes between the parties that may arise pursuant to this order will be heard and determined before an appropriate arbitrator, federal or state court located in Pittsburgh, Pennsylvania. The owner hereto acknowledges such court has the jurisdiction to interpret and enforce the provisions herein and/ or an arbitrator's judgment, and the Customer waives any and all objections that they may have as to personal jurisdiction or venue in any of the above courts.

	Peel, Check or Crack		10
	(in years)		10
		Between 20 North	5
	Color ∆ E<5.0	and South Latitude Above 20 North and	-
Duragloss®	(in years)	below South Latitude	5
1000†		Between 20 North	5
	Chalking >8 Rating	and South Latitude	3
	(in years)	Above 20 North and below South Latitude	5
	Peel, Check or Crack (in		
	years)		10
	, , , ,	Between 20 North	4
	Color ∆ E<5.0	and South Latitude Above 20 North and	7
Danlaaa®	(in years)	below South Latitude	10
Duragloss® 3000		Between 20 North	5
0000	Chalking >8 Rating	and South Latitude	5
	(in years)	Above 20 North and below South Latitude	10
	Gloss Retention	below South Latitude	
	≥80%		10
	(in years)		
		Between 20 North and South Latitude	10
	Peel, Check or Crack	Above 20 North and	20
	(in years)	below South Latitude	
		Between 20 North	10
Duragloss® 5000	Color Δ E<5.0 / <8.0	and South Latitude	10
3000	Vertical/Non Vertical (in years)	Above 20 North and below South Latitude	20
	` ′ ′	Between 20 North	10
	Chalking Rating >8 / >6 Vertical/Non Vertical	and South Latitude	10
	(in years)	Above 20 North and below South Latitude	20
	Peel, Check or Crack	Delow South Latitude	
	(in years)		20
Duragloss®	(iii yeais)	Between 20 North	10
DL	Chalking >8 Rating	and South Latitude	10
	(in years)	Above 20 North and below South Latitude	20
Duragloss® PFX (PrismFX)	Peel, Check or Crack	20.5W Coult Editude	
	(in years)		20
	())	Between 20 North	10
	Chalking >8 Rating	and South Latitude	10
	(in years)	Above 20 North and below South Latitude	20
	,	below South Latitude	20

[†] Excludes projects installed within 1 mile of salt water.

Page 3 WTY1003 EC 97914-019

^{*}This limited warranty applies only to products sold by Arconic and applied to metal that is used for installations occurring between the latitudes shown above unless the customer and Arconic specifically and in writing agree otherwise prior to Arconic's sale of the product to a coater.