

SMITH TRUCK CO.

RAVENS BY KRUIZ ECLIPSE 52

BUILT STRONG. BUILT TO LAST.



LIGHTER. STRONGER. SMARTER.

Premium all-aluminum construction
engineered for maximum payload
and long-term durability.




FABRICATED MAIN RAIL

Engineered for superior
strength and stability.



GALVANIZED SUSPENSION & LANDING GEAR

Standard galvanized components
for long-lasting protection.



HOLLOW-CORE ALUMINUM FLOOR

1-1/2" deep, multi-hollow core
extruded aluminum (6061-T6)
with (2) wood nailers.



HEAVY-DUTY REAR END

Two (2) vertical risers with
4" wide horizontal tubes
for added strength.

SPECIFICATIONS

Floor	1-1/2" depth, multi-hollow core extruded aluminum (6061-T6) with (2) wood nailers
Main Rail	11" deep in neck, 25" deep in main, 17" deep at rear
Outer Rail	6-3/4" deep extruded aluminum (6061-T6) one piece with integrated "J" track
Rib Rail	3-1/4" wide x 3/8" aluminum full length each side 6061-T6
Front Channel	9-3/4" deep one piece full width (6061-T6), square corners
Crossmembers	5" aluminum channel (6061-T6) on 15" or 22" centers.
Bumper	Two (2) heavy-duty vertical risers with 4" wide horizontal tube.
Dock Bumper	Two rubber bumpers.
Stake Pockets	4" H x 4" W x 1-5/8" D inside dimension on 24" centers with one (1) HD spool
Mud Flaps	Heavy-duty spray suppressant black rubber
Lengths	48', 51', and 53'
Widths	96" or 102"
Tires	255/75R22.5 OEM
Wheels/Disc	Eight (8) 8.25 x 22.5", 10-hole disc, hub piloted, unmount, machine finish aluminum wheels.
Hubs	Four (4) 10-stud hub piloted - Cast or Duralite.
Drums	Outboard mount light-weight hub piloted.
Brakes	16-1/2" x 7" Q-plus, non-asbestos lining with quick-change features, automatic slack adjusters, 4S/2M ABS system standard with aluminum air tank
Suspension	Air ride
Axles	71-1/2" or 77-1/2" track to match suspension.
Upper Coupler	48" height nominal
Landing Gear	Aluminum two-speed 50,000-lb capacity
King Pin Plate	1/2" aluminum plate, 19" from front standard
Electrical	DOT; sealed LED lights and harness
Finish	Swirl-finished aluminum suspension frame. All steel parts are galvanized.

BEAM LOAD RATINGS*

TRAILER SIZE	4 FT.	8 FT.	20 FT.	BASE** WEIGHT
48'	52,000	58,000	72,000	8,400

* Load ratings calculated based on 10 ft. widespread suspension
** Base model without options. Selected options may increase or decrease weight of finished trailer



LIGHTWEIGHT ALUMINUM

Maximize payload and fuel efficiency.



BUILT TO LAST

All-aluminum construction with galvanized components for long-term durability.



LOWER MAINTENANCE

Corrosion-resistant materials mean fewer repairs and less downtime.



PROVEN PERFORMANCE

Ravens quality and engineering you can trust.

**STRONGER PAYLOADS. LOWER COSTS.
MAXIMUM VALUE.**

989-930-0012

SMITHTRUCKCO.COM

ROSEBUSH, MI