

# 80 Series V Industrial True-RMS Multimeter with Temperature



# Accuracy and diagnostic functions for maximum industrial productivity

The new Fluke 87V has improved measurement functions, troubleshooting features, resolution and accuracy to solve more problems on motor drives, in plant automation, power distribution, and electromechanical equipment. The 87V operates very similar to the classic 87, but with more problem-solving power, safety, convenience and impact protection.

### New features for maximum productivity

- Unique function for accurate voltage and frequency measurements on adjustable speed motor drives and other electrically noisy equipment (87V)
- Built-in thermometer conveniently allows you to take temperature readings without having to carry a separate instrument (87V)
- Optional magnetic hanger for easy setup and viewing while freeing your hands for other tasks
- Large digit display with bright, two-level backlight makes the 80 Series V significantly easier to read than older models

#### **Electrical safety**

All inputs are protected to Category III, 1000 V and Category IV 600 V. They can withstand impulses in excess of 8,000 V and reduce risks related to surges and spikes.



### Specifications

Function	Range and resolution	Basic accuracy	
		83V	87V
DC Volts	600.0 mV, 6.000 V, 60.00 V, 600.0 V, 1000 V	0.1 %	0.05 %
AC Volts	600.0 mV, 6.000 V, 60.00 V, 600.0 V, 1000 V	0.5 %	0.7 % (True-rms)
DC Current	600.0 μA, 6000 μA, 60.00 mA, 600.0 mA, 6.000 A, 10.00 A	0.4 %	0.2 %
AC Current	600.0 μA, 6000 μA, 60.00 mA, 600.0 mA, 6.000 A, 10.00 A	1.2 %	1.0 % (True-rms)
Temperature (excl. probe)	-200 to 1090 °C (-328 to 1994 °F)	_	1.0 %
80BK Temperature Probe	-40 to 260 °C (-40 to 500 °F)	_	2.2 °C or 2 %
Resistance	600.0 Ω, 6.000 kΩ, 60.00 kΩ, 600.0 kΩ, 600.0 kΩ, 6.000 MΩ, 50.00 MΩ	0.4 %	0.2 %
Capacitance	10.00 nF, 100.0 nF, 1.000 μF, 10.00 μF, 100.0 μF, 9,999 μF	1.0 %	1.0 %
Frequency	199.99 Hz, 1.9999 kHz, 19.999 kHz, 199.99 kHz	0.005 %	0.005 %



## FLUKE ®

### **Comparison chart**

Feature	83V	87V
True-rms ac voltage and current for accurate measurements on non linear signals		•
Selectable filter for accurate voltage and frequency measurements on motor drives		•
0.05 % dc accuracy		•
4-1/2 digit mode for precise measurements		•
Built-in thermometer lets you carry one less tool		•
Large display digits and two-level bright white backlight for increased visibility		•
10,000 µF capacitance range for components and motor caps		•
Peak capture to record transients as fast as 250 µs		•
Measure up to 1000 V ac and dc		•
Measure up to 10 Å, 20 Å for up to 30 seconds		•
Auto and manual ranging for maximum flexibility	•	•
Analog bargraph		•
Resistance, continuity and diode test		•
Frequency to 200 kHz and % duty cycle		•
Min/Max and average recording to capture variations automatically		•
Relative mode to remove test lead resistance from low ohms measurements		•
Improved sleep mode for long battery life		•
Access door for fast battery changes without breaking the calibration seal		•
Limited lifetime warranty		•
Removable holster with built in test lead and probe storage		•
Cat IV 600 V and Cat III 1000 V electrical safety ratings		•
Basic test leads and alligator clips		•
Bead type thermocouple temperature probe		•

### **Included accessories**

Every Fluke 80 Series V meter comes packaged with TL75 Test Leads, AC72 Alligator Clips, holster, 9 V battery (installed), temperature probe (87V only) CD-ROM (user's manual and technical notes) and operator's guide.

### Ordering information

Fluke-83-5	Industrial Multimeter
Fluke-87-5	Industrial True-rms
	Multimeter with
	Temperature
Fluke-87-5/E	Industrial Electrician
	Combo Kit



### Fluke 87V/E Industrial Electrician Combo Kit

Includes special accessories to make industrial troubleshooting even more productive. Save more than \$50\* compared with the individual purchase price.

- A. 1.5 m heat resistant silicone test leads
- B. Removable test probes with 4 mm of exposed metal for use on industrial circuits
- C. Retractable long reach alligator clips
- D. Magnetic hanger to position and hold meter to steel surfaces
- E. Temperature probe

Packaged in a durable carrying case

\*Savings are noted in US\$

Fluke. Keeping your world up and running.

Fluke Corporation PO Box 9090, Everett, WA USA 98206 Fluke Europe B.V. PO Box 1186, 5602 BD Eindhoven, The Netherlands

For more information call: In the U.S.A. (800) 443-5853 or Fax (425) 446-5116 In Europe/M-East/Africa (31 40) 2 675 200 or Fax (31 40) 2 675 222 In Canada (800)-36-FLUKE or Fax (905) 890-6866 From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116 Web access: http://www.fluke.com/

©2004 Fluke Corporation. All rights reserved. Printed in U.S.A. 3/2004 2137623 D-ENG-P Rev A