



LADA

SERVICE SCHEDULE

LADA NIVA 2021 onwards:

REGISTRATION NUMBER:



PDI INSPECTION COMPLETED

MODEL: KMS:

DATE: BY: SIGNED:

SERVICE INTERVALS:

2,000 km:

Use ROSNEFT Kinetic GL-5 80W-90 transmission oil or similar

ESSENTIAL

- change transmission oil in the gearbox, rear and front axles, transfer case
- all other fluids level check
- check wheel bearings for wear
- check front wheel bearings for play, if necessary adjust torque.

ESSENTIAL SERVICING CARRIED OUT:

BY GARAGE (STAMP ETC)

KILOMETERS:

DATE:

SIGNED

2,000 km OPTIONAL BUT RECOMMENDED

Check:

Body condition:

- The presence of cracks and corrosion of the body, exfoliation of the mastic from the bottom and wheel arches
- The operation of the door locks, hood and tailgate
- The condition of the levers and suspension rods and their rubber-metal hinges; ball bearings; steering linkage joints; protective rubber covers and caps, rebound buffers; condition of rubber bushings; shock absorbers
- Total steering play
- Tightness of cooling systems, power supply and hydraulic drive of brakes, clutch and power steering; condition of hoses, pipes and connections
- Tightness of seals of components and assemblies
- Brake fluid level operation of the fluid level indicator in the brake fluid reservoir
- Coolant level
- Condition and tension of the alternator drive belt and accessory drive belt
- Condition of wires, reliability of connections and fastening clamps

- The operation of the generator, lighting, light and sound alarms, electrical equipment and electronic systems by indicators of the instrument cluster and other indicators on the instrument panel
- Lack of non-functional noise and knocking in the engine, transmission units and assemblies
- Power steering fluid level
- The operability of the electronic systems of the car with the help of the instrument panel indicators and the absence of fault codes in the memory of the controller

9,000 km or 1 year, whichever is soonest

Use LADA ULTRA 5W-40 engine oil or equivalent during maintenance.

ESSENTIAL

- motor oil change
- oil filter change
- check working fluids, refrigerant of the air conditioning system - topping up (topping up) if necessary *
- front brake pads - replace if necessary *
- check wheel bearings for wear and replace if necessary
- check front wheel bearings for play, if necessary adjust torque.

ESSENTIAL SERVICING CARRIED OUT:

BY GARAGE (STAMP ETC)

KILOMETERS:

DATE:

SIGNED

9000 km OPTIONAL BUT RECOMMENDED

Check:

Body condition:

- The presence of cracks and corrosion of the body, exfoliation of the mastic from the bottom and wheel arches
- The operation of the door locks, hood and tailgate
- The condition of the levers and suspension rods and their rubber-metal hinges; ball bearings; steering linkage joints; protective rubber covers and caps, rebound buffers; condition of rubber bushings; shock absorbers
- Total steering play
- Tightness of cooling systems, power supply and hydraulic drive of brakes, clutch and power steering; condition of hoses, pipes and connections
- Tightness of seals of components and assemblies
- Brake fluid level operation of the fluid level indicator in the brake fluid reservoir
- Coolant level
- Condition and tension of the alternator drive belt and accessory drive belt
- Condition of wires, reliability of connections and fastening clamps

- The operation of the generator, lighting, light and sound alarms, electrical equipment and electronic systems by indicators of the instrument cluster and other indicators on the instrument panel
- Lack of non-functional noise and knocking in the engine, transmission units and assemblies
- The operability of the service and parking brake systems
- Condition of front brake pads, brake discs
- Power steering fluid level
- Battery condition
- Compliance with established standards for the boundaries of light beams of headlights
- Power steering performance
- The operability of the electronic systems of the car with the help of the instrument panel indicators and the absence of fault codes in the memory of the controller

- Lubricate: door hinges, rear seat hinges, bonnet lock cable; door openers; fuel filler flap hinge and spring; axle, spring and cracker of the door lock striker
- Clean the drain holes of the sills, doors and the cavity of the front fenders

19,500 km or 2 years, whichever is soonest

ESSENTIAL

Use LADA ULTRA 5W-40 engine oil or similar

- replace motor oil
- replace oil filter
- replace generator belt
- check wheel bearings for wear and replace if necessary
- check front wheel bearings for play, if necessary adjust torque.
- check working fluids level, refrigerant of the air conditioning system - topping up (topping up) if necessary
- front brake pads - replace if necessary
- rear brake pads - replace if necessary

ESSENTIAL SERVICING CARRIED OUT:

BY GARAGE (STAMP ETC)

KILOMETERS:

DATE:

SIGNED

19,500 km OPTIONAL BUT RECOMMENDED

Check:

Body condition:

- The presence of cracks and corrosion of the body, exfoliation of mastic from the bottom and wheel arches
- The operation of the door locks, hood and tailgate
- The condition of the levers and suspension rods and their rubber-metal hinges; ball bearings; steering linkage joints; protective rubber covers and caps, rebound buffers; condition of rubber bushings; shock absorbers
- Total steering play
- Tightness of cooling systems, power supply and hydraulic drive of brakes, clutch and power steering; condition of hoses, pipes and connections
- Tightness of seals of components and assemblies
- Brake fluid level operation of the fluid level indicator in the brake fluid reservoir

- Coolant level
- Condition and tension of the alternator drive belt and accessory drive belt
- Condition of wires, reliability of connections and fastening clamps
- The operation of the generator, lighting, light and sound alarms, electrical equipment and electronic systems by indicators of the instrument cluster and other indicators on the instrument panel
- Lack of non-functional noise and knocking in the engine, transmission units and assemblies
- The operability of the service and parking brake systems
- Condition of front brake pads, brake discs
- Power steering fluid level
- Battery condition
- Compliance with established standards for the boundaries of light beams of headlights
- Power steering performance
- The operability of the electronic systems of the car with the help of the instrument panel indicators and the absence of fault codes in the memory of the controller
-
- Change the oil filter and oil in the engine crankcase, attach a label about the filled oil in the engine compartment
- Lubricate: door hinges, rear seat hinges, bonnet lock cable; door openers; fuel filler flap hinge and spring; axle, spring and cracker of the door lock striker
- Clean and grease the terminals and clamps of the battery and check the reliability of its fastening
- Clean the drain holes of the sills, doors and the cavity of the front fenders

29,500 km or 3 years, whichever is soonest

ESSENTIAL

Use LADA ULTRA 5W-40 engine oil or similar

- change motor oil
- change oil filter
- change engine air filter
- change spark plugs
- change fine fuel filter
- check working fluids, refrigerant of the air conditioning system - topping up (topping up) if necessary
- front brake pads - replace if necessary
- rear brake pads - replace if necessary
- check wheel bearings and replace if necessary
- check front wheel bearings for play, if necessary adjust torque.

ESSENTIAL SERVICING CARRIED OUT:

BY GARAGE (STAMP ETC)

KILOMETERS:

DATE:

SIGNED

29,500 km OPTIONAL BUT RECOMMENDED

Check:

Body condition:

- The presence of cracks and corrosion of the body, exfoliation of the mastic from the bottom and wheel arches
- The operation of the door locks, hood and tailgate
- The condition of the levers and suspension rods and their rubber-metal hinges; ball bearings; steering linkage joints; protective rubber covers and caps, rebound buffers; condition of rubber bushings; shock absorbers
- Total steering play
- Tightness of cooling systems, power supply and hydraulic drive of brakes, clutch and power steering; condition of hoses, pipes and connections
- Tightness of seals of components and assemblies
- Brake fluid level operation of the fluid level indicator in the brake fluid reservoir
- Coolant level
- Condition and tension of the alternator drive belt and accessory drive belt

- Condition of wires, reliability of connections and fastening clamps
 - The operation of the generator, lighting, light and sound alarms, electrical equipment and electronic systems by indicators of the instrument cluster and other indicators on the instrument panel
 - Lack of non-functional noise and knocking in the engine, transmission units and assemblies
 - The operability of the service and parking brake systems
 - Condition of front brake pads, brake discs
 - Power steering fluid level
 - Battery condition
 - Compliance with established standards for the boundaries of light beams of headlights
 - Power steering performance
 - The operability of the electronic systems of the car with the help of the instrument panel indicators and the absence of fault codes in the memory of the controller
-
- Lubricate: door hinges, rear seat hinges, bonnet lock cable; door openers; fuel filler flap hinge and spring; axle, spring and cracker of the door lock striker
 - Clean the drain holes of the sills, doors and the cavity of the front fenders

- Coolant level
 - Condition of wires, reliability of connections and fastening clamps
 - The operation of the generator, lighting, light and sound alarms, electrical equipment and electronic systems by indicators of the instrument cluster and other indicators on the instrument panel
 - Lack of non-functional noise and knocking in the engine, transmission units and assemblies
 - The operability of the service and parking brake systems
 - Condition of front brake pads, brake discs
 - Rear brake pad condition
 - Power steering fluid level
 - Battery condition
 - Compliance with established standards for the boundaries of light beams of headlights
 - Power steering performance
 - The operability of the electronic systems of the car with the help of the instrument panel indicators and the absence of fault codes in the memory of the controller
-
- Lubricate: door hinges, rear seat hinges, bonnet lock cable; door openers; fuel filler flap hinge and spring; axle, spring and cracker of the door lock striker
 - Clean and grease the terminals and clamps of the battery and check the reliability of its fastening
 - Clean the drain holes of the sills, doors and the cavity of the front fenders

49,500 km or 5 years, whichever is soonest

ESSENTIAL

Use LADA ULTRA 5W-40 engine oil or similar

- change motor oil
- change oil filter
- check working fluids, refrigerant of the air conditioning system - topping up (topping up) if necessary
- front brake pads - replace if necessary
- rear brake pads - replace if necessary
- check front wheel bearings for play, if necessary adjust torque.

ESSENTIAL SERVICING CARRIED OUT:

BY GARAGE (STAMP ETC)

KILOMETERS:

DATE:

SIGNED

49,500 km OPTIONAL BUT RECOMMENDED

Check:

Body condition:

- the presence of cracks and corrosion of the body, exfoliation of the mastic from the bottom and wheel arches
- the operation of the door locks, hood and tailgate
- The condition of the levers and suspension rods and their rubber-metal hinges; ball bearings; steering linkage joints; protective rubber covers and caps, rebound buffers; condition of rubber bushings; shock absorbers
- Total steering play
- Tightness of cooling systems, power supply and hydraulic drive of brakes, clutch and power steering; condition of hoses, pipes and connections
- Tightness of seals of components and assemblies
- Brake fluid level operation of the fluid level indicator in the brake fluid reservoir
- Coolant level
- Condition and tension of the alternator drive belt and accessory drive belt
- Condition of wires, reliability of connections and fastening clamps

- The operation of the generator, lighting, light and sound alarms, electrical equipment and electronic systems by indicators of the instrument cluster and other indicators on the instrument panel
- Lack of non-functional noise and knocking in the engine, transmission units and assemblies
- The operability of the service and parking brake systems
- Condition of front brake pads, brake discs
- Power steering fluid level
- Battery condition
- Compliance with established standards for the boundaries of light beams of headlights
- Power steering performance
- The operability of the electronic systems of the car with the help of the instrument panel indicators and the absence of fault codes in the memory of the controller

- Lubricate: door hinges, rear seat hinges, bonnet lock cable; door openers; fuel filler flap hinge and spring; axle, spring and cracker of the door lock striker
- Clean the drain holes of the sills, doors and the cavity of the front fenders

59,000 km or 6 years, whichever is sooner

Use LADA ULTRA 5W-40 engine oil or similar

- **Replace timing chain**
- change motor oil
- change oil filter
- check working fluids, refrigerant of the air conditioning system - topping up (topping up) if necessary
- front brake pads - replace if necessary
- rear brake pads - replace if necessary
- check front wheel bearings for play, if necessary adjust torque.

ESSENTIAL SERVICING CARRIED OUT:

BY GARAGE (STAMP ETC)

KILOMETERS:

DATE:

SIGNED

59,500 km OPTIONAL BUT RECOMMENDED

Check:

Body condition:

- the presence of cracks and corrosion of the body, exfoliation of the mastic from the bottom and wheel arches
- the operation of the door locks, hood and tailgate
- The condition of the levers and suspension rods and their rubber-metal hinges; ball bearings; steering linkage joints; protective rubber covers and caps, rebound buffers; condition of rubber bushings; shock absorbers
- Total steering play
- Tightness of cooling systems, power supply and hydraulic drive of brakes, clutch and power steering; condition of hoses, pipes and connections
- Tightness of seals of components and assemblies
- Brake fluid level operation of the fluid level indicator in the brake fluid reservoir
- Coolant level
- Condition and tension of the alternator drive belt and accessory drive belt
- Condition of wires, reliability of connections and fastening clamps

- The operation of the generator, lighting, light and sound alarms, electrical equipment and electronic systems by indicators of the instrument cluster and other indicators on the instrument panel
- Lack of non-functional noise and knocking in the engine, transmission units and assemblies
- The operability of the service and parking brake systems
- Condition of front brake pads, brake discs
- Power steering fluid level
- Battery condition
- Compliance with established standards for the boundaries of light beams of headlights
- Power steering performance
- The operability of the electronic systems of the car with the help of the instrument panel indicators and the absence of fault codes in the memory of the controller

- Lubricate: door hinges, rear seat hinges, bonnet lock cable; door openers; fuel filler flap hinge and spring; axle, spring and cracker of the door lock striker
- Clean the drain holes of the sills, doors and the cavity of the front fenders

69,500 or 7 years, whichever is soonest

ESSENTIAL

Use LADA ULTRA 5W-40 engine oil or similar during maintenance.

- change motor oil
- change oil filter
- change engine air filter
- change spark plugs
- change fine fuel filter
- change generator/alternator belt
- check working fluids, refrigerant of the air conditioning system - topping up (topping up) if necessary
- front brake pads - replace if necessary
- rear brake pads - replace if necessary
- check front wheel bearings for play, if necessary adjust torque.

ESSENTIAL SERVICING CARRIED OUT:

BY GARAGE (STAMP ETC)

KILOMETERS:

DATE:

SIGNED

69,500 km OPTIONAL BUT RECOMMENDED

Check:

Body condition:

- the presence of cracks and corrosion of the body, exfoliation of the mastic from the bottom and wheel arches
- the operation of the door locks, hood and tailgate
- The condition of the levers and suspension rods and their rubber-metal hinges; ball bearings; steering linkage joints; protective rubber covers and caps, rebound buffers; condition of rubber bushings; shock absorbers
- Total steering play
- Tightness of cooling systems, power supply and hydraulic drive of brakes, clutch and power steering; condition of hoses, pipes and connections
- Tightness of seals of components and assemblies
- Brake fluid level operation of the fluid level indicator in the brake fluid reservoir

- Coolant level
 - Condition of wires, reliability of connections and fastening clamps
 - The operation of the generator, lighting, light and sound alarms, electrical equipment and electronic systems by indicators of the instrument cluster and other indicators on the instrument panel
 - Lack of non-functional noise and knocking in the engine, transmission units and assemblies
 - The operability of the service and parking brake systems
 - Condition of front brake pads, brake discs
 - Rear brake pad condition
 - Power steering fluid level
 - Battery condition
 - Compliance with established standards for the boundaries of light beams of headlights
 - Power steering performance
 - The operability of the electronic systems of the car with the help of the instrument panel indicators and the absence of fault codes in the memory of the controller
-
- Lubricate: door hinges, rear seat hinges, bonnet lock cable; door openers; fuel filler flap hinge and spring; axle, spring and cracker of the door lock striker
 - Clean and grease the terminals and clamps of the battery and check the reliability of its fastening
 - Clean the drain holes of the sills, doors and the cavity of the front fenders

79,500 or 8 years, whichever is soonest: Repeat 7 year cycle from 9,000 km service.

END OF DOCUMENT

Blackheath Developments Ltd (Lada4x4)
2 Wricklemarsh Road
London
SE3 0NF
UK