



AISI S400-15/S1-16



# **AISI STANDARD**

**Supplement 1 to 2015 Edition  
of North American Standard  
for Seismic Design of  
Cold-Formed Steel  
Structural Systems**

## DISCLAIMER

The material contained herein has been developed by the American Iron and Steel Institute (AISI) Committee on Framing Standards. The Committee has made a diligent effort to present accurate, reliable, and useful information on seismic design for cold-formed steel structures. The Committee acknowledges and is grateful for the contributions of the numerous researchers, engineers, and others who have contributed to the body of knowledge on the subject. Specific references are included in the *Commentary on the Standard*.

With anticipated improvements in understanding of the behavior of cold-formed steel and the continuing development of new technology, this material will become dated. It is anticipated that AISI will publish updates of this material as new information becomes available, but this cannot be guaranteed.

The materials set forth herein are for general purposes only. They are not a substitute for competent professional advice. Application of this information to a specific project should be reviewed by a registered professional engineer. Indeed, in many jurisdictions, such a review is required by law. Anyone making use of the information set forth herein does so at their own risk and assumes any and all liability arising therefrom.

First Printing – September 2016

Copyright American Iron and Steel Institute 2016

## **AIISI COMMITTEE ON FRAMING STANDARDS**

Roger LaBoube, <i>Chairman</i>	Wei-Wen Yu Center for Cold-Formed Steel Structures
Steve Fox, <i>Vice Chairman</i>	Canadian Sheet Steel Building Institute
Helen Chen, <i>Secretary</i>	American Iron and Steel Institute
Don Allen	Super Stud Building Products
Bill Babich	Alpine TrusSteel
Brad Cameron	Cameron & Associates Engineering, LLC
Randy Daudet	Simpson Strong-Tie
Jim DesLaurier	Certified Steel Stud Association
Nader Elhajj	FrameCAD Solutions
Pat Ford	Steel Framing Industry Association
Rick Haws	Nucor Buildings Group
Danielle Jacobs	National Council of Structural Engineers Associations
Jeff Klaiman	ADTEK Engineers
Rob Madsen	Supreme Steel Framing System Association
Cris Moen	Virginia Polytechnic Institute and State University
J. R. Mujagic	Consulting Structural Engineer
Kenneth Pagano	Scosta Corporation
Mike Pellock	Aegis Metal Framing
Nabil Rahman	The Steel Network, Inc.
Greg Ralph	ClarkDietrich Building Systems
Ben Schafer	The Johns Hopkins University
Michael Schmeida	Gypsum Association
Fernando Sesma	California Expanded Metal Products
Sutton Stephens	Pacific Northwest Engineering, Inc.
Brandon Wahl	360 Engineering Group
Steven Walker	Light Gauge Steel Engineering Group, Inc.
Robert Warr	Frameworks Engineering, LLC
Lei Xu	University of Waterloo
Cheng Yu	University of North Texas
Rahim Zadeh	Steel Stud Manufacturers Association
Ron Ziemian	Structural Stability Research Council

**LATERAL DESIGN SUBCOMMITTEE**

Rob Madsen, <i>Chairman</i>	Supreme Steel Framing System Association
Helen Chen, <i>Secretary</i>	American Iron and Steel Institute
Don Allen	Super Stud Building Products
Patrick Bodwell	Verco Decking, Inc.
Jim DesLaurier	Certified Steel Stud Association
Nader Elhajj	FrameCAD Solutions
Brian Gerber	IAPMO Uniform Evaluation Service
Bill Gould	ICC-ES
Perry Green	Bechtel Power Corporation
Rick Haws	Nucor Buildings Group
Danielle Jacobs	National Council of Structural Engineers Associations
Roger LaBoube	Wei-Wen Yu Center for Cold-Formed Steel Structures
Cris Moen	Virginia Polytechnic Institute and State University
J.R. Mujagic	Structural Engineering Consultant
Ashwin Mupparapu	Structuneering, Inc.
Nabil Rahman	The Steel Network, Inc.
Greg Ralph	ClarkDietrich Building Systems
Colin Rogers	McGill University
Atsushi Sato	Nagoya Institute of Technology
Ben Schafer	The Johns Hopkins University
Walter Schultz	Nucor Vulcraft
Reynaud Serrette	Santa Clara University
Randy Shackelford	Simpson Strong-Tie
K.S. Sivakumaran	McMaster University
Matthew Speicher	NIST Engineering Laboratory
Tom Sputo	Steel Deck Institute
Shahabeddin Torabian	Cold-Formed Steel Research Consortium
Chia-Ming Uang	University of California, San Diego
Steve Walker	Light Gauge Steel Engineering Group, Inc.
Robert Warr	Frameworks Engineering, LLC
Lei Xu	University of Waterloo
Cheng Yu	University of North Texas
Rahim Zadeh	Steel Stud Manufacturers Association
Bill Zhang	Kansas State University

## SUPPLEMENT 1 TO 2015 EDITION OF NORTH AMERICAN STANDARD FOR SEISMIC DESIGN OF COLD-FORMED STEEL STRUCTURAL SYSTEMS

1. Revise AISI S400-15 Sections E1.3.3, E2.3.3, and E6.3.3 as indicated below:

### E1.3.3 Expected Strength [Probable Resistance]

The expected strength [probable resistance] ( $\Omega_E V_n$ ) shall be determined from the *nominal strength [resistance]* in accordance with this section.

In the U.S. and Mexico, the expected strength factor,  $\Omega_E$ , shall be 1.8 for shear walls sheathed with wood structural panels. ~~equal to overstrength factor,  $\Omega_o$ , determined in accordance with the applicable building code.~~

#### User Note:

~~In the U.S. and Mexico, for cold formed steel light frame shear walls sheathed with wood structural panels, specific research on the expected strength of the walls based on energy dissipation at the connection between the sheathing and studs has not been completed. As a result, the overstrength factor,  $\Omega_o$ , obtained from the applicable building code is used as a coarse estimate at this time. Based on ASCE 7,  $\Omega_o=3$  for bearing wall systems and 2.5 for building frame systems.~~

In Canada, the expected strength factor,  $\Omega_E$ , shall be 1.33 for walls with DFP wood-based structural panel sheathing or OSB wood-based structural panel sheathing, and 1.45 for walls with CSP wood-based structural panel sheathing.

### E2.3.3 Expected Strength [Probable Resistance]

The expected strength [probable resistance] ( $\Omega_E V_n$ ) shall be determined from the *nominal strength [resistance]* in accordance with this section.

In the U.S. and Mexico, the expected strength factor,  $\Omega_E$ , shall be 1.8 for shear walls with steel sheet sheathing. ~~be equal to the overstrength factor,  $\Omega_o$ , determined in accordance with the applicable building code.~~

#### User Note:

~~In the U.S. and Mexico, for cold formed steel light frame shear walls with steel sheet sheathing, specific research on the expected strength of the walls based on energy dissipation at the connection between the sheathing and studs has not been completed. As a result, the overstrength factor,  $\Omega_o$ , obtained from the applicable building code is used as a coarse estimate at this time. Based on ASCE 7,  $\Omega_o=3$  for bearing wall systems and 2.5 for building frame systems.~~

In Canada, the expected strength factor,  $\Omega_E$ , shall be 1.4 for walls with *steel sheet sheathing*.

### E6.3.3 Expected Strength

The expected strength ( $\Omega_E V_n$ ) shall be determined from the *nominal strength* in accordance with this section. The expected strength factor,  $\Omega_E$ , shall be equal to 1.5 for shear walls with gypsum board or fiberboard panel sheathing. ~~the overstrength factor,  $\Omega_o$ ,~~

determined in accordance with the applicable building code.

**User Note:**

In the U.S. and Mexico, for cold formed steel light frame shear walls sheathed with gypsum board panels or fiberboard panels, specific research on the expected strength of the walls based on energy dissipation at the connection between the sheathing and studs has not been completed. As a result, the overstrength factor,  $\Omega_o$ , obtained from the applicable building code is used as a coarse estimate at this time. Based on ASCE 7,  $\Omega_o=2.5$  for bearing wall systems and building frame systems.

**This Page is Intentionally Left Blank.**





## SUPPLEMENT 1 TO 2015 EDITION OF COMMENTARY ON NORTH AMERICAN STANDARD FOR SEISMIC DESIGN OF COLD-FORMED STEEL STRUCTURAL SYSTEMS

1. Revise AISI S400-15-C by adding Section B3.3, and revising Sections E1.3.3 and E6.3 as indicated below:

### **B3.3 Expected Strength [Probable Resistance]**

The expected strength [probable resistance] may be expressed as a factor ( $\Omega_E$ ) times the nominal strength.

In the United States and Mexico: In AISI S400-15, an upperbound (conservative) value for  $\Omega_E = \Omega_o$  was employed when additional information for determining  $\Omega_E$  was unavailable, e.g., in Section E1.3.3. In 2016, a more precise upperbound estimate for  $\Omega_E$  was recognized. At the design limit,  $\phi V_n = V_{be}/R$  where  $V_{be}$  is the elastic base shear demand. The expected equilibrium between the demand and capacity is  $\Omega_o V_{be}/R = V_n + V_o$ , where  $V_o$  is the lateral resistance of elements outside of the seismic force-resisting system (SFRS). Substituting the design limit for  $V_n$  and assuming, as an upperbound, that no force is carried outside of the SFRS ( $V_o = 0$ ) results in an upperbound estimate of  $\Omega_E = \phi \Omega_o$ . This upperbound would appear to reward systems with low  $\phi$  (i.e. highly variable). As an additional check, it is considered that the exceedance probability of the upperbound capacity ( $\Omega_E V_n$ ) should be the same as the lowerbound failure probability, assuming a symmetrical probability distribution. This implies:  $\Omega_E V_n = V_n + (V_n - \phi V_n)$ , or  $\Omega_E = 2 - \phi$ . Thus, an upperbound is established that  $\Omega_E = \max(\phi \Omega_o, 2 - \phi)$ . This upperbound is applied in this *Standard* when additional information is unavailable for determination of  $\Omega_E$ .

### **E1.3.3 Expected Strength [Probable Resistance]**

This *Standard* incorporates a *capacity-based design* approach in which an element (fuse) of the seismic force-resisting system of a structure is designed to dissipate energy. The fuse element, known as the *designated energy-dissipating mechanism*, must be able to carry seismic loads over extensive inelastic displacements without sudden failure. It is expected that the fuse element will fail in a ductile, stable and predictable manner, at which time it will reach and maintain its maximum load-carrying resistance. In a structure that makes use of *cold-formed steel framed shear walls* with *wood structural panels* as lateral force-resisting elements, the *shear walls* themselves can initially be thought of as the fuse elements in the larger lateral force-resisting system. More specifically, it is the sheathing-to-steel framing connections of the *shear wall* that have been shown to fail in a ductile fashion and hence, it is these connections that are the *designated energy-dissipating mechanism* – i.e., the fuse. Thus, we seek the expected strength of this mechanism so that it can be protected.

The *capacity-based design* approach stipulates that all other components and connections in the lateral load-carrying path must be designed to withstand the expected [probable] strength of the *designated energy-dissipating mechanism* (fuse) element, where the expected strength takes into account expected overstrength (strength above nominal) that may exist. In the case of a *cold-formed steel framed shear wall*, the system includes the *chord studs*, field

*studs, hold-down and anchorage, track, etc.; these components are designed to carry the expected [probable] strength of the shear wall while the sheathing-to-framing connections fail in a ductile manner. To design the chord studs and other components of the seismic force-resisting system, it is necessary to estimate the probable capacity of the shear wall based on a sheathing connection failure mode. This can be achieved by applying an overstrength factor to the nominal resistance (Figure C-E1.3.3-1).*

*In the United States and Mexico:* It should be noted that the *nominal strengths* shown in Table E1.3-1 are based on a degraded backbone curve determined using the SPD cyclic protocol (Figure C-E1.3.1-1). Testing of similar specimens with the SPD and CUREE cyclic protocol were 20 percent higher using the CUREE cyclic protocol (Boudreault, 2005). Thus, expected strengths in the United States and Mexico are at least 1.2 times  $v_n$  in Table E1.3-1. However, no additional analysis has been conducted for finding expected strength. As a result, the upperbound estimate introduced in Commentary Section B3.3 is employed:  $\Omega_E = \max(\phi\Omega_o, 2 - \phi)$ . a conservative approach has been adopted at this time. the system overstrength factor,  $\Omega_o$ , obtained from the applicable building code is used as a coarse (and conservative) estimate. For this system,  $\phi = 0.6$ , and Bbased on ASCE/SEI 7-10,  $\Omega_o = 3$  for bearing wall systems and 2.5 for building frame systems, resulting in  $\Omega_E = 1.8$ .

*(No changes to the rest of this section.)*

### E6.3 Shear Strength

The requirements for *nominal strength* of *shear walls* with gypsum board or fiberboard panel sheathing are comparable to those of *shear walls* with wood structural panel sheathing. Refer to Section E1.3.1, and also the following sections for additional commentary.

Strength of *Type I shear walls* with fiberboard panel sheathing are based on studies by the NAHB Research Center (NAHB, 2005) and by the American Fiberboard Association (PFS, 1996; and NAHB, 2006). The *nominal strength* values for *shear walls* faced with fiberboard in Table E6.3-1 were based on monotonic tests of fiberboard sheathed, cold-formed steel framed *shear walls* and were compared to the monotonic and cyclic tests that are the basis of the building code tabulated capacities for fiberboard sheathed, wood framed *shear walls*. For the 2-inch (50.8 mm) and 3-inch (76.2 mm) edge screw spacing, the *nominal strength* values in Table E6.3-1 were based on the average peak load from tests of two 8-foot (2.438-m)-wide by 8-foot (2.428-m)-tall wall specimens. These *nominal strength* values were found to be within 90 percent of the *nominal strength* values for similarly sheathed wood framed walls. The ratio of steel-to-wood *nominal strength* values increased as the edge (perimeter) fastener spacing increased and, therefore, extrapolating the 2/6 (92% ratio) and 3/6 (96% ratio) design values to 4/6 using a ratio of 90% was conservative. For the 4-inch (101.6 mm) edge screw spacing, the *nominal strength* values were calculated as 90 percent of the *nominal strength* value for a similarly sheathed wood framed wall.

*In the United States and Mexico:* The upperbound estimate for expected strength introduced in Commentary Section B3.3 is also used for gypsum board and fiberboard shear walls. For these shear walls, per ASCE/SEI 7-10 with bearing wall systems,  $\Omega_o = 2.5$ , and  $\phi = 0.6$ , results in an upperbound  $\Omega_E = 1.5$ .



25 Massachusetts Avenue NW  
Suite 800  
Washington, DC 20001  
[www.steel.org](http://www.steel.org)



AISI S400-15/S1-16E