

Multifunctional IP Video Phone BL-6600



Highlights

- ✓ 20 SIP lines
 - ✓ HD audio on speakerphone and handset
 - ✓ 7 inch capacitive touch screen
 - ✓ Up to 127 DSS keys entries available at the display
 - ✓ Video Codec H.264 support for receiving video calls
 - ✓ Dual Gigabit ports, integrated PoE
 - ✓ Stand with 2 adjustable angles of 40 and 50 degrees
- ✓ Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc



寶力科技服務有限公司
BAOLI TECHNOLOGY SERVICE LTD
電話:02-77035366

Generic

- 20 SIP Lines
- Support receiving Video call
- POE Enabled
- 7 inch capacitive touch screen
- Handset / Hands-free / Headsetmode
- Intelligent DSS Keys
- Optional External Power Supply

Phone Features

- Local Phonebook (2000 entries)
- Remote Phonebook (XML / LDAP, 2000 entries)
- Call logs (In / out / missed, 1000 entries)
- Black / White List Call Filtering
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS / Soft keys
- Network Time Synchronization
- Support Recording (Through Flash Drive or Server Recording)
- Action URL / Active URI
- UACSTA

Video

- Video codec: H.264
- Video call resolution: QCIF / CIF / VGA

Audio

- HD Voice Microphone / Speaker (Handset / Hands-free,
- HAC handset
- Wideband ADC / DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.726-32K, G.729AB, AMR, iLBC
- Wideband Codec: G.722, AMR-WB, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation
- (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

Networking

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4 / IPv6 / IPv4&IPv6
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- QoS
- VLAN
- LLDP
- RTCP-XR(RFC3611), VQ-RTCPXR(RFC 6035)

Protocols

- SIP2.0 over UDP / TCP / TLS
- RTP / RTCP / SRTP
- STUN / DHCP / LLDP / SNTP
- IPv6 / OpenVPN
- PPPoE / 802.1x / L2TP / TR-069
- FTP / TFTP / HTTP / HTTPS

Deployment & Maintenance

- Auto-Provisioning via FTP / TFTP / HTTP / HTTPS / DHCP
- Web Management Portall
- Web-based Packet Dump
- Configuration Export fImport
- Phonebook Import / Export
- Syslog
- Phonebook Import / Export

Call Features

- Call out Answer or Reject
- Mute Unmute (Microphone)
- Call Hold Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always / Busy / No Answer)
- Call Transfer (Attended / Unattended)
- Call Parking / Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (On server)
- 3-way Conference
- Hot Line
- Hot desking

Physical Specifications

- Main LCD x1: 7.0 inch (800x480) Capacitive touch screen
- Keypad: 26 keys, including
 - * 5 Function keys (Hold, MWI, Mute, Headset, Redial)
 - * 4 Navigation keys
 - * 1 OK key
 - * 1 Return key
 - * 12 Standard Phone Digits keys
 - * 2 Volume Control keys, Up / Down
 - * 1 Hands-free key
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5 Ethernet Cable x1
- Back Rack x1
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- USB2.0 Port x1: Standard A, Connect with Wi-Fi USB dongle or Flash Driver
- DC Power Input: 5V/2A
- Power Consumption (PoE): 2.6~9W
- Power Consumption (Adapter): 2.4~8W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation: Desktop Stand
- Color: Black
- Device Dimensions
 - * Desktop Stand (Angles 1): 268 x 185 x 189mm
 - * Desktop Stand (Angles 2): 268 x 201 x 168mm
- Gift Box Dimensions: 304 x 297 x 66mm
- Outer CTN Dimensions: 616 x 358 x 329mm (10PCS)



寶力科技服務有限公司

BAOLI TECHNOLOGY SERVICE LTD

電話:02-77035366

Portable USB Camera BL-60



Highlights

- Plug and Play
- Adjustable Angle and Flexible Placement
- HD 2 Mega Pixels Camera
- 1080P@30fps
- Privacy Shutter Switch
- Suitable for High-end Phones

Video Features

- 2 Mega Pixels
- Video Codec: H.264
- Video Call Resolution: 1080P@30fps
- Automatic/Manual White Balance
- Automatic Exposure Compensation
- Adjustable with Privacy Shutter
- View : Diagonal:102°/ Horizontal: 94° / Vertical: 62°
- Vertical Adjustment Angle: $\pm 20^\circ$

Physical Features

- Interfaces : Micro USB 2.0 Port x1
- Color: Dark grey
- Status Indicator Light x1 (with Two-color LED)
- Power: 5V @ <500mA via USB Port
- Working Temperature: -10~50°C
- Working Humidity: 10~90%

Package

- USB Cable x1
- Installation:
 - * Desktop
 - * Mounted on IP Phone or LCD monitor
- Device Dimensions: 51x90.14x141.31mm
- Gift Box Dimensions: 155x115x55mm
- Outer CTN Dimensions: 297x250x330 mm (20 PCS)



寶力科技服務有限公司

BAOLI TECHNOLOGY SERVICE LTD

電話:02-77035366