



US010248372B2

(12) **United States Patent
Hall**

(10) **Patent No.: US 10,248,372 B2**

(45) **Date of Patent: Apr. 2, 2019**

(54) **MODULAR DISPLAY PANELS**

(71) Applicant: **Ultravision Technologies, LLC**, Dallas,
TX (US)

(72) Inventor: **William Y. Hall**, Dallas, TX (US)

(73) Assignee: **ULTRAVISION TECHNOLOGIES,
LLC**, Dallas, TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/409,288**

(22) Filed: **Jan. 18, 2017**

(65) **Prior Publication Data**

US 2017/0123749 A1 May 4, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/550,685, filed on
Nov. 21, 2014, now Pat. No. 9,582,237.

(Continued)

(51) **Int. Cl.**

G09F 13/00 (2006.01)

G06F 3/14 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06F 3/1446** (2013.01); **G06F 3/147**
(2013.01); **G06F 3/1438** (2013.01); **G06T 1/60**
(2013.01);

(Continued)

(58) **Field of Classification Search**

CPC G06F 3/1446; G06F 3/147; G06F 1/1601;
G06F 1/182; G06F 1/183; G06F 1/188;
G06F 1/189; G06F 1/20; G06F 1/26;
G06F 3/1438; G09G 3/3216; G09G

3/2096; G09G 5/363; G09G 2300/026;

G09G 3/32; G09G 2360/04; G09G

2310/0286; H05K 1/18; H05K 5/363;

H05K 5/0017; H05K 5/0247;

(Continued)

(56)

References Cited

U.S. PATENT DOCUMENTS

1,816,254 A 7/1931 Heath

3,150,455 A 9/1964 Indorf

(Continued)

FOREIGN PATENT DOCUMENTS

CN 2520549 Y 11/2002

CN 2544372 Y 4/2003

(Continued)

OTHER PUBLICATIONS

Lighthouseled, "Possibilities" and "Specifications," Aug. 9, 2013, 1
page.

(Continued)

Primary Examiner — Insa Sadio


(74) *Attorney, Agent, or Firm* — Slater Matsil, LLP

(57)

ABSTRACT

An embodiment method of manufacturing modular panels
includes manufacturing a group of modular display panels,
including a first and second modular display panel that have
the same size and shape. The first modular display panel
includes a first pixel array arranged at a first pitch, and the
second modular display panel includes a second pixel array
that is arranged at a second pitch that is different than the
first pitch. Any two modular display panels in the group are
capable of being attached to each other in an integrated
display system.

29 Claims, 26 Drawing Sheets



Related U.S. Application Data			
(60)	Provisional application No. 62/065,510, filed on Oct. 17, 2014, provisional application No. 62/025,463, filed on Jul. 16, 2014, provisional application No. 61/922,631, filed on Dec. 31, 2013.		
(51)	Int. Cl.		
	<i>H01H 11/04</i>	(2006.01)	6,169,632 B1 1/2001 Kurtenbach et al.
	<i>G09G 5/00</i>	(2006.01)	6,175,342 B1 1/2001 Nicholson et al.
	<i>G09G 5/36</i>	(2006.01)	6,208,073 B1 3/2001 Wang et al.
	<i>H05K 13/00</i>	(2006.01)	6,237,290 B1 5/2001 Tokimoto et al.
	<i>G06T 1/60</i>	(2006.01)	6,314,669 B1 11/2001 Tucker
	<i>G09G 3/32</i>	(2016.01)	6,329,593 B1 12/2001 Yang
	<i>G06F 3/147</i>	(2006.01)	6,335,829 B1 1/2002 Van De Voorde
	<i>G09G 3/20</i>	(2006.01)	6,362,801 B1 3/2002 Yuhara
	<i>H05K 1/18</i>	(2006.01)	6,364,507 B1 4/2002 Yang
(52)	U.S. Cl.		
	CPC <i>G09G 3/2096</i> (2013.01); <i>G09G 3/32</i> (2013.01); <i>G09G 5/006</i> (2013.01); <i>G09G 5/363</i> (2013.01); <i>H01H 11/04</i> (2013.01); <i>H05K 1/18</i> (2013.01); <i>H05K 5/0017</i> (2013.01); <i>H05K 5/0247</i> (2013.01); <i>H05K 5/04</i> (2013.01); <i>H05K 5/06</i> (2013.01); <i>H05K 13/00</i> (2013.01); <i>G09G 3/2088</i> (2013.01); <i>G09G 2300/026</i> (2013.01); <i>G09G 2310/0286</i> (2013.01); <i>G09G 2340/14</i> (2013.01); <i>G09G 2360/04</i> (2013.01); <i>G09G 2360/06</i> (2013.01); <i>G09G 2380/06</i> (2013.01); <i>H05K 2201/10106</i> (2013.01); <i>Y10T 29/49002</i> (2015.01); <i>Y10T 29/49007</i> (2015.01); <i>Y10T 29/49105</i> (2015.01)		
(58)	Field of Classification Search		
	CPC <i>H05K 5/04</i> ; <i>H05K 5/06</i> ; <i>H05K 13/0023</i> ; <i>G06T 1/16</i>		
	USPC 345/690, 545, 1.3, 82; 348/383; 361/692		
	See application file for complete search history.		
(56)	References Cited		
	U.S. PATENT DOCUMENTS		
	4,457,090 A	7/1984 McDonough	7,210,957 B2 5/2007 Mrakovich et al.
	4,497,125 A	2/1985 Hutchinson	7,220,022 B2 5/2007 Allen et al.
	4,782,336 A	11/1988 Bailey	7,244,044 B2 7/2007 Liao
	4,964,231 A	10/1990 De Maat et al.	7,244,058 B2 7/2007 DiPenti et al.
	5,036,248 A	7/1991 McEwan et al.	7,245,279 B2 7/2007 Wang
	5,172,504 A	12/1992 De Maat et al.	7,267,459 B2 9/2007 Matheson
	5,313,729 A	5/1994 Sakai et al.	7,268,501 B1 9/2007 Chen
	5,341,088 A	8/1994 Davis	7,287,878 B2 10/2007 Miller
	5,379,202 A	1/1995 Daun	7,311,431 B2 12/2007 Chew et al.
	5,410,328 A	4/1995 Yoksza et al.	7,319,408 B2 1/2008 Temple
	5,446,440 A	8/1995 Gleason et al.	7,325,955 B2 2/2008 Lucas et al.
	5,523,769 A	6/1996 Lauer et al.	7,334,361 B2 2/2008 Schrimpf et al.
	5,563,470 A	10/1996 Li	7,336,195 B2 2/2008 Van De Ven
	5,600,910 A	2/1997 Blackburn	7,355,562 B2 4/2008 Schubert et al.
	5,722,767 A	3/1998 Lin	7,377,669 B2 5/2008 Farmer et al.
	5,785,415 A	7/1998 Matsumura et al.	7,450,085 B2 11/2008 Thielemans et al.
	5,796,376 A	8/1998 Banks	7,473,020 B2 1/2009 Pickering
	5,900,850 A	5/1999 Bailey et al.	7,495,576 B2 2/2009 Maskeny et al.
	5,914,698 A	6/1999 Nicholson et al.	7,502,950 B1 3/2009 Brands
	5,949,581 A	9/1999 Kurtenbach et al.	7,520,628 B1 4/2009 Sloan et al.
	5,990,802 A	11/1999 Maskeny	7,543,976 B2 6/2009 Abogabir
	6,045,240 A	4/2000 Hochstein	7,549,777 B2 6/2009 Huang
	6,065,854 A	5/2000 West et al.	7,557,781 B2 7/2009 Chuang et al.
	6,114,632 A	9/2000 Planas, Sr. et al.	7,572,043 B2 8/2009 Kolstee et al.
	6,150,996 A	11/2000 Nicholson et al.	7,576,707 B2 8/2009 Nishimura
	6,162,849 A	12/2000 Zhuo et al.	7,605,772 B2 10/2009 Syrstad
			7,614,771 B2 11/2009 Mckechnie et al.
			7,665,874 B2 2/2010 Chadwell et al.
			7,674,000 B2 3/2010 Valerio, Jr. et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,688,280 B2	3/2010	Callegari et al.	8,932,123 B2	1/2015	Murayama et al.
7,694,444 B2	4/2010	Miller et al.	8,963,895 B2	2/2015	Cope et al.
7,703,941 B2	4/2010	Lee	9,013,367 B2	4/2015	Cope
7,774,968 B2	8/2010	Nearman et al.	9,018,846 B2	4/2015	Chew
7,779,568 B2	8/2010	Gettelfinger et al.	9,047,039 B2	6/2015	Perkins et al.
7,797,865 B2	9/2010	Patel et al.	9,047,791 B2	6/2015	Cox et al.
7,823,308 B1	11/2010	Munson et al.	9,052,085 B2	6/2015	Chan
7,868,903 B2	1/2011	Wendler et al.	9,058,755 B2	6/2015	Cope et al.
7,869,198 B1	1/2011	Nearman et al.	9,071,809 B2	6/2015	Cope et al.
7,907,133 B2	3/2011	Joffer et al.	9,108,261 B1	8/2015	Patrick
7,926,213 B1	4/2011	Kludt et al.	9,134,773 B2	9/2015	Hall
7,928,968 B2	4/2011	Shon et al.	9,167,191 B2	10/2015	Kondo et al.
7,950,174 B2	5/2011	Xu	9,228,732 B2	1/2016	Li
7,971,378 B2	7/2011	Campoy Odena	9,234,652 B2	1/2016	Wu
7,972,031 B2	7/2011	Ray et al.	9,243,790 B2	1/2016	Speer et al.
7,994,516 B2	8/2011	Chan et al.	9,330,589 B2	5/2016	Cope et al.
8,007,121 B2	8/2011	Elliott et al.	9,349,306 B2	5/2016	Hall
8,016,452 B2	9/2011	Dunn	9,412,926 B2	8/2016	Keller et al.
8,066,403 B2	11/2011	Sanfilippo et al.	9,494,302 B2	11/2016	Shen et al.
8,074,387 B2	12/2011	Mancuso	9,538,588 B2	1/2017	Mutschelknaus et al.
8,081,145 B2	12/2011	Ronkholz et al.	9,546,781 B2	1/2017	Myers
8,092,046 B2	1/2012	Wu et al.	9,587,814 B2	3/2017	Carney et al.
8,104,204 B1	1/2012	Syrstad	9,615,474 B2	4/2017	He et al.
8,111,208 B2	2/2012	Brown	9,655,267 B2	5/2017	Cope et al.
8,113,687 B2	2/2012	Villard et al.	9,711,690 B2	7/2017	Li et al.
8,115,229 B2	2/2012	Christy	9,863,586 B2	1/2018	Yang et al.
8,122,627 B2	2/2012	Miller	9,916,782 B2	3/2018	Hall
8,130,175 B1	3/2012	Joffer et al.	9,964,261 B2	5/2018	Ying et al.
8,136,277 B2	3/2012	Patterson et al.	2001/0037591 A1	11/2001	Nicholson et al.
8,136,279 B1	3/2012	Nearman et al.	2002/0122134 A1	9/2002	Kalua
8,154,864 B1	4/2012	Nearman et al.	2002/0126086 A1	9/2002	Takeuchi et al.
8,156,672 B2	4/2012	Xu	2002/0176267 A1	11/2002	Tanaka et al.
8,168,990 B2	5/2012	Christy	2003/0058191 A1	3/2003	Yuhara et al.
8,172,097 B2	5/2012	Nearman et al.	2003/0058666 A1	3/2003	Myono
8,183,794 B2	5/2012	Grajcar	2003/0117420 A1 *	6/2003	Ando G09G 3/20 345/690
8,184,114 B2	5/2012	Oh et al.	2003/0120236 A1	6/2003	Graef et al.
8,228,261 B2	7/2012	Callegari et al.	2003/0146882 A1	8/2003	Ogino et al.
8,246,220 B2	8/2012	Epstein et al.	2003/0156406 A1	8/2003	Galli
8,269,700 B2	9/2012	Jotter et al.	2003/0156407 A1	8/2003	Galli
8,281,344 B1	10/2012	Mathias	2003/0158886 A1	8/2003	Walls et al.
8,301,939 B2	10/2012	Gloege et al.	2003/0167666 A1	9/2003	Close
8,314,433 B2	11/2012	Christy	2003/0193816 A1	10/2003	Rahn
8,344,410 B2	1/2013	Wendler et al.	2003/0210236 A1	11/2003	Martin et al.
8,350,788 B1	1/2013	Nearman et al.	2004/0008155 A1	1/2004	Cok
8,362,696 B2	1/2013	Zheng	2004/0040248 A1	3/2004	Vilnes
8,368,112 B2	2/2013	Chan et al.	2004/0090391 A1	5/2004	Kondo
D681,263 S	4/2013	Van Eekeren et al.	2004/0104871 A1	6/2004	Boldt, Jr. et al.
8,410,993 B2	4/2013	Jenks et al.	2004/0123501 A1	7/2004	Safavi et al.
8,414,149 B2	4/2013	Nearman	2004/0186723 A1	9/2004	Mizutani et al.
8,434,898 B2	5/2013	Sanfilippo et al.	2004/0196049 A1	10/2004	Yano et al.
8,465,178 B2	6/2013	Wilcox et al.	2004/0222941 A1	11/2004	Wong et al.
8,522,494 B2	9/2013	Ward	2004/0240230 A1	12/2004	Kitajima et al.
8,552,928 B2	10/2013	Wendler et al.	2005/0052373 A1	3/2005	Devos et al.
8,558,755 B2	10/2013	Kharrati et al.	2005/0052374 A1	3/2005	Devos et al.
8,581,269 B2	11/2013	Kuk et al.	2005/0052375 A1	3/2005	Devos et al.
8,599,108 B2	12/2013	Kline et al.	2005/0078104 A1	4/2005	Matthies et al.
8,604,509 B2	12/2013	Wendler et al.	2005/0081414 A1	4/2005	Lutz et al.
8,610,779 B2	12/2013	Wu	2005/0116667 A1	6/2005	Mueller et al.
8,624,425 B2	1/2014	Feng et al.	2005/0134525 A1	6/2005	Tanghe et al.
8,648,774 B2	2/2014	Kline et al.	2005/0134526 A1	6/2005	Willem et al.
8,678,612 B2	3/2014	Jasmin, Jr. et al.	2005/0151708 A1	7/2005	Farmer et al.
8,697,458 B2	4/2014	Nolan et al.	2005/0178034 A1	8/2005	Schubert et al.
8,702,048 B2	4/2014	Kludt et al.	2005/0189311 A1	9/2005	Colby et al.
8,702,262 B2	4/2014	Park et al.	2005/0190520 A1	9/2005	Schomaker et al.
8,714,665 B2	5/2014	Campagna et al.	2005/0212717 A1	9/2005	Baumstark
8,740,408 B2	6/2014	Yoon et al.	2005/0231949 A1	10/2005	Kim et al.
8,766,880 B2	7/2014	Kharrati et al.	2005/0259036 A1	11/2005	Callegari et al.
8,794,795 B2	8/2014	Yaphe et al.	2005/0259418 A1	11/2005	Callegari et al.
8,803,766 B2	8/2014	Kline et al.	2005/0264471 A1	12/2005	Yamazaki et al.
8,824,124 B1	9/2014	Carlson et al.	2006/0017658 A1	1/2006	Biondo et al.
8,824,125 B1	9/2014	Cox et al.	2006/0028594 A1	2/2006	Chou
8,858,028 B2	10/2014	Kim	2006/0031720 A1	2/2006	Choi
8,870,395 B2	10/2014	Wu	2006/0039142 A1	2/2006	Temple
8,922,458 B2	12/2014	Sefton et al.	2006/0055641 A1	3/2006	Robertus et al.
8,929,083 B2	1/2015	Cox et al.	2006/0056169 A1	3/2006	Lodhie et al.
			2006/0132048 A1	6/2006	Popovich
			2006/0139917 A1	6/2006	Ward
			2006/0164587 A1	7/2006	Oh

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0170614	A1	8/2006	Tzong et al.	
2006/0171148	A1	8/2006	Huang	
2006/0185612	A1	8/2006	Bonner et al.	
2006/0227003	A1	10/2006	Ven	
2006/0241878	A1	10/2006	Jung et al.	
2006/0242871	A1	11/2006	Kondo et al.	
2006/0243948	A1	11/2006	Ishiwa et al.	
2006/0244681	A1	11/2006	Nakajima	
2006/0254103	A1	11/2006	Strick et al.	
2006/0256033	A1	11/2006	Chan et al.	
2006/0262533	A1	11/2006	Lin et al.	
2006/0274493	A1	12/2006	Richardson et al.	
2006/0279493	A1	12/2006	Syrstad	
2007/0000849	A1	1/2007	Lutz et al.	
2007/0008259	A1	1/2007	Barker	
2007/0068055	A1	3/2007	Segan et al.	
2007/0241988	A1	10/2007	Zerphy et al.	
2007/0247842	A1	10/2007	Zampini et al.	
2007/0279314	A1	12/2007	Brown	
2008/0047184	A1	2/2008	Dean	
2008/0060234	A1	3/2008	Chou et al.	
2008/0078733	A1	4/2008	Nearman et al.	
2008/0130282	A1	6/2008	Negley	
2008/0141571	A1	6/2008	Kottwitz	
2008/0141572	A1	6/2008	Tomich et al.	
2008/0263924	A1	10/2008	Nearman et al.	
2008/0266206	A1*	10/2008	Nelson	G09F 9/33 345/1.3
2008/0285087	A1	11/2008	Perkins et al.	
2008/0303747	A1	12/2008	Velicescu	
2009/0009103	A1	1/2009	Mckechnie et al.	
2009/0009945	A1	1/2009	Johnson et al.	
2009/0009997	A1	1/2009	Sanfilippo et al.	
2009/0015997	A1	1/2009	Barajas et al.	
2009/0021497	A1	1/2009	Wendler et al.	
2009/0021532	A1	1/2009	Gloege et al.	
2009/0024929	A1	1/2009	Gloege et al.	
2009/0058760	A1	3/2009	Aoki	
2009/0073080	A1*	3/2009	Meersman	G02F 1/13336 345/1.3
2009/0096711	A1	4/2009	Jang et al.	
2009/0121986	A1	5/2009	Tu et al.	
2009/0128461	A1	5/2009	Geldard et al.	
2009/0146910	A1	6/2009	Gardner	
2009/0146918	A1	6/2009	Kline et al.	
2009/0146919	A1	6/2009	Kline et al.	
2009/0147028	A1	6/2009	Sefton et al.	
2009/0190353	A1	7/2009	Barker	
2009/0241388	A1	10/2009	Dunn	
2009/0251391	A1	10/2009	Ng et al.	
2009/0284978	A1	11/2009	Elliott et al.	
2009/0289160	A1	11/2009	Kludt et al.	
2009/0296387	A1	12/2009	Reisenauer et al.	
2009/0322251	A1	12/2009	Hilgers	
2010/0019535	A1	1/2010	Chang et al.	
2010/0026973	A1	2/2010	Hemphill et al.	
2010/0045689	A1*	2/2010	Hsieh	G09G 5/393 345/545
2010/0073914	A1	3/2010	Park et al.	
2010/0090934	A1	4/2010	Elliott et al.	
2010/0109571	A1	5/2010	Nishino et al.	
2010/0123732	A1	5/2010	Jenks et al.	
2010/0135022	A1	6/2010	Deguar	
2010/0245109	A1	9/2010	Ashoff et al.	
2010/0251583	A1	10/2010	Brown et al.	
2010/0270582	A1	10/2010	Nolan et al.	
2010/0288895	A1	11/2010	Shamie	
2010/0295424	A1	11/2010	Alexander	
2010/0295760	A1*	11/2010	Somerville	G09G 3/3216 345/82
2010/0309185	A1	12/2010	Koester et al.	
2011/0002129	A1	1/2011	Zheng et al.	
2011/0019414	A1	1/2011	Jiang et al.	
2011/0025696	A1	2/2011	Wyatt et al.	
2011/0031513	A1	2/2011	Hsieh et al.	

2011/0051409	A1	3/2011	Nearman	
2011/0057215	A1	3/2011	Chen et al.	
2011/0072697	A1	3/2011	Miller	
2011/0074833	A1	3/2011	Murayama et al.	
2011/0085321	A1	4/2011	Eli	
2011/0089824	A1	4/2011	Zheng	
2011/0090138	A1	4/2011	Zheng	
2011/0096568	A1	4/2011	Schattinger et al.	
2011/0116232	A1	5/2011	Brown et al.	
2011/0133659	A1	6/2011	Li et al.	
2011/0134640	A1	6/2011	Bertele	
2011/0138663	A1	6/2011	Chen	
2011/0140999	A1	6/2011	Beland et al.	
2011/0168653	A1	7/2011	Garrett et al.	
2011/0181493	A1	7/2011	Williams et al.	
2011/0181495	A1	7/2011	Chu et al.	
2011/0188235	A1	8/2011	Bollmann	
2011/0188981	A1	8/2011	Bonn et al.	
2011/0194284	A1	8/2011	Quaal et al.	
2011/0205757	A1	8/2011	Whyte	
2011/0216482	A1	9/2011	Moscovitch et al.	
2011/0219650	A1	9/2011	Wright et al.	
2011/0235332	A1	9/2011	Cheung	
2011/0267328	A1	11/2011	Venkatasubramanian et al.	
2011/0267699	A1	11/2011	Wu	
2012/0005563	A1	1/2012	Gloege et al.	
2012/0019490	A1	1/2012	Huang	
2012/0021873	A1	1/2012	Brunner	
2012/0062540	A1	3/2012	Quadri et al.	
2012/0112235	A1	5/2012	Preuschl et al.	
2012/0206277	A1	8/2012	Cai	
2012/0218753	A1	8/2012	Joffer et al.	
2012/0218758	A1	8/2012	Wang et al.	
2012/0236509	A1	9/2012	Cope et al.	
2012/0248950	A1	10/2012	Nibori	
2012/0299480	A1	11/2012	Peting et al.	
2012/0319926	A1	12/2012	Koeblich et al.	
2013/0002634	A1	1/2013	Wendler et al.	
2013/0027861	A1	1/2013	Rosenau et al.	
2013/0182440	A1	7/2013	Ferrie et al.	
2013/0200821	A1	8/2013	Yoneoka et al.	
2013/0229797	A1	9/2013	Nearman	
2013/0271973	A1	10/2013	Rycyna, III	
2013/0279161	A1	10/2013	Pickard et al.	
2013/0321387	A1	12/2013	Ohe	
2014/0085885	A1	3/2014	Hatano	
2014/0153241	A1	6/2014	Templeton	
2014/0160363	A1	6/2014	Mutschelknaus et al.	
2014/0259645	A1	9/2014	Cox et al.	
2014/0267784	A1	9/2014	Rykowski	
2014/0267896	A1*	9/2014	Cox	G09F 9/3026 348/383
2014/0268565	A1*	9/2014	Cox	H05K 5/0017 361/692
2014/0285963	A1	9/2014	Vasilevsky	
2014/0301088	A1	10/2014	Lu et al.	
2015/0145851	A1	5/2015	Takeda et al.	
2015/0205565	A1	7/2015	Koguchi	

FOREIGN PATENT DOCUMENTS

CN	2549557	Y	5/2003
CN	2646812	Y	10/2004
CN	1556516	A	12/2004
CN	2674579	Y	1/2005
CN	2706836	Y	6/2005
CN	2727885	Y	9/2005
CN	2733499	Y	10/2005
CN	3509179	D	2/2006
CN	2822095	Y	9/2006
CN	2824292	Y	10/2006
CN	2834111	Y	11/2006
CN	2874691	Y	2/2007
CN	2899008	Y	5/2007
CN	2906921	Y	5/2007
CN	200956227	Y	10/2007
CN	101250936	A	8/2008
CN	101294700	A	10/2008
CN	101334953	A	12/2008

(56)	References Cited			CN	202134169	U	2/2012
	FOREIGN PATENT DOCUMENTS			CN	102368367	A	3/2012
				CN	202171165	U	3/2012
				CN	102418912	A	4/2012
CN	101404316	A	4/2009	CN	202230681	U	5/2012
CN	201226214	Y	4/2009	CN	202230682	U	5/2012
CN	201229746	Y	4/2009	CN	102509520	A	6/2012
CN	201229747	Y	4/2009	CN	202266799	U	6/2012
CN	201233695	Y	5/2009	CN	101872828	B	7/2012
CN	201262959	Y	6/2009	CN	101872829	B	7/2012
CN	201307381	Y	9/2009	CN	102544319	A	7/2012
CN	201345201	Y	11/2009	CN	202307009	U	7/2012
CN	101629707	A	1/2010	CN	102623618	A	8/2012
CN	101699154	A	4/2010	CN	102623621	A	8/2012
CN	201438351	U	4/2010	CN	202383944	U	8/2012
CN	101701674	A	5/2010	CN	20242337	U	9/2012
CN	201449702	U	5/2010	CN	102682669	A	9/2012
CN	201465466	U	5/2010	CN	102682671	A	9/2012
CN	101355132	B	6/2010	CN	202422683	U	9/2012
CN	101737646	A	6/2010	CN	102737554	A	10/2012
CN	101737648	A	6/2010	CN	102738366	A	10/2012
CN	201539725	U	8/2010	CN	102760392	A	10/2012
CN	201540699	U	8/2010	CN	202502685	U	10/2012
CN	201550216	U	8/2010	CN	101872827	B	11/2012
CN	101834173	A	9/2010	CN	102168702	B	11/2012
CN	201575434	U	9/2010	CN	102800765	A	11/2012
CN	201576411	U	9/2010	CN	202521184	U	11/2012
CN	201576430	U	9/2010	CN	202523329	U	11/2012
CN	201577260	U	9/2010	CN	202523334	U	11/2012
CN	201584129	U	9/2010	CN	202523337	U	11/2012
CN	101887940	A	11/2010	CN	202523345	U	11/2012
CN	201622789	U	11/2010	CN	202523349	U	11/2012
CN	201651984	U	11/2010	CN	202523351	U	11/2012
CN	201655193	U	11/2010	CN	202523374	U	11/2012
CN	201655196	U	11/2010	CN	202523377	U	11/2012
CN	201681560	U	12/2010	CN	202549195	U	11/2012
CN	101640237	B	1/2011	CN	202563838	U	11/2012
CN	201748196	U	2/2011	CN	202581065	U	12/2012
CN	201748199	U	2/2011	CN	202584617	U	12/2012
CN	101546801	B	3/2011	CN	202584622	U	12/2012
CN	201765771	U	3/2011	CN	202584625	U	12/2012
CN	201796561	U	4/2011	CN	202601717	U	12/2012
CN	201803140	U	4/2011	CN	202602105	U	12/2012
CN	201803144	U	4/2011	CN	202615728	U	12/2012
CN	201804915	U	4/2011	CN	202632682	U	12/2012
CN	201812454	U	4/2011	CN	202646254	U	1/2013
CN	201812456	U	4/2011	CN	202650452	U	1/2013
CN	201838265	U	5/2011	CN	202650463	U	1/2013
CN	201845522	U	5/2011	CN	202656470	U	1/2013
CN	102110764	A	6/2011	CN	202677752	U	1/2013
CN	201868043	U	6/2011	CN	202677753	U	1/2013
CN	201868044	U	6/2011	CN	202679828	U	1/2013
CN	102136229	A	7/2011	CN	202691652	U	1/2013
CN	201904981	U	7/2011	CN	202707716	U	1/2013
CN	201910212	U	7/2011	CN	202713825	U	1/2013
CN	201910213	U	7/2011	CN	302301505	S	1/2013
CN	102163392	A	8/2011	CN	302301906	S	1/2013
CN	102168702	A	8/2011	CN	101740706	B	2/2013
CN	201916876	U	8/2011	CN	102185078	B	2/2013
CN	201918125	U	8/2011	CN	102930785	A	2/2013
CN	201925281	U	8/2011	CN	202721932	U	2/2013
CN	201946238	U	8/2011	CN	202736970	U	2/2013
CN	201954484	U	8/2011	CN	202743586	U	2/2013
CN	201956020	U	8/2011	CN	202758554	U	2/2013
CN	201965586	U	9/2011	CN	202758555	U	2/2013
CN	201973531	U	9/2011	CN	102163392	B	3/2013
CN	201973623	U	9/2011	CN	103000088	A	3/2013
CN	201975022	U	9/2011	CN	202795924	U	3/2013
CN	201976382	U	9/2011	CN	202816279	U	3/2013
CN	102214783	A	10/2011	CN	202838846	U	3/2013
CN	202012808	U	10/2011	CN	103022318	A	4/2013
CN	202025488	U	11/2011	CN	103065559	A	4/2013
CN	202042136	U	11/2011	CN	202855217	U	4/2013
CN	202049690	U	11/2011	CN	202887627	U	4/2013
CN	202058388	U	11/2011	CN	202905030	U	4/2013
CN	202067478	U	12/2011	CN	202905033	U	4/2013
CN	202084254	U	12/2011	CN	202905040	U	4/2013
CN	102314812	A	1/2012	CN	202905058	U	4/2013
CN	202102651	U	1/2012	CN	302417520	S	4/2013

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	302417587	S	4/2013	CN	104009145	A	8/2014
CN	103124483	A	5/2013	CN	104009146	A	8/2014
CN	101976720	B	6/2013	CN	203787033	U	8/2014
CN	103177664	A	6/2013	CN	302917815	S	8/2014
CN	103177665	A	6/2013	CN	203849976	U	9/2014
CN	202976707	U	6/2013	CN	203910233	U	10/2014
CN	101894898	B	7/2013	CN	203932101	U	11/2014
CN	103196051	A	7/2013	CN	203950801	U	11/2014
CN	203038588	U	7/2013	CN	203950834	U	11/2014
CN	203038597	U	7/2013	CN	204005499	U	12/2014
CN	203038598	U	7/2013	CN	204117521	U	1/2015
CN	203038599	U	7/2013	CN	204117522	U	1/2015
CN	203055361	U	7/2013	CN	303084137	S	1/2015
CN	203055365	U	7/2013	CN	303084275	S	1/2015
CN	203102774	U	7/2013	CN	204141352	U	2/2015
CN	203102775	U	7/2013	CN	204143784	U	2/2015
CN	103268738	A	8/2013	CN	204229808	U	3/2015
CN	203136407	U	8/2013	CN	102814429	B	4/2015
CN	203165372	U	8/2013	CN	204257141	U	4/2015
CN	103280164	A	9/2013	CN	204285400	U	4/2015
CN	203176910	U	9/2013	CN	204288709	U	4/2015
CN	203192335	U	9/2013	CN	303169413	S	4/2015
CN	203202526	U	9/2013	CN	303169414	S	4/2015
CN	203231179	U	9/2013	CN	303169875	S	4/2015
CN	103346238	A	10/2013	CN	303170948	S	4/2015
CN	103354067	A	10/2013	CN	303227404	S	5/2015
CN	203232680	U	10/2013	CN	204423826	U	6/2015
CN	203240341	U	10/2013	CN	103022318	B	7/2015
CN	203242660	U	10/2013	CN	204463732	U	7/2015
CN	203250487	U	10/2013	CN	204496855	U	7/2015
CN	203250491	U	10/2013	CN	303276898	S	7/2015
CN	302600355	S	10/2013	CN	303278324	S	7/2015
CN	302607812	S	10/2013	CN	204534276	U	8/2015
CN	302607814	S	10/2013	CN	303316383	S	8/2015
CN	103413497	A	11/2013	CN	303339773	S	8/2015
CN	103456244	A	12/2013	CN	303339774	S	8/2015
CN	103456247	A	12/2013	CN	103032767	B	9/2015
CN	203325368	U	12/2013	CN	103337224	B	9/2015
CN	203336167	U	12/2013	CN	204613541	U	9/2015
CN	203339216	U	12/2013	CN	204634223	U	9/2015
CN	203339217	U	12/2013	CN	204665178	U	9/2015
CN	302682535	S	12/2013	CN	103544896	B	10/2015
CN	102682669	B	1/2014	CN	103557498	B	10/2015
CN	203386338	U	1/2014	CN	204695705	U	10/2015
CN	203415183	U	1/2014	CN	303405173	S	10/2015
CN	302705434	S	1/2014	CN	204117522	U	1/2016
CN	302716898	S	1/2014	CN	103280164	B	2/2016
CN	302716899	S	1/2014	CN	103456244	B	2/2016
CN	203490915	U	3/2014	CN	105447283	A	3/2016
CN	203491298	U	3/2014	CN	103367612	B	4/2016
CN	203491299	U	3/2014	CN	103219447	B	5/2016
CN	302761262	S	3/2014	CN	105632354	A	6/2016
CN	302761263	S	3/2014	CN	205406020	U	7/2016
CN	103730068	A	4/2014	CN	205406022	U	7/2016
CN	203526759	U	4/2014	CN	205408340	U	7/2016
CN	203528543	U	4/2014	CN	303746225	S	7/2016
CN	203535913	U	4/2014	CN	103337583	B	8/2016
CN	203571647	U	4/2014	CN	103441209	B	8/2016
CN	203571663	U	4/2014	CN	103794702	B	8/2016
CN	203573584	U	4/2014	CN	205447200	U	8/2016
CN	203573585	U	4/2014	CN	205487176	U	8/2016
CN	203573586	U	4/2014	CN	205487177	U	8/2016
CN	203573592	U	4/2014	CN	303776642	S	8/2016
CN	302789638	S	4/2014	CN	303805061	S	8/2016
CN	302790357	S	4/2014	CN	205555209	U	9/2016
CN	302790361	S	4/2014	CN	104143315	B	11/2016
CN	203606693	U	5/2014	CN	103730563	B	4/2017
CN	203607042	U	5/2014	CN	304222223	S	7/2017
CN	203607050	U	5/2014	CN	103472817	B	12/2017
CN	203631082	U	6/2014	EP	0863496	A2	9/1998
CN	203644330	U	6/2014	EP	863496	A2	9/1998
CN	103956136	A	7/2014	EP	1469450	A1	10/2004
CN	203690339	U	7/2014	EP	2956925	A1	12/2015
CN	203743962	U	7/2014	GB	1585394	A	3/1981
CN	302864854	S	7/2014	JP	06337644	A	12/1994
				JP	0816114	A	1/1996
				JP	1138905	A	2/1999
				JP	1152878	A	2/1999
				JP	2001242796	A	9/2001

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2001337626	A	12/2001
JP	2002368284	A	12/2002
JP	2003092195	A	3/2003
JP	2004354571	A	12/2004
JP	2005062461	A	3/2005
JP	2005084683	A	3/2005
JP	2006023464	A	1/2006
JP	2006221067	A	8/2006
JP	2007533066	A	11/2007
JP	2010181721	A	8/2010
KR	20020069818	A	9/2002
WO	0223956	A2	3/2002
WO	2004019657	A2	3/2004
WO	2004042690	A1	5/2004
WO	2005083660	A2	9/2005
WO	2005103564	A1	11/2005
WO	2007061496	A2	5/2007
WO	2007083879	A1	7/2007
WO	2008157262	A2	12/2008
WO	2009000896	A2	12/2008
WO	2011062570	A1	5/2011
WO	2013159655	A1	10/2013
WO	2014005600	A2	1/2014
WO	2015103079	A1	7/2015

OTHER PUBLICATIONS

Samsung, "User Manual, UD22B," B146-00286A-02, Jul. 2012, 145 pages.

Prismview, A Samsung Electronics Company, "Deploying a Digital Billboard with Prismview, Steps from Contracting Through Installation," White Paper, Aug. 2012, 4 pages.

YESCO Electronics, "The Layered Service Approach for Digital Outdoor Displays," White Paper, YESCO Electronics Service Plans, Aug. 2012, 6 pages.

Lighthouse Create Impact, "10mm Visual Resolution with Oval LEDs, Bi10-ER, Large Scale LED Panel, A Modular System for Outdoor Applications," Operation Manual, Jul. 2011; Document version 1.3; 33 pages.

International Search Report and Written Opinion received in International Application No. PCT/US2014/072373 dated May 27, 2015, 19 pages.

Daktronics, "Daktronics LED Billboard Technology," www.daktronics.com Nov. 14, 2013, 3 pages.

Daktronics, "The Smarter Approach to Digital Outdoor," Daktronics Digital Billboard Products, 2013, 16 pages.

Ekta, "WOWStrip," www.ekta-led.com, Jun. 19, 2014, 5 pages.

"What is IP? Explained: Ingress Protection rating (IP Rating, IP65-IP68) system," Waterproof TVs Direct; Apr. 11, 2012; <http://waterproof-tvs-direct.co.uk/blog/waterproof-tv/what-is-ip-ip-explained-ingress-protection-rating-ip-rating-ip65-ip68-system>.

WOWstrip Semi-Transparent LED Displays product page, <http://www.ekta-led.com/prod/68/17/190/>, retrieved Jun. 19, 2014, 3 pages.

UK Intellectual Property Office, Search Report in Application No. GB1518912.9 dated Mar. 2, 2016, pp. 1-6.

Extended European Search Report received in EP Application No. 14875899.8 dated Aug. 2, 2016, 16 pages.

Lang, Justin, Buyers Guide, "LED Display Panels," PLSN.com, Nov. 2013, 2 pages.

Internet Archive Wayback Machine, "Outdoor/Indoor LED Display, LED Screen, LED Panel, LED Video Wall, LED Curtain, LED Strip," <https://web.archive.org/web/20130728075831/http://www.szaoto.com:80/product1.html>, Jul. 2013, 2 pages.

Internet Archive Wayback Machine, "AOTO M Series Rental LED Display," <https://web.archive.org/web/20111211101926/http://www.szaoto.com:80/product13.html>, Dec. 11, 2011, 1 page.

Internet Archive Wayback Machine, "AOTO M Series Rental LED Display," <https://web.archive.org/web/20130909053329/http://szaoto.com:80/product13.html>, Sep. 2013, 1 page.

ACC Silicones, "Clear Silicone Gel," <https://web.archive.org/web/20140622080139/https://www.acc-silicones.com/products/gels.ashx>, Jun. 22, 2014, 4 pages.

AOTO, Article "AOTO Launches World Highest Resolution Outdoor LED Display—M8 in ISE 2012," <http://en.aoto.com/article/detail/201705111014.html>, 2012, 3 pages.

Internet Archive Wayback Machine, "AOTO Launches Worlds Highest-Resolution M3 LED Display in ISE," https://www.szaoto.com:80/news_23.html, Dec. 11, 2011, 1 page.

Glux, "BAtn Series," www.glux.com.cn/en, 2013, 2 pages.

"C-5 Rental Display," Installation Manual, Nov. 15, 2011, R5905120, 79 pages.

CYsn, Glux Visual Effects Tech (Shenzhen) Co., Ltd, <http://www.glux.cc/business-provide-self-cysn.html>, Oct. 1, 2013, 2 pages.

Li Yan, et al., "Potting Process Design of Outdoor LED Display Module," CKNI, Dec. 31, 2006, 1 page.

Luminautics, "LED Display Primer," www.luminautisc.com, 2011, 21 pages.

Internet Archive Wayback Machine, AOTO M Series Rental LED Display, "M Series Rental LED Display," <https://web.archive.org/web/20111211101926/http://www.szaoto.com:80/product13.html>, Dec. 11, 2011, 1 page.

MOTn, Glux Visual Effects Tech (Shenzhen) Co., Ltd, <http://www.glux.cc/business-provide-self-cysn.html>, Oct. 1, 2013, 2 pages.

Internet Archive Wayback Machine, AOTO, "News Center," <http://szaoto.com/news.html>, Dec. 7, 2013, 2013, 3 pages.

Osram Opto Semiconductors, "Outdoor Capability of Silicone SMT LEDs used in LED Sign Board Applications," Jan. 31, 2004, 11 pages.

Barco, "Outdoor LED Display Solutions," SLite, www.barco.com, Apr. 2007, 4 pages.

SEfl, Glux Visual Effects Tech (Shenzhen) Co., Ltd, <http://www.glux.cc/business-provide-self-cysn.html>, Oct. 1, 2013, 2 pages.

Glux, "SEfl Series," www.glux.com.cn, 2013, 1 page.

Sony, "Large LED Display System," 2011, 8 pages.

VUEPIX, Product Catalog, 2012, www.vuepix.com, 36 pages.

Yung, K.C., et al., "Thermal Performance of High Brightness LED Array Package on PCB," Nov. 30, 2010, 2 pages.

"Respondents' Identification of Claim Terms Requiring Constructions," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, Investigative No. 337-TA-1114, Jul. 26, 2018, 10 pages.

"Complainant Ultravision Technologies, LLC's List of Claim Terms to be Construed," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, Investigative No. 337-TA-1114, Jul. 26, 2018, 9 pages.

"Respondents' Identification of Disputed Claim Terms and Proposed Construction," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, Investigative No. 337-TA-1114, Aug. 14, 2018, 20 pages.

"Complainant Ultravision Technologies, LLC's Proposed Claim Construction and Supporting Evidence," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, Investigative No. 337-TA-1114, Aug. 14, 2018, 22 pages.

"Respondents' Notice of Prior Art," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, Investigative No. 337-TA-1114, Sep. 10, 2018, 10 pages.

"Exhibit A—Respondents' Notice of Prior Art (Prior Art Publications)," RE: Certain Modular LED Display Panels and components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Sep. 10, 2018, 26 pages.

"Exhibit B—Respondents' Notice of Prior Art (Prior Art Products)," RE: Certain Modular LED Display Panels and Components

“Exhibit 34 of Respondents’ Combined Supplemental Responses to Opening Contention Interrogatories,” RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Sep. 21, 2018, 13 pages.

References Cited

"Exhibit 16 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 51 pages.

"Exhibit 17 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 46 pages.

"Exhibit 18 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 50 pages.

"Exhibit 19 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 26 pages.

"Exhibit 20 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 35 pages.

"Exhibit 21 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 38 pages.

"Exhibit 22 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 50 pages.

"Exhibit 23 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 52 pages.

"Exhibit 24 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 33 pages.

"Exhibit 25 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 32 pages.

"Exhibit 26 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 38 pages.

"Exhibit 27 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 14 pages.

"Exhibit 28 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumberg, L.L.P.*, United States International Trade Commission, ITC Inv. No. 337-TA-1114, Mar. 27, 2018, 27 pages.

"Exhibit 29 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v.*

[illegible]

(56)

References Cited

OTHER PUBLICATIONS

"Exhibit 44 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumbg, L.L.P.*, United States International Trade Commission, IITC Inv. No. 337-TA-1114, Mar. 27, 2018, 50 pages.

"Exhibit 45 of Complaint" RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumbg, L.L.P.*, United States International Trade Commission, IITC Inv. No. 337-TA-1114, Mar. 27, 2018, 36 pages.

"Exhibit 46 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumbg, L.L.P.*, United States International Trade Commission, IITC Inv. No. 337-TA-1114, Mar. 27, 2018, 5 pages.

"Exhibit 47 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumbg, L.L.P.*, United States International Trade Commission, IITC Inv. No. 337-TA-1114, Mar. 27, 2018, 29 pages.

"Exhibit 48 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumbg, L.L.P.*, United States International Trade Commission, IITC Inv. No. 337-TA-1114, Mar. 27, 2018, 4 pages.

"Exhibit 49 of Complaint," RE: Certain Modular LED Display Panels and Components Thereof, *Ultravision Technologies, Inc. v. Adduci, Mastriani and Schaumbg, L.L.P.*, United States International Trade Commission, IITC Inv. No. 337-TA-1114, Mar. 27, 2018, 8 pages.

NEC, "LED Wall Display," Indoor and Outdoor LED Wall Display for Professional-Grade Digital Signage, Empowered Innovation, pp. 1114-ITC0007950-1114-ITC0007951.

"DC-DC Converter Tutorial," Maxim Integrated, Tutorial 2031, Nov. 29, 2001, 14 Pages.

"Magic Cube LED Panel for Indoor/Outdoor," ROE Creative Display, pp. RESP_PRIORART-1114-ITC0002334-RESP_PRIORART-1114-ITC0002340.

"Magic Cube LED Panel for Indoor/Outdoor," Roe Creative Display, pp. RESP_PRIORART-1114-ITC0007759-RESP_PRIORART-1114-ITC0007762.

"4100 Series Digital Billboard," Installation Manual, Daktronics, DD1914625, Sep. 4, 2011, 51 pages.

"4100 Series Digital Billboard," Daktronics Service Manual, DD1922557, Jan. 4, 2012, 37 pages.

"Barco LiveDots Introduces 14mm Transparent LED Display," Light Sound Journal.com, Jun. 7, 2013, 2 pages.

"Building a DC-DC Power Supply that Works," Maxim Integrated, Tutorial 1897, Sep. 22, 2010, 10 pages.

"Element Labs Introduces Revolutionary Cobra TM Technology Platform," LEDs Magazine, Oct. 24, 2008, 3 pages.

"How to Apply the Acrylic Conformal Coating," MG Chemicals, Mar. 29, 2011, pp. 1-3, Ver. 1.

"Avago Technologies Introduces Industry's First Water Resistant High-Brightness Surface Mount Tricolor LEDs," LED, The Global Information Hub for Lighting Technologies, Products, Materials and Tools, Jan. 28, 2010 7 Pages.

"N2 System Modular LED Sign System," Cirrus LED Systems, 2 pages.

Clarendon Press Oxford, "The Compact Oxford English Dictionary," Second Edition, Complete Text Reproduced Micrographically, pp. PRIORART-ITC_001677-PRIORART-ITC_001679.

"DiColor I—Series Pro Touring LED Displays," Mega Systems Inc., 7 pages.

"EVLED Media Screen Series," Elation Professional, 8 Pages.

Hu, Run, et al., "Study on the Optical Properties of Conformal Coating Light-Emitting Diode by monte Carlo Simulation," IEEE Photonics technology Letter, Nov. 15, 2011, vol. 23, No. 22, pp. 1673-1675.

LED Industry News, "Multimedia Farms Selects Barco for Portable LED Display Solutions," LIGHTimes Online-LED Industry News, Aug. 3, 2010, pp. 1114-ITC0009454-1114-ITC0009456.

LED,"New Fully IP-65 Rated Indoor/Outdoor LED Display From PixLED," The Global Information Hub for Lighting Technologies, Products, Materials & Tools, Jan. 25, 2012, pp. 1114-ITC0009457-1114-ITC0009463.

Media Planet, "Digital Place-Based Media," Apr. 2010, No. 3, pp. 1114-ITC0009079-1114-ITC0009084.

"Mirage Semi-Transparent Led Curtain," Magic Digital Lighting, Clay Paky, www.claypaky.it, pp. 1114-ITC0004190-1114-ITC0004197.

NEMA, "Degrees of Protection Provided by Enclosures (IP Code)," Ansi/IEC 60529-2004 (R2011), NEMA Standards Publication, Nov. 3, 2004, pp. ITC-001872-ITC-001928.

Nichia Corporation, "Nichia Releases SMD LED for Outdoor Displays," LIGHTimes Online—LED Industry News, LED Applications, Single and Multi-Chip Packaged LEDs, Jun. 18, 2012, pp. 1114-ITC0009464-1114-ITC0009466.

Barco, Inc., "C11 Lightweight, indoor/outdoor LED video display," company website product technical specification sheet, M00360-R02-0111-DS Jan. 2011, 2 pages, Kortrijk, Belgium.

Barco, Inc., "C8," company website product specification sheet, Dec. 16, 2015, 3 pages.

Cirrus LED Systems, "N2 & X2 System Modular LED Sign System," product specification sheet, E352796, 1 page, San Rafael, United States.

Cirrus LED Systems, "Introducing N2," product brochure, 8 pages, San Rafael, United States.

Lang, Justin, "LED Display Panels," Buyers Guide, Nov. 2013, pp. 47-49, plsn.com.

Barco, Inc., "Barco LiveDots adds new member to its C-series LED display family," company website news press release, Apr. 8, 2013, 3 pages, Kortrijk, Belgium.

Barco, Inc., "PXL System User Manual," Revised Jun. 15, 2010, 196 pages.

Barco, Inc., "Say hello to our brand-new C8 LED display!," company website news press release, Apr. 8, 2013, 3 pages.

Cheng, Ting et al., "Thermal analysis and optimization of multiple LED packaging based on a general analytical solution," International Journal of Thermal Sciences 49 (2010), pp. 196-201, Elsevier.

Sturm, James C., et al., "Thermal Effects and Scaling in Organic Light-Emitting FLat-Panel Displays," Invited Paper, IEEE Journal of Selected Topics in Quantum Electronics, vol. 4, No. 1, Jan./Feb. 1998, pp. 75-82.

Shenzhen Dicolor Optoelectronics Co., Ltd., "U-Smart Series Outdoor Waterproof P10.66 LED Rental Screen," Presentation & introduction, 27 pages.

Hughes, Tom, "Understanding Outdoor LED Electronic Signs," Technology Report, Jul. 20, 2001, 20 pages, 711-6007, Adaptive Micro Systems, Inc.

Waterfire Signs, "Watch What Happens—2008 LED Signs," marketing brochure, Copyright 2007, 20 pages, Time-O-Matic, Danville, Illinois, USA.

Yescozette Magazine, "An Up-Close Look at Yesco Electronics," 3 pages.

PLSN, "Lighting More Than the Torch," Projection, Lights & Staging News, PLSN New Product Guide, p. 22, www.plsn.com, Sep. 2008, Vik. 9.8, pp. 1114-ITC0000408-1114-ITC0000479.

PLSN, "Backfield Scramble at Mile High Stadium," Projection, Lights & Staging News, Road Test: Vectorworks Spotlight 2009, p. 70, www.plsn.com, Oct. 2008, vol. 9.9, pp. 1114-ITC0000304-1114-ITC0000355.

PLSN, "Backfield Scramble at Mile High Stadium," Projection, Lights & Staging News, Road Test: Vectorworks Spotlight 2009, p. 70, www.plsn.com, Oct. 2008, vol. 9.9, pp. 1114-ITC0000356-1114-ITC0000407.

U.S. Appl. No. 61/922,631, pp. 1-75, filed Dec. 31, 2013.

U.S. Appl. No. 62/025,463, pp. 1-184 filed Jul. 16, 2014.

Roe, "Magic Cube," LED Panel for Indoor/Outdoor, Roe Creative Display, 4 pgs. 1114-ITC0007887-1114-ITC0007890.

(56)

References Cited**OTHER PUBLICATIONS**

SJ, "Measure Methods of Light Emitting Diode (LED) Panels," SJ/T 11281-2007, SJ/T 11281-2003, 2007, pp. 1114-ITC0002365-1114-ITC0002385.

SJ, "LED generic Specification for LED Panels," SJ/T 11141-2012, SJ/T 11141-2003, 2012, pp. 1114-ITC0002341-1114-ITC0002364.

SMD Diodes, "Semi-Transparent Led Curtain," Mar.-Apr. 2011, pp. 1114-ITC0004198-1114-ITC00044202.

Sony, "Large LED Display System," LPU-1601 LED Display Panel Unit, LPU-2001 Led Display Panel Unit, LDC-HD01 LED Display Control Processor, 2011, 1114-ITC0004205-1114-ITC0004212.

Sander, "Full Color LED Unit SDM-P20-OSD4S-88," Jun. 7, 2010, Version 1-5, pp. 1114-ITC0009467-1114-ITC0009471.

Barco, "LED Display Systems," LiveDots Product Catalog 2011, http://web.archive.org/web/20120318082027/http://www.barco.com/Downloads/liveDots_LED_Product_Catalog.pdf, Mar. 18, 2012, 28 pages.

Barco, C11 "Lightweight, Indoor/Outdoor LED Video Display," <http://web.archive.org/web/20100526031644/http://www.barco.com:80/en/product/2258/specs>, May 26, 2010, 1 page.

Xavier, Dominic Michael, "Development of a Large Scale Flexible LED Display Matrix for the Screen Industry," Thesis, Faculty of Built Environment and Engineering, Queensland University of Technology, Feb. 2013, 543 pages.

Daktronics, "Daktronics DVX LED Video Display, Waterproof Test," 4 pages.

Daktronics, "Daktronics Outdoor LED Video Waterproof Test with On-Board Fan and Power Supply," 5 pages.

LEDMan, 7 pages.

Watchfire, 18 pages.

"Mirage Semi-Transparent Led Curtain," Magic Digital Lighting, Clay Paky, www.claypaky.it, pp. 1114-ITC0004190-1114-ITC0004197.

Hughes, Tom, "Understanding Outdoor LED Electronic Signs," Technology Report, Jul. 20, 2001, 20 pages, 9711-6007, Adaptive Micro Systems, Inc.

Sander, "Full Color LED Unit SDM-P20-OSD4S-88," Jun. 7, 2010, Version 1-5, pp. 1114-ITC0009467-1114-ITC0009471.

Cirrus LED Systems, Internet Archive Wayback Machine, "The N2 System Setup & Installation Zero Lead Time," Outdoor LED Displays-Cirrus LED Systems, <https://web.archive.org/web/20131228140224/http://cirrusled.com/>, Dec. 28, 2013, 4 Pages.

Cirrus LED Systems, Internet Archive Wayback Machine, "Introducing N2 System Innovative Outdoor LED Display Solution from Cirrus," LED Panels, N2 System-Cirrus LED System, <https://web.archive.org/web/20130921080129/http://www.cirrusled.com/products/n2-system> Sep. 21, 2013, 3 Pages.

Cirrus LED, Internet Archive Wayback Machine, "Nubis System The Next Generation Reinventing the LED Display," LED Outdoor Display Signs, Electronic Digital Message Sign Billboards, LED Displays Manufacturer, <https://web.archive.org/web/20120213172356/http://www.cirrusled.com:80/>, Feb. 13, 2012, 1 Page.

Cirrus N2 LED Displays, Internet Archive Wayback Machine, "LED Panels," Martin Supply Company Inc., <https://web.archive.org/web/20130916051706/http://martin-supply.com/category/nubis>, Sep. 16, 2013, 2 Pages.

Cirrus LED Systems, Internet Archive Wayback Machine, "The Next Generation of LED Display," Outdoor LED Displays-Cirrus LED Systems, <https://web.archive.org/web/20130830230540/http://www.cirrusled.com/>, Aug. 30, 2013, 2 pages.

Cirrus LED Systems, Internet Archive Wayback Machine, "N2-19C," 19mm Pixel Pitch LED Sign-Cirrus LED Systems, <https://web.archive.org/web/20130921075058/http://www.cirrusled.com/products/n2-system/full-color-rgb/19mm-pixel-pitch-led-sign>, Sep. 21, 2013, 2 Pages.

Cirrus Systems, "N2 LED Display System Video," Published on Youtube on Jul. 24, 2013.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 1-59.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 60-107.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 108-160.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 161-222.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 223-280.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 281-340.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 341-405.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 406-468.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 469-536.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 537-595.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 596-666.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 667-723.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 724-787.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 788-852.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 853-936.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 937-998.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 999-1049.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 1050-1106.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 1107-1151.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 1152-1216.

Serial No. EP14875899.8, filed Sep. 18, 2015, pp. 1217-1285.

Serial No. EP14875899.8, filed Sep. 18, 2015, p. 1286.

* cited by examiner




Fig. 1A




Fig. 1B




Fig. 2A




Fig. 2B




Fig. 3A




Fig. 3B




Fig. 4




Fig. 5A




Fig. 5B




Fig. 5C




Fig. 5D




Fig. 5E




Fig. 5F





Fig. 5G






Fig. 6B




Fig. 6C




Fig. 6D




Fig. 6E




Fig. 7A




Fig. 7B








Fig. 7C





**Fig. 8**

**Fig. 9**

1

MODULAR DISPLAY PANELS**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of application Ser. No. 14/550,685, filed on Nov. 21, 2014, which claims the benefit of U.S. Provisional Application No. 62/065,510, filed on Oct. 17, 2014, U.S. Provisional Application No. 62/025,463, filed on Jul. 16, 2014, and U.S. Provisional Application No. 61/922,631, filed on Dec. 31, 2013, which applications are hereby incorporated herein by reference.

TECHNICAL FIELD

The present invention relates generally to displays, and, in particular embodiments, to a system and method for a modular display panels with different pitches.

BACKGROUND

Large displays (e.g., billboards), such as those commonly used for advertising in cities and along roads, generally have one or more pictures and/or text that are to be displayed under various light and weather conditions. As technology has advanced and introduced new lighting devices such as the light emitting diode (LED), such advances have been applied to large displays.

An LED display is a flat panel display, which uses an array of light-emitting diodes. A large display may be made of a single LED display or a panel of smaller LED panels. LED panels may be conventional panels made using discrete LEDs or surface-mounted device (SMD) panels. Most outdoor screens and some indoor screens are built around discrete LEDs, which are also known as individually mounted LEDs. A cluster of red, green, and blue diodes, or alternatively, a tri-color diode, is driven together to form a full-color pixel, usually square in shape. These pixels are spaced evenly apart and are measured from center to center for absolute pixel resolution.

Many LED display manufacturers sell displays with different resolutions. A present disadvantage of these LED displays is that each one must be a different size to accommodate the pitch needed to obtain the desired resolution. In turn, the existing cabinets and mounting structures must be built to be suitable with the size of the displays.

SUMMARY

Example embodiments of the present disclosure provide a system and method for modular display panels with different pitches.

In accordance with an example embodiment of the present invention, a method of manufacturing modular panels is provided. The method includes manufacturing a group of modular display panels, including a first and second modular display panel that have the same size and shape. The first modular display panel includes a first pixel array arranged at a first pitch, and the second modular display panel includes a second pixel array that is arranged at a second pitch that is different than the first pitch. Any two modular display panels in the group are capable of being attached to each other in an integrated display system.

In accordance with another example embodiment of the present invention, a product portfolio is provided. The product portfolio includes a group of modular display panels, including a first and second modular display panel that

2

have the same size and shape. The first modular display panel includes a first pixel array arranged at a first pitch, and the second modular display panel includes a second pixel array that is arranged at a second pitch that is different than the first pitch. Any two modular display panels in the group are capable of being attached to each other in an integrated display system.

In accordance with another example embodiment of the present invention, a modular display system is provided. The display system includes a mechanical support structure and a group of display panels mounted to the mechanical support structure to form an integrated display panel. The mechanical structure is configured to provide mechanical support to the group of display panels, which include a first display panel and a second display panel each having the same size and shape. The first display panel includes a power source, a first pixel array having a first display resolution and a first pitch, and a first controller coupled to the power source. The second display panel includes a second pixel array having a second display resolution and a second pitch.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

FIG. 1, which includes FIGS. 1A-1B, illustrates a modular multi-resolution display system in accordance with embodiments of the present invention;

FIG. 2, which includes FIGS. 2A and 2B, illustrates one embodiment of an LED panel that may be used as one of the LED panels in the modular multi-resolution display system;

FIG. 3, which includes FIGS. 3A and 3B, illustrates a cross-sectional view and receiver circuit diagram of an embodiment LED panel;

FIG. 4 illustrates an embodiment configuration for connecting LED panels to a video data source;

FIG. 5, which includes FIGS. 5A-5G, illustrates embodiment formats for digitally storing video data in video memory buffers of LED panels;

FIG. 6, which includes FIGS. 6A-6E, illustrates embodiment signaling configurations for transmitting data from a data source to LED panels;

FIG. 7, which includes FIGS. 7A-7E, illustrates embodiment panel circuitry for implementing the signaling configurations of FIG. 6; and

FIG. 8 illustrates a method of assembling the modular multi-panel display system in accordance with embodiments of the present invention.

FIG. 9 illustrates a method of configuring and displaying data on the modular multi-panel display system in accordance with embodiments of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Embodiments of the invention provide display panels, each of which provides a completely self-contained building block that is lightweight. These displays are designed to protect against weather, without a heavy cabinet, although it is understood that the present disclosure may be applied to lighting for any type of interior and/or exterior display. The lightweight design allows for easier installation and maintenance, thus lowering total cost of ownership.

In embodiments of the present invention, a number of different resolution display panels are manufactured and

sold but each of these panels is made to have the same physical dimensions. This approach saves cost because standard-size components can be used for the various models of displays that are available. Instead of maintaining inventory of eight different size housings for a product line that includes eight different resolution display panels, a single inventory can be kept, which will lower inventory costs.

Embodiments of the invention provide building block panels that are configurable with future expandability. These displays can offer complete expandability to upgrade in the future without having to replace the entire display. Installation is fast and easy with very little down-time, which allows any electronic message to be presented more quickly.

In some embodiments, the display panels are "hot swappable." By removing one screw in each of the four corners of the panel, servicing the display is fast and easy. Since a highly-trained, highly-paid electrician or technician is not needed to correct a problem, cost benefits can be achieved.

Various embodiments utilize enhanced pixel technology (EPT), which increases image capability. EPT allows image displays in the physical pitch spacing, but also has the ability to display the image in a resolution that is four-times greater.

Embodiments of the present invention will be described in further detail below. A modular multi-panel display system comprising display panels of differing resolutions to a frame will be described using FIG. 1. An embodiment method for initially setting up the modular multi-panel display will be described using FIG. 8. Various embodiments of display panels may be used in the modular multi-panel display, for example, as illustrated below in FIGS. 2 and 3. The panels are then electrically connected to a data source, as described further with respect to FIG. 4. As will be next described using FIG. 5, the transmitted data may be stored in the panels using various signaling formats. The data to be stored is then transmitted to the panels from a data source in accordance with various signaling configurations, as will be described in FIG. 6. Using FIG. 9, an embodiment method for configuring and displaying data on the modular multi-panel display will be described. Various electronic components of individual panels may be interconnected to support the signaling configurations of the modular display as illustrated in FIG. 7.

Referring now to FIG. 1, a modular multi-resolution display system in accordance with embodiments of the present invention is illustrated. FIG. 1A is a front view of a display system that includes display panels of different resolutions. FIG. 1B is a rear view of the display system that illustrates the frame for mounting the display panels.

Referring to FIG. 1A, in this particular example, three different resolution display panels are used, but it is understood that any configuration could be used. For example, Table 1 provides an example of the pitches used for a product line that includes eight different resolution display panels. A single system could include panels with each of the eight pitches shown in Table 1. The software driving the display would provide image data to each panel in a manner appropriate for that panel. Each of the panels in Table 1 is one foot by two feet in dimensions, as an example. The pitch and type of LED used is provided in the table. The pitch is the distance between any two pixels in the panel, and the type of LED may be, for example, a Surface Mount Device (SMD) or a Dual Inline Package (DIP).

TABLE 1

6.35 mm SMD Physical
7.62 mm SMD Physical

TABLE 1-continued

9.525 mm SMD Physical
12.7 mm SMD Physical
15.24 mm DIP Physical
19.05 mm DIP Virtual
25.4 mm DIP Virtual
30.48 mm DIP Virtual

Referring to FIG. 1A, this particular example shows a display 100 with an arbitrarily chosen 25 LED display panels 150 comprising three different resolution panels. In the present embodiment, the LED display panels 150 use LEDs for illumination, but it is understood that other light sources may be used in other embodiments. One of the advantages of the building block like configuration of the display panels is that any number of panels can be used to create integrated display systems of many sizes and shapes. For example, a display 100 could include 336 panels that are each 1'x2' in dimension to create a 14'x48' display. In such a display, because each panel is lighter than typical panels, the entire display could be built to weigh only 5500 pounds. This compares favorably to commercially available displays of the size, which generally weigh from 10,000 to 12,000 pounds. In another embodiment, a display 100 could include 320 LED display panels 150 arranged in ten rows and thirty-two columns so that the integrated display panel 100 has a display surface that is approximately fifty feet and four inches wide and fifteen feet and eight and three-quarters inches high. In other embodiments, displays with an arbitrary number of panels can be used.

The LED display panels 150 in the embodiment of FIG. 1A typically operate together to form a single image, although multiple images may be simultaneously presented by the display. Two or more LED display panels 150 can be coupled for power and/or data purposes, with an LED display panel 150 receiving power and/or data from a central source or another panel and passing through at least some of the power and/or data to one or more other panels. This further improves the modular aspect of the display 100, as a single LED display panel 150 can be easily connected to the display 100 when being installed and easily disconnected when being removed by decoupling the power and data connections from neighboring panels.

The power and data connections for the LED display panels 150 may be configured using one or more layouts, such as a ring, mesh, star, bus, tree, line, or fully-connected layout, or a combination thereof. In some embodiments the LED display panels 150 may be in a single network, while in other embodiments the LED display panels 150 may be divided into multiple networks. Power and data may be distributed using identical or different layouts. For example, power may be distributed in a line layout, while data may use a combination of line and star layouts.

In the embodiment of FIG. 1A, the bottom row has a first resolution such as, for example, a low resolution that is used for captions or other text. The top and corners use a second resolution, for example, a medium resolution to be used for background portions of the image. The center of the display, on the other hand, may have a higher resolution. This region would be capable of showing a more detailed image. Such a configuration is possible because the housings of all of the display panels are the same size and configuration regardless of the resolution. This allows a user to tailor the number of each panel type to gain the best tradeoff between cost and image quality.

5

Referring to FIGS. 1A and 1B, it is also noted that the uniform size and configuration of the panels enables the panels to be interchanged as needed. More specifically, as panels have an identical footprint in terms of height H, width W, and depth D1, their position on the frame 110 of FIG. 1B does not matter from a size standpoint, but only from a functionality standpoint. Accordingly, the design of the display 100 may then focus on issues such as the required resolution for a particular position and/or other issues such as weight and cost without the need to be concerned with how a particular panel will physically fit into a position on the frame.

Referring to FIG. 1B, the LED display panels 150 are individually attached to a frame 110, which enables each LED display panel to be installed or removed from the frame no without affecting the other panels. Each LED display panel 150 is a self-contained unit that couples directly to the frame 110. By “directly,” it is understood that another component or components may be positioned between the LED display panel 150 and the frame 110, but the panel is not placed inside a cabinet that is coupled to the frame 110. For example, in this embodiment attachment plates 145 are coupled to the LED display panels 150 and to the frame 110. Other embodiments use an alignment plate, which is a plate that couples to the housing of a panel and to the frame 110 and also interlocks with other alignment plates of adjacent panels, to aid in aligning the panel with adjacent panels. Further the panel may be coupled to the frame 110 without the use of any attachment plates or alignment plates. Whether the panel is coupled to the frame 110, attachment plate 145, and/or the alignment plate, any of these coupling approaches would be “direct” according to the present disclosure.

The attachment plate 145 (or an alignment plate) could be a solid material such as a metal plate or could be a conforming material such as a rubber material embedded with metal particles. In either case, it is desirable that the plate be thermally conductive. One or more attachment features 149 may be used to connect the attachment plate 145 to the LED display panel 150. In the embodiment illustrated in FIGS. 1B and 1C, the attachment plate 145 is a corner plate. Each corner plate is mechanically connected to corners of four of the LED display panels 150 to secure the LED display panels 150 to the horizontal beams 120A and vertical beams 120B of the frame 110.

The frame 110 comprises a plurality of horizontal beams 120A and vertical beams 120B forming the mechanical structure. The frame 110 may be relatively light in weight compared to frames needed to support cabinet mounted LED assemblies. In one embodiment, both horizontal beams 120A and vertical beams 120B may be used to support the LED display panels 150. In another embodiment, horizontal beams 120A but not the vertical beams 120B may be used to support the LED display panels 150. In a third embodiment, vertical beams 120B but not the horizontal beams 120A may be used to support the LED display panels 150.

The frame 110 may include support structures for the electrical cables, data cables, electrical power box powering the LED displays panels 150 and receiver unit 140 controlling power, data, and communication to the LED displays panels. However, the frame 110 does not include any additional enclosures to protect the LED panels, data, power cables from the environment. Rather, the frame 110 is exposed to the elements and further exposes the LED display panels 150 to the environment. The frame 110 also does not include air conditioning, fans, heating units to maintain the temperature of the LED display panels 150.

6

Rather, the LED display panels 150 are hermetically sealed themselves and are designed to be exposed to the outside ambient. Further, in various embodiments, there are not additional cabinets that are attached to the frame 110 or used for housing the LED display panels 150. Accordingly, in various embodiments, the multi-panel modular display, LED display panel 150 is designed to be only passively cooled.

FIGS. 2A-2B illustrate one embodiment of a panel 150A that may be used as one of the LED display panels 150 of FIGS. 1A-1C. FIG. 2A illustrates a front view of the embodiment panel 150A with LEDs aligned in a 16x32 configuration. FIG. 2B illustrates a back view of the panel of this embodiment panel 150A.

Referring to FIG. 2A, an embodiment panel 150A includes a substrate 202 that forms a front surface of the panel 150A. The substrate 202 in the present embodiment is rectangular in shape, with a top edge 204, a bottom edge 206, a right edge 208, and a left edge 210. A substrate surface 212 includes “pixels” 214 that are formed by one or more LEDs 216 on or within the substrate 202. The substrate 202 may form the front surface of the panel 150A, but may not be the outer surface in some embodiments. For example, a transparent or translucent material or coating may overlay the substrate 202 and the LEDs 216, thereby being positioned between the substrate 202/LEDs 216 and the environment. In the present example, each pixel 214 includes four LEDs 216 arranged in a pattern (e.g., a square). For example, the four LEDs 216 that form a pixel 214 may include a red LED, a green LED, a blue LED, and one other LED (e.g., a white LED, a second red LED, etc.). In some embodiments, the other LED may be a sensor. It is understood that more or fewer LEDs 216 may be used to form a single pixel 214, and the use of four LEDs 216 and their relative positioning as a square is for purposes of illustration only. In an embodiment, a single tri-color LED having red, green, and blue inputs forms a single pixel.

Referring to FIG. 2B, the back of panel 150A is illustrated. In the present example, the panel 150A includes coupling points 242 and 244. The panel 150A also has a number of connection points that include a “power in” point 222, a first data point 224, a second data point 226, and a “power out” point 230. One embodiment of the invention provides for an integrated data and power cable, which reduces the number of ports. The power in point 222 enables the panel 150A to receive power from a power source, which may be another panel. In an embodiment, the first data point 224 is a “data in” point that enables the panel to receive data from a data source, which may be another panel, and the second data point 226 is a “data out” point that enables the panel 150A to send data to another panel. In an embodiment where the first data point 224 and second data point 226 are bi-directional, they may each enable the panel 150A to send data to one or more other panels and to receive data from those panels. In other embodiments, the data points can be directional connection points. The power out point 230 enables the panel 150A to send power to another panel.

The connection points may be provided in various ways. For example, in one embodiment, the connection points may be jacks configured to receive corresponding plugs. In another embodiment, a cable may extend from the back panel with a connector (e.g., a jack or plug) affixed to the external end of the cable to provide an interface for another connector. It is understood that the connection points may be positioned and organized in many different ways.

Inside the panel, the power in point 222 and power out point 230 may be coupled to circuitry 236 as well as to the power supply 238. In such embodiments, the circuitry 236

may aid in regulating the reception and transmission of power. In other embodiments, the power in point 222 and power out point 230 may be coupled only to the power supply 238 with a pass through power connection allowing some of the received power to be passed from the power in point 222 to the power out point 230. In some embodiments, the circuitry 236 may identify data used for the panel 150A and also send all data on to other coupled panels via the second data point 226. In such embodiments, the other panels would then identify the information relevant to that particular panel from the data. In other embodiments, the circuitry 236 may remove the data needed for the panel 150A and selectively send data on to other coupled panels via the second data point 226. For example, the circuitry 236 may send only data corresponding to a particular panel to that panel rather than sending all data and letting the panel identify the corresponding data. In some embodiments, the circuitry 236 may include a network receiver card for receiving data over a wide area network, local area network (LAN), or wireless LAN (WLAN).

FIG. 3A illustrates a cross-sectional view of a second embodiment of an LED display panel 150. FIG. 3B illustrates an embodiment receiver circuit 325 of the LED display panel 150.

Referring to FIG. 3A, the casing 350 of the modular display panel 150 has openings through which a first cable 360 and a second cable 365 may be attached. The LED display panels 150 are electrically connected together for data and for power using the first cable 360 and second cable 365. In some embodiments, the first cable 360 is an input cable and the second cable 365 is an output cable. Each modular LED display panel 150 is capable of receiving input using an integrated data and power cable from a preceding modular LED display panel and providing an output using another integrated data and power cable to a succeeding modular LED display panel. Each cable ends with an endpoint device or connector, which is a socket or alternatively a plug.

The modular LED display panel 150 also comprises a plurality of LEDs 310 mounted on one or more printed circuit boards (PCBs) 320, which are housed within a hermetically sealed enclosure or casing. A framework of louvers 330 is attached to the PCB 320 using an adhesive 340, which prevents moisture from reaching the PCB. The LEDs 310 may be directly exposed to the ambient in the direction of light emission or may be covered by a transparent or translucent material or coating. A heat sink 380 is attached between the PCB 320 and the casing 350 and contacts both the PCB 320 and the casing 350 to maximize heat extraction.

A receiver circuit 325 is mounted on the PCB 320. The receiver circuit 325 may be a single chip in one embodiment. Alternatively, multiple components may be mounted on the PCB 320. The receiver circuit 325 may be configured to process the received media and control the operation of the individual LEDs 310. For example, when a single tri-color LED is used to form each pixel, the receiver circuit 325 determines the color and brightness of the LED 310 to be displayed at each pixel by, for example, adjusting the current or pulse width of a plurality of signals applied to the red, green, and blue input pins of the LED 310. When multiple single-color LEDs are used to form each pixel, the receiver circuit 325 determines the brightness of each LED 310 within each pixel by, for example, adjusting the current or pulse width of a single signal applied to the LED 310. A power supply unit 370 may be mounted over the casing 350 for powering the LEDs 310.

Referring to FIG. 3B, a data and power signal received at first cable 360 is processed at an interface circuit 351 of receiver circuit 325. The incoming power is provided to a power supply unit 370.

Another output from the incoming power is provided to second cable 365. This provides redundancy so that even if a component in the LED display panel 150 is not working, the output power is not disturbed. Similarly, second cable 365 includes all the data being received in first cable 360.

In this embodiment, the interface circuit 351 provides the received data to the graphics processor 357 through a data bus 354. In some embodiments, the interface circuit 351 provides only the data segments intended for the LED display panel 150. In other embodiments, the interface circuit 351 provides all incoming data to the graphics processor 357. For example, the graphics processor 357 may perform any necessary decoding or (when signaling between panels is analog) analog-to-digital conversion of the received media. In other embodiments, the interface circuit 351 interfaces directly with the LED controller 359 without use of a graphics processor 357. In the embodiment of FIG. 3B, the graphics processor 357, LED controller 359, or interface circuit 351 may use the buffer video memory 355 as needed to store video segments during processing. In some embodiments, the buffer video memory 355 may be a component of the LED controller 359. The buffer video memory 355 may also be used to digitally store video segments temporarily until the receiver circuit 325 collects enough data for simultaneous display by the LEDs 310. This collection of data may be a video frame for simultaneous display by all of the LEDs of the display panel, or it may be a smaller portion of data for display by a subset of the LEDs in accordance with, for example, a scanning pattern. The buffer video memory 355 may also be used to temporarily store video segments destined for other display panels.

The LED controller 359, which may include an address decoder (e.g., a demultiplexer), receives the media to be displayed and identifies individual LEDs in the LEDs 310 that need to be controlled. The LED controller 359 may determine an individual LED's color, brightness, refresh time, and other parameters associated to generate the display. For example, at each pixel location in the display, the color of the pixel may be selected by powering one or more combination of red, blue, green, and white LEDs. The LED controller 359 may include control circuitry such as a row selector and column selector for determining LED parameters as an example. In one embodiment, the LED controller 359 may provide these LED parameters to the current driver 353, which acts as either a current source or a current sink to select the appropriate current for the particular LED. In some embodiments, the current driver 353 acts as a current source or sink to provide a constant current with a constant pulse width to the LEDs 310. In other embodiments, the current driver 353 varies the duty cycle of a constant current to pulse width modulate the brightness of the LEDs 310. The current driver 353 may either be a component of the LED controller 359 or may be located outside the LED controller 359, such as, for example, being located inside the power supply unit 370.

The power supply unit 370 may include, for example, a power converter for converting ac to dc, which is supplied to the LEDs 310. Alternatively, the power supply unit 370 may include a down converter that down converts the voltage suitable for driving the LEDs 310. In one embodiment, the power supply unit includes a scan controller that interfaces directly with the LEDs 310. For example, the current driver 353 may provide a constant current to the

LEDs **310** while a scan controller of the power supply unit **370** controls the select line needed to turn ON or OFF a particular LED. In some embodiments, a scan controller of the power supply unit **370** is implemented as an array of switches or transistors that switches incoming power to a selected row or column of LEDs **310**. In other embodiments, the scan controller switches the output of the LED controller **359** to a selected row or column. The scan controller switches the LED controller output or power in accordance with, for example, an LED address, a row address, a column address, a pre-configured scanning pattern for scan groups of linked LEDs that should be activated simultaneously, or a scan select signal that specifies which scan group should be activated.

FIG. **4** illustrates an embodiment configuration for connecting LED display panels **150** to a video data source. Referring to FIG. **4**, the LED display panels **150** are arranged in an array of rows and columns. Each LED display panel **150** of each row is electrically connected to an adjacent LED display panel **150** within that row. Each LED display panel is also electrically connected to a data source and to a power source. In various embodiments, a receiver unit **140** is mounted to the mechanical support structure or frame **110**. The receiver unit **140** is configured to receive data from a controller **400** and to provide power, data, and communication to the LED display panels **150** through integrated power and data cables **460**. The first cable **360** and the second cable **365** in FIG. **3A** are specific applications of the integrated power and data cables **460** illustrated in FIG. **4**.

The integrated power and data cable **460** includes wires for carrying data/control information and wires for carrying power. The data/control wires may include twisted pair. The length of the data and power wires may be controlled to provide signal propagation within each LED display panel within a specific time. The data/control wires may be configured to transport data at a high bit rate, e.g., at least 1 Mbit/s, and may be 100-1000 Mbit/s. To minimize noise, the cable as a whole may be shielded or the data/control wires or twisted pairs of data/control wires may be shielded separately. In some embodiments, the power connections to the power wires can be configured so that power is run across all of a row (or any other group of panels). In this manner, if the power supply of any one of the panels fails, the other panels will continue to operate. In some embodiments, a first LED display panel in each row may be electrically coupled to the receiver unit **140**. The other LED display panels in each row may be daisy-chain coupled to an adjacent LED display panel.

A controller **400** may be connected to the receiver unit through a data network **440** that is a wired or wireless network. Data to be displayed at the multi-panel display system may be first received from a computer **450**, which may be a media server, at a controller **400**. The controller **400**, which may also be part of the media server, may transmit the data to be displayed to one or more receiver units **140**. A very large display may include more than one receiver units **140**. The receiver units **140** receive the data to be displayed from the controller **400**, and distribute it across to the multiple display panels.

The controller **400** may be remotely located or located on-site in various embodiments. The controller **400** is configured to provide data to display to the receiver unit **140**. The output of the controller **400** may be coupled through a network cable or WLAN to the receiver unit **140**. Alternatively, the output of the controller **400** may be coupled to an

ingress router of the internet and the receiver unit **140** may be coupled to an egress router if the controller **400** is located remotely.

The receiver unit **140** connects the LED display panels with data to be displayed on the integrated display and with power to power each of the LED display panels **150**. In one or more embodiments, the receiver unit **140** creates multiple outputs, where each output is configured for each panel under its control. Alternatively, the LED display panels **150** may be configured to decode the received data and select and display only the appropriate data intended to be displayed by that particular LED display panel **150**. The receiver unit **140** may transmit the media or data to be displayed in a suitable encoded format.

In one or more embodiments, the receiver unit **140** transmits analog video. For example, in one embodiment, composite video may be outputted by the receiver unit **140**. In a second embodiment, luminance-blue-difference-red-difference ($YC_B C_R$) analog component video may be outputted by the receiver unit **140**. In a third embodiment, luminance-chrominance (YC) encoded analog video may be outputted by the receiver unit **140**. In a fourth embodiment, red-green-blue (RGB) analog video may be outputted by the receiver unit **140**. In other embodiments, the output video of receiver unit **140** comprises video to be displayed encoded in a digital video format (e.g., 4:4:4 $YC_B C_R$, 4:2:2 $YC_B C_R$, 4:4:4 RGB, 4:2:2 RGB, etc.) by each of the display panels under the receiver unit **140**.

FIG. **5**, which includes FIGS. **5A-5G**, illustrates embodiment formats for digitally storing video data in video memory buffers of LED panels after the data has been transmitted by the receiver unit. FIG. **5A** illustrates digital storage of RGB component data stored in three data sets in accordance with a 4:4:4 sampling ratio after the data has, for example, been transmitted across three channels or has been serially multiplexed on a single transmission channel from the receiver unit. FIG. **5B** illustrates digital storage of RGB component data stored in four data sets in accordance with a 4:2:2 sampling ratio. FIG. **5C** illustrates digital storage of $YC_B C_R$ component data in three data sets in accordance with a 4:4:4 sampling ratio. FIG. **5D** illustrates digital storage of $YC_B C_R$ component data in three data sets in accordance with a 4:2:2 sampling ratio. FIG. **5E** illustrates digital storage of YC data in three data sets. FIG. **5F** illustrates digital storage of RGB data that is divided into three data sets in accordance with a pixel-by-pixel distribution.

FIG. **5A** illustrates an embodiment frame of video data distributed in three data sets in accordance with a 4:4:4 RGB component 24-bit format. In other embodiments, different numbers of data sets and memory locations could be used. This exemplary frame contains 1152 pixels organized into 24 horizontal lines or rows of 48 pixels each, which corresponds to a 1'x2' display panel with a pitch of 12.7 mm between pixels. Other frame sizes would be used for other embodiment panels having differing numbers of pixels. In this embodiment, data set A contains pixel components of 8 bits representing the blue component of each pixel. 8 bits is the word size of this embodiment. In other embodiments, different word sizes may be used. As an example, B_o is 8 bits of data storing the blue pixel value of the first pixel in the first line. A first group of 48 pixel blue components of 8 bits each precede a first new row divider. In an embodiment, this new row divider is a horizontal synchronization (HSYNC) symbol included in the data stream to demarcate the end of a horizontal line of data to be displayed. In other embodiments, the new row divider of FIG. **5A** indicates that preceding pixels are stored in a different portion of memory

11

than those pixels that follow the new row divider. This division into different areas of memory may be accomplished by, for example, sizing each memory partition to hold only the data necessary for a single row of pixels. Alternatively, a new row could be indicated by a control signal provided by the receiver unit to the panel to demarcate the end of a horizontal line of data to be displayed. The stored data contains each new row of data in subsequent groups of 48 blue components up to the end of the frame, which contains a total of 1152 8-bit blue components corresponding to the 1152 pixels in the frame. Similarly, data set B is divided into a new row after every 48 8-bit red pixel components in a set of 1152 red components, and data set C is a third digital data set is divided into a new row after every 48 8-bit green pixel components in a set of 1152 green components. In an embodiment, current driver 353 of FIG. 3B may use these RGB components in data sets A, B, and C to drive LEDs in an embodiment display panel having a 12.7 millimeter pitch.

FIG. 5B illustrates an embodiment frame of video data distributed over four digital memory locations of the buffer video memory 355 of FIG. 3B in accordance with a 4:2:2 RGB component 32-bit format. The difference between this embodiment and the embodiment of FIG. 5A is that 16 bits representing the red component of each pixel are included in the stored data, with 8 bits being provided by the R data in data set C and an additional 8 bits provided by the R' data in data set D.

FIG. 5C illustrates an embodiment frame of video data distributed over three digital memory locations of buffer video memory 355 in accordance with a 4:4:4 $Y_C B_C R_C$ component 24-bit format. The difference between this embodiment and the embodiment of FIG. 5A is that data set A contains blue difference data in 8-bit pixel components, data set B contains luminance data in 8-bit pixel components, and data set C contains red difference data in 8-bit pixel components.

FIG. 5D illustrates an embodiment frame of video data distributed over three digital memory locations of buffer video memory 355 in accordance with a 4:2:2 $Y_C B_C R_C$ component 24-bit format. The difference between this embodiment and the embodiment of FIG. 5C is that data set A contains 8-bit pixel components comprised of 4 bits representing the luminance component of each pixel and 4 bits representing either the blue-difference or red-difference component of each alternating pixel.

FIG. 5E illustrates an embodiment frame of equally sampled 24-bit YC video data distributed over three digital memory locations of buffer video memory 355. The difference between this embodiment and the embodiment of FIG. 5D is that blue difference and red difference data are replaced by 12-bit chrominance data, four bits of which are stored in each 8-bit pixel component of data set A, and eight bits of which are stored in each 8-bit pixel component of data set C.

FIG. 5F illustrates an embodiment frame of 4:4:4 24-bit RGB video data distributed over three digital memory locations of buffer video memory 355 in accordance with a pixel-by-pixel distribution. The difference between this embodiment and the embodiment of FIG. 5A is that the number of pixels in a video frame is divided between the three data sets so that, for example, all the component data for a given pixel could be stored in the same form in which it is transmitted over the same serial data channel. In this embodiment, each data set contains all components for a third of the pixels in a video frame, with the pixels assigned to each data set alternating with each pixel.

12

FIG. 5G illustrates an embodiment frame of 4:4:4 24-bit RGB data distributed over three data channels in accordance with a scanning pattern. The difference between this embodiment and the embodiment of FIG. 5A is that each data set is divided among two scan groups. During a first scanning period, the data in the first scan group of data sets A-C is digitally stored. During a second scanning period, the data in the second scan group of data sets A-C is digitally stored, overwriting the data in the first scan group. Storage of data continues in alternating scanning periods as each video frame is received and digitally stored in buffer video memory 355.

FIG. 6, which includes FIGS. 6A-6E, illustrates embodiment signaling configurations for transmitting data from the receiver unit to LED panels of different resolutions. FIG. 6A illustrates transmitting digital video data using a data-shifting daisy-chain configuration. FIG. 6B illustrates transmitting identifiably assigned digital video data using a pre-configured daisy-chain configuration. FIG. 6C illustrates transmitting identifiably assigned analog video data using a pre-configured daisy-chain configuration. FIG. 6D illustrates transmitting identifiably assigned digital video data in a dynamically adaptable daisy-chain configuration. FIG. 6E illustrates transmitting multiplexed digital video data using a data-shifting daisy-chain configuration.

FIG. 6A illustrates an embodiment transmitting serial digital video data to panels of different resolutions using a data-shifting daisy-chain configuration. The receiver unit 140 is pre-configured to know information about panels 150B-C, including the panels' resolutions, and pixel counts/local video frame sizes. A global video frame for collective display across embodiment panels 150B and 150C is divided into two local video frames. A first local video frame is divided into data sets 51E, 52E, and 53E that are stored in panel 150B. A variable number of data transmission channels M may be used. In this embodiment, when 3 data channels are used, panel 150B has 1,152 pixels organized into 24 horizontal lines of 48 pixels each, which could be implemented in, for example, a 1'x2' display panel with a pitch of 12.7 mm between pixels. A second local video frame is divided into data sets 51A-51D, 52A-52D, and 53A-53D that are stored in panel 150C. In this embodiment, when 3 data channels are used, panel 150C has 4608 pixels organized into 48 horizontal lines of 96 pixels each, which could be implemented in a 1'x2' display panel with a pitch of 6.35 mm between pixels. Different panel sizes and resolutions may be used in other embodiments.

In embodiments of the present invention, any of the formats of FIGS. 5A-5G may be used for the data sets 51A-E, 52A-E, and 53A-E that are respectively divided for transmission into M data channels and optionally into multiple scan groups and are then buffered into video memory in panels 150B and 150C. In other embodiments, other digital data storage formats may be used. In FIG. 6A, the video memories of panels 150B and 150C are implemented as shift registers 355A. When three data channels are used to transmit, for example, 4:4:4 RGB component video, blue pixel components could be transmitted in the first data channel, green components could be transmitted in the second data channel, and red components could be transmitted in the third data channel, so that buffered data sets 51A-51D collectively could represent the blue component of a 4,608 pixel local video frame, buffered data set 51E could represent the blue component of an 1152 pixel local video frame, and buffered data sets 52A-52E and 53A-53E could respectively represent the green and red components of these two frames. When more than three data channels are present,

13

the data could be divided into smaller bit amounts in each channel than the 4 or 8-bit groups depicted in the data sets of FIGS. 5A-5G. In other embodiments, any number of data channels could divide up the number of pixels in a video frame in accordance with the data set formatting depicted in FIG. 5F-5G.

In FIG. 6A, data set 51A is sent serially across the first data channel between the receiver unit 140 and panel 150B in accordance with a bit clock, until a first location in one of the shift registers 355A of panel 150B is full. Then data set 51B is sent serially across the first data channel between receiver unit 140 and panel 150B, and each bit of data set 51A is shifted into the shift registers 355A of panel 150C as each bit of data set 51B is received by panel 150B. Transmission of data sets 51C-51E continues until data sets 51A-51D are completely shifted into the shift registers 355A of panel 150C and data set 51E is stored in the shift registers 355A of 150B. In the same way, data sets 52A-52E and 53A-53E are sent serially by receiver unit 140 to panel 150B, with data sets 52A-52D and 53A-53D then shifted into the shift registers 355A of panel 150C so that only the local video frame for panel 150B comprising data sets 51E, 52E, and 53E continues to be stored in the shift registers in panel 150B. At this time, the local video frame for panel 150C comprising data sets 51A-51D, 52A-52D, and 53A-53D is stored in panel 150C.

A frame clock, latch signal, or other control signal provided by the receiver unit 140 may signal panels 150B and 150C to display the local video frames stored in their buffer memories. In an embodiment, HSYNC data is transmitted serially with pixel data. In other embodiments, new rows in the data are indicated by an HSYNC signal, latch signal, or other control signal provided by the receiver unit 140. In an embodiment, multi-pin connections can be used to support signaling in the channels between the receiver unit 140 and the panels 150B and 150C. An exemplary 16-pin connection includes a latch pin, a clock pin, five address pins, an enable pin, three data pins, a signaling voltage pin, a signaling ground pin, a power supply pin, a power return pin, and a power ground pin. More or fewer pins may be provided for any of the foregoing pin types, and not all pin types may be provided in a multi-pin connection.

FIG. 6B illustrates transmitting identifiably assigned digital video data using a pre-configured daisy-chain configuration. The difference between this embodiment and the embodiment of FIG. 6A is that video data is sent in segments/packets over one or more data channels using a multiple access technique such as packet addressing or time division multiplexing such that the destination panel assigned to each segment is identifiable. In an embodiment, before receiver unit 140 begins sending data, it initializes panels 150B and 150C using a control channel by providing the interface circuits 351 of both panels with a unique address, time slot number (TSN), or other identifying information, which each interface circuit stores in a memory 500. A video frame destined for one of the panels is divided into one or more video segments. In an embodiment, a destination address is inserted by receiver unit 140 into the data stream as a header to the video segment. In other embodiments, a video segment intended for one of panels 150B and 150C is inserted by receiver unit 140 into a time slot in the data stream in accordance with a TSN assigned to the destination panel. In other embodiments, the receiver unit 140 indicates using a control/address signal on the control channel to indicate which of panels 150B or 150C should be actively receiving data. Interface circuit 351 in panel 150B determines, in accordance with the control/address signal or

14

the address or TSN stored in its memory 500, whether data being received is intended for panel 150B, or whether it should be forwarded to the interface circuit of panel 150C.

In an embodiment, different panels 150B and 150C may have a different refresh rate. For example, panel 150B may have a slower refresh rate than panel 150C. The identifying information provided to panel 150B can notify it that inbound data from the receiver unit 140 is not intended to refresh panel 150B when panel 150B is not in its refresh period, in which case the inbound data will bypass the shift registers 355A of panel 150B. This bypassed data will then be delivered to panel 150C so that panel 150C may refresh its data in accordance with the higher refresh rate. For example, this may be used when panel 150B is intended to display text while panel 150C is intended to display high frame rate video such as sports or other action. By using multiple refresh rates, lower data rates may be used rather than having to send data to all panels at the refresh rate of the highest frame rate panel.

FIG. 6C illustrates transmitting assigned analog video data using a pre-configured daisy-chain configuration. The difference between this embodiment and the embodiment of FIG. 6B is that video data is sent in an analog form such as RGB component video, $YC_B C_R$ component video, composite video, S-video, etc., in assigned time slots such that the destination display panel can be determined by interface circuits 351 in accordance with the assigned TSN for each panel. Analog data arriving at one of the graphics processors 357 is converted to digital data that is stored in buffer video memory 355 in accordance with, for example, one of the digital storage formats of FIGS. 5A-5G.

FIG. 6D illustrates transmitting digital video data using a dynamically adaptable daisy-chain configuration. The difference between this embodiment and the embodiment of FIG. 6B is that panels 150B and 150C can be dynamically added to the configuration using a hot plug detect channel and a bi-directional control channel. When a panel 150C is added to the configuration, it sends a signal on the hot plug detect channel to notify receiver unit 140 of its existence. An initialization sequence is then performed over the control channel. Panel 150C sends the receiver unit 140 its resolution information. In embodiments of the invention, panel 150C or panel 150B determines a unique address for panel 150C in accordance with the address of existing panel 150B, and then sends this address to receiver unit 140 over the control channel. In other embodiments, receiver unit 140 assigns a unique address to panel 150C over the control channel, which the interface circuit 351 stores in memory 500. Interface circuit 351 in panel 150B determines in accordance with the stored address whether data being received is intended for panel 150B, or whether it should be forwarded to the interface circuit of panel 150C.

FIG. 6E illustrates transmitting row-multiplexed digital video data using a data-shifting daisy-chain configuration. The differences between this embodiment and the embodiment of FIG. 6A are that three data channels are used, another panel 150D is included in a daisy chain after panel 150C, data is divided by rows among different shift registers 355A, and a scanning pattern is used to reduce memory requirements of the panels. In this embodiment, the receiver unit 140 is pre-configured to know information about panels 150B-D, including the panels' resolutions, pixel counts/local video frame sizes, number of scan groups, refresh rates, and number of rows and columns of shift registers 355A of each scan group. A global video frame for collective display across embodiment panels 150B-150D is divided into three local video frames, which are each in turn divided

15

into 24 scan groups. A first scan group of a first local video frame is divided into data sets **51F**, **52F**, and **53F** that is stored in panel **150B**, which has 1,152 pixels organized into 24 horizontal lines of 48 pixels each and which could be implemented in, for example, a 1'x2' display panel with a pitch of 12.7 mm between pixels. A first scan group of a second local video frame is divided into data sets **51B-51E**, **52B-52E**, and **53B-53E** that are stored in panel **150C**, which has 4608 pixels organized into 48 horizontal lines of 96 pixels each. Panel **150C** could be implemented in, for example, a 1'x2' display panel with a pitch of 6.35 mm between pixels. A first scan group of a third local video frame is divided into data sets **51A**, **52A**, and **53A** that is stored in panel **150D**, which has the same resolution and number of pixels as panel **150B**. Different panel sizes and resolutions may be used in other embodiments.

In the embodiment of FIG. 6E, data set **51A** is sent serially across the first data channel between the receiver unit **140** and panel **150B** in accordance with a bit clock, until a first location in one of the shift registers **355A** of panel **150B** is full. Then data set **51B** is sent serially across the first data channel between the receiver unit **140** and panel **150B**, forcing data set **51A** to pass through the demultiplexer **502** of panel **150C** and into an active shift register in panel **150C**. In accordance with either a control signal (such as an address signal) or with the position in the data stream of the data set, the active shift register is either the combined first (topmost) shift register of panel **150C**—which is formed from two daisy-chained 48-position shift registers and corresponds to the Nth row of pixels in the panel's pixel array, or the combined second shift register—which corresponds to pixels on row N+24, with N being the active scanning period. Each combined shift register in panel **150C** contains 96 positions that correspond to the 96 columns in the pixel array. Each scan group contains two rows, such as the first 96-position shift register and the second 96-position shift register. When the active shift register of panel **150C** is full and additional data arrives at the active shift register, data set **51A** is then shifted into the first shift register of panel **150D**, passing through a demultiplexer included in the panel, for example, to support future changes in scanning pattern and shift register components. In this example, in accordance with the control signal the active shift register of panel **150C** is the first shift register when data sets **51B-51E** are shifted into panel **150C**, and the active shift register is the second shift register when data sets **51D-51E** are shifted into panel **150C**.

Referring again to FIG. 6E, transmission of data sets **51C-51F** continues until data set **51A** is completely shifted into panel **150D**, data sets **51B-51E** are completely shifted into the shift registers **355A** of panel **150C** and data set **51F** is stored in the first shift register of **150B**. In the same way, data sets **52A** and **53A** are sent serially by receiver unit **140** to panel **150D**, data sets **52B-52E** and **53B-53E** are sent to panel **150C**, and data sets **52F** and **53F** are sent by the receiver unit **140** to panel **150B**. In an embodiment, a scanning clock, latch signal, pre-configured, or other control signal provided by the receiver unit **140** may then signal panels **150B-150D** to display the scanning frames stored in their video memories. In other embodiments, the scanning frames are displayed in accordance with a timer.

Referring again to FIG. 6E, during scanning period N, panel **150C** illuminates the first and 25th row of pixels in its pixel array and panels **150B** and **150D** illuminate their first row of pixels in accordance with the data stored in video memory. During 23 subsequent scanning periods, additional data is shifted into panels **150B-150D**, which then in accor-

16

dance with the scanning period sequentially illuminate 23 other linked scan groups made up of pixel rows of the LED display. In other embodiments, any number of scanning periods may be used. The scanning period is indicated by, for example, a scan select signal, a scanning timer, or an address select signal sent by receiver unit **140**.

FIG. 7, which includes FIGS. 7A-7E, illustrates embodiment panel circuit diagrams implementing the signaling configurations of FIG. 6. FIG. 7A illustrates a panel with two shift registers coupled in parallel through two current drivers to two rows of pixels. FIG. 7B illustrates two shift registers coupled together to form a long shift register providing parallel data for two rows of pixels. FIG. 7C illustrates two shift registers coupled together to form a long shift register providing data for a single row of pixels. FIG. 7D illustrates a shift register coupled to a scan controller to provide data for multiple rows of pixels in accordance with a scanning pattern. FIG. 7E illustrates two shift registers coupled to a demultiplexer and to a scan controller to provide data for multiple rows of pixels in accordance with a scanning pattern.

Referring to FIG. 7A, only blue data driving blue LEDs is shown for illustrative purposes. In an embodiment, red and green data would drive red LEDs and green LEDs, which are not shown. In other embodiments, red, green, and blue data would drive different input pins of tri-colored LEDs. In FIG. 7A, data, power, and control signaling (including, for example address and latch signaling) is received at an interface circuit **351** of one of the panels. Power is then supplied to the power supply unit **370**, which then powers two rows that are 1x16 LED arrays **505** of blue LEDs. Blue data is shifted serially from the interface circuit to the shift registers **355A** of LED controller **359**. This data is shifted through a data bus **354**. In other embodiments, individual data wires take the place of the data bus **354**. The blue data is shifted in accordance with a latch or clock signal provided to the shift registers **355A**. As the shift registers **355A** fill with stored digital data words in their 16 data word positions, they provide this data on 16 parallel outputs to current drivers **353**. In accordance with a current driver synchronization signal (not shown), which may be derived from a clock or latch signal provided by the receiver unit **140** to interface circuit **351**, the current drivers **353** then act as current sinks to control the current or duty cycle of the two rows of 16 LEDs each in LED arrays **505**. Other embodiments may use current drivers as current sources, and may use shift registers of various sizes.

Referring to FIG. 7B, the difference between this embodiment and the embodiment of FIG. 7A is that two shift registers **355A** are coupled together to form a single long shift register. In FIG. 7B, 32 words of digital data must be stored in this combined shift register before data is provided on 32 parallel outputs to current drivers **353**, which then control the current or duty cycle of the two rows of 16 LEDs each in LED arrays **505**.

Referring to FIG. 7C, the difference between this embodiment and the embodiment of FIG. 7B is that the two 16-LED arrays **505** are configured to form a single row of 32 LEDs. In FIG. 7C, 32 words of digital data must be stored in a single long shift register before data is provided on 32 parallel outputs to current drivers **353**, which then control the current or duty cycle of the single row of 32 LEDs in LED arrays **505**.

Referring to FIG. 7D, only a single shift register **355A** is shown for illustrative purposes. In FIG. 7D, latch signaling from the interface circuit **351** passes to the shift register **355A** through a demultiplexer **502** that may also be coupled

17

to other shift registers that are not shown. The demultiplexer **502** acts as a register switch to provide the latch signal only to an active shift register, which prevents the remaining shift registers from shifting in incoming serial data. The demultiplexer is controlled by an address select signal to select the active shift register. A scan select signal or other control signal, a scan timer, or the ordering of latch signals may also be used to control the demultiplexer **502**. In other embodiments, the demultiplexer **502** acts as a data switch to pass serial data to the shift registers in accordance with, for example, the number of words received by a data counter.

Referring again to FIG. 7D, when the shift register **355A** is full of 16 words of stored digital data, it then provides this data on 16 parallel outputs to a current driver **353**, which then controls the current or duty cycle of 8 scan groups comprising one or more rows of 16 LEDs each in LED arrays **505**. The shift register **355A** receives data intended for the Nth LED row (the first row of the Nth scan group) during the Nth scan period. The power supply unit **370** includes a scan controller **700** that couples power to an active scan group in accordance with the address select signal provided by the receiver unit **140** to synchronize the demultiplexer **502** and scan controller **700**. A scan select signal or scan timer may also be used to synchronize the scan controller **700**. In other embodiments, the scan controller **700** is located outside the power supply unit **370** and may couple current from the current driver **353** to the LED arrays **505**. In FIG. 7D, the scan controller **700** is an array of switches **504**, which may be implemented, for example, as an array of transistors. The scan controller **700** may also be implemented using one or more demultiplexers.

Referring to FIG. 7E, the difference between this embodiment and the embodiment of FIG. 7D is that the rows of LEDs in LED arrays **505** are organized into only 4 scan groups of at least two rows each. The scan controller **700** switches power to pairs of rows in each of the 4 scan groups. When each of the two illustrated shift registers **355A** is full of 16 words of stored digital data, it then provides this data on 16 parallel outputs to a current driver **353**, which then controls the current or duty cycle of one row in each of the 4 scan groups. The demultiplexer **502** and the two shift registers **355A** and two current drivers **353** are all components of the LED controller **359**. In other embodiments, the demultiplexer **502** is located outside multiple LED controllers that each include only one shift register **355A** and current driver **353** that the demultiplexer **502** only activates one LED controller at a time.

Referring again to FIG. 7E, a first shift register provides data to control current to a first row in each of the 4 scan groups, and the second shift register provides data to control current to a second row in each of the 4 scan groups. In other embodiments, other numbers of shift registers may be used, and data for multiple rows in a scan group may be provided by a single scan group.

FIG. 8 illustrates a method of assembling the modular multi-panel display system discussed in various embodiments. A mechanical support structure such as the frame not described in FIG. 1 above is assembled taking into account various parameters such as the size and weight of the multi-panel display, location and zoning requirements, and others (box **801**). For example, as previously described, the mechanical support structure includes a plurality of vertical bars and horizontal bars. The mechanical support structure may be fabricated from a corrosion resistant material in one or more embodiments. For example, the mechanical support structure may be coated with a weather-proofing coating that prevents the underlying substrate from corroding.

18

A plurality of LED display panels are mounted on to the mechanical support structure so as to form an integrated display panel that includes an array of rows and columns of LED display panels as described in various embodiments (box **803**). Each of the LED display panels is hermetically sealed. Mounting the LED display panels may comprise mounting each LED display panel to a vertical or horizontal beam using an attachment plate.

Each of the LED display panels is electrically connected to a data source and to a power source (box **805**). For example, a first LED display panel in each row is electrically coupled to a receiver unit. The other LED display panels in each row may be daisy-chain coupled to an adjacent LED display panel. In embodiments that are dynamically adaptable, no further configuration of the data source is necessary. In pre-configured embodiments, the data source is configured with information related to, for example, the number of LED display panels and the resolution and pitch of each LED display panel in each daisy-chained row.

Since the assembled display structure is light weight, significant assembly advantages can be achieved. For example, the panels can be assembled within a warehouse that is remote from the final location where the display will be utilized. In other words, the panels can be assembled at a first location, shipped to second location and finalized at the second location.

In FIG. 9, a method of configuring and displaying data on the modular multi-panel display system in accordance with pre-configured embodiments of the present invention is illustrated. The panel is initially set up with mechanical and electrical connections in accordance with the method of FIG. 8 (box **901**). The controller **400** and receiver unit **140** are then configured with information about individual LED display panels **150**, including, for example, the panels' resolutions, pixel counts/local video frame sizes, number of scan groups, and number of rows and columns of each scan group. (box **902**). In other embodiments, the modular display system is dynamically adaptable so that the LED display panels **150** send panel information to the receiver unit **140**, which forwards some of all of this panel information to the controller **400**. In accordance with the panel information, the controller **400** sends data to the receiver unit **140**, which then sends data for display at the LED display panels **150** (box **903**). As an example, an LED display panel **150** may be removed and replaced with a panel having a different resolution (box **904**). The controller **400** and receiver unit **140** are then re-configured by an operator with updated panel information that includes the new resolution information (box **905**). In dynamically adaptable embodiments, the LED display panels **150** send panel information to the receiver unit **140** and then to the controller **400**. In accordance with this updated panel information, the controller **400** again sends data to the receiver unit **140**, which then sends data again for display at the LED display panels **150** (box **906**).

Although embodiments of the present invention have been described as being LED display panels, various embodiments of the present invention may also be applied to any type of display panel including organic display including passive-matrix or active-matrix displays, organic transistor based displays, micro-mirror displays, plasma display, liquid crystal display, surface-conduction electron-emitter display, field emission display, and others.

While this invention has been described with reference to illustrative embodiments, this description is not intended to be construed in a limiting sense. Various modifications and combinations of the illustrative embodiments, as well as

19

other embodiments of the invention, will be apparent to persons skilled in the art upon reference to the description. It is therefore intended that the appended claims encompass any such modifications or embodiments.

What is claimed is:

1. A modular display panel comprising:
 - a casing having a recess and attachment points for use in attachment as part of a multi-panel modular display, a perimeter of the casing being substantially rectangular and having a height and a width, wherein the height is half of the width;
 - a printed circuit board disposed in the recess;
 - a display surface comprising an array of LEDs attached to a front side of the printed circuit board, wherein each of the LEDs of the LED array is spaced from each respective adjacent LED of the LED array by a pitch, wherein the pitch is a predetermined constant number, and
 - wherein the pitch does not depend on the height and the width; and
 - a driver circuit electrically coupled to the printed circuit board.
2. The display panel of claim 1, wherein the display panel is waterproof against submersion in up to 3 feet of water.
3. The display panel of claim 1, wherein the pitch is selected from the group consisting of 6.35 mm, 16.62 mm, 18.525 mm, 21.7 mm, 24.24 mm, 28.05 mm, 25.4 mm, and 30.48 mm.
4. The display panel of claim 1, wherein the casing comprises a plastic casing.
5. The display panel of claim 1, wherein the casing comprises an aluminum casing.
6. The display panel of claim 1, wherein each of the LEDs of the array of LEDs is a surface mount device (SMD) module, the SMD module comprising a plurality of LED devices, and wherein the pitch is selected from the group consisting of 6.35 mm, 16.62 mm, 18.525 mm, and 21.7 mm.
7. The display panel of claim 1, further comprising a cable connector configured to provide power and data to the modular display panel, the cable connector comprising:
 - a plurality of data connectors surrounded by an end enclosure, each data connector electrically coupled to a corresponding data wire; and
 - a plurality of power connectors surrounded by the end enclosure, each power connector electrically coupled to a corresponding power wire.
8. The display panel of claim 1, further comprising a power supply unit mounted outside the casing.
9. The display panel of claim 1, further comprising a power supply unit disposed within the casing.
10. A modular display panel comprising:
 - a casing having a recess and attachment points for use in attachment as part of a multi-panel modular display, a perimeter of the casing being substantially rectangular and having a height and a width, wherein the height is half of the width;
 - a printed circuit board disposed in the recess;
 - an array of LEDs attached to a front side of the printed circuit board, the LEDs arranged along a plurality of rows, wherein along any row of the plurality of rows, each of the LEDs of the LED array is spaced from each respective adjacent LED of the LED array by a fixed distance along a row, and wherein the fixed distance does not depend on the height and the width; and
 - a driver circuit electrically coupled to the printed circuit board; and

20

- a power converter for powering the array of LEDs, wherein the display panel is configured to be detachably attached to a support structure, wherein the support structure is configured to support a plurality of display panels.
- 11. The display panel of claim 10, wherein the display panel is completely waterproof against submersion in up to 3 feet of water.
- 12. The display panel of claim 10, wherein the casing comprises a plastic casing.
- 13. The display panel of claim 10, wherein the casing comprises an aluminum casing.
- 14. The display panel of claim 10, wherein each of the LEDs of the array of LEDs is a surface mount device (SMD) module, the SMD module comprising a plurality of LED devices.
- 15. The display panel of claim 10, further comprising a cable connector configured to provide power and data to the modular display panel, the cable connector comprising:
 - a plurality of data connectors surrounded by an end enclosure, each data connector electrically coupled to a corresponding data wire; and
 - a plurality of power connectors surrounded by the end enclosure, each power connector electrically coupled to a corresponding power wire.
- 16. The display panel of claim 10, wherein the power converter is mounted outside the casing.
- 17. The display panel of claim 10, wherein the power converter is disposed within the casing.
- 18. A modular digital display system comprising:
 - a mechanical support structure comprising a plurality of vertical beams and a plurality of horizontal beams;
 - a plurality of digital display panels mounted to the mechanical support structure so as to form an integrated display panel, the integrated display panel comprising a display surface, wherein the mechanical support structure is configured to provide mechanical support to the plurality of digital display panels, wherein the display surface is water proof and requires no additional weather protection cabinetry;
 - wherein all of the plurality of digital display panels have the same length, width, height, and shape, wherein each display panel has a substantially rectangular perimeter having a height and a width, wherein the height is half of the width; and
 - wherein each of the display panels comprises a plurality of LEDs arranged in a pixel array, wherein, for each of the display panels,
 - each LED of the plurality of LEDs is spaced from each respective adjacent LED of the plurality of LEDs by a predefined pitch, and
 - wherein the predefined pitch does not depend on the height and the width.
- 19. The system of claim 18, wherein the display surface comprises a first region and a second region;
 - wherein the first region comprises a first display panel and the second region comprises a second display panel attached to the first display panel; and
 - wherein the pixel array of the first display panel has a first resolution and the pixel array of the second display panel has a second resolution that is different than the first resolution.
- 20. The system of claim 19, wherein the plurality of digital display panels further comprises a third display panel, and wherein the third display panel comprises a third pixel array having a third resolution that is different from the first resolution.

21

21. The system of claim 19, wherein the second display panel is located along a bottom edge of the display surface.

22. The system of claim 19, wherein the first display panel is one of a plurality of display panels having the first resolution that are arranged in a central region of the display surface, and wherein the second display panel is one of a plurality of display panels having the second resolution located at an outer edge of the display surface.

23. The system of claim 19, further comprising a receiver unit coupled to the plurality of digital display panels;

wherein the first display panel further comprises a first video memory;

wherein the second display panel further comprises a second video memory;

wherein the receiver unit is configured to provide a first identifiable video segment to the first display panel and a second identifiable video segment to the second display panel;

wherein the first display panel is configured to digitally store the first identifiable video segment in the first video memory in accordance with a first unique identifier, the first unique identifier comprising a time-slot number or an address; and

wherein the second display panel is configured to digitally store the second identifiable video segment in the second video memory in accordance with a second unique identifier, the second unique identifier comprising a time-slot number or an address.

24. The system of claim 19, further comprising a receiver unit coupled to the plurality of digital display panels;

wherein the first display panel further comprises a first video memory of a first size;

wherein the second display panel further comprises a second video memory of a second size that is different than the first size;

wherein the receiver unit is configured to provide the first display panel a first video segment sized in accordance with the first size preceded by a second video segment sized in accordance with the second size;

wherein the first display panel is configured to shift the second video segment to the second display panel;

wherein the second display panel is configured to digitally store the second video segment to completely fill the second video memory; and

wherein the first display panel is configured to digitally store the first video segment to completely fill the first video memory.

25. The system of claim 18, wherein each display panel further comprises a power supply and a switch array coupled to the power supply and to the pixel array; and

22

wherein, for each display panel, the switch array is configured to switch power to an input of a light emitting pixel unit in the pixel array in accordance with at least one of a scan select signal, a scan timer, and an address select signal.

26. The system of claim 18, wherein each display panel further comprises a data switch and a plurality of controllers; wherein, for each display panel, the data switch is configured to select a first active controller from the plurality of controllers in accordance with at least one of a scan select signal, a scan timer, an address select signal, a latch signal, and a data counter; and wherein the first active controller comprises a first shift register coupled to a first current driver.

27. A method of manufacturing a plurality of display panels, the method comprising:

providing a plurality of housings, each housing having a recess and attachment points for use in attachment as part of a multi-panel modular display, wherein each display panel has a height and a width, wherein the height is half of the width, and wherein all of the plurality of display panels have the same height and width;

forming a first-display panel by mounting a first printed circuit board within a first one of the housings, the first printed circuit board having a first array of LEDs, the LEDs being attached to a front side of the first printed circuit board to form a first display, wherein each of the LEDs of the first array of LEDs is spaced from each respective adjacent LED of the first array of LEDs by a first pitch; and

forming a second display panel by mounting a second printed circuit board within a second one of the housings, the second printed circuit board having a second array of LEDs, the LEDs being attached to a front side of the second printed circuit board to form a second display, wherein each of the LEDs of the second array of LEDs is spaced from each respective adjacent LED of the second array of LEDs by a second pitch, and wherein the second pitch is different than the first pitch.

28. The method of claim 27, further comprising: sealing the first display panel to be completely waterproof against submersion in up to 3 feet of water; and sealing the second display panel to be completely waterproof against submersion in up to 3 feet of water.

29. The method of claim 27, further comprising: sealing the first display panel against water penetration within the recess; and sealing the second display panel against water penetration within the recess.

* * * * *