

(12) **United States Patent**  
**Auyeung et al.**

(10) **Patent No.:** **US 9,685,102 B1**  
(45) **Date of Patent:** **Jun. 20, 2017**

(54) **LED LIGHTING ASSEMBLY WITH  
UNIFORM OUTPUT INDEPENDENT OF  
NUMBER OF NUMBER OF ACTIVE LEDES,  
AND METHOD**

(58) **Field of Classification Search**  
CPC ..... F21Y 2105/001; F21S 4/008; F21V 5/08;  
F21V 5/007; F21V 5/045; F21V 29/004;  
(Continued)

(71) Applicant: **Ultravision Technologies, LLC**, Dallas,  
TX (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **David Siucheong Auyeung**, Carrollton,  
TX (US); **William Y Hall**, Dallas, TX  
(US); **Simon Magarill**, Mountain View,  
CA (US)

2,254,961 A 9/1941 Lawrence et al.  
4,235,285 A 11/1980 Johnson et al.  
(Continued)

(73) Assignee: **Ultravision Technologies, LLC**, Dallas,  
TX (US)

CA 2615706 A1 9/2006  
CN 201925854 U 8/2011  
(Continued)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

OTHER PUBLICATIONS

(21) Appl. No.: **15/429,320**

Adaptive Micro Systems, LLC, "Signs—Sealed and Delivered!  
Adaptive's Approach to Heat Management," Mar. 2008, 2 pages.

(22) Filed: **Feb. 10, 2017**

(Continued)

*Primary Examiner* — Ismael Negrón

(74) *Attorney, Agent, or Firm* — Slater Matsil, LLP

**Related U.S. Application Data**

(57) **ABSTRACT**


(60) Continuation of application No. 15/216,562, filed on  
Jul. 21, 2016, now Pat. No. 9,659,511, which is a  
(Continued)

A lighting assembly includes LEDs arranged at a surface of  
a substrate, and optical elements proximate the LEDs such  
that each optical element overlies a single LED and each  
LED underlies a single optical element. Each optical ele-  
ment includes a first part, a second part intersecting the first  
part such that a normal to surface of the second part  
intersects a normal to the surface of the first part, and a third  
part extending away from the associated LED beyond a  
region between the first and second part. The LEDs and  
optical elements are configured such that light from each  
LED is directed towards an area to be illuminated in a  
uniform pattern covering the area.

(51) **Int. Cl.**  
**F21V 5/04** (2006.01)  
**G09F 13/02** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G09F 13/22** (2013.01); **F21V 5/007**  
(2013.01); **F21V 21/26** (2013.01); **F21V**  
**29/745** (2015.01);  
(Continued)

**26 Claims, 13 Drawing Sheets**



**Related U.S. Application Data**

- division of application No. 14/968,520, filed on Dec. 14, 2015, now Pat. No. 9,589,488, which is a division of application No. 14/706,634, filed on May 7, 2015, now Pat. No. 9,212,803, which is a continuation of application No. 14/630,500, filed on Feb. 24, 2015, which is a continuation of application No. 13/836,517, filed on Mar. 15, 2013, now Pat. No. 8,974,077.
- (60) Provisional application No. 61/677,346, filed on Jul. 30, 2012.
- (51) **Int. Cl.**  
**G09F 13/22** (2006.01)  
**F21V 29/89** (2015.01)  
**F21V 29/74** (2015.01)  
**F21V 5/00** (2015.01)  
**F21V 29/83** (2015.01)  
**F21V 21/26** (2006.01)  
**G09F 15/00** (2006.01)  
**F21Y 105/16** (2016.01)  
**F21Y 115/10** (2016.01)
- (52) **U.S. Cl.**  
CPC ..... **F21V 29/83** (2015.01); **F21V 29/89** (2015.01); **G09F 13/02** (2013.01); **G09F 15/005** (2013.01); **G09F 15/0037** (2013.01); **F21Y 2105/16** (2016.08); **F21Y 2115/10** (2016.08); **G09F 2013/222** (2013.01)
- (58) **Field of Classification Search**  
CPC ..... F21V 29/74; F21V 29/745; F21V 29/76; G09F 13/02  
See application file for complete search history.

(56) **References Cited**

## U.S. PATENT DOCUMENTS

4,679,118	A	7/1987	Johnson et al.	7,153,002	B2	12/2006	Kim et al.
5,036,248	A	7/1991	McEwan et al.	7,159,997	B2	1/2007	Reo et al.
5,083,194	A	1/1992	Bartilson	7,246,931	B2	7/2007	Hsieh et al.
5,329,426	A	7/1994	Villani	7,336,195	B2	2/2008	van de Ven
5,384,940	A	1/1995	Soule et al.	7,339,202	B2	3/2008	Chiu et al.
5,803,579	A	9/1998	Turnbull et al.	7,374,306	B2	5/2008	Liu
5,818,640	A	10/1998	Watanabe et al.	7,374,316	B2	5/2008	Kuo et al.
5,857,767	A	1/1999	Hochstein	7,375,381	B2	5/2008	Shimizu et al.
5,896,093	A	4/1999	Sjobom	7,390,117	B2	6/2008	Leatherdale et al.
5,924,788	A	7/1999	Parkyn, Jr.	7,396,146	B2	7/2008	Wang
5,926,320	A	7/1999	Parkyn, Jr. et al.	7,410,275	B2	8/2008	Sommers et al.
6,045,240	A	4/2000	Hochstein	7,434,964	B1	10/2008	Zheng et al.
6,274,924	B1	8/2001	Carey et al.	7,458,706	B1	12/2008	Liu et al.
6,364,507	B1	4/2002	Yang	7,478,915	B1	1/2009	Pedersen
6,428,189	B1	8/2002	Hochstein	7,513,639	B2	4/2009	Wang
6,517,218	B2	2/2003	Hochstein	7,513,653	B1	4/2009	Liu et al.
6,536,923	B1	3/2003	Merz	7,549,777	B2	6/2009	Huang
6,547,423	B2	4/2003	Marshall et al.	7,572,654	B2	8/2009	Chang
6,582,103	B1	6/2003	Popovich	7,618,162	B1	11/2009	Parkyn et al.
6,607,286	B2	8/2003	West et al.	7,618,163	B2	11/2009	Wilcox
6,674,096	B2	1/2004	Sommers	7,654,684	B1	2/2010	Wight et al.
6,741,351	B2	5/2004	Marshall et al.	7,665,862	B2	2/2010	Villard
6,783,269	B2	8/2004	Pashley et al.	7,674,019	B2	3/2010	Parkyn et al.
6,784,603	B2	8/2004	Pelka et al.	7,686,469	B2	3/2010	Ruud et al.
6,799,864	B2	10/2004	Bohler et al.	7,736,019	B2	6/2010	Shimada et al.
6,837,605	B2	1/2005	Reill	7,748,863	B1	7/2010	Holman et al.
6,864,513	B2	3/2005	Lin et al.	7,753,561	B2	7/2010	Chaves et al.
6,896,381	B2	5/2005	Benitez et al.	7,753,564	B2	7/2010	Cheng et al.
6,918,684	B2	7/2005	Harvey	7,841,750	B2	11/2010	Wilcox et al.
6,948,838	B2	9/2005	Kunstler	7,857,483	B2	12/2010	Storch et al.
7,006,306	B2	2/2006	Falicoff et al.	7,866,851	B2	1/2011	Chang
7,009,213	B2	3/2006	Camras et al.	7,896,522	B2	3/2011	Heller et al.
7,048,400	B2	5/2006	Murasko et al.	7,905,634	B2	3/2011	Agurok et al.
7,118,236	B2	10/2006	Hahm et al.	7,942,559	B2	5/2011	Holder et al.
7,144,135	B2	12/2006	Martin et al.	7,952,262	B2	5/2011	Wilcox et al.
				7,959,326	B2	6/2011	Laporte
				7,980,733	B2	7/2011	Shih et al.
				7,997,761	B2	8/2011	Peck et al.
				8,002,435	B2	8/2011	Laporte
				8,035,119	B2	10/2011	Ng et al.
				8,052,303	B2	11/2011	Lo et al.
				8,056,614	B2	11/2011	Chen et al.
				8,092,049	B2	1/2012	Kinnune et al.
				8,101,434	B2	1/2012	Guillien et al.
				8,192,048	B2	6/2012	Kristoffersen et al.
				8,201,970	B2	6/2012	Wang et al.
				8,210,723	B2	7/2012	Peck et al.
				8,215,814	B2	7/2012	Marcoux
				8,235,553	B2	8/2012	Minami et al.
				8,246,219	B2	8/2012	Teng et al.
				8,262,252	B2	9/2012	Bergman et al.
				8,267,551	B2	9/2012	Lin
				8,273,158	B2	9/2012	Jarrier et al.
				8,308,331	B2	11/2012	Loh
				8,310,158	B2	11/2012	Coplin et al.
				8,330,387	B2	12/2012	York et al.
				8,338,841	B2	12/2012	Lerman et al.
				8,348,461	B2	1/2013	Wilcox et al.
				8,360,613	B2	1/2013	Little, Jr.
				8,376,585	B2	2/2013	Noeth
				8,408,737	B2	4/2013	Wright et al.
				8,454,194	B2	6/2013	Liu
				8,454,215	B2	6/2013	Bollmann
				8,465,178	B2	6/2013	Wilcox et al.
				8,469,552	B2	6/2013	Moeller
				8,476,650	B2	7/2013	Liao
				8,547,023	B2	10/2013	Chang et al.
				8,567,987	B2	10/2013	Wronski
				8,573,815	B2	11/2013	Mallory et al.
				8,577,434	B2	11/2013	Merchant et al.
				8,585,253	B2	11/2013	Duong et al.
				8,602,599	B2	12/2013	Zimmer et al.
				8,610,357	B2	12/2013	Stoll et al.
				8,622,574	B2	1/2014	Liu
				8,628,217	B2	1/2014	Moshtagh
				8,632,225	B2	1/2014	Koo et al.
				8,651,693	B2	2/2014	Josefowicz et al.
				8,662,704	B2	3/2014	Carraher et al.
				8,733,981	B2	5/2014	Jiang et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,789,967 B2 7/2014 Gordin et al.  
 8,801,221 B2 8/2014 Lin et al.  
 8,824,125 B1 9/2014 Cox et al.  
 8,835,958 B2 9/2014 Hsieh  
 8,858,024 B2 10/2014 Wu et al.  
 8,864,344 B2 10/2014 Jiang et al.  
 8,870,410 B2 10/2014 Auyeung  
 8,870,413 B2 10/2014 Auyeung  
 8,876,325 B2 11/2014 Lu et al.  
 8,922,734 B2 12/2014 Lin  
 8,931,934 B2 1/2015 Lin  
 9,046,293 B2 6/2015 Pelka et al.  
 9,182,101 B2 11/2015 Nakamura et al.  
 2003/0099105 A1 5/2003 Watson  
 2004/0004827 A1 1/2004 Guest  
 2005/0018428 A1 1/2005 Harvey  
 2005/0047170 A1 3/2005 Hilburger et al.  
 2005/0151141 A1 7/2005 Grottsch et al.  
 2006/0076568 A1 4/2006 Keller et al.  
 2006/0081863 A1 4/2006 Kim et al.  
 2006/0146531 A1 7/2006 Reo et al.  
 2006/0245083 A1 11/2006 Chou et al.  
 2007/0201225 A1 8/2007 Holder et al.  
 2007/0257270 A1 11/2007 Lu et al.  
 2007/0279904 A1 12/2007 Tasch et al.  
 2008/0073663 A1 3/2008 Chang  
 2008/0080179 A1 4/2008 Giorgi  
 2008/0084693 A1 4/2008 Shimada et al.  
 2008/0084701 A1 4/2008 Van De Ven et al.  
 2008/0180014 A1 7/2008 Tzeng et al.  
 2008/0212319 A1 9/2008 Klipstein  
 2008/0247173 A1 10/2008 Danek et al.  
 2008/0273327 A1 11/2008 Wilcox et al.  
 2009/0097265 A1 4/2009 Sun et al.  
 2009/0154158 A1 6/2009 Cheng et al.  
 2009/0180281 A1 7/2009 Ahland, III et al.  
 2009/0256459 A1 10/2009 Liu  
 2009/0262532 A1 10/2009 Wilcox et al.  
 2009/0267474 A1 10/2009 Zhou et al.  
 2009/0273933 A1 11/2009 Woodward et al.  
 2009/0290338 A1 11/2009 Heller et al.  
 2009/0296407 A1 12/2009 Bailey  
 2009/0303711 A1 12/2009 Remus et al.  
 2010/0008094 A1 1/2010 Shuai et al.  
 2010/0014289 A1 1/2010 Thomas et al.  
 2010/0014290 A1 1/2010 Wilcox  
 2010/0027271 A1 2/2010 Wilcox et al.  
 2010/0039810 A1 2/2010 Holder et al.  
 2010/0046225 A1 2/2010 Zheng  
 2010/0085774 A1 4/2010 Park  
 2010/0118531 A1 5/2010 Montagne  
 2010/0128488 A1 5/2010 Marcoux  
 2010/0149801 A1 6/2010 Lo et al.  
 2010/0172135 A1 7/2010 Holder et al.  
 2010/0195330 A1 8/2010 Schaefer et al.  
 2010/0232155 A1 9/2010 Wang  
 2010/0296267 A1 11/2010 Yu et al.  
 2010/0296283 A1 11/2010 Taskar et al.  
 2010/0302785 A1 12/2010 Zhou  
 2010/0302786 A1 12/2010 Wilcox et al.  
 2011/0002120 A1 1/2011 Song et al.  
 2011/0031887 A1 2/2011 Stoll et al.  
 2011/0038151 A1 2/2011 Carraher et al.  
 2011/0063857 A1 3/2011 Li et al.  
 2011/0068708 A1 3/2011 Coplin et al.  
 2011/0075409 A1 3/2011 Zheng  
 2011/0149548 A1 6/2011 Yang et al.  
 2011/0170283 A1 7/2011 Chan  
 2011/0205744 A1 8/2011 Kim  
 2011/0219650 A1 9/2011 Wright et al.  
 2011/0242807 A1 10/2011 Little, Jr. et al.  
 2011/0242816 A1 10/2011 Chowdhury et al.  
 2011/0278633 A1 11/2011 Clifford  
 2011/0280003 A1 11/2011 Hsu et al.  
 2012/0014115 A1 1/2012 Park et al.

2012/0043560 A1 2/2012 Wu et al.  
 2012/0080699 A1 4/2012 Chowdhury et al.  
 2012/0087125 A1 4/2012 Liu  
 2012/0163005 A1 6/2012 Liu  
 2012/0201022 A1 8/2012 van de Ven et al.  
 2012/0250321 A1 10/2012 Blincoc et al.  
 2012/0307495 A1 12/2012 Shih  
 2013/0010468 A1 1/2013 Stoll et al.  
 2013/0057861 A1 3/2013 Ishii et al.  
 2013/0063970 A1 3/2013 Oh  
 2013/0135861 A1 5/2013 Chen et al.  
 2013/0163005 A1 6/2013 Tsang  
 2013/0193850 A1 8/2013 Demuynck et al.  
 2013/0270585 A1 10/2013 Mei et al.  
 2013/0291414 A1 11/2013 Cegnar  
 2013/0335979 A1 12/2013 Lauret et al.  
 2014/0016326 A1 1/2014 Dieker et al.  
 2014/0029253 A1 1/2014 Auyeung  
 2014/0029259 A1 1/2014 Auyeung  
 2014/0029274 A1 1/2014 Auyeung  
 2014/0085905 A1 3/2014 Broughton  
 2014/0104851 A1 4/2014 Auyeung  
 2014/0112007 A1 4/2014 Auyeung  
 2014/0168963 A1 6/2014 Stone et al.  
 2014/0168998 A1 6/2014 Tang et al.  
 2014/0268761 A1 9/2014 Raleigh et al.  
 2014/0373348 A1 12/2014 Li

## FOREIGN PATENT DOCUMENTS

CN 202629916 U 12/2012  
 CN 102889549 A 1/2013  
 DE 202005016441 U1 2/2007  
 EP 1078301 A1 2/2001  
 EP 1528603 A2 5/2005  
 EP 1988576 A1 11/2008  
 EP 2039985 A2 3/2009  
 EP 2092859 A1 8/2009  
 EP 2172696 A1 4/2010  
 EP 2378337 A2 10/2011  
 EP 2416062 A2 2/2012  
 EP 2448021 A2 5/2012  
 EP 2553331 A1 2/2013  
 EP 2622267 A1 8/2013  
 GB 2421584 A 6/2006  
 JP 2003195790 A 7/2003  
 JP 2005024706 A 1/2005  
 JP 2005217094 A 8/2005  
 JP 2005327820 A 11/2005  
 JP 2007035951 A 2/2007  
 JP 2007281260 A 10/2007  
 JP 2011060575 A 3/2011  
 JP 2012054115 A 3/2012  
 JP 2012113276 A 6/2012  
 WO 2004051223 A2 6/2004  
 WO 2006033770 A2 3/2006  
 WO 2006126123 A1 11/2006  
 WO 2008047335 A1 4/2008  
 WO 2008122941 A1 10/2008  
 WO 2009064607 A1 5/2009  
 WO 2010010494 A1 1/2010  
 WO 2010033545 A2 3/2010  
 WO 2010130732 A1 11/2010  
 WO 2011041813 A1 4/2011  
 WO 2011042837 A1 4/2011  
 WO 2011123267 A1 10/2011  
 WO 2012021718 A1 2/2012  
 WO 2012095242 A1 7/2012  
 WO 2012121718 A1 9/2012

## OTHER PUBLICATIONS

“Advanced Lighting Guidelines,” 2001 Edition, New Buildings Institute, Inc., Jul. 20, 2001, 394 pages.  
 Dieker, et al., U.S. Appl. No. 61/659,828, filed Jun. 14, 2012, “Asymmetric Area Lighting Lens with Improved Uniformity,” 14 pages.

(56)

**References Cited**

## OTHER PUBLICATIONS

Barco, "DB-x20 Digital Billboard Out-of-Home Media LED Screen," Apr. 2009, 6 pages.

Batinsey, J., "Outdoor Lighting Ordinance Guide," Jun. 2006, 17 pages.

Chang, R. et al., "LED Backlight Module by Lightguide-Diffusive Component," Journal of Display Technology, vol. 8, No. 2, Feb. 2012, pp. 79-86.

Chen, C. et al., "P-72: Inclined LED Array for Large-Sized Backlight System," Society for Information Display, International Symposium, Digest of Technical Papers, SID 05 Digest, May 2005, pp. 558-561.

"Unified Development Code," Chapter 10 of the Tyler Code of Ordinances, City of Tyler, Apr. 23, 2008, 378 pages.

Defendants Invalidity Contentions, Appendix A, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-19.

Defendants Invalidity Contentions, ExhibitA01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-80.

Defendants Invalidity Contentions, ExhibitA02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-74.

Defendants Invalidity Contentions, ExhibitA03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-52.

Defendants Invalidity Contentions, ExhibitA04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-53.

Defendants Invalidity Contentions, ExhibitB01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-34.

Defendants Invalidity Contentions, ExhibitB02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-36.

Defendants Invalidity Contentions, ExhibitB03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-21.

Defendants Invalidity Contentions, ExhibitB04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-27.

Defendants Invalidity Contentions, ExhibitC01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-52.

Defendants Invalidity Contentions, ExhibitC02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-67.

Defendants Invalidity Contentions, ExhibitC03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-35.

Defendants Invalidity Contentions, ExhibitC04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-87.

Defendants Invalidity Contentions, ExhibitC05, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-51.

Defendants Invalidity Contentions, ExhibitC06, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-79.

Defendants Invalidity Contentions, ExhibitD01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-109.

Defendants Invalidity Contentions, ExhibitD02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-186.

Defendants Invalidity Contentions, ExhibitD03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-133.

Defendants Invalidity Contentions, ExhibitD04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-111.

Defendants Invalidity Contentions, ExhibitD05, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-133.

Defendants Invalidity Contentions, ExhibitD06, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-135.

Defendants Invalidity Contentions, ExhibitE01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-169.

Defendants Invalidity Contentions, ExhibitE02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-192.

Defendants Invalidity Contentions, ExhibitE03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-443.

Defendants Invalidity Contentions, ExhibitE04, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-171.

Defendants Invalidity Contentions, ExhibitF01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-34.

Defendants Invalidity Contentions, ExhibitF02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-13.

Defendants Invalidity Contentions, ExhibitF03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-100.

Defendants Invalidity Contentions, ExhibitG01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-30.

Defendants Invalidity Contentions, ExhibitG02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-11.

Defendants Invalidity Contentions, ExhibitG03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-94.

Defendants Invalidity Contentions, ExhibitH01 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-60.

Defendants Invalidity Contentions, ExhibitH02 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-26.

Defendants Invalidity Contentions, ExhibitH03 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-71.

Defendants Invalidity Contentions, ExhibitH04 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-151.

Defendants Invalidity Contentions, ExhibitH05 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-181.

Defendants Invalidity Contentions, ExhibitI01 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-168.

Deepa, R. et al., "Modeling and Simulation of Multielement LED Source," The Illuminating Engineering Institute of Japan, Journal of Light & Visual Environment, vol. 35, No. 1, Jun. 21, 2011, pp. 34-41.

Deepa, R. et al., Optimization of multi-element LED source for uniform illumination of plane surface, Optical Society of America, Optics Express, vol. 19, No. S4, Jul. 4, 2011, pp. A639-A648.

Design & Engineering Services, "Advanced Lighting Systems for Externally Lit Billboards," ET 08.12 Report, Southern California Edison, Jan. 4, 2010, 58 pages.

Whang, et al., "Designing Uniform Illumination Systems by Surface-Tailored Lens and Configurations of LED Arrays," IEEE 2009, Journal of Display Technology, vol. 5, No. 3, Mar. 2009, pp. 94-103.

Ding, Y., "Freeform LED lens for uniform illumination," Optics Express, vol. 16, No. 17, Aug. 18, 2008, 9 pages.

(56)

## References Cited

## OTHER PUBLICATIONS

- Arik, M., "Thermal Management of LEDs: Package to System," Third International Conference on Solid State Lighting, Proc. of SPIE, vol. 5187, Jan. 21, 2012, pp. 64-75.
- "General Catalog—2012," Thorlux Lighting, Dec. 2012, 164 pages.
- Tracepro, "LED Reflector and Lens Simulation Using TracePro Illumination Design and Analysis Software," White Paper, Oct. 2013, 11 pages.
- Tsai, J. et al., "LED Backlight Module by a Lightguide-Diffusive Component With Tetrahedron Reflector Array," J. Display Tech., vol. 8, No. 6, Jun. 2012, pp. 321-328.
- Hubbell Lighting, "Universal Lighting Technologies Invention Disclosure," Jun. 14, 2012, 15 pages.
- Wang, K. et al., "Freeform LED Lens for Rectangularly Prescribed Illumination," J. Opt. A: Pure Appl. Opt., No. 11, Aug. 2009, 105501, 10 pages.
- Wang, K. et al., "New reversing design method for LED uniform illumination," Optics Express, vol. 19, Issue S4, Jul. 4, 2011, pp. A830-A840.
- West, R.S. et al., "43.4: High Brightness Direct LED Backlight for LCD-TV," SID 03 Digest, May 2003, 4 pages.
- Wu, D. et al., "Freeform Lens Design for Uniform Illumination with Extended Source," 2011 IN V I Conf. Elecs. Packaging Tech. & High Density Packaging, Aug. 2011, pp. 1085-1089.
- Wu, R. et al., "Optimization Design of Irradiance Array for LED Uniform Rectangular Illumination," Applied Optics, vol. 1, No. 13, May 2012, pp. 2257-2263.
- Zhenrong, Z. et al., "Freeform Surface Lens for LED Uniform Illumination," Applied Optics, vol. 48, No. 35, Dec. 2009, pp. 6627-6634.
- Zhu, Z. et al., "Uniform Illumination Design by Configuration of LED Array and Diffuse Reflection Surface for Color Vision Application," J. Display tech, vol. 7, No. 2, Feb. 2011, pp. 84-89.
- Lee, S., "How to Select a Heat Sink," <http://www.electronics-cooling.com/1995/06/how-to-select-a-heat-sink/>, Jun. 1, 1995, pp. 1-10.
- Huang, K. et al., "Free-form lens design for LED indoor illumination," Proc. of SPIE, vol. 7852, Nov. 15, 2010, pp. 78521 D-1-78521 D-8.
- "The Lighting Handbook," 12-18, IES 10th Edition, Dec. 6, 2011, 1 page.
- "The Lighting Handbook," 8-17, IES 10th Edition, Dec. 6, 2011, 2 pages.
- Steigerwald, et al., "Illumination with Solid State Lighting Technology," IEEE Journal on Selected Topics in Quantum Electronics, vol. 8, No. 2, Mar./Apr. 2002, pp. 310-320.
- Defendant Irvin International, Inc.'s Answer, Affirmative Defenses, and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 6, 2016, pp. 1-41.
- Jeon, H. et al., "Illuminance Distribution and Photosynthetic Photon Flux Density Characteristics of LED Lighting with Periodic Lattice Arrangements," Transactions on Electrical and Electronic Materials, vol. 13, No. 1, Feb. 25, 2012, pp. 16-18.
- Jiang, J., "Optical design of a freeform TIR lens for LED street-light," Optik—International Journal for Light and Electron Optics, vol. 121, Issue 19, Oct. 2010, pp. 1761-1765.
- Defendants Corrected Joint Invalidity Contentions, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-108.
- Keller, A., "Signs of the Times," [floridatrend.com](http://floridatrend.com), Dec. 2011, pp. 50-53.
- Kim, Yu-Sin, et al., "Development of a Numerical Model for the Luminous Intensity Distribution of a Planar Prism LED Luminaire for Applying an Optimization Algorithm," Luekos, vol. 9, No. 1, Jul. 2012, pp. 57-72.
- Lakkio, O., "Winning the Optical Challenges in LED Street Lighting," Digi-Key, May 27, 2011, 5 pages.
- Lamar's First Amended Answer and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 8, 2016, pp. 1-61.
- "BILLIE—The Bright Answer for Billboard Lighting," Ledil Product Release, Dec. 8, 2013, 2 pages.
- "LEDIL Standard Optics for Osram LEDs," Ledil, Jan. 2011, 60 pages.
- "Strada 6in1 Module for Streeting Lighting," Ledil, 2010, 1 page, [http://ledil.fi/sites/default/files/Documents/Technical/Articles/Article\\_2.pdf](http://ledil.fi/sites/default/files/Documents/Technical/Articles/Article_2.pdf)>>.
- LEDIL, "Who is LEDIL?," [www.ledil.com](http://www.ledil.com), Mar. 22, 2011, 17 pages.
- LEDIL, "Who is LEDIL?," [www.ledil.com](http://www.ledil.com), May 22, 2011, 68 pages.
- Lee, S. et al., "Driving Performance and Digital Billboards Final Report," Virginia Tech Transportation Institute, Center for Automotive Safety Research, Mar. 22, 2007, 90 pages.
- Lee, Hsiao-Wen, et al., "Improvement of Illumination Uniformity for LED Flat Panel Light by Using Micro-Secondary Lens Array," Optics Express, vol. 20, No. S6, Nov. 5, 2012, 11 pages.
- Lighting Solutions Techzone Magazine, "Look Inside Today's Lighting Technology," Digi-Key Corporation, TZL112.US, Jun. 7, 2011, 76 pages.
- Liu, Peng, et al., "Optimized Design of LED Freeform Lens for Uniform Circular Illumination," Journal of Zhejiang University—Science C (Computers & Electronics), 2012, pp. 929-936.
- Lo, Y. et al., "Optical Design of a Butterfly Lens for a Street Light Based on a Double-Cluster LED," Microelectronics Reliability, vol. 52, May 2011, pp. 889-893.
- LED Professional Review, Issue 17, Jan./Feb. 2010, 52 pages.
- LED Professional Review, Issue 18, Mar./Apr. 2010, 64 pages.
- LED Professional Review, Issue 19, May/Jun. 2010, 64 pages.
- LED Professional Review, Issue 20, Jul./Aug. 2010, 48 pages.
- LED Professional Review, Issue 21, Sep./Oct. 2010, 64 pages.
- LED Professional Review, Issue 22, Nov./Dec. 2010, 60 pages.
- Defendant American Lighting Technologies, Inc. D/B/A Lighting Technologies' Amended Answer, Affirmative Defenses and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 27, 2016, pp. 1-43.
- Defendant American Lighting Technologies, Inc. D/B/A Lighting Technologies' Answer and Affirmative Defenses to plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 6, 2016, pp. 1-37.
- Luminatics, "LED Display Primer," 2011, pp. 1-21.
- Luo, X. et al., "Automated Optimization of an Aspheric Light-Emitting Diode Lens for Uniform Illumination," Applied Optics, vol. 50, No. 20, Jul. 2011, pp. 3412-3418.
- Moreno, I., "Configuration of LED Arrays for Uniform Illumination," Proc. of SPIE, vol. 5622, Oct. 2004, pp. 713-718.
- "LED Ad-Poster Billboard Luminaire," Neptun, Jan. 2012, 1 page.
- "LED Ad-Poster Billboard Luminaire," Neptun, May 25, 2011, 1 page.
- Office Action Summary received in U.S. Appl. No. 14/630,500, mailed Dec. 31, 2015, 65 pages.
- "Street Lighting with LED Lights Sources Application Note," OSRAM Opto Semiconductors, Jan. 2009, pp. 1-10.
- Parkyn, William A., "Segmented Illumination Lenses for Steplighting and Wall-Washing," SPIE Conference on Current Development in Optical Design and Optical Engineering VIII, Denver, Colorado, Jul. 1999, SPIE vol. 3779, pp. 363-370.
- Qin, Z. et al., "Analysis of Condition for Uniform Lighting Generated by Array of Light Emitting Diodes with Large View Angle," Optics Express, vol. 18, No. 16, Aug. 2010, pp. 17460-17476.
- Ramane, D. et al., "Automated Test Jig for Uniformity Evaluation of Luminaries," IJAET, vol. 3, No. 1, Mar. 2012, pp. 41-47.
- Ramane, D. et al., "Optimization of multi-element LED source for uniform illumination of plane surface," Optical Society of America, Optics Express, vol. 19, No. S4, Jul. 4, 2011, pp. A639-A648.
- "Starbeam," Thorlux Lighting, Brochure, Aug. 2012, 8 pages.
- "Starbeam," Thorlux Lighting, Brochure, Jul. 2015, 4 pages.
- "Starbeam," Thorlux Lighting, Brochure, Mar. 2014, 16 pages.
- "Starbeam," Thorlux Lighting, Technical Information, Mar. 2014, 10 pages.
- "Starflood," Thorlux Lighting, Brochure, Mar. 2016, 16 pages.

(56)

**References Cited**

OTHER PUBLICATIONS

“Starflood; High performance mini LED floodlights,” Thorlux Lighting, Retrieved Jul. 21, 2016, 16 pages, <<<http://www.thorlux.com/luminaires/starflood>>>.

Cheng, et al., “The Research of LED Arrays for Uniform Illumination,” *Advances in Information Sciences and Service Sciences (AISS)*, vol. 4, No. 10, Jun. 2012, pp. 174-182.

P.R. 4-3 Joint Claim Construction and Prehearing Statement, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jan. 27, 2017, pp. 1-20.




FIG. 1A




FIG. 1B




FIG. 1C







FIG. 1D








FIG. 3C




FIG. 4B








FIG. 4A






FIG. 6A





FIG. 6B






FIG. 7A





FIG. 7B








FIG. 8B




FIG. 8C




FIG. 8G




FIG. 8F




FIG. 8E




FIG. 8D




FIG. 8H




FIG. 8J





FIG. 8I



1

# LED LIGHTING ASSEMBLY WITH UNIFORM OUTPUT INDEPENDENT OF NUMBER OF NUMBER OF ACTIVE LEDs, AND METHOD

This is a continuation of U.S. patent application Ser. No. 15/216,562, filed Jul. 21, 2016, which is a divisional of U.S. patent application Ser. No. 14/968,520, filed Dec. 14, 2015, which is a division of U.S. patent application Ser. No. 14/706,634, filed May 7, 2015, which is a continuation of U.S. patent application Ser. No. 14/630,500, filed Feb. 24, 2015, which is a continuation of U.S. patent application Ser. No. 13/836,517, filed Mar. 15, 2013, which claims the benefit of U.S. Provisional Application No. 61/677,346, filed on Jul. 30, 2012, which applications are all hereby incorporated herein by reference.

The following patents and applications are related:

U.S. Pat. Appl. No. 61/677,340, filed Jul. 20, 2012  
U.S. Pat. Appl. No. 61/677,346, filed Jul. 30, 2012  
U.S. Pat. Appl. No. 61/677,352, filed Jul. 30, 2012  
U.S. patent application Ser. No. 13/836,517, filed Mar. 15, 2013 (now U.S. Pat. No. 8,974,077)  
U.S. patent application Ser. No. 13/836,612, filed Mar. 15, 2013 (now U.S. Pat. No. 8,870,410)  
U.S. patent application Ser. No. 13/836,710, filed Mar. 15, 2013 (now U.S. Pat. No. 9,062,873)  
U.S. patent application Ser. No. 14/137,306, filed Dec. 30, 2013 (now U.S. Pat. No. 8,985,806)  
U.S. patent application Ser. No. 14/137,343, filed Dec. 20, 2013 (now U.S. Pat. No. 8,870,413)  
U.S. patent application Ser. No. 14/137,380, filed Dec. 20, 2013 (now U.S. Pat. No. 9,068,738)  
U.S. patent application Ser. No. 14/630,500, filed Feb. 24, 2015 (co-pending)  
U.S. patent application Ser. No. 14/635,907, filed Mar. 2, 2015 (now U.S. Pat. No. 9,234,642)  
U.S. patent application Ser. No. 14/706,634, filed May 7, 2015 (now U.S. Pat. No. 9,212,803)  
U.S. patent application Ser. No. 14/968,520, filed Dec. 14, 2015 (co-pending)  
U.S. patent application Ser. No. 14/992,680, filed Jan. 11, 2016 (now U.S. Pat. No. 9,349,307)  
U.S. patent application Ser. No. 15/162,278, filed May 23, 2016 (co-pending)  
U.S. patent application Ser. No. 15/208,483, filed Jul. 12, 2016 (now U.S. Pat. No. 9,514,663)  
U.S. patent application Ser. No. 15,208,521, filed Jul. 12, 2016 (now U.S. Pat. No. 9,524,661)  
U.S. patent application Ser. No. 15/216,562, filed Jul. 21, 2016 (co-pending)  
U.S. patent application Ser. No. 15/216,595, filed Jul. 21, 2016 (now U.S. Pat. No. 9,542,870)  
U.S. patent application Ser. No. 15/413,277, filed Jan. 23, 2017 (co-pending)  
U.S. patent application Ser. No. 15/413,306, filed Jan. 23, 2017 (co-pending)

## TECHNICAL FIELD

The following disclosure relates to lighting systems and, more particularly, to lighting systems using light emitting diodes to externally illuminate signs.

## SUMMARY

The present invention, in one aspect thereof, comprises a back panel for use in a light emitting diode (LED) lighting

2

assembly. An extruded substrate formed of a thermally conductive material is provided, the substrate having a plurality of fins extending from a first side of the substrate, each of the fins having a substantially rectangular shape oriented so that a longitudinal axis of the fin is substantially parallel to a longitudinal axis of the substrate. At least some of the fins include a hole formed through the fin to enable heated air to rise through the fins. A plurality of LEDs are mounted on a second side of the substrate, and oriented in a longitudinal orientation with the fins oriented parallel to the bottom edge of a surface to be illuminated, such that heat rises perpendicular to the surface of the fin.

## BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding, reference is now made to the following description taken in conjunction with the accompanying drawings in which:

FIG. 1A illustrates one embodiment of a billboard that may be externally lighted by one or more lighting assemblies;

FIGS. 1B-1D illustrate embodiments of angular positions of the lighting assembly of FIG. 1 relative to the billboard;

FIG. 2 illustrates one embodiment of a lighting assembly that may be used to light the billboard of FIG. 1;

FIGS. 3A and 3B illustrate one embodiment of a back panel that may be used in the lighting assembly of FIG. 2;

FIG. 3C illustrates one embodiment of the back panel of FIGS. 3A and 3B with a light panel and an optics panel that may also be used in the lighting assembly of FIG. 2;

FIGS. 4A and 4B illustrate one embodiment of a light panel that may be used with the lighting assembly of FIG. 2;

FIGS. 5A, 5B, 5C and 5D illustrate one embodiment of an optics panel that may be used with the lighting assembly of FIG. 2;

FIGS. 6A-6C illustrate a more detailed embodiment of the lighting assembly of FIG. 2;

FIGS. 7A and 7B illustrate an embodiment of a back panel that may be used with the lighting assembly of FIGS. 6A-6C;

FIG. 8A illustrates an embodiment of an LED assembly and an optics panel that may be used with the lighting assembly of FIG. 6;

FIGS. 8B-8J illustrates embodiments of the optics panel of FIG. 8A and optical elements that may be used to form part of the optics panel; and

FIG. 9 illustrates a more detailed embodiment of the lighting assembly of FIG. 2.

## DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Billboards, such as those commonly used for advertising in cities and along roads, often have a picture and/or text that must be externally illuminated to be visible in low-light conditions. As technology has advanced and introduced new lighting devices such as the light emitting diode (LED), such advances have been applied to billboards. However, current lighting designs have limitations and improvements are needed. Although billboards are used herein for purposes of example, it is understood that the present disclosure may be applied to lighting for any type of sign that is externally illuminated.

Referring to FIG. 1A, one embodiment of a billboard **100** is illustrated. The billboard **100** includes a surface **102** onto which a picture and/or text may be painted, mounted, or

3

otherwise affixed. The surface **102** may be any size, such as a commonly used size having a width of forty-eight feet wide and a height of fourteen feet. The surface **102** may be provided by placing a backing material on a frame **104** made of steel and/or other materials. The frame **104** may be mounted on one or more support poles **106**, which may be considered part of the frame **104** or separate from the frame **104**. The billboard **100** may include a walkway or other support structure **108** that enables the surface **102** to be more easily accessed.

One or more lighting assemblies **110** may be coupled to the walkway **108** (e.g., to a safety rail or to the walkway itself) and/or to another structural member of the billboard **100** to illuminate some or all of the surface **102** in low light conditions. The lighting assembly **110** may be mounted at or near a top edge **112** of the billboard **100**, a bottom edge **114** of the billboard **100**, a right edge **116** of the billboard **100**, and/or a bottom edge **118** of the billboard **100**. The lighting assembly **110** may be centered (e.g., located in approximately the center of the billboard **100**) or off center as illustrated in FIG. 1A.

With additional reference to FIGS. 1B-1D, a surface **120** of the lighting assembly **110** may be parallel with respect to the surface **102** of the billboard **100** (FIG. 1B), may be perpendicular with respect to the surface **102** (FIG. 1C), or may be angled with respect to the surface **102** (FIG. 1D). It is understood that the lighting assembly **110** may be placed in many different orientations and locations relative to the billboard **100** and to one another, and the illustrated positions are only for purposes of example. Furthermore, it is understood that references to “top,” “bottom,” “left,” and “right” are used in the present disclosure for purposes of description and do not necessarily denote a fixed position. For example, the billboard **100** may be turned on end, and the referenced “top,” “bottom,” “left,” and “right” edges may still be readily identifiable although the “top” edge would be the “left” edge or the “right” edge.

One problem with current lighting technology is that it can be difficult to direct light only onto the surface **102** and even more difficult to do so evenly. This may be due partly to the placement of the lighting assembly **110**, as shown in FIGS. 1B-1D. As the lighting assembly **110** is off center relative to the surface **102**, light emitted from the lighting assembly **110** may not evenly strike the surface **102**. One problem with uneven illumination is that certain parts of the surface **102** may be more brightly illuminated than other parts. This creates “hot spots” that may be undesirable. Attempting to evenly illuminate the surface **102** may cause light to be directed past the edges **112**, **114**, **116**, and **118** as attempts are made to balance out hot spots in particular areas. However, light that does not strike the surface **102** is wasted and may create problems (e.g., light pollution), as well as waste illumination that could be used for the surface **102**.

In addition to the difficulties of evenly illuminating the surface **102**, the use of LEDs in an exterior lighting environment involves issues such as heat dissipation and protecting the LEDs against environmental conditions such as moisture. The presence of moving mechanical features such as fans that may be used to provide increased airflow for cooling may create additional reliability problems. Due to the difficulty and expense of replacing and/or repairing the lighting assembly **110** in combination with the desire to provide consistent lighting while minimizing downtime, such issues should be addressed in a manner that enhances reliability and uptime.

4

Referring to FIG. 2, one embodiment of a lighting assembly **200** is illustrated. The lighting assembly **200** provides a more detailed embodiment of the lighting assembly **110** of FIG. 1. The lighting assembly **200** includes a back panel **202**, a light panel **204** (e.g., a printed circuit board (PCB)) having a plurality of LEDs (not shown) mounted thereon, and an optics panel **206**. As will be described below in more detailed examples, light from the LEDs of the light panel **204** may be directed by the optics panel **206** to illuminate the surface **102** of the billboard **100** of FIG. 1. The back panel **202** may be configured to serve as a supporting substrate for the light panel **204** and optics panel **206**, as well as to dissipate heat produced by the LEDs.

It is understood that any of the back panel **202**, light panel **204**, and optics panel **206** may actually be two or more physical substrates rather than a single panel as illustrated in FIG. 2. Furthermore, it is understood that there may be additional panels positioned behind the back panel **202**, in front of the optics panel **206**, and/or between the back panel **202** and light panel **204** and/or between the light panel **204** and optics panel **206**.

Referring to FIGS. 3A-3C, one embodiment of the back panel **202** is illustrated with a front surface **302** and a back surface **304**. The back panel **202** includes a top edge **306**, a bottom edge **308**, a right edge **310**, and a left edge **312**. The panel **202** may be formed of one or more thermally conductive materials (e.g., aluminum) and/or other materials.

The front surface **302** provides a mounting surface for the light panel **204**. In some embodiments, the front surface **302** of the panel **202** may include one or more protrusions **314a** and **314b** that are substantially parallel to the top edge **306**. The protrusions **314a** and **314b** may be configured to protect the light panel **204** from moisture. Although only two protrusions **314a** and **314b** are illustrated, it is understood that a single protrusion may be provided or three or more protrusions may be provided. Furthermore, such protrusions may vary in length, shape (e.g., may have angled or curved surfaces), orientation, and/or location on the front surface **302**.

Referring specifically to FIG. 3C, a light panel **204** and an optical panel **206** may be mounted under the protrusion **314a** (FIG. 3C). Moisture running down the front surface **302** in the direction of arrow **316** may strike the protrusion **314a** and be directed away from the light panel **204** and optical panel **206** as shown by arrow **318**. Although not shown, moisture may also be directed length down the protrusion **314a**. Accordingly, protrusion **314a** may serve as a gutter and aid in directing moisture away from a joint **320** where the optical panel **206** abuts the front surface **302**. This may be beneficial even when a moisture resistant compound is used to seal the joint **320**. In embodiments where there are multiple light panels **204** arranged vertically on the front surface **302**, there may be a protrusion positioned above each light panel **204**. For example, the protrusion **314a** may be positioned directly above one light panel **204** and the protrusion **314b** may be positioned directly above another light panel **204**.

Referring specifically to FIG. 3B, the back surface **304** may be configured to increase heat dissipation. For example, the back surface **304** may be configured with a heat sink provided by fins **322a-322N**, where N denotes a total number of fins. The fins **322a-322N** increase the surface area of the back surface **304**, thereby providing for additional heat dissipation to the surrounding air. The fins **322a-322N** may be formed as part of the panel **202** or may be otherwise coupled to the panel **202** (e.g., may be part of a discrete heat sink that is coupled to the back surface **304**). Some or all of

the fins **322a-322N** may be angled, as shown by fins **322a** and **322b**. In some embodiments, holes (not shown) may be provided in some or all of the fins **322a-322N** to aid in air circulation. In such embodiments, the holes may cause a chimney effect in which heated air rises through the holes and is replaced by cooler air. This may be particularly effective in environments where natural air movement is limited.

Referring to FIGS. **4A** and **4B**, one embodiment of a single PCB **402** of the light panel **204** is illustrated. In the present example, the light panel **204** may include multiple PCBs **402**, although it is understood that any number of PCBs may be used based on design issues such as the amount of illumination needed, the amount of illumination provided by a single PCB **402**, the size of the surface **102** of the billboard **100**, and/or other factors. As shown in the present embodiment with a substantially rectangular cross-section, the PCB **402** includes a front surface **404**, a back surface **406**, a top edge **408**, a bottom edge **410**, a right edge **412**, and a left edge **414**.

The PCB **402** may include one or more strings of LEDs **416**, with multiple LEDs **416** in a string. For example, a string may include eight LEDs **416** and each PCB **402** may include two strings for a total of sixteen LEDs **416**. In this configuration, a light panel **204** having eight PCBs **402** would include ninety-six LEDs **416**. It is understood that although the PCBs **402** are shown as being substantially identical, they may be different in terms of size, shape, and other factors for a single light panel **204**.

In the present example, the LEDs **416** are surface mounted, but it is understood that the LEDs **416** may be coupled to the panel **204** using through hole or another coupling process. The surface mounted configuration may ensure that a maximum surface area of each LED **416** is in contact with the PCB **402**, which is in turn in contact with the back panel **202** responsible for heat dissipation. Each string of LEDs may receive a constant current with the current divided evenly among the LEDs **416**.

Referring to FIGS. **5A**, **5B**, **5C** and **5D**, one embodiment of a single lens panel **500** of the optics panel **206** is illustrated. In the present example, the optics panel **206** may include multiple lens panels **500**, although it is understood that any number of lens panels may be used based on design issues such as the number, arrangement, and orientation of the LEDs **416**, the size of the surface **102**, and/or other factors. As shown in the present embodiment with a substantially rectangular cross-section that is configured for use with the PCB **402** of FIG. **4**, a single lens panel **500** includes a front surface **502**, a back surface **504**, a top side **506**, a bottom side **508**, a right side **510**, and a left side **512**. The sides **506**, **508**, **510**, and **512** may form a cavity into which the PCB **402** may fit, thereby providing protection for the PCB **402** from environmental conditions such as moisture.

The lens panel **500** may include a beveled or angled top side **506** and/or bottom side **508** as illustrated in FIG. **5B**. The beveling/angling may aid in preventing moisture from reaching the PCB **402** under the lens panel **500**, as water will more readily flow from the area of the joint **320** (FIG. **3C**) due to the angled surface than if the top side **506** was relatively flat.

The lens panel **500** may include multiple optical elements **514**. A single optical element **514** may be provided for each LED **416**, a single optical element **514** may be provided for multiple LEDs **416**, and/or multiple optical elements **514** may be provided for a single LED **416**. In some embodi-

ments, the optical elements **514** may be provided by a single multi-layer optical element system provided by the lens panel **500**.

In the present example, the optical elements **514** are configured so that the light emitted from each LED **416** is projected onto the entire surface **102** of the billboard **100**. In other words, if all other LEDs **416** were switched off except for a single LED **416**, the entire surface **102** would be illuminated at the level of illumination provided by the single LED **416**. In one embodiment, the rectangular target area of the surface **102** would be evenly illuminated by the LED **416**, while areas beyond the edges **112**, **114**, **116**, and **118** would receive no illumination at all or at least a minimal amount of illumination from the LED **416**. What is meant by “evenly” is that the illumination with a uniformity that achieves a 3:1 ratio of the average illumination to the minimum. Thus, by designing the lens in such a manner, when all LEDs are operating, the light from the collective thereof will illuminate the surface at the 3:1 ratio. When one or more LEDs fail, the overall illumination decreases, but the uniformity maintains the same uniformity. Also, as described hereinabove, the “surface” refers to the surface that is associated with a particular LED panel. It may be that an overall illuminated surface is segmented and multiple panels are provided, each associated with a particular segment.

FIG. **5C** illustrates a detail of the lens assembly. Each of the diodes **416** is mounted on the board **408** at a minimum distance. Overlying the board and LEDs **416** is transparent lens substrate **520**. This substrate **520** has a plurality of lens structures **522**, each associated with one of the LEDs **416**, such that each of the LEDs **416** has the light emitted therefrom directed outward towards the surface, each lens structure being substantially the same. The minimum distance is designed such that overlapping light from adjacent LEDs does not create interference patterns and result in dead spots on the surface. The lens structure **522** is designed to create the 3:1 uniformity and also, the lens structure is designed to “direct” the light from an edge of the surface to cover the entire surface. This is shown by the angle of the light rays in FIG. **5C**. Also, the beveled edge **530** will basically surround the PCB **402**, thus protecting it from moisture. The lens substrate **520** is secured with screws (not shown).

FIG. **5D** illustrates a detail of the lens structure **522**. This structure includes an interior surface **524** and an exterior surface **526** that shapes and directs the light in the correct pattern. This is an acrylic material. With such a design, the lighting assembly can be disposed at an edge of the surface to illuminate the entire surface.

In some embodiments, as shown in FIG. **1**, two lighting assemblies **110** may be used. Each lighting assembly may be powered by a separate power supply (not shown), and may be configured to illuminate the entire surface **102**. In such an embodiment, if one power supply fails, the remaining lighting assembly **110** will still illuminate the entire surface **102**, although at a lesser intensity than when both lighting assemblies **110** are functioning. This provides evenly distributed illumination when both lighting assemblies **110** are functioning correctly, and continues to provide evenly distributed illumination when one lighting assembly **110** malfunctions. Accordingly, the entire surface **102** of the billboard **100** may be illuminated even when an entire lighting assembly **110** has malfunctioned and is providing no illumination at all due to the redundancy provided by configuration of the lighting assemblies **110**.

Furthermore, in some embodiments as described above, each LED **416** of a single lighting assembly **110** may be configured via the optical elements **514** to illuminate the entire surface **102**. In such embodiments, if one or more LEDs **416** or strings of LEDs fails, the remaining LEDs **416** will still illuminate the entire surface **102**, although at a lesser intensity than when the failed LEDs **416** are functioning. This provides evenly distributed illumination when all LEDs **416** are functioning correctly, and continues to provide evenly distributed illumination when one or more LEDs are malfunctioning. Accordingly, the billboard **100** may be illuminated even when multiple LEDs **416** have malfunctioned and are providing no illumination at all due to the redundancy provided by configuration of the lighting assemblies **110**.

It is understood that some embodiments may direct substantially all illumination from a lighting assembly **110** evenly across the surface **102** while some illumination is not evenly distributed. For example, substantially all LEDs **416** may be directed to each evenly illuminate the surface **102** with the exception of a relatively small number of LEDs **416**. In such cases, the illumination provided by the remaining LED or LEDs **416** may be directed to one or more portions of the surface **102**. If done properly, this may be accomplished while minimizing any noticeable unevenness in the overall illumination, even if one of the remaining LEDs **416** malfunctions. For example, the lighting assembly **110** may be configured to direct the illumination provided by one LED **416** to only the left half of the surface **102**, while directing the illumination from another LED **416** to only the right half of the surface **102**. The loss of one of these two LEDs may not noticeably impact the illumination of the surface **102**. It is understood that such variations are within the scope of this disclosure.

In embodiments where the illumination is evenly distributed across the surface **102**, it is understood that the optics panel **206** may be configured specifically for the light panel **204** and the surface **102**. For example, assuming the surface **102** is forty-eight feet wide and sixteen feet high, the lens panel **500** of FIG. **5** may be specifically designed for use with the PCB **402** of FIG. **4**. This design may be based on the particular layout of the PCB **402** (e.g., the number and arrangement of the LEDs **416**), the amount of illumination provided by the LEDs **416**, the size of the surface **102**, the distance between the lens panel **500** and the surface **102**, the angle at which the lens panel **500** is mounted relative to the surface **102** (e.g., FIGS. **1B-1D**), and/or other factors. Accordingly, changes in any of these factors may entail a change in the design of the lens panel **500** in order to again evenly distribute the illumination provided by each LED **416** across the entire surface **102**. It is understood that various standard configurations of the lighting assembly **110** may be developed for various billboard and/or other externally illuminated signs so that a particular configuration may be provided based on the parameters associated with a particular billboard and/or externally illuminated sign.

Referring to FIGS. **6A-6C**, one embodiment of a lighting assembly **600** is illustrated that provides a more detailed embodiment of the lighting assembly **200** of FIG. **2**. The lighting assembly **600** includes a back panel **602**, a light panel formed by multiple LED assemblies (denoted by reference number **800** in FIG. **8A**), and an optics panel formed by multiple lens panels **604**. Accordingly, as described previously, the light panel **204** in the current example is represented by multiple LED assemblies **800** and the optics panel **206** is represented by multiple lens panels

**604**. In the present embodiment, the lighting assembly **600** includes four LED assemblies **800** and four lens panels **604**.

Although various attachment mechanisms (e.g., threaded screws, bolts, and/or other fasteners) may be used to coupled the lens panels and LED assemblies to the back panel **602**, the present embodiment uses multiple threaded fasteners **605** (e.g., screws) that extend through the lens panels and the LED assemblies and engage threaded holes in the back panel **602**.

The lighting assembly **600** is also illustrated with a mounting plate **606** that couples to the back panel **602** and to an adjustable mounting bracket **608**. The adjustable mounting bracket **608** may be used to couple the lighting assembly **600** to a portion of the billboard **100** (FIG. **1**) and/or to another support member. A power supply enclosure **610** may be coupled to the mounting plate **606** and configured contain a power supply (not shown) capable of supplying power to LEDs of the LED assemblies **800**. It is noted that separating the power supply from the back panel **602** may aid in heat dissipation by the back panel **602** as it does not have to dissipate heat from the power supply to the same extent as if the power supply was mounted directly to the back panel **602**.

The location of the power supply may also be beneficial as snow not melted by the heat produced by the LED may be melted by heat produced by the power supply. This may aid in reducing snow buildup on the LEDs.

With additional reference to FIGS. **7A** and **7B**, one embodiment of the back panel of FIG. **602** is illustrated. A front surface **700** includes multiple protrusions **702** that may be configured to protect the light panels (not shown) against moisture as previously described. The front surface **700** may include additional protrusions **704**.

A back surface **706** includes multiple fins **708** that form a heat sink to aid in the dissipation of heat from the back panel **602**. In the present example, the fins **708** are substantially rectangular in shape. In the present example, the back panel **602** is extruded and the fins **708** run parallel to the top edge with a longitudinal axis of each fin **708** being substantially parallel to a longitudinal axis of the back panel **602**. Forming the fins **708** in a vertical manner is possible, but may increase the cost of the back panel **602** due to the extrusion process. As shown, the fins **708** may be substantially perpendicular to the back surface **706**, and/or may be angled. In the present example, the fins **708** are angled such that near the top of the back panel **702**, the fins **708** are angled towards the top.

Because the fins **708** are parallel to the top edge, heat may be trapped due to its inability to rise vertically. Accordingly, holes **710** may be present in some or all of the fins **708** (marked but not actually visible in the side view of FIG. **7B**) to provide paths for the heat to rise vertically in spite of the orientation of the fins **708**. The holes **710** may create a chimney effect that increases air flow across the fins **708** and aids in the cooling process. In some embodiments, some or all of the fins **708** may be angled such that heat is not trapped.

The back surface **706** may also include a groove **712** that is configured to receive a tongue of the mounting plate **606** in a tongue-in-groove manner.

With additional reference to FIGS. **8A-8J**, embodiments of a single LED assembly **800** and a single lens panel **604** that may be used with the lighting assembly **600** are illustrated. As shown, the single LED assembly **800** and the single optics panel **604** may be configured for use together.

Referring specifically to FIG. **8A**, the LED assembly **800** includes a substrate **802** (e.g., a PCB) onto which are

mounted multiple LEDs **804**. In the present example, the LED assembly **800** includes two strings of eight LEDs **804** each for a total of sixteen LEDs **804**. It is understood that this is merely an example, and there may be more or fewer LEDs **804** on the light panel **800**, and the LEDs **804** may be arranged in many different ways on the substrate **802**.

Referring also to FIGS. **8B-8J**, the optics panel **604** may include optical elements **806** arranged on an upper surface **808** of the optics panel **604**. The optics panel **604** may further include sides **810**, **812**, **814**, and **816** that are configured to fit around the edge of the substrate **802** of the light panel **800**. The bottom edge of each side **810**, **812**, **814**, and **816** abuts the front surface **700** of the back panel **602** and may be sealed to the front surface **700** using a moisture resistant sealant.

As shown in FIGS. **8D-8H**, a single optical element **806** may include multiple lens elements designed to distribute the illumination provided by a single LED **804** across a surface such as the surface **102** of FIG. **1**. A first lens element **820** may be positioned proximate to the LED **804**, and additional lens elements **822**, **824**, and **826** may be positioned above the lens element **820**. Multiple optical elements **806** may be combined and formed as a single optics panel **604** that is configured to operate with the LED assembly **800**.

Referring to FIG. **9**, another embodiment of a lighting assembly **900** is illustrated that provides a more detailed embodiment of the lighting assembly **200** of FIG. **2**. The lighting assembly **900** is similar to the lighting assembly **600** of FIG. **6**, but includes six LED assemblies rather than the four six LED assemblies of the lighting assembly **600**. It is understood that the lighting assembly **900** may require a larger power supply than the lighting assembly **600** (e.g., a one hundred and fifty watt power supply instead of a one hundred and twenty watt power supply).

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. A method of illuminating an area using a light assembly that includes a plurality of light emitting diodes (LEDs) and a plurality of optical elements, each optical element associated with one of the plurality of LEDs and each LED associated with one of the optical elements, the method comprising:

directing light away from the plurality of LEDs toward the area, wherein directing the light comprises directing the light such that light exiting from each optical element is directed across the area; and

wherein each optical element includes:

a first element;

a second element that intersects with the first element in a region between the first element and the second element, wherein the first element and the second element are shaped so that at least one surface normal of the first element intersect with at least one surface normal of the second element; and

a third element extending beyond the region between the first element and the second element in a direction away from the associated LED;

wherein if some of the LEDs fail to operate during directing the light away from the plurality of LEDs, the step of directing the light comprises directing the light

from operative ones of the plurality of LEDs toward the area such that the light from each operative LED is directed across the area.

2. The method of claim 1, wherein the light assembly is configured so that failure of one or more of the LEDs will cause an illumination level of light emitted from the light assembly to decrease while a uniformity of the light emitted from the light assembly remains substantially the same.

3. The method of claim 1, wherein directing the light away from the plurality of LEDs comprises directing the light in a manner that does not create hot spots or result in dead spots on the area.

4. The method of claim 1, wherein the area comprises a display surface of a billboard and wherein directing the light from the plurality of LEDs comprises illuminating the entire display surface of the billboard, the display surface extending between outer edges of the billboard.

5. The method of claim 4, wherein the display surface is illuminated in a manner that avoids light pollution.

6. The method of claim 1, wherein:

the area comprises a display surface of a billboard;

the billboard is 48 feet wide between outer edges of the billboard;

the display surface of the billboard displays media content;

directing the light from the plurality of LEDs comprises illuminating a first portion of the display surface of the billboard;

the method further comprises directing light from a second light assembly to illuminate a second portion of the display surface of the billboard; and

the light assembly and the second light assembly illuminate the display surface of the billboard between the outer edges of the billboard so media content on the display surface can be viewed using only the light assembly and the second light assembly.

7. The method of claim 6, wherein the display surface is illuminated in a manner that avoids light pollution.

8. A method of illuminating an area using a light assembly that includes a plurality of light emitting diodes (LEDs) and a plurality of optical elements, each optical element associated with one of the plurality of LEDs and each LED associated with one of the optical elements, the method comprising:

directing light from the plurality of LEDs toward the area, wherein directing the light comprises directing the light from each LED of the plurality of LEDs through the associated optical element such that light exiting from each optical element of the plurality of optical elements is directed across the area; and

wherein each optical element of the plurality of optical elements includes:

a first element;

a second element that intersects with the first element in a region between the first element and the second element, wherein the first element and the second element are shaped so that at least one surface normal of the first element intersects with at least one surface normal of the second element and wherein the first and the second elements are configured so that the light from the associated LED exits the associated optical element through the first and the second elements; and

a third element extending beyond the region between the first element and the second element in a direction away from the associated LED; and



## 11

wherein the light assembly configured so that failure of one or more of the LEDs will cause an illumination level of light emitted from the light assembly to decrease while a uniformity of the light emitted from the light assembly remains substantially the same.

9. The method of claim 8, wherein directing the light from the plurality of LEDs toward the area comprises directing the light that does not create hot spots or result in dead spots on the area.

10. The method of claim 8, wherein the area comprises a display surface of a billboard and wherein directing the light from the plurality of LEDs comprises illuminating the display surface of the billboard, the display surface extending between outer edges of the billboard.

11. The method of claim 10, wherein areas adjacent outer edges of the billboard receive a minimal amount of illumination from the plurality of LEDs.

12. The method of claim 8, wherein:

the area comprises a display surface of a billboard;

the billboard is 48 feet wide between outer edges of the billboard;

the display surface of the billboard displays media content;

directing the light from the plurality of LEDs comprises illuminating a first portion of the display surface of the billboard;

the method further comprises directing light from a second light assembly to illuminate a second portion of the display surface of the billboard; and

the light assembly and the second light assembly illuminate the display surface of the billboard between the outer edges of the billboard so media content on the display surface can be viewed using only the light assembly and the second light assembly.

13. The method of claim 12, wherein light is directed from the light assembly and the second light assembly in a manner that avoids light pollution.

14. A method of illuminating an area using a light assembly that includes a plurality of light emitting diodes (LEDs) and a plurality of optical elements, each optical element associated with one of the plurality of LEDs and each LED associated with one of the plurality of optical elements, the method comprising:

directing light from a set of LEDs of the plurality of LEDs toward the area, wherein directing the light comprises directing the light from each LED of the set of LEDs through the associated optical element such that light is directed across the area, wherein the set of LEDs includes all or some of the LEDs;

wherein each optical element of the plurality of optical elements includes:

a first element;

a second element that intersects with the first element in a region between the first element and the second element, wherein the first element and the second element are shaped so that at least one surface normal of the first element intersects with at least one surface normal of the second element and wherein the first and the second elements are configured so that the light from the associated LED exits the associated optical element through the first and the second elements; and

a third element extending beyond the region between the first element and the second element in a direction away from the associated LED; and

wherein directing the light from the set of LEDs toward the area comprises directing the light in a manner that

## 12

does not create hot spots or result in dead spots on the area regardless of whether the set of LEDs includes all of the LEDs of the plurality of LEDs or some of the LEDs of the plurality of LEDs.

15. The method of claim 14, wherein some of the plurality of LEDs fail to operate during directing the light from the plurality of LEDs and wherein the step of directing the light comprises directing the light from operative ones of the plurality of LEDs toward the area such that the light from each operative LED is directed across the area.

16. The method of claim 14, wherein the light assembly configured so that failure of one or more of the set of LEDs will cause an illumination level of light emitted from the light assembly to decrease while a uniformity of the light emitted from the light assembly remains substantially the same.

17. The method of claim 14, wherein the area comprises a display surface of a billboard and wherein directing the light from the plurality of LEDs comprises illuminating the display surface of the billboard, the display surface extending between outer edges of the billboard.

18. The method of claim 17, wherein the display surface of the billboard is illuminated in a manner that avoids light pollution.

19. The method of claim 14, wherein:

the area comprises a display surface of a billboard;

the billboard is 48 feet wide between outer edges of the billboard;

the display surface of the billboard displays media content;

directing the light from the plurality of LEDs comprises illuminating a first portion of the display surface of the billboard;

the method further comprises directing light from a second light assembly to illuminate a second portion of the display surface of the billboard; and

the light assembly and the second light assembly illuminate the display surface of the billboard between the outer edges of the billboard so media content on the display surface can be viewed using only the light assembly and the second light assembly.

20. The method of claim 19, wherein the display surface of the billboard is illuminated in a manner that avoids light pollution.

21. A method of illuminating a billboard using a first light assembly that includes a plurality of light emitting diodes (LEDs) and a plurality of optical elements and a second light assembly that includes a plurality of LEDs and a plurality of optical elements, each optical element associated with one of the plurality of LEDs and each LED associated with one of the optical elements, the method comprising:

directing light from the first light assembly toward a first portion the billboard, wherein the light is directed across the first portion of the billboard; and

directing light from the second light assembly toward a second portion the billboard, wherein the light is directed across the second portion of the billboard;

wherein each optical element of the plurality of optical elements includes:

a first element;

a second element that intersects with the first element in a region between the first element and the second element, wherein the first element and the second element are shaped so that at least one surface normal of the first element intersect with at least one surface normal of the second element and wherein the first and the second elements are configured so

13

that the light from the associated LED exits the associated optical element through the first and the second elements; and  
 a third element extending beyond the region between the first element and the second element in a direction away from the associated LED;  
 wherein the billboard is 48 feet wide between outer edges of the billboard;  
 wherein first and second portions of the billboard form a display surface that displays media content;  
 wherein the billboard includes only the first and second portions; and  
 wherein the first light assembly and the second light assembly illuminate the display surface of the billboard between the outer edges of the billboard so the media content is visible using only the first and second light assemblies.  
 22. The method of claim 21, wherein if some of the plurality of LEDs of the first light assembly fail to operate while directing light from the first light assembly, the step of directing light from the first light assembly comprises directing light from operative LEDs of the first light assembly toward the first portion of the billboard so that the media content of the first portion of the billboard is visible using only the first light assembly.

14

23. The method of claim 21, wherein some of the plurality of LEDs of the first light assembly fail to operate while directing light from the first light assembly, and wherein the step of directing light from the first light assembly comprises directing the light from operative LEDs of the first light assembly toward the first portion of the billboard so that the light from each operative LED is directed across the first portion of the billboard.

24. The method of claim 21, wherein the first light assembly configured so that failure of one or more of the LEDs of the first light assembly fail will cause an illumination level of light emitted from the first light assembly to decrease while a uniformity of the light emitted from the first light assembly remains substantially the same.

25. The method of claim 24, wherein directing the light from first light assembly comprises directing in a manner that does not create hot spots or result in dead spots on the first portion of the billboard.

26. The method of claim 21, wherein light is directed from the first light assembly and the second light assembly in a manner that avoids light pollution.

\* \* \* \* \*