



US009734737B2

(12) **United States Patent**
Auyeung et al.

(10) **Patent No.:** **US 9,734,737 B2**
(45) **Date of Patent:** ***Aug. 15, 2017**

(54) **OUTDOOR BILLBOARD WITH LIGHTING ASSEMBLIES**

(71) Applicant: **Ultravision Technologies, LLC**, Dallas, TX (US)

(72) Inventors: **David Siucheong Auyeung**, Carrollton, TX (US); **William Y. Hall**, Dallas, TX (US); **Simon Magarill**, Mountain View, CA (US)

(73) Assignee: **Ultravision Technologies, LLC**, Dallas, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 19 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/162,278**

(22) Filed: **May 23, 2016**

(65) **Prior Publication Data**

US 2016/0267823 A1 Sep. 15, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/992,680, filed on Jan. 11, 2016, now Pat. No. 9,349,307, which is a (Continued)

(51) **Int. Cl.**
F21V 1/00 (2006.01)
F21V 11/00 (2015.01)

(Continued)

(52) **U.S. Cl.**
CPC **G09F 13/22** (2013.01); **F21K 9/60** (2016.08); **F21S 6/006** (2013.01); **F21V 5/007** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC F21V 29/745; F21V 29/76; F21V 29/83; F21V 31/00; F21V 5/007; G09F 13/02; (Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,254,961 A 9/1941 Lawrence et al.
4,235,285 A 11/1980 Johnson et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2615706 A1 9/2006
CN 201925854 U 8/2011

(Continued)

OTHER PUBLICATIONS

Dieker, et al., U.S. Appl. No. 61/659,828, filed Jun. 14, 2012, "Asymmetric Area Lighting Lens with Improved Uniformity," 14 pages.

(Continued)


Primary Examiner — Alexander Garlen

(74) *Attorney, Agent, or Firm* — Slater Matsil, LLP

(57) **ABSTRACT**

A billboard includes a support structure and first and second lighting assemblies. Each lighting assembly includes a number of circuit boards arranged in a common orientation. Each circuit board of the first lighting assembly is planar and has a number of LEDs and optical elements attached thereto. The LEDs are thermally coupled to a first heat sink. The LEDs are arranged in rows on each circuit board, with each row including a number of LEDs mounted so that all of the LEDs are arranged in a common orientation. Each optical element is disposed over only one associated LED. The optical elements are arranged to direct the light across a portion of the display surface.

29 Claims, 13 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/635,907, filed on Mar. 2, 2015, now Pat. No. 9,234,642, which is a continuation of application No. 13/836,517, filed on Mar. 15, 2013, now Pat. No. 8,974,077.

- (60) Provisional application No. 61/677,346, filed on Jul. 30, 2012.

(51) **Int. Cl.**

G09F 13/22 (2006.01)
F21V 5/00 (2015.01)
F21V 29/74 (2015.01)
F21V 29/00 (2015.01)
F21V 29/15 (2015.01)
F21V 33/00 (2006.01)
G09F 15/00 (2006.01)
F21S 6/00 (2006.01)
G09F 13/02 (2006.01)
F21V 29/503 (2015.01)
F21V 29/76 (2015.01)
F21K 9/60 (2016.01)
G02B 19/00 (2006.01)
F21W 131/40 (2006.01)
F21Y 101/00 (2016.01)
F21Y 105/12 (2016.01)
F21Y 105/10 (2016.01)
F21Y 115/10 (2016.01)

(52) **U.S. Cl.**

CPC **F21V 29/00** (2013.01); **F21V 29/15** (2015.01); **F21V 29/22** (2013.01); **F21V 29/503** (2015.01); **F21V 29/74** (2015.01); **F21V 29/763** (2015.01); **F21V 33/00** (2013.01); **G09F 13/02** (2013.01); **G09F 15/00** (2013.01); **F21W 2131/40** (2013.01); **F21Y 2101/00** (2013.01); **F21Y 2105/10** (2016.08); **F21Y 2105/12** (2016.08); **F21Y 2115/10** (2016.08); **G02B 19/0014** (2013.01); **G02B 19/0028** (2013.01); **G02B 19/0061** (2013.01); **G02B 19/0066** (2013.01); **G09F 2013/222** (2013.01)

(58) **Field of Classification Search**

CPC G09F 13/22; G09F 15/00; G09F 2013/222; F21Y 2115/10; F21Y 2105/16
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,679,118 A 7/1987 Johnson et al.
 5,036,248 A 7/1991 McEwan et al.
 5,083,194 A 1/1992 Bartilson
 5,329,426 A 7/1994 Villani
 5,384,940 A 1/1995 Soule et al.
 5,803,579 A 9/1998 Turnbull et al.
 5,818,640 A 10/1998 Watanabe et al.
 5,857,767 A 1/1999 Hochstein
 5,896,093 A 4/1999 Sjobom
 5,924,788 A 7/1999 Parkyn, Jr.
 5,926,320 A 7/1999 Parkyn, Jr. et al.
 6,045,240 A 4/2000 Hochstein
 6,274,924 B1 8/2001 Carey et al.
 6,364,507 B1 4/2002 Yang
 6,428,189 B1 8/2002 Hochstein
 6,517,218 B2 2/2003 Hochstein
 6,536,923 B1 3/2003 Merz
 6,547,423 B2 4/2003 Marshall et al.
 6,582,103 B1 6/2003 Popovich

6,607,286 B2 8/2003 West et al.
 6,674,096 B2 1/2004 Sommers
 6,741,351 B2 5/2004 Marshall et al.
 6,783,269 B2 8/2004 Pashley et al.
 6,784,603 B2 8/2004 Pelka et al.
 6,799,864 B2 10/2004 Bohler et al.
 6,837,605 B2 1/2005 Reill
 6,864,513 B2 3/2005 Lin et al.
 6,896,381 B2 5/2005 Benitez et al.
 6,918,684 B2 7/2005 Harvey
 6,948,838 B2 9/2005 Kunstler
 7,006,306 B2 2/2006 Falicoff et al.
 7,009,213 B2 3/2006 Camras et al.
 7,048,400 B2 5/2006 Murasko et al.
 7,118,236 B2 10/2006 Hahm et al.
 7,144,135 B2 12/2006 Martin et al.
 7,153,002 B2 12/2006 Kim et al.
 7,159,997 B2 1/2007 Reo et al.
 7,246,931 B2 7/2007 Hsieh et al.
 7,336,195 B2 2/2008 van de Ven
 7,339,202 B2 3/2008 Chiu et al.
 7,374,306 B2 5/2008 Liu
 7,374,316 B2 5/2008 Kuo et al.
 7,375,381 B2 5/2008 Shimizu et al.
 7,390,117 B2 6/2008 Leatherdale et al.
 7,396,146 B2 7/2008 Wang
 7,410,275 B2 8/2008 Sommers et al.
 7,434,964 B1 10/2008 Zheng et al.
 7,458,706 B1 12/2008 Liu et al.
 7,478,915 B1 1/2009 Pedersen
 7,513,639 B2 4/2009 Wang
 7,513,653 B1 4/2009 Liu et al.
 7,549,777 B2 6/2009 Huang
 7,572,654 B2 8/2009 Chang
 7,618,162 B1 11/2009 Parkyn et al.
 7,618,163 B2 11/2009 Wilcox
 7,654,684 B1 2/2010 Wight et al.
 7,665,862 B2 2/2010 Villard
 7,674,019 B2 3/2010 Parkyn et al.
 7,686,469 B2 3/2010 Ruud et al.
 7,736,019 B2 6/2010 Shimada et al.
 7,748,863 B1 7/2010 Holman et al.
 7,753,561 B2 7/2010 Chaves et al.
 7,753,564 B2 7/2010 Cheng et al.
 7,841,750 B2 11/2010 Wilcox et al.
 7,857,483 B2 12/2010 Storch et al.
 7,866,851 B2 1/2011 Chang
 7,896,522 B2 3/2011 Heller et al.
 7,905,634 B2 3/2011 Agurok et al.
 7,942,559 B2 5/2011 Holder et al.
 7,952,262 B2 5/2011 Wilcox et al.
 7,959,326 B2 6/2011 Laporte
 7,980,733 B2 7/2011 Shih et al.
 7,997,761 B2 8/2011 Peck et al.
 8,002,435 B2 8/2011 Laporte
 8,035,119 B2 10/2011 Ng et al.
 8,052,303 B2 11/2011 Lo et al.
 8,056,614 B2 11/2011 Chen et al.
 8,092,049 B2 1/2012 Kinnune et al.
 8,101,434 B2 1/2012 Guillien et al.
 8,192,048 B2 6/2012 Kristoffersen et al.
 8,201,970 B2 6/2012 Wang et al.
 8,210,723 B2 7/2012 Peck et al.
 8,215,814 B2 7/2012 Marcoux
 8,235,553 B2 8/2012 Minami et al.
 8,246,219 B2 8/2012 Teng et al.
 8,262,252 B2 9/2012 Bergman et al.
 8,267,551 B2 9/2012 Lin
 8,273,158 B2 9/2012 Jarrier et al.
 8,308,331 B2 11/2012 Loh
 8,310,158 B2 11/2012 Coplin et al.
 8,330,387 B2 12/2012 York et al.
 8,338,841 B2 12/2012 Lerman et al.
 8,348,461 B2 1/2013 Wilcox et al.
 8,360,613 B2 1/2013 Little, Jr.
 8,376,585 B2 2/2013 Noeth
 8,408,737 B2 4/2013 Wright et al.
 8,454,194 B2 6/2013 Liu
 8,454,215 B2 6/2013 Bollmann

(56)

References Cited

U.S. PATENT DOCUMENTS

8,465,178	B2	6/2013	Wilcox et al.
8,469,552	B2	6/2013	Moeller
8,476,650	B2	7/2013	Liao
8,547,023	B2	10/2013	Chang et al.
8,567,987	B2	10/2013	Wronski
8,573,815	B2	11/2013	Mallory et al.
8,577,434	B2	11/2013	Merchant et al.
8,585,253	B2	11/2013	Duong et al.
8,602,599	B2	12/2013	Zimmer et al.
8,610,357	B2	12/2013	Stoll et al.
8,622,574	B2	1/2014	Liu
8,628,217	B2	1/2014	Moshtagh
8,632,225	B2	1/2014	Koo et al.
8,651,693	B2	2/2014	Josefowicz et al.
8,662,704	B2	3/2014	Carraher et al.
8,733,981	B2	5/2014	Jiang et al.
8,789,967	B2	7/2014	Gordin et al.
8,801,221	B2	8/2014	Lin et al.
8,824,125	B1	9/2014	Cox et al.
8,835,958	B2	9/2014	Hsieh
8,858,024	B2	10/2014	Wu et al.
8,864,344	B2	10/2014	Jiang et al.
8,870,410	B2	10/2014	Auyeung
8,870,413	B2	10/2014	Auyeung
8,876,325	B2	11/2014	Lu et al.
8,922,734	B2	12/2014	Lin
8,931,934	B2	1/2015	Lin
9,046,293	B2	6/2015	Pelka et al.
9,182,101	B2	11/2015	Nakamura et al.
2003/0099105	A1	5/2003	Watson
2004/0004827	A1	1/2004	Guest
2005/0018428	A1	1/2005	Harvey
2005/0047170	A1	3/2005	Hilburger et al.
2005/0151141	A1	7/2005	Grotsch et al.
2006/0076568	A1	4/2006	Keller et al.
2006/0081863	A1	4/2006	Kim et al.
2006/0146531	A1	7/2006	Reo et al.
2006/0245083	A1	11/2006	Chou et al.
2007/0201225	A1	8/2007	Holder et al.
2007/0257270	A1	11/2007	Lu et al.
2007/0279904	A1	12/2007	Tasch et al.
2008/0073663	A1	3/2008	Chang
2008/0080179	A1	4/2008	Giorgi
2008/0084693	A1	4/2008	Shimada et al.
2008/0084701	A1	4/2008	Van De Ven et al.
2008/0180014	A1	7/2008	Tzeng et al.
2008/0212319	A1	9/2008	Klipstein
2008/0247173	A1	10/2008	Danek et al.
2008/0273327	A1	11/2008	Wilcox et al.
2009/0097265	A1	4/2009	Sun et al.
2009/0154158	A1	6/2009	Cheng et al.
2009/0180281	A1	7/2009	Ahland, III et al.
2009/0256459	A1	10/2009	Liu
2009/0262532	A1	10/2009	Wilcox et al.
2009/0267474	A1	10/2009	Zhou et al.
2009/0273933	A1	11/2009	Woodward et al.
2009/0290338	A1	11/2009	Heller et al.
2009/0296407	A1	12/2009	Bailey
2009/0303711	A1	12/2009	Remus et al.
2010/0008094	A1	1/2010	Shuai et al.
2010/0014289	A1	1/2010	Thomas et al.
2010/0014290	A1	1/2010	Wilcox
2010/0027271	A1	2/2010	Wilcox et al.
2010/0039810	A1	2/2010	Holder et al.
2010/0046225	A1	2/2010	Zheng
2010/0085774	A1	4/2010	Park
2010/0118531	A1	5/2010	Montagne
2010/0128488	A1	5/2010	Marcoux
2010/0149801	A1	6/2010	Lo et al.
2010/0172135	A1	7/2010	Holder et al.
2010/0195330	A1	8/2010	Schaefer et al.
2010/0232155	A1	9/2010	Wang
2010/0296267	A1	11/2010	Yu et al.
2010/0296283	A1	11/2010	Taskar et al.
2010/0302785	A1	12/2010	Zhou
2010/0302786	A1	12/2010	Wilcox et al.
2011/0002120	A1	1/2011	Song et al.
2011/0031887	A1	2/2011	Stoll et al.
2011/0038151	A1	2/2011	Carraher et al.
2011/0063857	A1	3/2011	Li et al.
2011/0068708	A1	3/2011	Coplin et al.
2011/0075409	A1	3/2011	Zheng
2011/0149548	A1	6/2011	Yang et al.
2011/0170283	A1	7/2011	Chan
2011/0205744	A1	8/2011	Kim
2011/0219650	A1	9/2011	Wright et al.
2011/0242807	A1	10/2011	Little, Jr. et al.
2011/0242816	A1	10/2011	Chowdhury et al.
2011/0278633	A1	11/2011	Clifford
2011/0280003	A1	11/2011	Hsu et al.
2012/0014115	A1	1/2012	Park et al.
2012/0043560	A1	2/2012	Wu et al.
2012/0080699	A1	4/2012	Chowdhury et al.
2012/0087125	A1	4/2012	Liu
2012/0163005	A1	6/2012	Liu
2012/0201022	A1	8/2012	van de Ven et al.
2012/0250321	A1	10/2012	Blincoe et al.
2012/0307495	A1	12/2012	Shih
2013/0010468	A1	1/2013	Stoll et al.
2013/0057861	A1	3/2013	Ishii et al.
2013/0063970	A1	3/2013	Oh
2013/0135861	A1	5/2013	Chen et al.
2013/0163005	A1	6/2013	Tsang
2013/0193850	A1	8/2013	Demuyne et al.
2013/0270585	A1	10/2013	Mei et al.
2013/0291414	A1	11/2013	Cegnar
2013/0335979	A1	12/2013	Lauret et al.
2014/0016326	A1	1/2014	Dieker et al.
2014/0029253	A1	1/2014	Auyeung
2014/0029259	A1	1/2014	Auyeung
2014/0029274	A1	1/2014	Auyeung
2014/0085905	A1	3/2014	Broughton
2014/0104851	A1	4/2014	Auyeung
2014/0112007	A1	4/2014	Auyeung
2014/0168963	A1	6/2014	Stone et al.
2014/0168998	A1	6/2014	Tang et al.
2014/0268761	A1	9/2014	Raleigh et al.
2014/0373348	A1	12/2014	Li

FOREIGN PATENT DOCUMENTS

CN	202629916	U	12/2012
CN	102889549	A	1/2013
DE	202005016441	U1	2/2007
EP	1078301	A1	2/2001
EP	1528603	A2	5/2005
EP	1988576	A1	11/2008
EP	2039985	A2	3/2009
EP	2092859	A1	8/2009
EP	2172696	A1	4/2010
EP	2378337	A2	10/2011
EP	2416062	A2	2/2012
EP	2448021	A2	5/2012
EP	2553331	A1	2/2013
EP	2622267	A1	8/2013
GB	2421584	A	6/2006
JP	2003195790	A	7/2003
JP	2005024706	A	1/2005
JP	2005217094	A	8/2005
JP	2005327820	A	11/2005
JP	2007035951	A	2/2007
JP	2007281260	A	10/2007
JP	2011060575	A	3/2011
JP	2012054115	A	3/2012
JP	2012113276	A	6/2012
WO	2004051223	A2	6/2004
WO	2006033770	A2	3/2006
WO	2006126123	A1	11/2006
WO	2008047335	A1	4/2008
WO	2008122941	A1	10/2008
WO	2009064607	A1	5/2009
WO	2010010494	A1	1/2010
WO	2010033545	A2	3/2010
WO	2010130732	A1	11/2010

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2011041813	A1	4/2011
WO	2011042837	A1	4/2011
WO	2011123267	A1	10/2011
WO	2012021718	A1	2/2012
WO	2012095242	A1	7/2012
WO	2012121718	A1	9/2012

OTHER PUBLICATIONS

Whang, et al., "Designing Uniform Illumination Systems by Surface-Tailored Lens and Configurations of LED Arrays," IEEE 2009, Journal of Display Technology, vol. 5, No. 3, Mar. 2009, pp. 94-103.

Lee, S., "How to Select a Heat Sink," <http://www.electronics-cooling.com/1995/06/how-to-select-a-heat-sink/>, Jun. 1, 1995, pp. 1-10.

Steigerwald, et al., "Illumination with Solid State Lighting Technology," IEEE Journal on Selected Topics in Quantum Electronics, vol. 8, No. 2, Mar./Apr. 2002, pp. 310-320.

Kim, Yu-Sin, et al., "Development of a Numerical Model for the Luminous Intensity Distribution of a Planar Prism LED Luminaire for Applying an Optimization Algorithm," Luekos, vol. 9, No. 1, Jul. 2012, pp. 57-72.

Lee, Hsiao-Wen, et al., "Improvement of Illumination Uniformity for LED Flat Panel Light by Using Micro-Secondary Lens Array," Optics Express, vol. 20, No. S6, Nov. 5, 2012, 11 pages.

Liu, Peng, et al., "Optimized Design of LED Freeform Lens for Uniform Circular Illumination," Journal of Zhejiang University—Science C (Computers & Electronics), 2012, pp. 929-936.

Office Action Summary received in U.S. Appl. No. 14/630,500, mailed Dec. 31, 2015, 65 pages.

Parkyn, William A., "Segmented Illumination Lenses for Steplighting and Wall-Washing," SPIE Conference on Current Development in Optical Design and Optical Engineering VIII, Denver, Colorado, Jul. 1999, SPIE vol. 3779, pp. 363-370.

Cheng, et al., "The Research of LED Arrays for Uniform Illumination," Advances in Information Sciences and Service Sciences (AISS), vol. 4, No. 10, Jun. 2012, pp. 174-182.

Arik, M., "Thermal Management of LEDs: Package to System," Third International Conference on Solid State Lighting, Proc. of SPIE, vol. 5187, Jan. 21, 2012, pp. 64-75.

Tracepro, "LED Reflector and Lens Simulation Using TracePro Illumination Design and Analysis Software," White Paper, Oct. 2013, 11 pages.

Hubbell Lighting, "Universal Lighting Technologies Invention Disclosure," Jun. 14, 2012, 15 pages.

Adaptive Micro Systems, LLC, "Signs—Sealed and Delivered! Adaptive's Approach to Heat Management," Mar. 2008, 2 pages.

"Advanced Lighting Guidelines," 2001 Edition, New Buildings Institute, Inc., Jul. 20, 2001, 394 pages.

Barco, "DB-x20 Digital Billboard Out-of-Home Media LED Screen," Apr. 2009, 6 pages.

Batinsey, J., "Outdoor Lighting Ordinance Guide," Jun. 2006, 17 pages.

Chang, R. et al., "LED Backlight Module by Lightguide-Diffusive Component," Journal of Display Technology, vol. 8, No. 2, Feb. 2012, pp. 79-86.

Chen, C. et al., "P-72: Inclined LED Array for Large-Sized Backlight System," Society for Information Display, International Symposium, Digest of Technical Papers, SID 05 Digest, May 2005, pp. 558-561.

"Unified Development Code," Chapter 10 of the Tyler Code of Ordinances, City of Tyler, Apr. 23, 2008, 378 pages.

Defendants Invalidity Contentions, Appendix A, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-19.

Defendants Invalidity Contentions, ExhibitA01, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-80.

Defendants Invalidity Contentions, ExhibitA02, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-74.

Defendants Invalidity Contentions, ExhibitA03, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-52.

Defendants Invalidity Contentions, ExhibitA04, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-53.

Defendants Invalidity Contentions, ExhibitB01, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-34.

Defendants Invalidity Contentions, ExhibitB02, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-36.

Defendants Invalidity Contentions, ExhibitB03, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-21.

Defendants Invalidity Contentions, ExhibitB04, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-27.

Defendants Invalidity Contentions, ExhibitC01, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-52.

Defendants Invalidity Contentions, ExhibitC02, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-67.

Defendants Invalidity Contentions, ExhibitC03, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-35.

Defendants Invalidity Contentions, ExhibitC04, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-87.

Defendants Invalidity Contentions, ExhibitC05, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-51.

Defendants Invalidity Contentions, ExhibitC06, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-79.

Defendants Invalidity Contentions, ExhibitD01, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-109.

Defendants Invalidity Contentions, ExhibitD02, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-186.

Defendants Invalidity Contentions, ExhibitD03, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-133.

Defendants Invalidity Contentions, ExhibitD04, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-111.

Defendants Invalidity Contentions, ExhibitD05, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-133.

Defendants Invalidity Contentions, ExhibitD06, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-135.

Defendants Invalidity Contentions, ExhibitE01, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-169.

Defendants Invalidity Contentions, ExhibitE02, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-192.

Defendants Invalidity Contentions, ExhibitE03, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-443.

Defendants Invalidity Contentions, ExhibitE04, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-171.

Defendants Invalidity Contentions, ExhibitF01, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-34.

(56)

References Cited

OTHER PUBLICATIONS

- Defendants Invalidity Contentions, ExhibitF02, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-13.
- Defendants Invalidity Contentions, ExhibitF03, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-100.
- Defendants Invalidity Contentions, ExhibitG01, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-30.
- Defendants Invalidity Contentions, ExhibitG02, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-11.
- Defendants Invalidity Contentions, ExhibitG03, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-94.
- Defendants Invalidity Contentions, ExhibitH01 (redacted), *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-60.
- Defendants Invalidity Contentions, ExhibitH02 (redacted), *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-26.
- Defendants Invalidity Contentions, ExhibitH03 (redacted), *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-71.
- Defendants Invalidity Contentions, ExhibitH04 (redacted), *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-151.
- Defendants Invalidity Contentions, ExhibitH05 (redacted), *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-181.
- Defendants Invalidity Contentions, ExhibitI01 (redacted), *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-168.
- Deepa, R. et al., "Modeling and Simulation of Multielement LED Source," The Illuminating Engineering Institute of Japan, Journal of Light & Visual Environment, vol. 35, No. 1, Jun. 21, 2011, pp. 34-41.
- Deepa, R. et al., Optimization of multi-element LED source for uniform illumination of plane surface, Optics Society of America, Optics Express, vol. 19, No. S4, Jul. 4, 2011, pp. A639-A648.
- Design & Engineering Services, "Advanced Lighting Systems for Externally Lit Billboards," ET 08.12 Report, Southern California Edison, Jan. 4, 2010, 58 pages.
- Ding, Y., "Freeform LED lens for uniform illumination," Optics Express, vol. 16, No. 17, Aug. 18, 2008, 9 pages.
- Huang, K. et al., "Free-form lens design for LED indoor illumination," Proc. of SPIE, vol. 7852, Nov. 15, 2010, pp. 78521 D-1-78521 D-8.
- "The Lighting Handbook," 12-18, IES 10th Edition, Dec. 6, 2011, 1 page.
- "The Lighting Handbook," 8-17, IES 10th Edition, Dec. 6, 2011, 2 pages.
- Jeon, H. et al., Illuminance Distribution and Photosynthetic Photon Flux Density Characteristics of LED Lighting with Periodic Lattice Arrangements, Transactions on Electrical and Electronic Materials, vol. 13, No. 1, Feb. 25, 2012, pp. 16-18.
- Jiang, J., "Optical design of a freeform TIR lens for LED street-light," Optik—International Journal for Light and Electron Optics, vol. 121, Issue 19, Oct. 2010, pp. 1761-1765.
- Defendants Corrected Joint Invalidity Contentions, *Ultravision Technologies v. Lamar et al.*, Ed. Texas, Case No. 2:16-cv-374, Sep. 9, 2016, pp. 1-108.
- Keller, A., "Signs of the Times," Floridatrend.com, Dec. 2011, pp. 50-53.
- Lakkio, O., "Winning the Optical Challenges in LED Street Lighting," Digi-Key, May 27, 2011, 5 pages.
- "Billie—The Bright Answer for Billboard Lighting," Ledil Product Release, Dec. 8, 2013, 2 pages.
- "Ledil Standard Optics for Osram LEDs," Ledil, Jan. 2011, 60 pages.
- "Strada 6in1 Module for Streeting Lighting," Ledil, 2010, 1 page, <<http://ledil.fi/sites/default/files/Documents/Technical/Articles/Article_2.pdf>>.
- Ledil, "Who is Ledil?," www.ledil.com, Mar. 22, 2011, 17 pages.
- Ledil, "Who is Ledil?," www.ledil.com, May 22, 2011, 68 pages.
- Lee, S. et al., "Driving Performance and Digital Billboards Final Report," Virginia Tech Transportation Institute, Center for Automotive Safety Research, Mar. 22, 2007, 90 pages.
- Lighting Solutions Techzone Magazine, "Look Inside Today's Lighting Technology," Digi-Key Corporation, TZL112.US, Jun. 7, 2011, 76 pages.
- Lo, Y. et al., "Optical Design of a Butterfly Lens for a Street Light Based on a Double-Cluster LED," Microelectronics Reliability, vol. 52, May 2011, pp. 889-893.
- Luminautics, "LED Display Primer," 2011, pp. 1-21.
- Luo, X. et al., "Automated Optimization of an Aspheric Light-Emitting Diode Lens for Uniform Illumination," Applied Optics, vol. 50, No. 20, Jul. 2011, pp. 3412-3418.
- Moreno, I., "Configuration of LED Arrays for Uniform Illumination," Proc. of SPIE, vol. 5622, Oct. 2004, pp. 713-718.
- "LED Ad-Poster Billboard Luminaire," Neptun, Jan. 2012, 1 page.
- "LED Ad-Poster Billboard Luminaire," Neptun, May 25, 2011, 1 page.
- "Street Lighting with LED Lights Sources Application Note," OSRAM Opto Semiconductors, Jan. 2009, pp. 1-10.
- Qin, Z. et al., "Analysis of Condition for Uniform Lighting Generated by Array of Light Emitting Diodes with Large View Angle," Optics Express, vol. 18, No. 16, Aug. 2010, pp. 17460-17476.
- Ramane, D. et al., "Automated Test Jig for Uniformity Evaluation of Luminaries," IJAET, vol. 3, No. 1, Mar. 2012, pp. 41-47.
- "Starbeam," Thorlux Lighting, Brochure, Aug. 2012, 8 pages.
- "Starbeam," Thorlux Lighting, Brochure, Jul. 2015, 4 pages.
- "Starbeam," Thorlux Lighting, Brochure, Mar. 2014, 16 pages.
- "Starbeam," Thorlux Lighting, Technical Information, Mar. 2014, 10 pages.
- "Starflood," Thorlux Lighting, Brochure, Mar. 2016, 16 pages.
- "Starflood; High performance mini LED floodlights," Thorlux Lighting, Retrieved Jul. 21, 2016, 16 pages, <<<http://www.thorlux.com/luminaires/starflood>>>.
- "General Catalog—2012," Thorlux Lighting, Dec. 2012, 164 pages.
- Tsai, J. et al., "LED Backlight Module by a Lightguide-Diffusive Component With Tetrahedron Reflector Array," J. Display Tech., vol. 8, No. 6, Jun. 2012, pp. 321-328.
- Wang, K. et al., "Freeform LED Lens for Rectangularly Prescribed Illumination," J. Opt. A: Pure Appl. Opt., No. 11, Aug. 2009, 105501, 10 pages.
- Wang, K. et al., "New reversing design method for LED uniform illumination," Optics Express, vol. 19, Issue S4, Jul. 1, 2011, pp. A830-A840.
- West, R.S. et al., "43.4: High Brightness Direct LED Backlight for LCD-TV," SID 03 Digest, May 2003, 4 pages.
- Wu, D. et al., "Freeform Lens Design for Uniform Illumination with Extended Source," 2011 In▼ I Conf. Elecs. Packaging Tech. & High Density Packaging, Aug. 2011, pp. 1085-1089.
- Wu, R. et al., "Optimization Design of Irradiance Array for LED Uniform Rectangular Illumination," Applied Optics, vol. 1, No. 13, May 2012, pp. 2257-2263.
- Zhenrong, Z. et al., "Freeform Surface Lens for LED Uniform Illumination," Applied Optics, vol. 48, No. 35, Dec. 2009, pp. 6627-6634.
- Zhu, Z. et al., "Uniform Illumination Design by Configuration of LED Array and Diffuse Reflection Surface for Color Vision Application," J. Display tech, vol. 7, No. 2, Feb. 2011, pp. 84-89.
- LED Professional Review, Issue 17, Jan./Feb. 2010, 52 pages.
- LED Professional Review, Issue 18, Mar./Apr. 2010, 64 pages.
- LED Professional Review, Issue 19, May/Jun. 2010, 64 pages.
- LED Professional Review, Issue 20, Jul./Aug. 2010, 48 pages.
- LED Professional Review, Issue 21, Sep./Oct. 2010, 64 pages.
- LED Professional Review, Issue 22, Nov./Dec. 2010, 60 pages.

(56)

References Cited

OTHER PUBLICATIONS

P.R. 4-3 Joint Claim Construction and Prehearing Statement, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jan. 27, 2017, pp. 1-20.

Defendant Irvin International, Inc.'s Answer, Affirmative Defenses, and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 6, 2016, pp. 1-41 (see p. 39).

Lamar's First Amended Answer and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 8, 2016, pp. 1-61 (see p. 53).

Defendant American Lighting Technologies, Inc. D/B/A Lighting Technologies' Amended Answer, Affirmative Defenses and Counterclaims to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 27, 2016, pp. 1-43 (see p. 38).

Defendant American Lighting Technologies, Inc. D/B/A Lighting Technologies' Answer and Affirmative Defenses to Plaintiff's Complaint, *Ultravision Technologies v. Lamar et al.*, E.D. Texas, Case No. 2:16-cv-374, filed Jun. 6, 2016, pp. 1-37.




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2




FIG. 3B




FIG. 3A




FIG. 3C




FIG. 4B








FIG. 4A






FIG. 6A





FIG. 6B






FIG. 7A





FIG. 7B






FIG. 8B




FIG. 8C




FIG. 8G




FIG. 8F




FIG. 8E




FIG. 8D




FIG. 8J




FIG. 8I





FIG. 8H



1

OUTDOOR BILLBOARD WITH LIGHTING ASSEMBLIES

This is a continuation of Ser. No. 14/992,680, filed Jan. 11, 2016, which is a continuation of U.S. patent application Ser. No. 14/635,907, filed Mar. 2, 2015, which is a continuation of U.S. patent application Ser. No. 13/836,517, filed Mar. 15, 2013, which claims the benefit of U.S. Provisional Application No. 61/677,346, filed on Jul. 30, 2012, which applications are hereby incorporated herein by reference.

The following patents and applications are related:

U.S. Pat. Appl. No. 61/677,340, filed Jul. 20, 2012
 U.S. Pat. Appl. No. 61/677,346, filed Jul. 30, 2012
 U.S. Pat. Appl. No. 61/677,352, filed Jul. 30, 2012
 U.S. patent application Ser. No. 13/836,517, filed Mar. 15, 2013 (now U.S. Pat. No. 8,974,077)
 U.S. patent application Ser. No. 13/836,612, filed Mar. 15, 2013 (now U.S. Pat. No. 8,870,410)
 U.S. patent application Ser. No. 13/836,710, filed Mar. 15, 2013 (now U.S. Pat. No. 9,062,873)
 U.S. patent application Ser. No. 14/137,306, filed Dec. 30, 2013 (now U.S. Pat. No. 8,985,806)
 U.S. patent application Ser. No. 14/137,343, filed Dec. 20, 2013 (now U.S. Pat. No. 8,870,413)
 U.S. patent application Ser. No. 14/137,380, filed Dec. 20, 2013 (now U.S. Pat. No. 9,068,738)
 U.S. patent application Ser. No. 14/630,500, filed Feb. 24, 2015 (co-pending)
 U.S. patent application Ser. No. 14/635,907, filed Mar. 2, 2015 (now U.S. Pat. No. 9,234,642)
 U.S. patent application Ser. No. 14/706,634, filed May 7, 2015 (now U.S. Pat. No. 9,212,803)
 U.S. patent application Ser. No. 14/968,520, filed Dec. 14, 2015 (co-pending)
 U.S. patent application Ser. No. 14/992,690, filed Jan. 11, 2016 (now U.S. Pat. No. 9,349,307)

TECHNICAL FIELD

The following disclosure relates to lighting systems and, more particularly, to lighting systems using light emitting diodes to externally illuminate signs.

SUMMARY

The present invention, in one aspect thereof, comprises a back panel for use in a light emitting diode (LED) lighting assembly. An extruded substrate formed of a thermally conductive material is provided, the substrate having a plurality of fins extending from a first side of the substrate, each of the fins having a substantially rectangular shape oriented so that a longitudinal axis of the fin is substantially parallel to a longitudinal axis of the substrate. At least some of the fins include a hole formed through the fin to enable heated air to rise through the fins. A plurality of LEDs are mounted on a second side of the substrate, and oriented in a longitudinal orientation with the fins oriented parallel to the bottom edge of a surface to be illuminated, such that heat rises perpendicular to the surface of the fin.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding, reference is now made to the following description taken in conjunction with the accompanying Drawings in which:

2

FIG. 1A illustrates one embodiment of a billboard that may be externally lighted by one or more lighting assemblies;

FIGS. 1B-1D illustrate embodiments of angular positions of the lighting assembly of FIG. 1 relative to the billboard;

FIG. 2 illustrates one embodiment of a lighting assembly that may be used to light the billboard of FIG. 1;

FIGS. 3A and 3B illustrate one embodiment of a back panel that may be used in the lighting assembly of FIG. 2;

FIG. 3C illustrates one embodiment of the back panel of FIGS. 3A and 3B with a light panel and an optics panel that may also be used in the lighting assembly of FIG. 2;

FIGS. 4A and 4B illustrate one embodiment of a light panel that may be used with the lighting assembly of FIG. 2;

FIGS. 5A, 5B, 5C and 5D illustrate one embodiment of an optics panel that may be used with the lighting assembly of FIG. 2;

FIGS. 6A-6C illustrate a more detailed embodiment of the lighting assembly of FIG. 2;

FIGS. 7A and 7B illustrate an embodiment of a back panel that may be used with the lighting assembly of FIGS. 6A-6C;

FIG. 8A illustrates an embodiment of an LED assembly and an optics panel that may be used with the lighting assembly of FIG. 6;

FIGS. 8B-8J illustrates embodiments of the optics panel of FIG. 8A and optical elements that may be used to form part of the optics panel; and

FIG. 9 illustrates a more detailed embodiment of the lighting assembly of FIG. 2.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Billboards, such as those commonly used for advertising in cities and along roads, often have a picture and/or text that must be externally illuminated to be visible in low-light conditions. As technology has advanced and introduced new lighting devices such as the light emitting diode (LED), such advances have been applied to billboards. However, current lighting designs have limitations and improvements are needed. Although billboards are used herein for purposes of example, it is understood that the present disclosure may be applied to lighting for any type of sign that is externally illuminated.

Referring to FIG. 1A, one embodiment of a billboard **100** is illustrated. The billboard **100** includes a surface **102** onto which a picture and/or text may be painted, mounted, or otherwise affixed. The surface **102** may be any size, such as a commonly used size having a width of forty-eight feet wide and a height of fourteen feet. The surface **102** may be provided by placing a backing material on a frame **104** made of steel and/or other materials. The frame **104** may be mounted on one or more support poles **106**, which may be considered part of the frame **104** or separate from the frame **104**. The billboard **100** may include a walkway or other support structure **108** that enables the surface **102** to be more easily accessed.

One or more lighting assemblies **110** may be coupled to the walkway **108** (e.g., to a safety rail or to the walkway itself) and/or to another structural member of the billboard **100** to illuminate some or all of the surface **102** in low light conditions. The lighting assembly **110** may be mounted at or near a top edge **112** of the billboard **100**, a bottom edge **114** of the billboard **100**, a right edge **116** of the billboard **100**, and/or a bottom edge **118** of the billboard **100**. The lighting

assembly **110** may be centered (e.g., located in approximately the center of the billboard **100**) or off center as illustrated in FIG. 1A.

With additional reference to FIGS. 1B-1D, a surface **120** of the lighting assembly **110** may be parallel with respect to the surface **102** of the billboard **100** (FIG. 1B), may be perpendicular with respect to the surface **102** (FIG. 1C), or may be angled with respect to the surface **102** (FIG. 1D). It is understood that the lighting assembly **110** may be placed in many different orientations and locations relative to the billboard **100** and to one another, and the illustrated positions are only for purposes of example. Furthermore, it is understood that references to “top,” “bottom,” “left,” and “right” are used in the present disclosure for purposes of description and do not necessarily denote a fixed position. For example, the billboard **100** may be turned on end, and the referenced “top,” “bottom,” “left,” and “right” edges may still be readily identifiable although the “top” edge would be the “left” edge or the “right” edge.

One problem with current lighting technology is that it can be difficult to direct light only onto the surface **102** and even more difficult to do so evenly. This may be due partly to the placement of the lighting assembly **110**, as shown in FIGS. 1B-1D. As the lighting assembly **110** is off center relative to the surface **102**, light emitted from the lighting assembly **110** may not evenly strike the surface **102**. One problem with uneven illumination is that certain parts of the surface **102** may be more brightly illuminated than other parts. This creates “hot spots” that may be undesirable. Attempting to evenly illuminate the surface **102** may cause light to be directed past the edges **112**, **114**, **116**, and **118** as attempts are made to balance out hot spots in particular areas. However, light that does not strike the surface **102** is wasted and may create problems (e.g., light pollution), as well as waste illumination that could be used for the surface **102**.

In addition to the difficulties of evenly illuminating the surface **102**, the use of LEDs in an exterior lighting environment involves issues such as heat dissipation and protecting the LEDs against environmental conditions such as moisture. The presence of moving mechanical features such as fans that may be used to provide increased airflow for cooling may create additional reliability problems. Due to the difficulty and expense of replacing and/or repairing the lighting assembly **110** in combination with the desire to provide consistent lighting while minimizing downtime, such issues should be addressed in a manner that enhances reliability and uptime.

Referring to FIG. 2, one embodiment of a lighting assembly **200** is illustrated. The lighting assembly **200** provides a more detailed embodiment of the lighting assembly **110** of FIG. 1. The lighting assembly **200** includes a back panel **202**, a light panel **204** (e.g., a printed circuit board (PCB)) having a plurality of LEDs (not shown) mounted thereon, and an optics panel **206**. As will be described below in more detailed examples, light from the LEDs of the light panel **204** may be directed by the optics panel **206** to illuminate the surface **102** of the billboard **100** of FIG. 1. The back panel **202** may be configured to serve as a supporting substrate for the light panel **204** and optics panel **206**, as well as to dissipate heat produced by the LEDs.

It is understood that any of the back panel **202**, light panel **204**, and optics panel **206** may actually be two or more physical substrates rather than a single panel as illustrated in FIG. 2. Furthermore, it is understood that there may be additional panels positioned behind the back panel **202**, in

front of the optics panel **206**, and/or between the back panel **202** and light panel **204** and/or between the light panel **204** and optics panel **206**.

Referring to FIGS. 3A-3C, one embodiment of the back panel **202** is illustrated with a front surface **302** and a back surface **304**. The back panel **202** includes a top edge **306**, a bottom edge **308**, a right edge **310**, and a left edge **312**. The panel **202** may be formed of one or more thermally conductive materials (e.g., aluminum) and/or other materials.

The front surface **302** provides a mounting surface for the light panel **204**. In some embodiments, the front surface **302** of the panel **202** may include one or more protrusions **314a** and **314b** that are substantially parallel to the top edge **306**. The protrusions **314a** and **314b** may be configured to protect the light panel **204** from moisture. Although only two protrusions **314a** and **314b** are illustrated, it is understood that a single protrusion may be provided or three or more protrusions may be provided. Furthermore, such protrusions may vary in length, shape (e.g., may have angled or curved surfaces), orientation, and/or location on the front surface **302**.

Referring specifically to FIG. 3C, a light panel **204** and an optical panel **206** may be mounted under the protrusion **314a** (FIG. 3C). Moisture running down the front surface **302** in the direction of arrow **316** may strike the protrusion **314a** and be directed away from the light panel **204** and optical panel **206** as shown by arrow **318**. Although not shown, moisture may also be directed length down the protrusion **314a**. Accordingly, protrusion **314a** may serve as a gutter and aid in directing moisture away from a joint **320** where the optical panel **206** abuts the front surface **302**. This may be beneficial even when a moisture resistant compound is used to seal the joint **320**. In embodiments where there are multiple light panels **204** arranged vertically on the front surface **302**, there may be a protrusion positioned above each light panel **204**. For example, the protrusion **314a** may be positioned directly above one light panel **204** and the protrusion **314b** may be positioned directly above another light panel **204**.

Referring specifically to FIG. 3B, the back surface **304** may be configured to increase heat dissipation. For example, the back surface **304** may be configured with a heat sink provided by fins **322a-322N**, where N denotes a total number of fins. The fins **322a-322N** increase the surface area of the back surface **304**, thereby providing for additional heat dissipation to the surrounding air. The fins **322a-322N** may be formed as part of the panel **202** or may be otherwise coupled to the panel **202** (e.g., may be part of a discrete heat sink that is coupled to the back surface **304**). Some or all of the fins **322a-322N** may be angled, as shown by fins **322a** and **322b**. In some embodiments, holes (not shown) may be provided in some or all of the fins **322a-322N** to aid in air circulation. In such embodiments, the holes may cause a chimney effect in which heated air rises through the holes and is replaced by cooler air. This may be particularly effective in environments where natural air movement is limited.

Referring to FIGS. 4A and 4B, one embodiment of a single PCB **402** of the light panel **204** is illustrated. In the present example, the light panel **204** may include multiple PCBs **402**, although it is understood that any number of PCBs may be used based on design issues such as the amount of illumination needed, the amount of illumination provided by a single PCB **402**, the size of the surface **102** of the billboard **100**, and/or other factors. As shown in the present embodiment with a substantially rectangular cross-

5

section, the PCB 402 includes a front surface 404, a back surface 406, a top edge 408, a bottom edge 410, a right edge 412, and a left edge 414.

The PCB 402 may include one or more strings of LEDs 416, with multiple LEDs 416 in a string. For example, a string may include eight LEDs 416 and each PCB 402 may include two strings for a total of sixteen LEDs 416. In this configuration, a light panel 204 having eight PCBs 402 would include ninety-six LEDs 416. It is understood that although the PCBs 402 are shown as being substantially identical, they may be different in terms of size, shape, and other factors for a single light panel 204.

In the present example, the LEDs 416 are surface mounted, but it is understood that the LEDs 416 may be coupled to the panel 204 using through hole or another coupling process. The surface mounted configuration may ensure that a maximum surface area of each LED 416 is in contact with the PCB 402, which is in turn in contact with the back panel 202 responsible for heat dissipation. Each string of LEDs may receive a constant current with the current divided evenly among the LEDs 416.

Referring to FIGS. 5A, 5B, 5C and 5D, one embodiment of a single lens panel 500 of the optics panel 206 is illustrated. In the present example, the optics panel 206 may include multiple lens panels 500, although it is understood that any number of lens panels may be used based on design issues such as the number, arrangement, and orientation of the LEDs 416, the size of the surface 102, and/or other factors. As shown in the present embodiment with a substantially rectangular cross-section that is configured for use with the PCB 402 of FIG. 4, a single lens panel 500 includes a front surface 502, a back surface 504, a top side 506, a bottom side 508, a right side 510, and a left side 512. The sides 506, 508, 510, and 512 may form a cavity into which the PCB 402 may fit, thereby providing protection for the PCB 402 from environmental conditions such as moisture.

The lens panel 500 may include a beveled or angled top side 506 and/or bottom side 508 as illustrated in FIG. 5B. The beveling/angling may aid in preventing moisture from reaching the PCB 402 under the lens panel 500, as water will more readily flow from the area of the joint 320 (FIG. 3C) due to the angled surface than if the top side 506 was relatively flat.

The lens panel 500 may include multiple optical elements 514. A single optical element 514 may be provided for each LED 416, a single optical element 514 may be provided for multiple LEDs 416, and/or multiple optical elements 514 may be provided for a single LED 416. In some embodiments, the optical elements 514 may be provided by a single multi-layer optical element system provided by the lens panel 500.

In the present example, the optical elements 514 are configured so that the light emitted from each LED 416 is projected onto the entire surface 102 of the billboard 100. In other words, if all other LEDs 416 were switched off except for a single LED 416, the entire surface 102 would be illuminated at the level of illumination provided by the single LED 416. In one embodiment, the rectangular target area of the surface 102 would be evenly illuminated by the LED 416, while areas beyond the edges 112, 114, 116, and 118 would receive no illumination at all or at least a minimal amount of illumination from the LED 416. What is meant by “evenly” is that the illumination with a uniformity that achieves a 3:1 ratio of the average illumination to the minimum. Thus, by designing the lens in such a manner, when all LEDs are operating, the light from the collective thereof will illuminate the surface at the 3:1 ratio. When one

6

or more LEDs fail, the overall illumination decreases, but the uniformity maintains the same uniformity. Also, as described hereinabove, the “surface” refers to the surface that is associated with a particular LED panel. It may be that an overall illuminated surface is segmented and multiple panels are provided, each associated with a particular segment.

FIG. 5C illustrates a detail of the lens assembly. Each of the diodes 416 is mounted on the board 408 at a minimum distance. Overlying the board and LEDs 416 is transparent lens substrate 520. This substrate 520 has a plurality of lens structures 522, each associated with one of the LEDs 416, such that each of the LEDs 416 has the light emitted therefrom directed outward towards the surface, each lens structure being substantially the same. The minimum distance is designed such that overlapping light from adjacent LEDs does not create interference patterns and result in dead spots on the surface. The lens structure 522 is designed to create the 3:1 uniformity and also, the lens structure is designed to “direct” the light from an edge of the surface to cover the entire surface. This is shown by the angle of the light rays in FIG. 5C. Also, the beveled edge 530 will basically surround the PCB 402, thus protecting it from moisture. The lens substrate 520 is secured with screws (not shown).

FIG. 5D illustrates a detail of the lens structure 522. This structure includes an interior surface 524 and an exterior surface 526 that shapes and directs the light in the correct pattern. This is an acrylic material. With such a design, the lighting assembly can be disposed at an edge of the surface to illuminate the entire surface.

In some embodiments, as shown in FIG. 1, two lighting assemblies 110 may be used. Each lighting assembly may be powered by a separate power supply (not shown), and may be configured to illuminate the entire surface 102. In such an embodiment, if one power supply fails, the remaining lighting assembly 110 will still illuminate the entire surface 102, although at a lesser intensity than when both lighting assemblies 110 are functioning. This provides evenly distributed illumination when both lighting assemblies 110 are functioning correctly, and continues to provide evenly distributed illumination when one lighting assembly 110 malfunctions. Accordingly, the entire surface 102 of the billboard 100 may be illuminated even when an entire lighting assembly 110 has malfunctioned and is providing no illumination at all due to the redundancy provided by configuration of the lighting assemblies 110.

Furthermore, in some embodiments as described above, each LED 416 of a single lighting assembly 110 may be configured via the optical elements 514 to illuminate the entire surface 102. In such embodiments, if one or more LEDs 416 or strings of LEDs fails, the remaining LEDs 416 will still illuminate the entire surface 102, although at a lesser intensity than when the failed LEDs 416 are functioning. This provides evenly distributed illumination when all LEDs 416 are functioning correctly, and continues to provide evenly distributed illumination when one or more LEDs are malfunctioning. Accordingly, the billboard 100 may be illuminated even when multiple LEDs 416 have malfunctioned and are providing no illumination at all due to the redundancy provided by configuration of the lighting assemblies 110.

It is understood that some embodiments may direct substantially all illumination from a lighting assembly 110 evenly across the surface 102 while some illumination is not evenly distributed. For example, substantially all LEDs 416 may be directed to each evenly illuminate the surface 102

with the exception of a relatively small number of LEDs 416. In such cases, the illumination provided by the remaining LED or LEDs 416 may be directed to one or more portions of the surface 102. If done properly, this may be accomplished while minimizing any noticeable unevenness in the overall illumination, even if one of the remaining LEDs 416 malfunctions. For example, the lighting assembly 110 may be configured to direct the illumination provided by one LED 416 to only the left half of the surface 102, while directing the illumination from another LED 416 to only the right half of the surface 102. The loss of one of these two LEDs may not noticeably impact the illumination of the surface 102. It is understood that such variations are within the scope of this disclosure.

In embodiments where the illumination is evenly distributed across the surface 102, it is understood that the optics panel 206 may be configured specifically for the light panel 204 and the surface 102. For example, assuming the surface 102 is forty-eight feet wide and sixteen feet high, the lens panel 500 of FIG. 5 may be specifically designed for use with the PCB 402 of FIG. 4. This design may be based on the particular layout of the PCB 402 (e.g., the number and arrangement of the LEDs 416), the amount of illumination provided by the LEDs 416, the size of the surface 102, the distance between the lens panel 500 and the surface 102, the angle at which the lens panel 500 is mounted relative to the surface 102 (e.g., FIGS. 1B-1D), and/or other factors. Accordingly, changes in any of these factors may entail a change in the design of the lens panel 500 in order to again evenly distribute the illumination provided by each LED 416 across the entire surface 102. It is understood that various standard configurations of the lighting assembly 110 may be developed for various billboard and/or other externally illuminated signs so that a particular configuration may be provided based on the parameters associated with a particular billboard and/or externally illuminated sign.

Referring to FIGS. 6A-6C, one embodiment of a lighting assembly 600 is illustrated that provides a more detailed embodiment of the lighting assembly 200 of FIG. 2. The lighting assembly 600 includes a back panel 602, a light panel formed by multiple LED assemblies (denoted by reference number 800 in FIG. 8A), and an optics panel formed by multiple lens panels 604. Accordingly, as described previously, the light panel 204 in the current example is represented by multiple LED assemblies 800 and the optics panel 206 is represented by multiple lens panels 604. In the present embodiment, the lighting assembly 600 includes four LED assemblies 800 and four lens panels 604.

Although various attachment mechanisms (e.g., threaded screws, bolts, and/or other fasteners) may be used to couple the lens panels and LED assemblies to the back panel 602, the present embodiment uses multiple threaded fasteners 605 (e.g., screws) that extend through the lens panels and the LED assemblies and engage threaded holes in the back panel 602.

The lighting assembly 600 is also illustrated with a mounting plate 606 that couples to the back panel 602 and to an adjustable mounting bracket 608. The adjustable mounting bracket 608 may be used to couple the lighting assembly 600 to a portion of the billboard 100 (FIG. 1) and/or to another support member. A power supply enclosure 610 may be coupled to the mounting plate 606 and configured to contain a power supply (not shown) capable of supplying power to LEDs of the LED assemblies 800. It is noted that separating the power supply from the back panel 602 may aid in heat dissipation by the back panel 602 as it

does not have to dissipate heat from the power supply to the same extent as if the power supply was mounted directly to the back panel 602.

The location of the power supply may also be beneficial as snow not melted by the heat produced by the LED may be melted by heat produced by the power supply. This may aid in reducing snow buildup on the LEDs.

With additional reference to FIGS. 7A and 7B, one embodiment of the back panel of FIG. 602 is illustrated. A front surface 700 includes multiple protrusions 702 that may be configured to protect the light panels (not shown) against moisture as previously described. The front surface 700 may include additional protrusions 704.

A back surface 706 includes multiple fins 708 that form a heat sink to aid in the dissipation of heat from the back panel 602. In the present example, the fins 708 are substantially rectangular in shape. In the present example, the back panel 602 is extruded and the fins 708 run parallel to the top edge with a longitudinal axis of each fin 708 being substantially parallel to a longitudinal axis of the back panel 602. Forming the fins 708 in a vertical manner is possible, but may increase the cost of the back panel 602 due to the extrusion process. As shown, the fins 708 may be substantially perpendicular to the back surface 706, and/or may be angled. In the present example, the fins 708 are angled such that near the top of the back panel 702, the fins 708 are angled towards the top.

Because the fins 708 are parallel to the top edge, heat may be trapped due to its inability to rise vertically. Accordingly, holes 710 may be present in some or all of the fins 708 (marked but not actually visible in the side view of FIG. 7B) to provide paths for the heat to rise vertically in spite of the orientation of the fins 708. The holes 710 may create a chimney effect that increases air flow across the fins 708 and aids in the cooling process. In some embodiments, some or all of the fins 708 may be angled such that heat is not trapped.

The back surface 706 may also include a groove 712 that is configured to receive a tongue of the mounting plate 606 in a tongue-in-groove manner.

With additional reference to FIGS. 8A-8J, embodiments of a single LED assembly 800 and a single lens panel 604 that may be used with the lighting assembly 600 are illustrated. As shown, the single LED assembly 800 and the single optics panel 604 may be configured for use together.

Referring specifically to FIG. 8A, the LED assembly 800 includes a substrate 802 (e.g., a PCB) onto which are mounted multiple LEDs 804. In the present example, the LED assembly 800 includes two strings of eight LEDs 804 each for a total of sixteen LEDs 804. It is understood that this is merely an example, and there may be more or fewer LEDs 804 on the light panel 800, and the LEDs 804 may be arranged in many different ways on the substrate 802.

Referring also to FIGS. 8B-8J, the optics panel 604 may include optical elements 806 arranged on an upper surface 808 of the optics panel 604. The optics panel 604 may further include sides 810, 812, 814, and 816 that are configured to fit around the edge of the substrate 802 of the light panel 800. The bottom edge of each side 810, 812, 814, and 816 abuts the front surface 700 of the back panel 602 and may be sealed to the front surface 700 using a moisture resistant sealant.

As shown in FIGS. 8D-8H, a single optical element 806 may include multiple lens elements designed to distribute the illumination provided by a single LED 804 across a surface such as the surface 102 of FIG. 1. A first lens element 820 may be positioned proximate to the LED 804, and

9

additional lens elements **822**, **824**, and **826** may be positioned above the lens element **820**. Multiple optical elements **806** may be combined and formed as a single optics panel **604** that is configured to operate with the LED assembly **800**.

Referring to FIG. 9, another embodiment of a lighting assembly **900** is illustrated that provides a more detailed embodiment of the lighting assembly **200** of FIG. 2. The lighting assembly **900** is similar to the lighting assembly **600** of FIG. 6, but includes six LED assemblies rather than the four six LED assemblies of the lighting assembly **600**. It is understood that the lighting assembly **900** may require a larger power supply than the lighting assembly **600** (e.g., a one hundred and fifty watt power supply instead of a one hundred and twenty watt power supply).

Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions and alterations can be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. A billboard comprising:

a support structure;

a display surface mounted on the support structure, the display surface having visual media content displayed thereon, the visual media content comprising a picture and/or text, wherein the display surface has a width of forty-eight feet along an upper edge and a lower edge of the display surface and a height of fourteen feet along a left side edge and a right side edge of the display surface, the display surface comprising a first portion extending from the lower edge to the upper edge adjacent the left side edge and a second portion extending from the lower edge to the upper edge adjacent the right side edge, the first and second portions together extending from the left side edge to the right side edge;

a first lighting assembly that includes a plurality of circuit boards arranged in a common orientation, each circuit board of the first lighting assembly being planar and having a first plurality of light emitting diodes (LEDs) and a first plurality of optical elements attached thereto, the first plurality of LEDs being thermally coupled to a first heat sink, wherein the LEDs of the first plurality of LEDs are arranged in a plurality of rows on each circuit board, each row including a plurality of LEDs mounted so that all of the LEDs of the first lighting assembly are arranged in a common orientation, and wherein each optical element of the first plurality of optical elements is disposed over only one associated LED, the optical elements being arranged to direct the light from each LED across the first portion of the display surface, wherein all of the circuit boards of the first lighting assembly are mounted in a single assembly; and

a second lighting assembly that includes a plurality of circuit boards arranged in a common orientation, each circuit board of the second lighting assembly being planar and having a second plurality of LEDs and a second plurality of optical elements attached thereto, the second plurality of LEDs being thermally coupled to a second heat sink, wherein the LEDs of the second plurality of LEDs are arranged in a plurality of rows on each circuit board, each row including a plurality of LEDs mounted so that all of the LEDs of the second lighting assembly are arranged in a common orientation, and wherein each optical element of the second

10

plurality of optical elements is disposed over only one associated LED, the optical elements being arranged to direct the light from each LED across the second portion of the display surface, wherein all of the circuit boards of the second lighting assembly are mounted in a single assembly, wherein the display surface can be illuminated using only the first lighting assembly and the second lighting assembly so that the visual media content can be viewed without additional light.

2. The billboard of claim 1, wherein each circuit board of the first lighting assembly includes only two rows of LEDs and optical elements; and

wherein each circuit board of the second lighting assembly includes only two rows of LEDs and optical elements.

3. The billboard of claim 2, wherein the first lighting assembly includes two circuit boards arranged in a first row that extends in a direction parallel to the lower edge of the display surface, and wherein the second lighting assembly includes two circuit boards arranged in a second row that extends in the direction parallel to the lower edge of the display surface.

4. The billboard of claim 3, wherein the first lighting assembly further includes two additional circuit boards arranged in a third row parallel to the two circuit boards arranged in the first row, and wherein the second lighting assembly further includes two additional circuit boards arranged in a fourth row parallel to the two circuit boards arranged in the second row.

5. The billboard of claim 2, wherein the first lighting assembly includes three circuit boards arranged in a first row that extends in a direction parallel to the lower edge of the display surface, and wherein the second lighting assembly includes three circuit boards arranged in a second row that extends in the direction parallel to the lower edge of the display surface.

6. The billboard of claim 1, wherein each optical element of the plurality of optical elements of the first and the second lighting assemblies comprises a first portion, a second portion and a third portion, a first side, a second side opposite the first side, and a third side perpendicular to the first side and the second side;

wherein the first portion comprises a first element comprising a first convex-shaped surface disposed at the first side;

wherein the second portion comprises a second element comprising a second convex-shaped surface disposed at the second side, wherein the second convex-shaped surface intersects with the first convex-shaped surface at an acute angle in a region between the first element and the second element, wherein light from an associated LED exits the optical element through the first and the second convex-shaped surfaces; and

wherein the third portion comprises a third element disposed at the third side, wherein the third element extends beyond the first element and the second element in a direction away from the associated LED.

7. The billboard of claim 1, wherein each optical element of the plurality of optical elements of the first and the second lighting assemblies comprises a first portion, a second portion and a third portion, a first side, a second side opposite the first side, and a third side perpendicular to the first side and the second side;

wherein the first portion of the optical element comprises a first element disposed at the first side;

wherein the second portion of the optical element comprises a second element disposed at the second side;

11

wherein the third portion of the optical element comprises a third element disposed at the third side; and wherein the third element extends beyond the first element and the second element in a direction away from an associated LED.

8. The billboard of claim 7, wherein the first element includes a first outer surface and a first inner surface facing the associated LED, and the second element includes a second outer surface and a second inner surface facing the associated LED;

wherein the first inner surface is located at a first nearest distance from the associated LED and the second inner surface is located at a second nearest distance from the associated LED; and

wherein a region between the first inner surface and the second inner surface is at a third nearest distance from the associated LED, wherein the third nearest distance is shorter than either the first nearest distance or the second nearest distance.

9. The billboard of claim 1, further comprising a walkway attached to the support structure adjacent the lower edge of the display surface, wherein an uppermost surface of the walkway is vertically spaced at a distance lower than the lower edge of the display surface, wherein the first lighting assembly is attached to the walkway, and wherein the second lighting assembly is attached to the walkway at a location laterally spaced from the first lighting assembly.

10. A method of illuminating the billboard of claim 1 using only the first and second lighting assemblies, the method comprising:

illuminating the first portion of the display surface using the first lighting assembly; and

at the same time, illuminating the second portion of the display surface using the second lighting assembly.

11. The method of claim 10 wherein:

illuminating the first portion of the display surface comprises illuminating the first portion of the display surface by emitting light from the first plurality of LEDs and redirecting the light across the first portion using the first plurality of optical elements so that the visual media content of the first portion of the display surface is visible without any additional light; and

illuminating the second portion of the display surface comprises illuminating the second portion of the display surface by emitting light from the second plurality of LEDs and redirecting the light across the second portion using the second plurality of optical elements so that the visual media content of the second portion of the display surface is visible without any additional light.

12. A billboard comprising:

a support structure;

a display surface mounted on the support structure, the display surface having visual media content displayed thereon, the visual media content comprising a picture and/or text, wherein the display surface has a width of forty-eight feet along an upper edge and a lower edge of the display surface and a height of fourteen feet along a left side edge and a right side edge of the display surface, the display surface comprising a first portion extending from the lower edge to the upper edge adjacent the left side edge and a second portion extending from the lower edge to the upper edge adjacent the right side edge, the first and second portions together extending from the left side edge to the right side edge;

12

a first lighting assembly directed toward the display surface, wherein the first lighting assembly comprises: a first carrier;

a first lighting unit secured to the first carrier, the first lighting unit comprising a single planar circuit board, a plurality of light emitting diodes (LEDs) attached to the single planar circuit board, and a plurality of optical elements, wherein each optical element is disposed over only one associated LED, wherein the first lighting unit is configured to direct light across the first portion of the display surface; and

a second lighting unit secured to the first carrier, the second lighting unit comprising only a single planar circuit board, a plurality of LEDs attached to the single planar circuit board, and a plurality of optical elements, wherein each optical element is disposed over only one associated LED, wherein the second lighting unit is configured to direct light across the first portion of the display surface; and

a second lighting assembly directed toward the display surface, wherein the second lighting assembly comprises:

a second carrier;

a third lighting unit secured to the second carrier, the third lighting unit comprising only a single planar circuit board, a plurality of LEDs attached to the single planar circuit board, and a plurality of optical elements, wherein each optical element is disposed over only one associated LED, wherein the third lighting unit is configured to direct light across the second portion of the display surface; and

a fourth lighting unit secured to the second carrier, the fourth lighting unit comprising only a single planar circuit board, a plurality of LEDs attached to the single planar circuit board, and a plurality of optical elements, wherein each optical element is disposed over only one associated LED, wherein the fourth lighting unit is configured to direct light across the second portion of the display surface;

wherein the display surface can be illuminated using only the first lighting assembly and the second lighting assembly so that the visual media content can be viewed without any light other than light from the first lighting assembly and the second lighting assembly.

13. The billboard of claim 12, wherein the first lighting assembly is configured to uniformly illuminate the first portion of the display surface, and wherein the second lighting assembly is configured to uniformly illuminate the second portion of the display surface.

14. The billboard of claim 13, wherein each and every LED of the first lighting assembly is configured to uniformly illuminate the first portion of the display surface, and wherein each and every LED of the second lighting assembly is configured to uniformly illuminate the second portion of the display surface.

15. The billboard of claim 12, wherein the optical elements of the first lighting assembly each include a first portion, a second portion and a third portion arranged to direct the light across the first portion of the display surface; and

wherein the optical elements of the second lighting assembly each include a first portion, a second portion and a third portion arranged to direct the light across the second portion of the display surface.

16. The billboard of claim 15, wherein each optical element of the plurality of optical elements of the first and the second lighting assemblies comprises:

13

- a first side, a second side opposite the first side, and a third side perpendicular to the first side and the second side;
- a first element comprising a first convex-shaped surface disposed at the first side;
- a second element comprising a second convex-shaped surface disposed at the second side, wherein the second convex-shaped surface intersects with the first convex-shaped surface at an acute angle in a region between the first element and the second element, wherein the light from the associated LED exits the optical element through the first and the second convex-shaped surfaces; and
- a third element disposed at the third side, wherein the third element extends beyond the first element and the second element in a direction away from the associated LED.

17. The billboard of claim 15, wherein each optical element of the plurality of optical elements of the first and the second lighting assemblies comprises:

- a first side, a second side opposite the first side, and a third side perpendicular to the first side and the second side;
- a first element disposed at the first side;
- a second element disposed at the second side;
- a third element disposed at the third side;
- wherein the third element extends beyond the first element and the second element in a direction away from the associated LED;
- wherein the first element includes a first outer surface and a first inner surface facing the associated LED, and the second element includes a second outer surface and a second inner surface facing the associated LED;
- wherein the first inner surface is located at a first nearest distance from the associated LED and the second inner surface is located at a second nearest distance from the associated LED; and
- wherein the first inner surface and the second inner surface connect at a connection region that is at a third nearest distance from the associated LED, wherein the third nearest distance is shorter than either the first nearest distance or the second nearest distance.

18. The billboard of claim 12, wherein the first carrier is formed from a thermally conductive material, wherein a plurality of fins extend away from the first, the second and the third lighting units.

19. A method of illuminating the billboard of claim 12 using only the first and second lighting assemblies, the method comprising:

- illuminating the first portion of the display surface using the first lighting assembly; and
- at the same time, illuminating the second portion of the display surface using the second lighting assembly.

20. The method of claim 19 wherein:

- illuminating the first portion of the display surface comprises illuminating the first portion of the display surface by emitting light from the first plurality of LEDs and redirecting the light across the first portion using the first plurality of optical elements so that the visual media content of the first portion of the display surface is visible without any additional light; and
- illuminating the second portion of the display surface comprises illuminating the second portion of the display surface by emitting light from the second plurality of LEDs and redirecting the light across the second portion using the second plurality of optical elements so that the visual media content of the second portion of the display surface is visible without any additional light.

14

21. A billboard comprising:

- a support structure;
- a display surface mounted on the support structure, the display surface having a width of forty-eight feet along an upper edge and a lower edge of the display surface and a height of fourteen feet along a left side edge and a right side edge of the display surface, the display surface comprising a first portion extending from the lower edge to the upper edge adjacent the left side edge and a second portion extending from the lower edge to the upper edge adjacent the right side edge, the first and second portions together extending from the left side edge to the right side edge;
- a first lighting assembly that includes a plurality of circuit boards arranged in a common orientation, each circuit board of the first lighting assembly being planar and having a first plurality of light emitting diodes (LEDs) arranged in a first row and a second row attached thereto, the first lighting assembly also including a first plurality of optical elements arranged in the first row and the second row over the plurality of LEDs such that each optical element overlies only one associated LED, the optical elements arranged to direct light from each of the first plurality of LEDs across the first portion of the display surface; and
- a second lighting assembly that includes a plurality of circuit boards arranged in a common orientation, each circuit board of the second lighting assembly being planar and having a second plurality of LEDs arranged in a first row and a second row attached thereto, the second lighting assembly also including a second plurality of optical elements arranged in the first row and the second row over the second plurality of LEDs such that each optical element overlies only one associated LED, the optical elements arranged to direct light from each of the second plurality of LEDs across the second portion of the display surface;
- wherein the first lighting assembly is mounted at a first location, and wherein the second lighting assembly is mounted at a second location, wherein the first location is laterally spaced from the second location along the width of the display surface; and
- wherein the display surface of the billboard can be illuminated using only the first lighting assembly and the second lighting assembly so that visual media content on the display surface can be viewed without additional lighting.

22. The billboard of claim 21, wherein the optical elements of the first and the second lighting assemblies are arranged so that areas beyond edges of the display surface receive minimum illumination.

23. The billboard of claim 21, wherein each optical element of the first and the second lighting assemblies comprises:

- a first side, a second side opposite the first side, and a third side perpendicular to the first side and the second side;
- a first element comprising a first convex-shaped surface disposed at the first side;
- a second element comprising a second convex-shaped surface disposed at the second side, wherein the second convex-shaped surface intersects with the first convex-shaped surface at an acute angle in a region between the first element and the second element, wherein the light from the associated LED exits the optical element through the first and the second convex-shaped surfaces; and

15

a third element disposed at the third side, wherein the third element extends beyond the first element and the second element in a direction away from the associated LED.

24. The billboard of claim 21, wherein each optical element of the first and the second lighting assemblies comprises:

a first side, a second side opposite the first side, and a third side perpendicular to the first side and the second side; a first element disposed at the first side; a second element disposed at the second side; a third element disposed at the third side;

wherein the third element extends beyond the first element and the second element in a direction away from the associated LED;

wherein the first element includes a first outer surface and a first inner surface facing the associated LED, and the second element includes a second outer surface and a second inner surface facing the associated LED;

wherein the first inner surface is located at a first nearest distance from the associated LED and the second inner surface is located at a second nearest distance from the associated LED; and

wherein the first inner surface and the second inner surface connect at a connection region that is at a third nearest distance from the associated LED, wherein the third nearest distance is shorter than either the first nearest distance or the second nearest distance.

25. A method of illuminating the billboard of claim 21 using only the first and second lighting assemblies, the method comprising:

illuminating the first portion of the display surface using the first lighting assembly; and

at the same time, illuminating the second portion of the display surface using the second lighting assembly.

26. A method of illuminating the billboard of claim 25 wherein:

illuminating the first portion of the display surface comprises illuminating the first portion of the display surface by emitting light from the first plurality of LEDs and redirecting the light across the first portion using the first plurality of optical elements so that the visual media content of the first portion of the display surface is visible without any additional light; and

illuminating the second portion of the display surface comprises illuminating the second portion of the display surface by emitting light from the second plurality of LEDs and redirecting the light across the second portion using the second plurality of optical elements so that the visual media content of the second portion of the display surface is visible without any additional light.

27. The billboard of claim 1, wherein the rows of LEDs on each circuit board extend along a longitudinal axis of the circuit board and wherein the first heat sink of each circuit board of the first lighting assembly comprises a first section substantially parallel to the circuit board and a plurality of fins extending away from the first section and substantially perpendicular thereto, a longitudinal axis of each fin being substantially perpendicular to the longitudinal axis of the circuit board.

28. The billboard of claim 12, wherein the first lighting unit further comprises a heat sink thermally coupled to the circuit board so that the circuit board is between each LED

16

and the heat sink, the LEDs being arranged in rows that extend along a longitudinal axis of the circuit board, wherein the heat sink comprises a first section substantially parallel to the circuit board and a plurality of fins extending away from the first section and substantially perpendicular thereto, a longitudinal axis of each fin being substantially perpendicular to the longitudinal axis of the circuit board;

wherein the second lighting unit further comprises a heat sink thermally coupled to the circuit board so that the circuit board is between each LED and the heat sink, the LEDs being arranged in rows that extend along a longitudinal axis of the circuit board, wherein the heat sink comprises a first section substantially parallel to the circuit board and a plurality of fins extending away from the first section and substantially perpendicular thereto, a longitudinal axis of each fin being substantially perpendicular to the longitudinal axis of the circuit board;

wherein the third lighting unit further comprises a heat sink thermally coupled to the circuit board so that the circuit board is between each LED and the heat sink, the LEDs being arranged in rows that extend along a longitudinal axis of the circuit board, wherein the heat sink comprises a first section substantially parallel to the circuit board and a plurality of fins extending away from the first section and substantially perpendicular thereto, a longitudinal axis of each fin being substantially perpendicular to the longitudinal axis of the circuit board; and

wherein the fourth lighting unit further comprises a heat sink thermally coupled to the circuit board so that the circuit board is between each LED and the heat sink, the LEDs being arranged in rows that extend along a longitudinal axis of the circuit board, wherein the heat sink comprises a first section substantially parallel to the circuit board and a plurality of fins extending away from the first section and substantially perpendicular thereto, a longitudinal axis of each fin being substantially perpendicular to the longitudinal axis of the circuit board.

29. The billboard of claim 21, wherein the first lighting assembly further comprises a plurality of heat sinks, each heat sink thermally coupled to an associated one of the circuit boards, each circuit board having a longitudinal axis along which the first and second rows of LEDs extend, wherein each heat sink comprises a first section substantially parallel to the associated circuit board and a plurality of fins extending away from the first section and substantially perpendicular thereto, a longitudinal axis of each fin being substantially perpendicular to the longitudinal axis of the circuit board; and

wherein the second lighting assembly further comprises a plurality of heat sinks, each heat sink thermally coupled to an associated one of the circuit boards, each circuit board having a longitudinal axis along which the first and second rows of LEDs extend, wherein each heat sink comprises a first section substantially parallel to the associated circuit board and a plurality of fins extending away from the first section and substantially perpendicular thereto, a longitudinal axis of each fin being substantially perpendicular to the longitudinal axis of the circuit board.

* * * * *